

Object-Oriented Concepts

Lecture Objectives

- Understand object-oriented software development concepts
 - Types, classes, and objects
 - Encapsulation
 - Inheritance
- Understand the relationships between Object-Oriented Programming (OOP) and Object-Oriented Analysis and Design (OOA and OOD)

OO Development

- OO Development is the predominant paradigm for the modern software life-cycle
- Life Cycles phases vary depending on the size and type of project, but can include:
 - Business Analysis - what are the *business processes* and *actors* that the software will interact with (e.g., a University Student Registration system)
 - Requirements Analysis - what are the *actors* and *use cases* for the software (e.g., students, professors, ... ; registering for a course, ...)
 - Design - what are the objects and classes of the software (e.g., course, subject, transcript, ...)
 - Code and unit test
 - System and Integration Testing
- **High quality software requires close attention to analysis and design, not just programming!**

OO Development (cont.)

- In this course, we focus on programming
- However, the connection between programming and design and analysis needs to be emphasized:
 - What is a “good” candidate class or object?
 - How can we identify the operations (methods) and attributes of such classes and objects?
 - How should we define relations between classes and objects?
- **For all but trivial projects, classes and their relations need to be designed before coding commences!**
- Fortunately, there is single international standard for OOA&D
 - The Unified Modelling Language (UML), which is well supported by open-source and commercial software tools.

OO Development (cont.)


- We will assume that analysis has been done
 - We have written descriptions of what the software should do, either as point-form requirements or use cases
- The focus is on guidelines for answering the following design questions:
 - What is a “good” candidate class or object?
 - How can we identify the operations (methods) and attributes of such classes and objects?
 - How should we define relations between classes and objects?
- OOD is very *subjective* - tradeoffs need to be made between simplicity and adaptability based on through domain knowledge and business constraints.

Objects


- From Grady Booch, *Object-Oriented Design with Applications*:
“An *object* has *state*, *behaviour* and *identity*...”
 - State means data: information, attributes, or properties
 - Behaviour means operations that query or change the object's state
 - Identity means that each object must be unique and precisely defined
- OO systems model real-world systems by simulating real-world objects
 - But only the behaviour and state relevant to the system being implemented

Objects (cont.)


- Which of the real-world entities might correspond to objects in a computer system, and why?



ACME's London
Warehouse



Throckmorton's
order from ACME



The World Bank



The Government

Objects (cont.)


- “The Government” is not a well-defined identity
 - e.g. do we mean State, Federal, Local or overseas governments?
- But the other three examples all have state, behaviour and identity
 - The warehouse has stock that can be shipped
 - The order has items and a price and can be cancelled
 - The world bank has member countries that contribute funds
- *Candidate objects* can be recognized quite easily from written requirements and use cases.
- A safe assumption would be that **proper nouns are candidate objects**.
 - Proper nouns in English are capitalized, or preceded by “the ...”
- Many proper nouns in a requirements document are vague or describe external entities
 - e.g., “the system”, “the user”, ...

Classes


- Similar objects are classified, or grouped, into *classes*
 - All have the same data members, though with different values
 - All share identical behaviour
- An object belongs to only one class
 - Specified when the object is created
 - Inheritance allows classes to have common properties and operations
 - The *state* design pattern allows an object to appear to change its class

Classes (cont.)


- To what classes in a computer system might the following objects belong?



ACME's London
Warehouse



Throckmorton's
order from ACME



The World Bank

Classes (cont.)

- Possible answers
 - Acme's London Warehouse - `class Warehouse`
 - Throckmorton's Order from Acme - `class Order`
 - The World Bank - `class WorldBank`
- Sometimes there should only be one instance of a class
 - This is usually known at design time
 - There is only one `World Bank`, in a class of its own
 - At the programming level, the code should enforce this

Classes (cont.)


- What programming or design techniques might we use to achieve this in Java or another OOP?
- The *singleton* design pattern will solve the problem
 - A design pattern is just a standard way of solving a common design and coding problem
 - Design patterns were first described in the book “Design Patterns” by Gamma, Helm, Johnson, and Vlissades (the “GoF”) in 1995

Classes (cont.)

- Once we have identified classes, it is useful at design time to identify the operations and attributes of those classes
 - Operations (*methods*), are things you can do to that class's objects
 - Attributes are properties of objects of that class (may be constants)
- Candidate attributes, methods, and classes can all be identified from a natural language description of the application or use cases
 - Common nouns attributes or classes
 - Verbs methods

Classes: An example

- Suppose we wish to implement a simple event log
 - Just counting the number of events
 - Later we will develop a more sophisticated event log
 - That record details of the events
- The operations on the EventLog will be `set(int)` and `increment()`
 - The increment operation will return the new count of the EventLog



Classes (cont.)

```
// File "EventLog.h"
class EventLog {
    // default is private
    int count;
public:
    int increment() {
        return ++count;
    }
    void set(int value) {
        count = value;
    }
};
```

```
#include "eventlog.h"
#include <iostream>
using namespace std;
int main() {
    EventLog c1, c2;
    c1.set(0);
    cout << c1.increment();
    c2 = c1;
    cout << c1.increment();
    cout << c2.increment();
    return 0;
}
```

Output is:
1 2 2

- Class objects may be assigned, passed as arguments, and returned by functions

```
c2 = c1; // 'memberwise copy':
        // same as c2.count = c1.count; IF count were public
```

Classes (cont.)

- Java class variables are very different!
 - Java class variables are references to dynamically allocated objects
 - Assigning one variable to another makes them both refer to the same object
 - What would the program output have been if EventLog was a Java class?
- Our class requires that the user call `set(0)` to initialize an EventLog object before it is used
 - In C/C++ global data is initialized to zero, but it is unsafe to rely on implicit initialization
 - How can we ensure that an object is initialized correctly?

Constructors

- A member function with the same name as the class is a constructor
- Constructors are invoked whenever a class instance is allocated
- **Each class should have a constructor member function**

```
class EventLog {  
    int count;  
public:  
    EventLog() { count = 0; }  
    // other members  
};
```

Constructor
definition

Implicit constructor call
when c0 allocated

```
EventLog c0;  
  
cout << c0.increment(); // 1 is output
```

Constructors (cont.)

- C++ provides another syntax for initializing data members: a member initialiser list

```
class EventLog {  
    int count;  
public:  
    EventLog() :  
        count(0) // member initialiser list  
    {}          // empty constructor body  
    // other methods  
};
```

- Member initialiser lists have a more object-oriented style
 - Data members are passed arguments to initialize themselves
- Member initialiser lists must be used for initializing base classes, data members with constructors, and constant data members

Constructors (cont.)

- A constructor cannot be explicitly called as a member function

```
EventLog c0;    // constructor call: c0.count = 0  
c0.EventLog(); // compile error
```

- A constructor call by itself causes a temporary object to be allocated

```
EventLog c1;  
c1.increment();  
c1 = EventLog(); // In this example, c1.set(0)  
                // would be simpler and more readable
```

- The call `EventLog()` constructs a temporary `EventLog` object, which is then assigned (copied) to `c1`
- The temporary `EventLog` object is reclaimed automatically at the end of the statement
- A constructor that can be called with no arguments is called a *default constructor*


Constructors (cont.)

- It is illegal to have a return type, or return expression, in a constructor
- It is also illegal to initialize data members outside the constructor
- A constructor has no explicit return type. It effectively “returns” a properly initialized object of its class

```
class EventLog {  
    int count = 0;    // illegal initialization  
public:  
    void EventLog()    // illegal to have void here!  
                        // : count(0) SHOULD BE HERE  
    {}                // no code needed in body  
};
```

Overloading

- Most modern programming languages provide overloading
 - Multiple meanings for one name or symbol in one scope
 - Overloading happens at compile time



- Functions and operators should have the same name if and only if they perform the same operation on different data types.

Overloading (cont.)

- C++ allows overloading of function names and operators

```
point1.move(1,2);  
point2.move(point1);  
line1.move(1,2);
```

move could be relative or absolute.
moves in the program should behave the same
if they have the same name.
If they are different, rename as: `move_by` and `move_to`

- Methods in the same class can have the same name if their declarations have different parameter types

File "eventlog.h"
two constructors and
two set methods

Default constructor

```
class EventLog {  
    int count;  
public:  
    void set() { set(0); }  
    void set(int value) { count = value; }  
    EventLog() : count(0) {}  
    EventLog(int init) : count (init) {}  
    int increment() { return ++count; }  
};
```

Overloading (cont.)

- One member function can call another; the current object is implicit
 - `set()` calls `set(int)` above
- What if one constructor calls another?
 - If below we used: `EventLog() { EventLog(0); }`

```
class EventLog {  
    int count;  
public:  
    void set() { set(0); }  
    void set(int value) { count = value; }  
    EventLog() : count(0) {}  
    EventLog(int init) : count (init) {}  
  
    int increment() { return ++count; }  
};
```

Overloading (cont.)

- A constructor call just creates a temporary object
 - One constructor should not call another!

```
class EventLog {  
    int count;  
public:  
    EventLog() : { EventLog(0); }  
    EventLog(int init) : count (init) {}  
    // other members  
};
```

The call `EventLog(0)` creates a temporary `EventLog` object. The count of this object is not initialized

Overloading (cont.)

```
#include "eventlog.h"
#include <iostream>

using namespace std;

int main() {
    EventLog c1(42);
    EventLog c2;

    cout << c2.increment() << '\n';
    cout << c1.increment() << '\n';
    c1.set();
    c2.set(42);

    cout << c2.increment() << '\n';
    cout << c1.increment() << '\n';
    return 0;
}
```

two overloaded constructor calls

Do not declare as: `EventLog c2();`
Causes a syntax error later as this declared `c2` as a C function returning an `EventLog`

Output

```
1
43
43
1
```

Default Arguments

- Overloading is used for arguments with simple defaults
 - Values used if no argument is supplied by the caller
- C++ provides a simple mechanism for declaring functions with default arguments
 - Trailing arguments can have default initialization
- Using default arguments simplifies our `EventLog` class

```
class EventLog {  
    int count;  
public:  
    void set(int value = 0) { count = value; }  
    EventLog(int init = 0): count(init) {}  
    int increment() { return ++count; }  
};
```

Default argument for the
set member function

Default argument for constructor

Default Arguments (cont.)

- A function declaration with defaults is equivalent to several separate overloaded function declarations

```
int doit(int, int=0, int=0, int=0);  
// equivalent to FOUR functions: doit(int), doit(int, int),  
// doit(int, int, int), and doit(int, int, int, int)
```

- If a parameter has default, all remainings must have defaults

```
int doitagain(int, int=0, int, int=0); // compile error
```

- Intermediate arguments in a call cannot use defaults
 - Used only when no arguments remain

```
doit(11, , , 10); // compile error
```


- Overuse of overloading and defaults can cause maintenance headaches

Separate Compilation

- A *compilation unit* consists of a C++ source code file and all the header files that it `#includes`
 - By convention, source code files have an extension `.cpp` or `.cc` and header files have an extension `.h`
- The C++ compiler generates an object file for each compilation unit
 - Object files contain relocatable machine code
 - By convention, object files have an extension `.o` or `.obj`

Separate Compilation (cont.)

- One or more object files are then linked to form an executable binary file.



- A header file can be `#included` by many source files
 - But should not be included repeatedly within a compilation unit
 - Use of the preprocessor `#ifndef` prevents coincidental repeated includes.

Separate Compilation (cont.)

- Unlike Java, C/C++ imposes no restriction or relation between file names and their contents
- **Good style is one class per file, both with the same name.**

```
// File foo.cpp
#include "A.h"
#include "B.h"
#include "C.h"
class Foo {
    ...
};
...
```

One file must have a global main to create an executable

```
// File bar.cpp
#include "C.h"
#include "D.h"
class Bar {
    ...
};
...
```

```
>gcc -c foo.cpp
>gcc -c bar.cpp
>gcc -o foobar foo.o bar.o
# or gcc -o foobar foo.cpp bar.cpp
>./foobar
```

Separate Compilation (cont.)

- Often, some methods are defined in the header file, and some in the '.cpp' file
 - Placing short member definitions in the header file is done for efficiency
 - The compiler can *inline* such definitions

```
// File eventlog.h:  
class EventLog {  
    int count;  
public:  
    EventLog() : count(0) {}  
    int increment();  
    void set(int value);  
};
```

constructor defined in the .h file;
increment and set defined in
the .cpp file

```
// File: eventlog.cpp  
#include "eventlog.h"  
int EventLog::increment() {  
    return ++count;  
}  
void EventLog::set(int value) {  
    count = value;  
}
```

Separate Compilation (cont.)

- An inline function call is replaced by the function code
 - Placing short member definitions in the header file is done for efficiency
 - The compiler can inline such definitions

```
// File eventlog.h:  
class EventLog {  
    int count;  
public:  
    inline EventLog()  
        : count(0) {}  
    int increment();  
    void set(int value) {  
        count = value;  
    }  
};
```

inline legal here, but implicit
as this is a member function
definition in a .h file

```
#include "eventlog.h"  
...  
Eventlog c1;  
int main() {  
    ...  
    c1.set(42);  
    ...  
}
```

no code generated, static
storage initialization to 0

call replaced by:
c1.count = 42;


– <https://www.youtube.com/watch?v=B2HDcKUT67s>

Declarations and Definitions

- In the “compile and link” model that C/C++ use
 - Many compilation units can include references to the *same* library files
 - The executable code for these libraries files needs to be loaded *just once*
 - How to ensure that library code is not duplicated when loaded?

Declarations and Definitions (cont.)

- The solution adopted by C/C++, and many other compiled languages, is that...
 - header files, which can be repeatedly included, should not allocate storage
 - They can contain only *declarations*, not *definitions*



Declarations and Definitions (cont.)

- A declaration (of a variable, function, or class) - in a `.h` file
 - Does not allocate storage
 - Tells the compiler about attributes of the identifier that will be defined elsewhere - in a `.cc` file

```
// some.h or .cpp file
extern int i;           // variable declaration
int main(int argc, char* argv[]); // function declaration
class Account;         // class declaration
```

class declarations are needed when two class declarations reference each other, e.g.,

```
class B;
// now we can declare a pointer to B
class A { ... B* bp; ... }
class B { ... A* ap; ... }
```

Declarations and Definitions (cont.)

- A *definition* of a
 - Variable - allocates storage, specifies initial value (if any)
 - Function - specifies the code to be executed when the function is called
 - Class - declares the members of the class

```
// some .cpp file
int i = 0; // variable definition
int main(int argc, char* argv[]) {
    // function definition
}
class Account {
    // class definition
    // member declarations and definitions
};
```

Declarations and Definitions (cont.)

- Class definitions are needed and allowed in header files in C++
 - The C rule of “no definitions in .h files” has had to be relaxed
- Because C++ is downward compatible with C, C++ programs can mix OO and non-OO code:
 - OO code: data and functions members of classes
 - Non-OO (C style) code: global data and functions
- Non-OO code is “unsafe” as all global data is public.
- C++ programs should not mix C style and C++ style programming - it is unsafe and hard to maintain.

UML Notation

- UML is a language that allows modelling object-oriented systems.
- While *class diagrams* are of special interest to this course, it is also important to know how to model requirements!
 - *For this we make use cases!*

Classes (cont.)

- For example, a `create_order` use case:
- A salesperson enters the customer's number, a new order is created for the customer. The salesperson adds the items and their quantity into the order. ...
- What classes, operations, and attributes appear in this use case?

Classes (cont.)


- Possible classes, operations, and attributes for this use case are:
 - class customer - attribute: number
 - class order - operation: create, add_items
 - class item
- salesperson is probably not a class
 - Instead it is an external user of the system, or actor
- Customer number is an attribute as it has no operations - just get and set its value
- item is probably a class as it has attributes and operations

Classes (cont.)

- OOA depends on “domain knowledge”
 - From users and domain experts, not always from written requirements
 - For example, an order might record the id of the salesperson creating the order - then salesperson might need to be an attribute or class


UML Notation - Classes

- UML represents classes as rectangles
 - With the name of the class (required), methods and attributes optional
 - Methods and attributes are added as the design is iteratively refined



C++ Syntax - Classes

- To implement a UML class, we need to know the types of all attributes and methods
- Suppose `number` is a C/C++ `int`, then class `Customer` can be defined as




UML Notation - Class Diagrams

- *Class diagrams* show the *static* relationships between classes and objects
 - A `Customer` will have zero or more `Orders`
- There are four types of static relationships in UML class diagrams
 - ***Association*** - “has a”
 - ***Aggregation*** - a special form of association
 - ***Inheritance*** - “is a (kind of)”
 - ***Dependency*** - “uses a”
- These phrases are used in analysis to determine the class relationships
- What verb phrase best describes the relation between an `Order` and an `Item` - “has a”, “is a”, or “uses a”?

UML Association

- Association models the relation “has” between objects




- What might the attributes of an `Item` be?
- Are any attribute values shared or are they unique to each `Order`?

Refactoring Classes

- The attributes of an Item might include:
 - id (bar code),
 - info,
 - price,
 - quantity_in_order,
 - quantity_in_stock
- The attribute values of id, info, price, and quantity_in_stock are shared by many Items, but quantity_in_order is unique to each Order...
- Is such sharing desirable? If not, how can we avoid it?

Refactoring Classes (cont.)


- **Duplication is considered undesirable in any OO design or program**
 - It can be removed by mechanisms including *inheritance*, *delegation*
 - In this case, we use *normalization* - split classes to remove duplicate data:
- Item **is split into**
 - ItemType
 - OrderItem



- **This is an example of *refactoring*:**
 - An increment improvement in a design or program
 - This refactoring is closely related to “database normalization”

UML Aggregation

- Aggregation models the object relation “part of,” or “is composed of”
 - A “stronger” class relation than association (“has”)




<https://www.youtube.com/watch?v=X9yvOI4Ywew>

UML aggregation (cont.)

- An `OrderItem` is part of an `Order`
 - An `Order` owns its `OrderItems` —`OrderItems` are not shared
 - The only way to access an `OrderItem` is through their owner `Order`
 - The `Order` creates and destroys its `OrderItems`
- Aggregation is controversial—different experts define it in different ways
 - What if not all of the above apply? Is it still aggregation?
 - Our recommendation: “When in doubt, leave it out”

Inheritance in UML

- Inheritance models the object relation “is a kind of”
 - A SavingsAccount is a kind of BankAccount
 - Thus any attribute or method of a BankAccount also applies to a SavingsAccount



Inheritance in C++

Money would be typedef'ed in a header file as a decimal type

```
// File: bankaccount.h
class BankAccount {
private:
    Money balance;
    int account_num;
public:
    Money get_balance() {
        return balance;
    }
    // other members,
    // e.g., constructor
};
```

public modifier needed to allow users of the *derived* class to access members of the *base* class

#include of file containing the base class definition needed. Double quotes are used as this is a user file, not a system file

```
#include "bankaccount.h"
...
class CheckingAccount : public BankAccount {
private:
    std::list<Check*> check_list;
public:
    void deposit(Money m) { ... }
    void withdraw(Money m) { ... }
    void write_check(Check* cp) { ... }
    // other members, e.g., constructor
};
```