

The results are in! See what nearly 90,000 developers picked as their most loved, dreaded, and desired coding languages and more in the 2019 Developer Survey.

Python add new item to dictionary [duplicate]

[Ask Question](#)

459



This question already has an answer here:

[Add new keys to a dictionary?](#) 15 answers



101

I want to add an item to an existing dictionary in python. For example, this is my dictionary:

```
default_data = {  
    'item1': 1,  
    'item2': 2,  
}
```

I want to add new item such that:

```
default_data = default_data + {'item3':3}
```

How to achieve this?

[python](#)[dictionary](#)[items](#)

edited Jun 21 '16 at 14:25

[Chaitanya Bapat](#)

327 1 8 22

asked Jun 20 '11 at 19:07

[brsbilgic](#)


4,379 8 50 82

marked as duplicate by [Shai](#), [Ber](#), [alecxe](#), [FallenAngel](#), [SysDragon](#)
Jun 11 '13 at 8:12




This question has been asked before and already has an answer. If those answers do not fully address your question, please [ask a new question](#).

12 docs.python.org/tutorial/datastructures.html#dictionaries – [Ignacio Vazquez-Abrams](#) Jun 20 '11

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

- 3 @machine yearning:
meta.stackexchange.com/questions/5280/embrace-the-non-googlers –
 Fred Larson Jun 20 '11 at 19:15 
-
- I apologize, I did not realize the depth of policy on this type of matter.
 Thanks for the link, it was informative.
 – machine yearning Jun 20 '11 at 19:21
-
- @machine yearning: Good find. I've voted to close as an exact duplicate.
 – Fred Larson Jun 20 '11 at 19:32
-

3 Answers

-  `default_data['item3'] = 3`
- 1035  Easy as py.
-  Another possible solution:
- `default_data.update({'item3': 3})`

which is nice if you want to insert multiple items at once.

answered Jun 20 '11 at 19:08



[Chris Eberle](#)

38k 9 68 104

- 14 This response is more useful than that at the duplicate post! +1 for improving on something simple! –
[machine yearning](#) Jun 20 '11 at 19:29
-
- 1 Sorry for the thread necro, but is there any reason to prefer one method over the other when adding one item? – [Warrick](#) Feb 26 '13 at 14:01
-
- 4 @Warrick there's absolutely no difference except for personal taste. Personally I find the first to be a little more intuitive for just one item. –
[Chris Eberle](#) Feb 26 '13 at 19:22
-
- which is faster? – [user3067923](#) Jul 8 '17 at 20:59
-
- 1 @user3067923 This is pure conjecture but I *imagine* that the first one would be marginally faster since it's mutating the dict in place, whereas the second one has to create a temporary dict, then mutate, then garbage collect the temporary dict. I'd need to benchmark it to say definitively. –
[Chris Eberle](#) Sep 6 '17 at 23:35

It can be as simple as:

66 `default_data['item3'] = 3`

As [Chris' answer](#) says, you can use [update](#) to add more than one item. An example:

```
default_data.update({'item4': 4, 'item5': 5})
```

Please see the docs about [dictionaries as data structures](#) and [dictionaries as built-in types](#).

edited May 23 '17 at 12:18



Community ♦

1 1

answered Jun 20 '11 at 19:09



GreenMatt

13.7k 6 42 70

-
- 1 Useful for knowing that you can do multiple items in an update. – [tisaconundrum](#) Sep 24 '17 at 14:10
-

It occurred to me that you may have actually be asking how to implement the + operator for dictionaries, the following seems to work:

23

```
>>> class Dict(dict):
...     def __add__(self, other):
...         copy = self.copy()
...         copy.update(other)
...         return copy
...     def __radd__(self, other):
...         copy = other.copy()
...         copy.update(self)
...         return copy
...
>>> default_data = Dict({'item1': 1})
>>> default_data + {'item3': 3}
{'item2': 2, 'item3': 3, 'item1': 1}
>>> {'test1': 1} + Dict(test2=2)
{'test1': 1, 'test2': 2}
```

Note that this is more overhead than using `dict[key] = value` or `dict.update()`, so I would recommend against using this solution unless you intend to create a new dictionary anyway.

**148k** 17 198 257

2 If you don't want to implement your own operators, you can also do `dict(default_data.items() + {'item3': 3}.items())` – [Pakman](#)
Aug 23 '13 at 13:56

1 [@Pakman's](#) comment doesn't work in Python3 (see: [stackoverflow.com/questions/13361510/...](https://stackoverflow.com/questions/13361510/)) – [Prof](#) Feb 21 '16 at 21:15
