

Harvest 21

Database Data Dictionary

Complete table & column reference for the Harvest 21 platform database

30

Tables

277

Total Columns

8

Domains

Postgr
eSQL
15

Backend: Supabase (PostgreSQL) · Auth: Supabase Auth · Payments: Stripe

Generated: March 27, 2026

DOMAINS

Auth & Identity

Pages

Prayers

Messaging

Organizations

Donations

Social / Follow

Homepage & Footer

Table of Contents

AUTH & IDENTITY

auth.users	—
users	—
user_roles	—
supporter_profiles	—

ORGANIZATIONS

missionaries	—
agencies	—
churches	—
colleges	—

AUTH & IDENTITY

donors	—
--------	---

PAGES

pages	—
page_approvals	—
page_media	—
page_widgets	—

DONATIONS

page_donations	—
donation_receipts	—

PRAYERS

prayers	—
prayer_reactions	—
prayer_updates	—

SOCIAL / FOLLOW

missionary_followers	—
church_followers	—
missionary_missionary_followers	—
missionary_churches	—
notifications	—

DIRECT MESSAGING

conversations	—
conversation_members	—
messages	—
message_reports	—

Homepage & Footer

homepage_banners	—
homepage_settings	—
footer_content	—

Auth & Identity

Data Dictionary Section

auth.users

Domain: Auth & Identity

Supabase managed authentication table. Stores all authenticated user credentials and session data. This is an external Supabase table and should not be modified directly. All other user-facing tables reference this via user_id (UUID).

Columns

Column Name	Data Type	Null	Key	Default	Description
id	uuid	N	PK	gen_random_uuid()	Unique user identifier (UUID), primary key for auth system.
email	text	Y			User's email address used for authentication.
created_at	timestampz	Y		now()	Timestamp when the auth account was created.
email_confirmed_at	timestampz	Y			Timestamp of email verification confirmation.
raw_app_meta_data	jsonb	Y			Provider and providers list (e.g. email, google).

Constraints & Indexes

- PRIMARY KEY: id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

users

Domain: Auth & Identity

Application-level user profile table. Extends auth.users with role, status, and display information. Every person who logs in should have a corresponding record here. The role field controls access permissions across the platform.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key.
user_id	uuid	Y	FK		References auth.users.id. Links app profile to auth account.
role	smallint	Y	FK		References user_roles.id. Controls platform access level.
status	varchar	Y		Pending	Account status: Pending, Active, Suspended, Inactive.
first_name	varchar	Y			User's first name for display purposes.
last_name	varchar	Y			User's last name for display purposes.
email	text	N			Email address (copied from auth for quick lookup).
last_activity	timestampz	Y			Timestamp of the user's most recent platform activity.
created_at	timestampz	N		now()	Timestamp when the user profile was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: role — user_roles.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

user_roles

Domain: Auth & Identity

Lookup table defining available user roles on the platform. Role IDs are referenced by users.role. Example values: 1 = Admin, 2 = Staff, 3 = Missionary, 4 = Donor, 5 = Church, 6 = Agency.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Unique role identifier. Referenced by users.role.
role	varchar	Y			Human-readable role label (e.g. Admin, Missionary, Donor).

Constraints & Indexes

- PRIMARY KEY: id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

supporter_profiles

Domain: Auth & Identity

Profile records specifically for supporter-type users (donors/followers who are not missionaries). Created when a supporter completes their profile. Stores contact information required for engagement and communication.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key.
user_id	uuid	N	FK		References auth.users.id. One-to-one with auth account.
first_name	text	N			Supporter's first name. Required field.
last_name	text	N			Supporter's last name. Required field.
email	text	N			Supporter's email address. Must be valid email format.
country_of_residence	text	N			Country where the supporter currently resides.
phone_number	text	Y			Optional phone number for contact purposes.
created_at	timestamptz	N		now()	Timestamp when the profile was created.
updated_at	timestamptz	N		now()	Timestamp of the last profile update.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Organizations

Data Dictionary Section

missionaries

Domain: Organizations

Central entity for missionary profiles. Each missionary has a user account and belongs to one or more organizations (agency, sending church, mission field church, college). Contains mission field information, Stripe Connect details for payouts, and messaging preferences.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key.
user_id	uuid	Y	FK		References auth.users.id. Links missionary to login account.
agency_id	bigint	Y	FK		References agencies.id. Mission agency the missionary belongs to.
sending_church_id	bigint	Y	FK		References churches.id. Home/sending church of the missionary.
mission_field_church_id	bigint	Y	FK		References churches.id. Church on the mission field (if applicable).
college_id	bigint	Y	FK		References colleges.id. Bible college or seminary attended.
first_name	varchar	N			Missionary's first name. Required.
last_name	varchar	N			Missionary's last name. Required.
email	text	Y	UQ		Contact email. Unique across all missionaries.
phone_number	varchar	Y			Contact phone number.
country_of_residence	varchar	Y			Country where the missionary currently lives.
destination_country	varchar	Y			Country or region of missionary service.
mission_status	varchar	Y			Current status: On-Field, Furlough, or Deputation.
biography	text	Y			Personal biography/testimony displayed on the profile page.
open_to_visits	boolean	Y		false	Whether the missionary accepts in-person visits from supporters.
allow_direct_messages	boolean	Y		true	Whether the missionary accepts direct messages from supporters.
stripe_account_id	text	Y			Stripe Connect account ID for direct payouts to the missionary.
payout_status	text	Y		not_started	Stripe payout onboarding status: not_started, pending, created, verified, incomplete.
payout_setup_completed_at	timestamptz	Y			Timestamp when Stripe Connect onboarding was completed.
created_at	timestamptz	Y		now()	Timestamp when the missionary record was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: agency_id — agencies.id
- FOREIGN KEY: sending_church_id — churches.id
- FOREIGN KEY: mission_field_church_id — churches.id
- FOREIGN KEY: college_id — colleges.id
- UNIQUE: email
- ROW LEVEL SECURITY (RLS) is enabled on this table.

agencies

Domain: Organizations

Mission agencies that oversee and support missionaries. An agency can be associated with multiple missionaries. The `contact_user_id` identifies the agency administrator who manages the agency account on the platform.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key.
contact_user_id	uuid	Y	FK		References auth.users.id. Primary admin contact for the agency.
name	varchar	N			Official agency name. Required.
email	text	Y			Agency contact email address.
phone_number	varchar	Y			Agency main phone number.
address	text	Y			Street address of the agency headquarters.
city	varchar	Y			City of the agency headquarters.
state	varchar	Y			State or province of the agency.
country	varchar	Y			Country of the agency headquarters.
website	text	Y			Agency website URL.
created_at	timestampz	Y		now()	Timestamp when the agency was added to the platform.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: contact_user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

churches

Domain: Organizations

Church organizations that partner with missionaries as sending or supporting churches. A church can send multiple missionaries and can follow missionary activity. Churches can have their own landing pages on the platform.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key.
contact_user_id	uuid	Y	FK		References auth.users.id. Primary admin contact for the church.
name	varchar	N			Official church name. Required.
phone_number	varchar	Y			Church main phone number.
address	text	Y			Street address of the church.
city	varchar	Y			City where the church is located.
state	varchar	Y			State or province where the church is located.
country	varchar	Y			Country where the church is located.
website	text	Y			Church website URL.
created_at	timestampz	Y		now()	Timestamp when the church was added to the platform.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: contact_user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

colleges

Domain: Organizations

Bible colleges and seminaries associated with missionaries' training. A missionary may list their college as part of their profile. Colleges can be managed by an admin contact user.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key.
contact_user_id	uuid	Y	FK		References auth.users.id. Admin contact for the college.
name	varchar	N			Official college name. Required.
email	text	Y			College contact email.
phone_number	varchar	Y			College main phone number.
address	text	Y			Street address of the college.
city	varchar	Y			City where the college is located.
country	varchar	Y			Country where the college is located.
website	text	Y			College website URL.
created_at	timestampz	Y		now()	Timestamp when the college was added to the platform.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: contact_user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Auth & Identity

Data Dictionary Section

donors

Domain: Auth & Identity

Donor profile records for individuals who make financial contributions. Linked to auth.users for authenticated donors. Anonymous donations may create a donor record without a user_id. Tracks Stripe customer data and total donated amount for reporting.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS)
user_id	uuid	Y	FK		References auth.users.id. Null for guest/anonymous donors.
first_name	text	N			Donor's first name. Required.
last_name	text	N			Donor's last name. Required.
email	text	Y	UQ		Donor email. Unique constraint — one donor profile per email
phone_number	text	Y			Donor's phone number for contact.
country	text	Y			Donor's country of residence.
city	text	Y			Donor's city of residence.
address	text	Y			Donor's mailing address.
postal_code	text	Y			Donor's postal / zip code.
organization_name	text	Y			Organization name if donating on behalf of a group or church.
stripe_customer_id	text	Y			Stripe customer ID for managing payment methods and subscriptions
donation_preference	text	Y			Donor's preferred giving frequency (one_time, monthly, etc.).
total_donated	numeric(12,2)	Y		0	Cumulative total donated amount across all transactions (USD)
is_active	boolean	Y		true	Whether the donor profile is currently active.
updated_at	timestamptz	Y		now()	Timestamp of last profile update.
created_at	timestamptz	Y		now()	Timestamp when the donor profile was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- UNIQUE: email
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Pages

Data Dictionary Section

pages

Domain: Pages

Public-facing profile pages for all organization types (missionary, church, agency, college, donor). Uses a polymorphic relationship: organization_type identifies the entity type and organization_id points to the corresponding table's primary key. Each entity type can have at most one page (enforced by unique constraint). Controls the donation mode per page.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
organization_type	text	N			Entity type: missionary church college agency donor.
organization_id	bigint	N			ID of the entity in the corresponding organization table (e.g., missionary_id).
page_url	text	Y	UQ		URL-friendly slug for the public profile page. Globally unique.
profile_photo_url	text	Y			Storage URL for the profile/avatar photo.
banner_photo_url	text	Y			Storage URL for the header banner image.
short_quote	text	Y			A short tagline or scripture verse displayed prominently.
about_text	text	Y			Full about/biography text for the profile page.
intro_text	text	Y			Short introductory text shown on preview cards.
is_published	boolean	Y		false	Whether the page is publicly visible. Must be approved to publish.
donation_mode	text	Y			Controls donations: harvest21 (platform), external (redirect URL), off (disabled).
external_donation_url	text	Y			External donation URL used when donation_mode = external.
published_at	timestamptz	Y			Timestamp when the page was first published.
created_at	timestamptz	Y		now()	Timestamp when the page record was created.
updated_at	timestamptz	Y		now()	Timestamp of the last page update.

Constraints & Indexes

- PRIMARY KEY: id
- UNIQUE: page_url
- ROW LEVEL SECURITY (RLS) is enabled on this table.

page_approvals

Domain: Pages

Tracks the approval workflow for publishing profile pages. A page must go through agency approval before being published. Status progresses from Pending !' Agency Approved !' Published. Admins can also Unpublish a page.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS)
page_id	bigint	N	FK		References pages.id. Cascades on delete.
requested_by	uuid	Y	FK		References auth.users.id. User who submitted the page for approval.
approved_by	uuid	Y	FK		References auth.users.id. Admin/agency who approved or rejected.
status	text	Y		Pending	Workflow status: Pending Agency Approved Published Unpublished
reviewed_at	timestamptz	Y			Timestamp when the approval decision was made.
created_at	timestamptz	Y		now()	Timestamp when the approval request was submitted.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: page_id — pages.id
- FOREIGN KEY: requested_by — auth.users
- FOREIGN KEY: approved_by — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

page_media

Domain: Pages

Media assets (images and videos) associated with a profile page. Supports multiple media items per page displayed in a gallery. Media is only visible to public when the parent page is published.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
page_id	bigint	N	FK		References pages.id. Cascades on delete.
media_type	text	Y			Asset type: image or video.
media_url	text	N			Storage or CDN URL of the media asset.
description	text	Y			Caption or description for the media item.
thumbnail_url	text	Y			URL of the video thumbnail image (for video type).
views	integer	Y			View count for this media item.
reactions	integer	Y			Reaction/like count for this media item.
created_at	timestampz	Y		now()	Timestamp when the media was uploaded.
updated_at	timestampz	Y			Timestamp of the last media metadata update.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: page_id — pages.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

page_widgets

Domain: Pages

Configurable content widgets displayed on a profile page. Widgets can display custom content sections such as prayer requests, ministry updates, or fundraising goals. Widget configuration is stored as JSONB for flexibility.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
page_id	bigint	N	FK		References pages.id. Cascades on delete.
widget_type	text	Y			Widget category identifier (e.g. prayer_list, update_feed, social_media).
widget_title	text	Y			Display title shown above the widget on the profile page.
widget_data	jsonb	Y			Flexible JSON configuration and content data for the widget.
created_at	timestampz	Y		now()	Timestamp when the widget was added to the page.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: page_id — pages.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Donations

Data Dictionary Section

page_donations

Domain: Donations

Records every donation transaction made through the platform. Supports both one-time and recurring donations via Stripe. Contains denormalized donor name and email fields (donor_first_name, donor_last_name, donor_email) captured at transaction time to preserve billing intent regardless of profile changes. The optional designation field allows donors to earmark gifts for specific projects.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
donor_id	bigint	Y	FK		References donors.id. Null for anonymous donations. Cascades to null on donor delete.
page_id	bigint	N	FK		References pages.id. The missionary/org page that received the donation.
user_id	uuid	Y	FK		References auth.users.id. Authenticated user who made the donation (available for reports).
amount	numeric(12,2)	N			Donation amount in the specified currency (e.g. 25.00).
currency	text	Y		USD	ISO 4217 currency code. Defaults to USD.
transaction_ref	text	Y			Legacy or external transaction reference number.
status	text	Y		Pending	Transaction status: Pending Complete Failed Refunded Suspended.
type	text	Y		one_time	Donation type: one_time (single charge) or recurring (subscription).
stripe_payment_intent_id	text	Y			Stripe PaymentIntent ID for one-time donations. Used for webhook reconciliation.
stripe_subscription_id	text	Y			Stripe Subscription ID for recurring donations.
stripe_invoice_id	text	Y			Stripe Invoice ID associated with a recurring donation cycle.
designation	text	Y			Optional donor-specified label for the gift (max 50 chars). Ex: "Korea Church Plant".
donor_first_name	text	Y			First name from billing form at donation time (denormalized snapshot).
donor_last_name	text	Y			Last name from billing form at donation time (denormalized snapshot).
donor_email	text	Y			Email from billing form at donation time (denormalized snapshot).
created_at	timestamptz	Y		now()	Timestamp when the donation record was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: donor_id — donors.id
- FOREIGN KEY: page_id — pages.id
- FOREIGN KEY: user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

donation_receipts

Domain: Donations

Official receipt records generated for each completed donation. Each receipt has a unique receipt number for accounting. Tracks delivery status of the emailed receipt to the donor. Linked to both the donation transaction and the donor profile.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
page_donation_id	bigint	N	FK		References page_donations.id. The transaction this receipt belongs to.
donor_id	bigint	Y	FK		References donors.id. The donor who receives this receipt.
amount	numeric	N			Amount shown on the receipt (matches donation amount).
currency	text	N		USD	Currency code for the receipt amount.
receipt_number	text	N	UQ		Unique human-readable receipt number for accounting reference.
issued_at	timestamptz	N		now()	Timestamp when the receipt was formally issued.
sent_at	timestamptz	Y			Timestamp when the receipt email was sent to the donor.
delivery_status	text	Y		pending	Email delivery status: pending sent delivered failed.
created_at	timestamptz	N		now()	Timestamp when the receipt record was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: page_donation_id — page_donations.id
- FOREIGN KEY: donor_id — donors.id
- UNIQUE: receipt_number
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Prayers

Data Dictionary Section

prayers

Domain: Prayers

Prayer requests created by users and associated with profile pages. Supports public and private visibility. Tracks amen (reaction) counts and update counts. Soft-deleted via deleted_at rather than hard deletes to preserve referential integrity.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing primary key.
user_id	uuid	N	FK		References auth.users.id. Author of the prayer request.
page_id	bigint	Y	FK		References pages.id. Page this prayer is associated with (optional).
title	text	Y			Optional short title/subject for the prayer request.
body	text	N			Main prayer request text. Required.
is_published	boolean	N		true	Whether the prayer is visible to others (unpublished = draft).
visibility	text	N		public	Audience: public (anyone) private (author only) suggestions (followers only)
amen_count	integer	N		0	Count of amen reactions. Maintained by trigger keep_amen_count
update_count	integer	N		0	Count of prayer updates/answers. Maintained by trigger keep_update_count
share_count	integer	N		0	Number of times this prayer has been shared externally.
deleted_at	timestamptz	Y			Soft delete timestamp. Non-null means the record is logically deleted.
created_at	timestamptz	N		now()	Timestamp when the prayer was created.
updated_at	timestamptz	N		now()	Timestamp of last update. Maintained by set_updated_at trigger.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: page_id — pages.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

prayer_reactions

Domain: Prayers

Records "Amen" reactions from users on prayer requests. One reaction per user per prayer (enforced by unique constraint). When a reaction is inserted or deleted, the bump_amen_count trigger updates prayers.amen_count automatically.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing primary key.
user_id	uuid	N	FK		References auth.users.id. User who reacted. Cascades on delete.
prayer_id	bigint	N	FK		References prayers.id. Prayer that received the reaction. Cascades on delete.
type	text	N		amen	Reaction type. Currently only "amen" is supported.
created_at	timestamptz	N		now()	Timestamp when the reaction was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: prayer_id — prayers.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

prayer_updates

Domain: Prayers

Text updates/answers posted by the prayer author on a prayer request. Allows the original author to share how God answered or updated the situation. The bump_update_count trigger keeps prayers.update_count in sync.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing primary key.
user_id	uuid	N	FK		References auth.users.id. Author posting the update. Cascades on delete.
prayer_id	bigint	N	FK		References prayers.id. Parent prayer request. Cascades on delete.
body	text	N			Content of the prayer update or answered prayer testimony.
created_at	timestampz	N		now()	Timestamp when the update was posted.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: prayer_id — prayers.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Social / Follow

Data Dictionary Section

missionary_followers

Domain: Social / Follow

Tracks follow requests and approved follower relationships between supporters and missionaries. A user sends a follow request (status: pending) and the missionary approves or rejects it. Once accepted, the supporter can view supporter-only content and send direct messages. The optional note field allows the requester to introduce themselves.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
missionary_id	bigint	N	FK		References missionaries.id. The missionary being followed. Cascades on delete.
user_id	uuid	N	FK		References auth.users.id. The user sending the follow request.
status	text	N		pending	Follow status: pending accepted rejected. Unique per pair.
note	text	Y			Optional introduction note from the requester (max 100 chars).
requested_at	timestamptz	Y		now()	Timestamp when the follow request was submitted.
reviewed_at	timestamptz	Y			Timestamp when the missionary reviewed the request.
reviewed_by	uuid	Y	FK		References auth.users.id. Who approved/rejected (usually the missionary).
created_at	timestamptz	Y		now()	Timestamp when the record was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: missionary_id — missionaries.id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: reviewed_by — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

church_followers

Domain: Social / Follow

Tracks follow relationships between users and church organizations. Works similarly to missionary_followers with an approval workflow. Allows churches to approve who can see supporter-only content on their page.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
church_id	bigint	N	FK		References churches.id. The church being followed.
user_id	uuid	N	FK		References auth.users.id. The user sending the follow request.
status	text	N		pending	Follow status: pending accepted rejected.
note	text	Y			Optional introduction note from the requester (max 100 chars).
requested_at	timestamptz	Y		now()	Timestamp when the follow request was submitted.
reviewed_at	timestamptz	Y			Timestamp when the church admin reviewed the request.
reviewed_by	uuid	Y	FK		References auth.users.id. Who reviewed the request.
created_at	timestamptz	Y		now()	Timestamp when the record was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: church_id — churches.id
- FOREIGN KEY: user_id — auth.users
- FOREIGN KEY: reviewed_by — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

missionary_missionary_followers

Domain: Social / Follow

Tracks peer follow relationships between missionaries (missionary-to-missionary following). Allows missionaries to follow each other's ministry updates. Uses the same approval workflow as missionary_followers. The note field allows the requesting missionary to introduce themselves.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS)
followed_missionary_id	bigint	N	FK		References missionaries.id. The missionary whose content is being followed.
follower_missionary_id	bigint	N	FK		References missionaries.id. The missionary doing the following.
status	text	N		pending	Follow status: pending accepted rejected.
note	text	Y			Optional introduction note from the requester (max 100 chars).
reviewed_at	timestamptz	Y			Timestamp when the target missionary reviewed the request.
reviewed_by	uuid	Y	FK		References auth.users.id. Who reviewed the request.
created_at	timestamptz	Y		now()	Timestamp when the record was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: followed_missionary_id — missionaries.id
- FOREIGN KEY: follower_missionary_id — missionaries.id
- FOREIGN KEY: reviewed_by — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

missionary_churches

Domain: Social / Follow

Many-to-many pivot table linking missionaries to churches with a typed relationship. A missionary can have multiple church relationships (sending, supporting, partner). A church can support multiple missionaries. Used to build the missionary's church network displayed on their profile.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
missionary_id	bigint	N	FK		References missionaries.id. Cascades on delete.
church_id	bigint	N	FK		References churches.id. Cascades on delete.
relationship_type	text	Y		supporting	Nature of the relationship: sending supporting partner.
is_active	boolean	Y		true	Whether this church-missionary relationship is currently active.
created_at	timestampz	Y		now()	Timestamp when the relationship was established.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: missionary_id — missionaries.id
- FOREIGN KEY: church_id — churches.id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

notifications

Domain: Social / Follow

In-app notification records delivered to users. Generated automatically when follow requests are received, approved, or when other platform events occur. Supports soft notification clearing via is_read flag. Can reference a related entity (e.g. a follow request ID) for deep linking.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
user_id	uuid	N	FK		References auth.users.id. Recipient of the notification.
type	text	N			Notification category (e.g. follow_request, follow_approved, notification_received).
title	text	N			Short notification title displayed in the notification list.
message	text	Y			Longer notification body text.
is_read	boolean	Y		false	Whether the user has read/dismissed this notification.
related_entity_type	text	Y			Type of entity this notification refers to (e.g. notification_received).
related_entity_id	bigint	Y			ID of the related entity for deep linking from the notification.
created_at	timestampz	Y		now()	Timestamp when the notification was generated.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Direct Messaging

Data Dictionary Section

conversations

Domain: Direct Messaging

Direct message thread between one missionary and one supporter. Each unique missionary–supporter pair can have only one conversation (enforced by unique constraint). Stores a preview of the last message for efficient list rendering without loading messages.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
missionary_id	bigint	N	FK		References missionaries.id. One of the two participants. Cascades on delete.
supporter_id	uuid	N	FK		References auth.users.id. The supporter participant. Cascades on delete.
last_message_at	timestamptz	Y		now()	Timestamp of the most recent message. Used for sorting conversations list.
last_message_preview	text	Y			Truncated preview of the most recent message content.
last_message_sender_id	uuid	Y			auth.users.id of who sent the last message.
created_at	timestamptz	Y		now()	Timestamp when the conversation was started.
updated_at	timestamptz	Y		now()	Timestamp of the last conversation update.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: missionary_id — missionaries.id
- FOREIGN KEY: supporter_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

conversation_members

Domain: Direct Messaging

Tracks participants in each conversation and their unread message count. Each conversation has exactly two members (the missionary and the supporter). Provides efficient access control and per-user unread badge counts without scanning the messages table.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
conversation_id	bigint	N	FK		References conversations.id. Cascades on delete.
user_id	uuid	N	FK		References auth.users.id. A participant in the conversation. Cascades on delete.
unread_count	integer	Y		0	Number of unread messages for this participant. Used for badge display.
last_read_at	timestampz	Y		now()	Timestamp of when this participant last read the conversation.
created_at	timestampz	Y		now()	Timestamp when the membership was created.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: conversation_id — conversations.id
- FOREIGN KEY: user_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

messages

Domain: Direct Messaging

Individual message records within a conversation. Messages are limited to 5,000 characters. Real-time delivery is enabled via Supabase Realtime subscriptions on this table. The is_read flag tracks individual message read status.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
conversation_id	bigint	N	FK		References conversations.id. Cascades on delete.
sender_id	uuid	N	FK		References auth.users.id. User who sent the message.
content	text	N			Message body text. Must be 1–5,000 characters (CHECK CONSTRAINT).
is_read	boolean	Y		false	Whether the recipient has read this specific message.
created_at	timestamptz	Y		now()	Timestamp when the message was sent.
updated_at	timestamptz	Y		now()	Timestamp of last message edit (if editing is supported).

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: conversation_id — conversations.id
- FOREIGN KEY: sender_id — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

message_reports

Domain: Direct Messaging

Abuse reports submitted by users for inappropriate messages or conversations. Supports moderation workflows where admins can review and resolve reports. Can reference either a specific message or the entire conversation.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS)
conversation_id	bigint	N	FK		References conversations.id. The conversation containing the reported content.
message_id	bigint	Y	FK		References messages.id. Specific message reported (null if reporting whole conversation)
reported_by	uuid	N	FK		References auth.users.id. User who filed the report.
report_type	text	N			Report category: message (specific message) or conversation (entire thread)
reason	text	Y			Detailed reason or description provided by the reporter.
status	text	Y		pending	Review status: pending reviewed resolved.
reviewed_by	uuid	Y	FK		References auth.users.id. Admin who reviewed the report.
reviewed_at	timestamptz	Y			Timestamp when the admin reviewed the report.
created_at	timestamptz	Y		now()	Timestamp when the report was submitted.

Constraints & Indexes

- PRIMARY KEY: id
- FOREIGN KEY: conversation_id — conversations.id
- FOREIGN KEY: message_id — messages.id
- FOREIGN KEY: reported_by — auth.users
- FOREIGN KEY: reviewed_by — auth.users
- ROW LEVEL SECURITY (RLS) is enabled on this table.

Homepage & Footer

Data Dictionary Section

homepage_banners

Domain: Homepage & Footer

Carousel and static banner images displayed on the public homepage. Each banner has a mission field location, descriptive text, and image URL. The display_order field controls the sequence of carousel slides. Managed by admins through the homepage settings panel.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS).
banner_type	text	Y		carousel	Display type: carousel static video.
is_active	boolean	Y		true	Whether this banner is currently shown on the homepage.
display_order	integer	N			Sort order for carousel display. Lower numbers appear first.
location	text	N			Mission field location label displayed on the banner (e.g. "Ghana").
description	text	N			Short description text overlaid or shown beneath the banner image.
image_url	text	N			Path or URL to the banner image file.
scroll_duration	integer	Y		5000	Auto-scroll duration in milliseconds for carousel mode.
created_at	timestamptz	Y		now()	Timestamp when the banner was added.
updated_at	timestamptz	Y		now()	Timestamp of last banner update.

Constraints & Indexes

- PRIMARY KEY: id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

homepage_settings

Domain: Homepage & Footer

Singleton configuration table for homepage carousel behaviour. Only one row is expected. Controls global carousel settings such as auto-scroll timing, navigation arrows, and pagination dots. Managed through the admin homepage settings panel.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS). Expect single row.
banner_type	text	Y		carousel	Global banner display type: carousel static video.
auto_scroll	boolean	Y		true	Whether the carousel auto-advances between slides.
scroll_timing	integer	Y		5000	Auto-advance interval in milliseconds.
show_navigation_arrows	boolean	Y		true	Whether left/right navigation arrows are displayed.
show_pagination_dots	boolean	Y		true	Whether slide indicator dots are displayed below the carousel.
created_at	timestamptz	Y		now()	Timestamp when the settings record was created.
updated_at	timestamptz	Y		now()	Timestamp of last settings update.

Constraints & Indexes

- PRIMARY KEY: id
- ROW LEVEL SECURITY (RLS) is enabled on this table.

footer_content

Domain: Homepage & Footer

Stores editable text content for all footer navigation pages (About Us, Statement of Faith, FAQ, Privacy Policy, etc.). Each page_type is unique, meaning one content block exists per footer page. Content is managed by admins through the site settings panel.

Columns

Column Name	Data Type	Null	Key	Default	Description
id	bigint	N	PK	identity	Auto-incrementing surrogate primary key (GENERATED ALWAYS)
page_type	text	N	UQ		Footer page identifier (unique): about_us statement_of_faith dental food contact_us etc.
title	text	N			Page heading displayed at the top of the footer content
content	text	N			Full page body content in plain text or markdown format.
created_at	timestamptz	Y		now()	Timestamp when the content was first created.
updated_at	timestamptz	Y		now()	Timestamp of the last content edit.

Constraints & Indexes

- PRIMARY KEY: id
- UNIQUE: page_type
- ROW LEVEL SECURITY (RLS) is enabled on this table.