With this object you've access to the SAP Business one Datainterface (DI-API)

Note: If it possible: User *Beas Service Layer*. This is the new interface for creating documents and support all Beas Rules.

How to use ue_api_sbo:

You can declare it with

```
declare=[objektname]=ue_api_sbo
```

Now you can access the DI-API directly via Object Names.

Example: change item-entry

```
declare=myitem=ue_api_sbo
myitem=getbusinessobject=oitem
myitem=getbykey=A001
myitem=itemname=new itemname
myitem=update
destroy=myitem
```

You can access almost any Property with api_sbo. api_sbo will not perform any checks.
More information can be found within the SAP SDK Documentation.

Important: Only one DI-API Object a time is allowed.

don't work with

```
declare=b1=ue_api_sbo
declare=b2=ue_api_sbo
```

because you can have problems with special variables as example "<getlasterror>"
After using the DI-API object: Destroy it! Otherwise you can produce bad mirror effects.

Error handling

The Object return values in the return object

Return code: <objectname.ret_code> -1 = error, 1 = ok

Return Text: <objectname.ret_text> Return last error

Additional information about error you can read with <objectname.getlasterror>.

```
vdoc.add
if <vdoc.ret_code> = -1 then
 message=fehler$error create Order: <vdoc.getlasterror>
end if
```

Functions like add, getbusinessobject, update, getbykey and so on will return "value"

```
vdoc.ret_code = 1  = ok
vdoc.ret_code = -1 = error
```

Additional examples

Create goods receipt

```
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=59
di_doc=lines=itemcode=Jesús
di_doc=lines=quantity=1
di_doc=add

if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
 return failure
end if
destroy=di_doc
```

Goods Receipt with UDF

```
//Create goods receipt with UserFields
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=59
di_doc=lines=itemcode=RM
di_doc=lines=quantity=1
di_doc=lines=userfield=U_test2=N
di_doc=add

if <di_doc.ret_code> = -1 then
```

```
 message=error$item not found <di_doc.getlasterror>
 return failure
end if
destroy=di_doc
```

Goods Receipt with Batches and Serials

```
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=59
di_doc=lines=itemcode=RAWMAT_NORMAL
di_doc=lines=quantity=100
di_doc=lines=add
di_doc=lines=itemcode=RAWMAT_BATCH
di_doc=lines=quantity=100
di_doc=lines=batchnumber=batchnumber=<today,yyyymmdd>
di_doc=lines=batchnumber=quantity=100
di_doc=lines=add
di_doc=lines=itemcode=RAWMAT_SERIAL
di_doc=lines=quantity=5
di_doc=lines=serialnumbers=internalserialnumber=<today,yyyymmdd><now,hhmmss>_1
di_doc=lines=serialnumbers=quantity=1
di_doc=lines=serialnumbers=add
di_doc=lines=serialnumbers=internalserialnumber=<today,yyyymmdd><now,hhmmss>_2
di_doc=lines=serialnumbers=quantity=1
di_doc=lines=serialnumbers=add
di_doc=lines=serialnumbers=internalserialnumber=<today,yyyymmdd><now,hhmmss>_3
di_doc=lines=serialnumbers=quantity=1
di_doc=lines=serialnumbers=add
di_doc=lines=serialnumbers=internalserialnumber=<today,yyyymmdd><now,hhmmss>_4
di_doc=lines=serialnumbers=quantity=1
di_doc=lines=serialnumbers=add
di_doc=lines=serialnumbers=internalserialnumber=<today,yyyymmdd><now,hhmmss>_5
di_doc=lines=serialnumbers=quantity=1
di_doc=add

if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
```

```
 return failure
end if
destroy=di_doc
```

Create Purchase order

```
//Work with Purchase order
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=22
di_doc=cardcode=P001
di_doc=lines=itemcode=Jesús
di_doc=lines=quantity=1
di_doc=add

if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
 return failure
end if

destroy di_doc
```

Create Goods Receipt PO based on a purchase order

```
//Create Goods receipt PO based on a purchase order
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=20
di_doc=lines=itemcode=Jesús
di_doc=lines=quantity=2
di_doc=lines=basetype=22
di_doc=lines=baseentry=1371
di_doc=lines=baseline=0
di_doc=add
if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
 return failure
end if

destroy di_doc
```

Create SAP Receipt from production

```
//Create SAP receipt from production
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=59
//di_doc=lines=itemcode=SAP_BOM
di_doc=lines=quantity=1
di_doc=lines=basetype=202
di_doc=lines=baseentry=34
di_doc=lines=baseline=0
di_doc=add
if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
 return failure
end if

destroy di_doc
```

Sales return with Batchnumbers

```
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=16
di_doc=cardcode=C001
di_doc=lines=itemcode=batchitem
di_doc=lines=quantity=2
di_doc=lines=whscode=02
di_doc=lines=batchnumber=batchnum=test
di_doc=lines=batchnumber=quantity=1
di_doc=lines=batchnumber=add
di_doc=lines=batchnumber=batchnum=test2
di_doc=lines=batchnumber=quantity=1
di_doc=add

if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
 return failure
end if
```

```
setvar=newkey=<di_doc.getnewobjectkey>


destroy di_doc
```

Create Inventory transfer based on a transfer request

```
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=16
di_doc=lines=itemcode=Jesús
di_doc=lines=quantity=1
di_doc=lines=batchnumber=batchnum=111
di_doc=lines=batchnumber=quantity=1
di_doc=lines=basetype=5
di_doc=lines=baseentry=<ls_docentry>
di_doc=lines=baseline=<ls_linenum>
di_doc=add

//Create Inventory transfer
declare=di_doc=ue_api_sbo
di_doc=getbusinessobject=67
di_doc=lines=itemcode=RM_B
di_doc=lines=quantity=1
di_doc=lines=batchnumber=batchnum=20190209
di_doc=lines=batchnumber=quantity=1
di_doc=lines=fromwhscode=01
di_doc=lines=whscode=02
di_doc=add

if <di_doc.ret_code> = -1 then
 message=error$item not found <di_doc.getlasterror>
 return failure
end if

setvar=newkey=<di_doc.getnewobjectkey>


destroy di_doc
```

Functions

debug=y	extended Debugging
connect_extern	connect to external database. see connect_extern

Methoden (generell)

add	add a document return variable "value" 0=failure, 1=ok Example ...

```
// create manual goods receipt
// table oign/ign1
declare=mrcp=ue_api_sbo
mrcp=getbusinessobject=59
// set current stationname
mrcp=U_beas_station=<stationname>
mrcp=line.itemcode=9008100021
mrcp=line.price=3.44
mrcp=line.quantity=5
mrcp=add
// error?
if <value> = 0 then
 messagebox=error$$document not created:
<mrcp.getlasterror>
 destroy=mrcp
 return failure
end if
// get last docentry - from this station
select max("DocEntry") into ll_docentry from
"OIGE" &
   where "U_beas_station"=<stationname,dbstring>
```

	messagebox=ok$$Document <ll_docentry> created
cancel	cancel
close	close the document
savetofile=<file>	save document to file
savexml=<file>	save document to xmlfile
getasxml=<file>	get document from xml-file
getbusinessobject=<documenttype>	create business object (see examples). see documenttyp
getbusinessobjectfromxml=<path>	Load object from definition saved in "path" file
update	save return variable "value" 0 = failure, 1 = ok In Silent-Mode return variable "errortext" with the current Error, only if value=0
getbykey	get entry (only char. if numeric: getbykeynum) after loading you can get all information from the current object. Attention: only with correct lower / uppercase
getbykey	get entry (typ numeric)
silent=true/false	set silent-Mode in silent-mode beas set only variables and send no error-Meesage