# CVEs más relevantes de la semana

Del 06/10/2026 al 13/10/2026

Porque el primer paso para defender es conocer las amenazas.



# CVE-2026-93675

Descripción: IBM Langflow OSS 1.0.0 through 1.12.2 could allow a remote attacker to execute arbitrary code due to an expected dependency confusion.

CVSS: 8.8 (HIGH)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:U/C:H/I:H/A:H

Tipo: CWE-440

Tecnología: No especificado

Publicado el: 2026-10-07

# CVE-2026-81535

Descripción: In wolfSSH through 1.5.0 built with --enable-fwd, DoChannelOpen() in src/internal.c gates only direct-tcpip channel opens with the forwarding policy callback. forwarded-tcpip opens are admitted without an authorization check and are not capped in number, allowing a malicious SSH peer to make an endpoint allocate unbounded per-channel buffers for forwarding channels the application never authori...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-862

Tecnología: No especificado

Publicado el: 2026-10-07



vulnerability in Apache Jackrabbit.

Jackrabbit WebDAV server attaches a cached authenticated session
on any Lock-Token/TransactionId/SubscriptionId/If-header field
token match with

no credential check.

This issue affects Apache Jackrabbit: from 2.23.0 through 2.23.5,
from 2.22.0 through 2.22.4, from 2.20.0 through 2.20.17.

Users...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-384



# CVE-2026-76454

Descripción: A vulnerability in the Cisco Smart Licensing Utility API of Cisco License On-Prem, formerly Cisco Smart Software Manager On-Prem (SSM On-Prem), could allow an unauthenticated, remote attacker to write arbitrary files to the system or cause a DoS condition on an affected application. This vulnerability is due to improper input validation and a lack of authentication in the management API. An ...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:H

Tipo: CWE-23

Tecnología: No especificado

Publicado el: 2026-10-07

# CVE-2026-76459

Descripción: As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco NX-OS engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-76459 are related to out-of-bounds write issues that are grouped und...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-10-07

# CVE-2026-76285

Descripción: Improper Adherence to Coding Standards. Splunk addressed multiple internally identified vulnerabilities in Splunk Enterprise versions 10.4.3, 10.2.7, 10.0.10, and 9.4.15. The vulnerabilities are grouped by Common Weakness Enumeration (CWE), with one Common Vulnerabilities and Exposures (CVE) identifier assigned to each group. See Details for more information.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-710

Tecnología: No especificado

Publicado el: 2026-10-07

# CVE-2026-87659

Descripción: A critical authorization bypass vulnerability exists in the Management Server handling of Brocade Fabric OS versions before 10.0.1. A compromised switch connected to the fabric can transmit crafted inband Fibre Channel vendor-unique CT (Common Transport) management requests to bypass administrative authentication. Successful exploitation allows an unauthorized peer switch to execute administrat...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-107699

Descripción: ppt2png through 0.0.6 contains an OS command injection vulnerability that allows attackers to execute operating system commands by supplying unsanitized input or output path arguments. Attackers can append shell metacharacters such as ';' to file names passed to child_process.exec() in ppt2png.js, running commands with Node.js process privileges.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-78

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-104075

Descripción: TVU Networks Receiver/Transceiver devices running firmware before version 7.9 contain an authentication bypass vulnerability in the web management login endpoint POST /tvu/Login that allows remote unauthenticated attackers to obtain an administrative session by submitting an empty or absent UserName parameter. Attackers can send a crafted HTTP request directly, bypassing client-side JavaScript ...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-288

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-106629

Descripción: Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session. Scope is...

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-10-13

# Resumen del Reporte

CVEs analizados: 100

Promedio CVSS: 9.61

Fuente: nvd.nist.gov

Nos vemos la próxima semana. Hack the Cat 



# CVE-2026-82334

Descripción: IBM Guardium Data Protection 12.0, 12.1, 12.2 is vulnerable to a heap-based out-of-bounds read in the TDS7 LOGIN7 protocol parser. A remote attacker could send a specially crafted TDS LOGIN7 packet containing invalid offset or length values, potentially causing information disclosure or denial of service.

CVSS: 8.1 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-125

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-82335

Descripción: IBM Guardium Data Protection 12.0, 12.1, 12.2 is vulnerable to a heap-based buffer overflow in the MongoDB protocol parser. A remote attacker could send a specially crafted MongoDB SCRAM username containing an excessive length and cause memory corruption, potentially resulting in denial of service or arbitrary code execution.

CVSS: 8.1 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-82344

Descripción: IBM Guardium Data Protection 12.0, 12.1 is vulnerable to a heap-based buffer overflow in the S-TAP TrafficTap TDS login reassembly functionality. An unauthenticated remote attacker can send crafted TDS login fragments that exceed the fixed-size reassembly buffer, potentially resulting in denial of service or arbitrary code execution on the affected system.

CVSS: 8.1 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-107779

Descripción: Dromara Skyeye through commit 003549ae5615bd114ba5bb8ddf6a8e8ead97c321 contains a missing authentication vulnerability in bundled xxl-job-admin JobInfoController endpoints annotated with @PermissionLimit(limit = false). Unauthenticated attackers can POST GLUE_SHELL, GLUE_PYTHON, or GLUE_POWERSHELL jobs with attacker-supplied glueSource to /jobinfo/addAndStart, executing commands on the executor...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-10-08

# CVE-2026-76779

Descripción: Dell Secure Connect Gateway (SCG) Policy Manager, versions prior to 5.34.00.16, contains an Improper Restriction of Excessive Authentication Attempts vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to Elevation of privileges, Protection mechanism bypass, and Unauthorized access.

CVSS: 7.4 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-307

Tecnología: No especificado

Publicado el: 2026-10-09

# CVE-2026-108107

Descripción: PHPNuxBill through 2025.3.20 contains an unauthenticated SQL injection vulnerability in the radius.php FreeRADIUS REST endpoint that interpolates request parameters into whereRaw() queries. Attackers can send crafted username, macAddr or nasid parameters to the accounting or authenticate actions to extract customer records and credentials via time-based blind SQL injection.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-89

Tecnología: No especificado

Publicado el: 2026-10-09

# CVE-2026-108707

Descripción: Wukong_HRM through commit 186115e contains an authentication bypass vulnerability in ParamAspect that allows unauthenticated attackers to call every HRM API endpoint by omitting the AUTH-TOKEN header. Attackers gain HR administrator access to read payslips, salary history and employee personal data, download attachments, and modify or delete company-wide HR records.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-287

Tecnología: No especificado

Publicado el: 2026-10-11

# CVE-2026-108540

Descripción: A flaw has been found in OpenSpug Spug up to 3.4.0/4.0.1. This impacts an unknown function of the file /exec/transfer of the component File Transfer. Executing a manipulation can lead to os command injection. The attack may be launched remotely. The exploit has been published and may be used. The vendor was contacted early about this disclosure but did not respond in any way.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-10-11

# CVE-2026-108860

Descripción: BotSharp through 5.2.0 contains an authentication bypass vulnerability that allows unauthenticated remote attackers to forge bearer tokens using the hard-coded Jwt:Key in WebStarter appsettings.json. Attackers can sign tokens with the committed HMAC secret and fixed botsharp issuer and audience to impersonate any known user, including administrators, on Authorize-protected API routes.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-321

Tecnología: No especificado

Publicado el: 2026-10-11

# CVE-2026-108804

Descripción: A vulnerability was detected in TRENDnet TEW-751DR, TEW-752DRU and TEW733GR 1.03B01/1.03B03. Affected is the function fwrite of the file pigwidgeon.cgi of the component Web Management Backend. The manipulation of the argument service results in os command injection. It is possible to launch the attack remotely. The exploit is now public and may be used. The vendor confirms: "As this router was ...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108892

Descripción: A vulnerability was determined in Linksys E1700 1.0.0.4.003. This vulnerability affects the function ssid1MACFilter of the file /goform/ssid1MACFilter of the component Mac Filter. This manipulation of the argument newap_text_%d causes stack-based buffer overflow. The attack may be initiated remotely. The exploit has been publicly disclosed and may be utilized. The vendor was contacted early abo...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108894

Descripción: A security flaw has been discovered in Linksys E1700 1.0.0.4.003. Impacted is the function addStaticRoute of the file /goform/addStaticRoute of the component Static Route Handler. Performing a manipulation of the argument staticRoute_IP_setting/staticRoute_Netmask_setting/staticRoute_Gateway_setting/staticRoute_Metric_setting results in os command injection. Remote exploitation of the attack is...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108896

Descripción: A vulnerability was found in Linksys E1700 1.0.0.4.003. This affects the function setLinksysIpv6 of the file /goform/setLinksysIpv6. The manipulation of the argument _6rd_prefix/_6rd_prefix_len results in os command injection. The attack can be launched remotely. The exploit has been made public and could be used. The vendor was contacted early about this disclosure but did not respond in any way.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108914

Descripción: A flaw has been found in Edimax BR-6208AC 1.32. Affected by this issue is some unknown functionality of the file /goform/formWlSiteSurvey. This manipulation of the argument ifname causes buffer overflow. Remote exploitation of the attack is possible. The exploit has been published and may be used. The vendor was contacted early about this disclosure but did not respond in any way. This vulnerab...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-109321

Descripción: Grav Login OAuth plugin (grav-plugin-login-oauth) before 1.4.3 provisions OAuth accounts as ordinary Grav users with a deterministic <provider>.<id> username and an unsalted MD5 hash of the provider identifier as the password, without disabling password login. Unauthenticated remote attackers who learn or guess a provider identifier can reproduce these credentials and log in, gaining administra...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-1391

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108918

Descripción: A vulnerability was identified in Edimax BR-6208AC 1.32. Impacted is an unknown function of the file /goform/formWlanMP. The manipulation of the argument readE2P leads to command injection. It is possible to initiate the attack remotely. The exploit is publicly available and might be used. The vendor was contacted early about this disclosure but did not respond in any way. This vulnerability on...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-74

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-87744

Descripción: A flaw was found in Quarkus REST Data Panache. This vulnerability allows unauthenticated attackers to bypass security controls on generated endpoints. When a developer customizes a specific operation using @MethodProperties without explicitly re-declaring security roles, the code generator silently drops class-level security requirements. This results in the affected endpoint defaulting to perm...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-425

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108929

Descripción: A flaw has been found in Netcore NR268 1.7.121109. The affected element is the function execvp of the file /router/DDNSset.cgi of the component DDNS. Executing a manipulation of the argument Hostname can lead to argument injection. The attack can be launched remotely.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-74

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-109566

Descripción: Rapyd Admin from 9.0.0 before 9.20.0 contains a hard-coded credentials vulnerability that allows remote unauthenticated attackers to gain super-admin access through an AuthSeeder-created admin@laravel account with password admin. The account is seeded by the setup installer and silently re-created on every rpd:make run, letting attackers log in as a global super admin bypassing per-record autho...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-798

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-82101

Descripción: IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to cause a denial of service due to a path traversal vulnerability.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:N/I:H/A:H

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-82110

Descripción: IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to execute arbitrary code due to improper validation of pathname during a path traversal.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:N/I:H/A:H

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-10-12

# CVE-2026-108971

Descripción: A flaw has been found in D-Link DCS-930L B1.08B4. This impacts the function mpfd_decode of the file bootloader_region.bin of the component Emergency HTTP Recovery Server. Executing a manipulation of the argument firmware can lead to improper verification of cryptographic signature. The attack may be performed from remote. The exploit has been published and may be used.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-345

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-109108

Descripción: A security vulnerability has been detected in Wavlink WL-WN530BE1-A 251117. This affects the function popen of the file /cgi-bin/uploadVpn.cgi. Such manipulation of the argument Type leads to os command injection. The attack may be performed from remote. The exploit has been disclosed publicly and may be used. The vendor was contacted early about this disclosure.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-109109

Descripción: A vulnerability was detected in Wavlink WL-WN530BE1-A 251117. This vulnerability affects the function strcpy of the file /cgi-bin/ExportAllSettings.cgi of the component Settings Export CGI. Performing a manipulation of the argument HTTP_COOKIE/X-Cmd results in stack-based buffer overflow. It is possible to initiate the attack remotely. The exploit is now public and may be used. The vendor was c...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-109110

Descripción: A flaw has been found in Wavlink WL-WN592AX6 250422. This issue affects the function system of the component wmapd Daemon. Executing a manipulation can lead to os command injection. It is possible to launch the attack remotely. The exploit has been published and may be used. The vendor was contacted early about this disclosure.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-44415

Descripción: Affected systems do not properly restrict access to internal APIs and paths for authenticated users. This could allow an authenticated remote attacker to access sensitive internal information, which in the worst case could be leveraged to facilitate unauthorized access to the system or result in the deletion of data.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-35

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-63353

Descripción: Affected devices do not properly sanitize comment fields contained in imported trace files before rendering them on the Trace page. This could allow an attacker to social engineer an authorized user who holds the function right "Read diagnostics" into importing a specially crafted trace file. Successful exploitation could allow attacker-controlled JavaScript to execute in the user's browser ...

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-63354

Descripción: Affected devices do not properly validate and sanitize visual marker data contained in imported CSV trace files before rendering it on the Trace page.  This could allow an attacker to social engineer an authorized user who holds the function right "Read diagnostics" into importing a specially crafted trace file. Successful exploitation could allow attacker-controlled JavaScript to execute in ...

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-109157

Descripción: A vulnerability was found in TRENDnet TEW-432BRP 3.10B20. Affected by this vulnerability is the function formTcpipSetup of the file /goform/formTcpipSetup. Performing a manipulation of the argument Name results in stack-based buffer overflow. It is possible to initiate the attack remotely. The exploit has been made public and could be used. The vendor confirms: "As this router was EOL'd in 2011...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-74040

Descripción: Wazuh versions from 3.9.0 before 4.14.8 contain an arbitrary file overwrite vulnerability in MasterHandler.process_files_from_worker allowing a cluster worker to overwrite protected master files. Attackers controlling a worker can use a trailing-slash basename bypass and missing extra_valid enforcement to overwrite ossec.conf and agent.conf, achieving root remote code execution across the manag...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-862

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-74041

Descripción: Wazuh 4.14.3 before 4.14.8 contains a case-sensitivity mismatch between the ossec.conf validator and wazuh-logcollector that bypasses remote-command validation. Authenticated users with manager:update_config can inject an uppercase LOG_FORMAT command localfile that the collector runs as root on reload.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-178

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-100133

Descripción: Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session. Scope is changed.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-100202

Descripción: Use after free in Windows Message Queuing Queue Manager allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-100219

Descripción: Use after free in Microsoft QUIC allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-100222

Descripción: Heap-based buffer overflow in Network Policy Server (NPS) allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-102210

Descripción: Heap-based buffer overflow in Windows Text Shaping allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-103849

Descripción: Adobe Commerce is affected by an Improper Neutralization of Special Elements Used in a Template Engine vulnerability that could result in arbitrary code execution in the context of the current user, potentially gaining elevated access or control over the victim's account or session. Exploitation of this issue does not require user interaction. Scope is changed.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-1336

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-105010

Descripción: Use after free in Microsoft Windows Search Component allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-105016

Descripción: Heap-based buffer overflow in Microsoft QUIC allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-110130

Descripción: Dockhand before 1.0.45 contains an authentication bypass in which the global auth hook skips authentication for any path ending in a static-asset extension such as .js, including /api/* routes, and the user-mutation handlers fail open for unauthenticated callers. Unauthenticated remote attackers can send a PUT request to /api/users/<id>.js to reset the admin's or any user's password and take ov...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-288

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-69634

Descripción: Heap-based buffer overflow in Windows iSCSI allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-69639

Descripción: Heap-based buffer overflow in Windows Libarchive allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-69705

Descripción: Out-of-bounds write in Windows iSCSI allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-69883

Descripción: Use after free in Windows iSCSI allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-69886

Descripción: Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70024

Descripción: Stack-based buffer overflow in Windows Internet Information Services allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70096

Descripción: Heap-based buffer overflow in Windows Rich Text Edit Control allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70147

Descripción: Heap-based buffer overflow in Microsoft PostScript Printer Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70153

Descripción: Heap-based buffer overflow in Microsoft PostScript Printer Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70157

Descripción: Heap-based buffer overflow in Windows System Information Console allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70188

Descripción: Inconsistent interpretation of http requests ('http request/response smuggling') in ASP.NET Core allows an unauthorized attacker to bypass a security feature over a network.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-444

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70242

Descripción: Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70279

Descripción: Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Exchange Server allows an unauthorized attacker to perform spoofing over a network.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70291

Descripción: Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-70300

Descripción: Untrusted pointer dereference in Microsoft Office Word allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-822

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83517

Descripción: Heap-based buffer overflow in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83519

Descripción: Heap-based buffer overflow in Windows Error Reporting allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83578

Descripción: Integer underflow (wrap or wraparound) in Windows PowerShell allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83693

Descripción: Heap-based buffer overflow in Windows Error Reporting allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83748

Descripción: Heap-based buffer overflow in Windows Error Reporting allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83770

Descripción: Heap-based buffer overflow in Windows Text Shaping allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83780

Descripción: Use after free in Windows CCFFilter Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83782

Descripción: Heap-based buffer overflow in Windows Shell allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83862

Descripción: Use after free in Windows Network Load Balancing allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83869

Descripción: Integer underflow (wrap or wraparound) in DNS Server allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-191

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83910

Descripción: Out-of-bounds write in RPC Runtime allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-83935

Descripción: Heap-based buffer overflow in Microsoft XML allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-84015

Descripción: Heap-based buffer overflow in Remote Access Point-to-Point Protocol (PPP) EAP-TLS allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-85792

Descripción: Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-85806

Descripción: Integer underflow (wrap or wraparound) in Network Policy Server (NPS) allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-121

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-85809

Descripción: Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-85814

Descripción: Heap-based buffer overflow in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-85818

Descripción: Improper verification of cryptographic signature in Windows Schannel allows an unauthorized attacker to perform spoofing over a network.

CVSS: 9.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-347

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-85928

Descripción: Heap-based buffer overflow in Windows Volume Manager Extension Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-88092

Descripción: Inconsistent interpretation of http requests ('http request/response smuggling') in ASP.NET Core allows an unauthorized attacker to perform tampering over a network.

CVSS: 9.4 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:L

Tipo: CWE-444

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-88102

Descripción: Use after free in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-88156

Descripción: Stack-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-121

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-91013

Descripción: Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session. Scope is changed.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-92464

Descripción: Adobe Commerce is affected by an Improper Input Validation vulnerability that could result in arbitrary code execution in the context of the current user. An attacker with high privileges could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-92909

Descripción: Adobe Commerce is affected by an Incorrect Authorization vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-863

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-96113

Descripción: Heap-based buffer overflow in DNS Server allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-97016

Descripción: Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-97805

Descripción: Out-of-bounds read in Windows Partition Management Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-97814

Descripción: Heap-based buffer overflow in Windows Text Shaping allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-97815

Descripción: Heap-based buffer overflow in Windows Error Reporting allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-97816

Descripción: Use after free in OpenSSH for Windows allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-102238

Descripción: Improper limitation of a pathname to a restricted directory ('path traversal') in Visual Studio Code allows an unauthorized attacker to execute code over a network.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-103848

Descripción: Adobe Experience Manager is affected by an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability that could result in arbitrary code execution in the context of the current user. A low-privileged attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-78

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-105895

Descripción: Adobe Experience Manager is affected by an Improper Input Validation vulnerability that could result in arbitrary code execution in the context of the current user, potentially gaining elevated access or control over the victim's account or session. Exploitation of this issue does not require user interaction. Scope is changed.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-10-13

# CVE-2026-106626

Descripción: Adobe Experience Manager is affected by an Improper Input Validation vulnerability that could result in arbitrary code execution in the context of the current user. An attacker with high privileges could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-10-13