

CVEs más relevantes de la semana

Del 02/06/2026 al 09/06/2026

Porque el primer paso para defender es conocer las amenazas.



CVE-2026-5076

Descripción: The ARMember Premium plugin for WordPress is vulnerable to an insecure password reset mechanism in all versions up to, and including, 7.3.1. The plugin stores a plaintext copy of the password reset key in the `arm\_reset\_password\_key` user meta field when a user requests a password reset. This is in addition to the hashed key that WordPress core stores securely in `wp\_users.user\_activation\_key`....

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-287

Tecnología: No especificado

Publicado el: 2026-06-02



CVE-2026-35075

Descripción: An unauthenticated remote attacker can recover a default, hard coded password from a firmware image and thus gain full access to all affected devices.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-1393

Tecnología: No especificado

Publicado el: 2026-06-03



CVE-2026-5241

Descripción: A vulnerability in the LightGlue model loading path of huggingface/transformers version 5.2.0 allows an attacker-controlled model repository to execute arbitrary code during model initialization. The issue arises because the `'trust_remote_code'` parameter, intended to prevent remote code execution, is overridden by untrusted serialized configuration data in a nested code path. Specifically, when...

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-829

Tecnología: No especificado

Publicado el: 2026-06-03



CVE-2026-49185

Descripción: The FieldX MDM adb messaging topic passes unverified payloads directly into Runtime.exec(), allowing command/instruction injection.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-78

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-49186

Descripción: The local MQTT broker does not enforce topic-level Access Control Lists (ACLs). This allows any client to subscribe using wildcard characters (# or +) to enumerate hidden network devices or publish rogue control commands.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-287

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-49188

Descripción: The ai_cmd utility executes with full root permissions. It pipes socket inputs directly to popen(), paving the way for unauthenticated users to execute arbitrary root commands.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-489

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-49191

Descripción: The production build of the M3WebServer hard-codes its backend API keys, which can be easily intercepted through verbose error handling pages.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-287

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-50208

Descripción: High-risk TrustAllCerts routines disable standard TLS certificate validation. Combined with hard-coded DES symmetric encryption keys, a Man-in-the-Middle (MITM) actor could decrypt network traffic.

CVSS: 9.4 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:L

Tipo: CWE-330

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-50211

Descripción: Leftover engineering diagnostics and factory-level diagnostic software remain exposed on retail builds, giving malicious apps write privileges to internal NVRAM registers.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-134

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-50214

Descripción: The /v1/Plan service relies entirely on a shared global API token for full administrative management, allowing arbitrary creation of zero-cost network access plans.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-345

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-50225

Descripción: The registration path /v1/account/register provides no bot mitigation mechanisms, allowing malicious automated systems to flood the database.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-4104

Descripción: Authorization bypass through User-Controlled SQL primary key vulnerability in Akmer Informatics Automation Industry and Trade Ltd. Co. TeknoPass allows SQL Injection.

This issue affects TeknoPass: from 20210501 through 20260429.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-89

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2019-25727

Descripción: WordPress Plugin ad manager wd 1.0.11 contains an arbitrary file download vulnerability that allows unauthenticated attackers to download sensitive files by manipulating the path parameter. Attackers can send GET requests to the edit.php endpoint with export=export_csv and a malicious path parameter to read arbitrary files like wp-config.php accessible to the web server.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2019-25729

Descripción: PDF Signer 3.0 contains a server-side template injection vulnerability that allows unauthenticated attackers to execute arbitrary code by injecting PHP commands through the CSRF-TOKEN cookie parameter. Attackers can craft malicious cookie values containing template injection payloads like `shell_exec()` to execute system commands and retrieve sensitive information from the server.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-352

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2019-25738

Descripción: WordPress Hybrid Composer 1.4.6 contains an unauthenticated settings change vulnerability that allows unauthenticated attackers to modify WordPress options by exploiting the hc_ajax_save_option action. Attackers can send POST requests to the admin-ajax.php endpoint with the action parameter set to hc_ajax_save_option to enable user registration and set the default role to administrator, enablin...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2019-25741

Descripción: Mobatek MobaXterm 12.1 contains a structured exception handling (SEH) based buffer overflow vulnerability in the username field of session files that allows remote attackers to execute arbitrary code. Attackers can craft a malicious MobaXterm sessions file with overflow data that triggers the vulnerability when imported and executed, enabling reverse shell execution with user privileges.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-120

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-25550

Descripción: Seagull Software BarTender 2010, 2016, and 2019 contain an unauthenticated remote code execution vulnerability in the .NET Remoting service exposed on TCP port 7375 via BtSystem.Service.exe. The service registers an unauthenticated singleton endpoint — BarTenderSystem for BarTender 2016 <= R9, and DataServiceSingleton for BarTender 2019 <= R10 — configured with BinaryServerFormatterSinkProvider...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-48040

Descripción: The netty incubator codec.bhttp is a java language binary http parser. The library implements Oblivious HTTP (RFC 9458) using BoringSSL's HPKE C library via JNI. When deriving native memory addresses for cryptographic operations versions prior to 0.0.22.Final provide a fallback path for direct ByteBufs that do not expose their memory address through 'hasMemoryAddress()'. This fallback occurs wh...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-125

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-50292

Descripción: In libinput before 1.30.4 and 1.31.x before 1.31.3, libinput-device-group unescaped phys output can inject udev properties leading to arbitrary root code execution

CVSS: 7.4 (HIGH)

Vector: CVSS:3.1/AV:L/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-93

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-10931

Descripción: Use after free in FileSystem in Google Chrome prior to 149.0.7827.53 allowed a remote attacker to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: High)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-10966

Descripción: Inappropriate implementation in Codecs in Google Chrome prior to 149.0.7827.53 allowed a remote attacker to potentially perform a sandbox escape via a crafted video file. (Chromium security severity: High)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-10971

Descripción: Insufficient validation of untrusted input in Printing in Google Chrome on Windows prior to 149.0.7827.53 allowed a remote attacker who had compromised the renderer process to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: High)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-10972

Descripción: Use after free in Ozone in Google Chrome on Linux prior to 149.0.7827.53 allowed a remote attacker to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: High)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-10974

Descripción: Insufficient validation of untrusted input in ANGLE in Google Chrome prior to 149.0.7827.53 allowed a remote attacker to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: High)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-10990

Descripción: Use after free in Glic in Google Chrome prior to 149.0.7827.53 allowed a remote attacker who had compromised the renderer process to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: Medium)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-11002

Descripción: Use after free in Autofill in Google Chrome prior to 149.0.7827.53 allowed a remote attacker who had compromised the renderer process to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: Medium)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-11113

Descripción: Insufficient validation of untrusted input in ANGLE in Google Chrome prior to 149.0.7827.53 allowed a remote attacker who had compromised the renderer process to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: Medium)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-11120

Descripción: Insufficient validation of untrusted input in Enterprise Reporting in Google Chrome prior to 149.0.7827.53 allowed a remote attacker who had compromised the renderer process to potentially perform a sandbox escape via a crafted HTML page. (Chromium security severity: Medium)

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2026-48567

Descripción: Authentication bypass by spoofing in Azure HorizonDB allows an unauthorized attacker to elevate privileges over a network.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:H

Tipo: CWE-290

Tecnología: No especificado

Publicado el: 2026-06-04



CVE-2025-71317

Descripción: NetMan 204 contains a hard-coded backdoor account with the username and password 'eurek' that grants administrative access. A remote, unauthenticated attacker can authenticate through the cgi-bin/login.cgi endpoint (for example /cgi-bin/login.cgi?username=eurek&password=eurek, which due to lax parameter validation can be shortened to /cgi-bin/login.cgi?username=eurek%20eurek) to obtain administ...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-798

Tecnología: No especificado

Publicado el: 2026-06-05



CVE-2025-71318

Descripción: NetMan 204 fails to enforce authentication on its administrative pages and command endpoints. A remote, unauthenticated attacker can directly request administrative pages (such as administration.html, administration-commands.html, and configuration.html) to disclose sensitive information including LDAP configuration and active user details, and can invoke privileged UPS control commands — inclu...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-06-05



CVE-2026-10580

Descripción: The Hippoo Mobile App for WooCommerce plugin for WordPress is vulnerable to Authentication Bypass leading to Administrator Account Takeover in all versions up to and including 1.9.4. This is due to a logic conflation in HippooPermissions::get_user_permissions(), which returns the same null sentinel for both administrators and unauthenticated visitors — a value that HippooPermissions::has_role_a...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-285

Tecnología: No especificado

Publicado el: 2026-06-05



CVE-2023-54352

Descripción: WordPress Seotheme contains a remote code execution vulnerability that allows unauthenticated attackers to execute arbitrary PHP code by uploading malicious files to the theme directory. Attackers can access the uploaded PHP shell at /wp-content/themes/seotheme/mar.php to execute system commands and upload additional files for persistent access.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2024-58348

Descripción: WordPress Background Image Cropper version 1.2 contains a remote code execution vulnerability that allows unauthenticated attackers to upload arbitrary files by accessing the ups.php endpoint. Attackers can upload PHP files through the file upload form in the plugin directory to execute arbitrary code on the server.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-434

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2024-58349

Descripción: WordPress Theme Travelscape 1.0.3 contains an arbitrary file upload vulnerability that allows unauthenticated attackers to upload malicious files by exploiting insufficient validation in the theme's upload functionality. Attackers can upload arbitrary files to the theme directory and execute them to achieve remote code execution on the affected WordPress installation.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-434

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2026-11499

Descripción: A vulnerability was determined in Tenda HG7HG9 and HG10 300001138_en_xpon. This affects the function formDOMAINBLK of the file /boaform/formDOMAINBLK. Executing a manipulation of the argument blkDomain can lead to stack-based buffer overflow. The attack may be performed from remote.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2026-25555

Descripción: OpenBullet2 through version 0.3.2 contains an authentication bypass vulnerability in the API key authentication middleware that allows unauthenticated attackers to gain admin access by supplying an empty X-API-Key header value. Attackers can exploit the middleware's comparison of the supplied header against an empty AdminApiKey default string to access the admin console and all API endpoints wi...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-305

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2026-39910

Descripción: STACKIT IaaS API contains a missing authorization check vulnerability that allows authenticated, low-privileged attackers to escalate privileges to full organization compromise by attaching arbitrary service accounts to virtual machines they control. Attackers can exploit the unvalidated PUT servers service-accounts endpoint to attach high-privileged service accounts and query the Instance Meta...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-862

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2026-41448

Descripción: AdGuard Home, when started with the --glinet flag, contains an authentication bypass vulnerability that allows unauthenticated attackers to gain full admin access by supplying a path traversal sequence in the Admin-Token cookie, exploiting unsanitized string concatenation in the token file path construction within the authglinet middleware. Attackers can craft a request with a traversal payload...

CVSS: 9.4 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:L

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-06-08



CVE-2026-40128

Descripción: SAP NetWeaver Application Server Java (Web Container) allows an unauthenticated attacker to craft a malicious HTTP logon request that manipulates file inclusion parameters, enabling path traversal and processing of the included file. Processing the included file could allow the attacker to view or modify sensitive information or render any part of the local system unavailable.

CVSS: 9.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-35

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-44748

Descripción: SAP NetWeaver Application Server ABAP and ABAP Platform allows an authenticated attacker with normal privileges to obtain a valid signed message and send modified signed XML documents to the verifier. This may result in acceptance of tampered identity information leading to unauthorized access to sensitive user data and potential disruption of normal system usage. This causes a high impact on c...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-347

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-9698

Descripción: DBI versions before 1.648 for Perl saved errors in a limited-sized buffer.

Error messages that were returned when RaiseError, PrintError or HandleError were set were written to a 200-byte buffer without a length limit.

Attackers that can influence the error text in an application can trigger a buffer overflow.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2017-20251

Descripción: WordPress Insert PHP plugin versions before 3.3.1 contain a PHP code injection vulnerability that allows unauthenticated attackers to execute arbitrary PHP code by injecting malicious shortcodes through the WordPress REST API. Attackers can send POST requests to the wp-json/wp/v2/posts endpoint with crafted content containing insert_php shortcodes to include and execute remote PHP files on the ...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-94

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-7486

Descripción: Improper neutralization of special elements used in an SQL command ('SQL injection') vulnerability in Netcad Software Inc. E-[]mar allows SQL Injection.

This issue affects E-[]mar: from 2.10.1.0 before 3.0.2.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-89

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-8025

Descripción: Improper neutralization of special elements used in an SQL command ('SQL injection') vulnerability in MOSK Information Technologies Ltd. CBS Platform allows SQL Injection.

This issue affects CBS Platform: through 09062026. NOTE: The vendor was contacted and it was learned that the product is not supported.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-89

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-26142

Descripción: Deserialization of untrusted data in Nuance PowerScribe allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-42904

Descripción: Heap-based buffer overflow in Windows TCP/IP allows an unauthorized attacker to elevate privileges over an adjacent network.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:A/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-44815

Descripción: Stack-based buffer overflow in Windows DHCP Client allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-121

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-45602

Descripción: No cwe for this issue in Windows DHCP Server allows an unauthorized attacker to perform tampering over a network.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: N/A

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-45657

Descripción: Use after free in Windows Kernel allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-47281

Descripción: Improper input validation in Visual Studio Code allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-47291

Descripción: Integer overflow or wraparound in Windows HTTP.sys allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-06-09



CVE-2026-47643

Descripción: External control of file name or path in Azure Stack Edge allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-73

Tecnología: No especificado

Publicado el: 2026-06-09



Resumen del Reporte

CVEs analizados: 53

Promedio CVSS: 9.65

Fuente: nvd.nist.gov

Nos vemos la próxima semana. Hack the Cat ☹

