

# CVEs más relevantes de la semana

Del 19/05/2026 al 26/05/2026

Porque el primer paso para defender es conocer las amenazas.



## CVE-2026-33642

Descripción: Kitty is a cross-platform GPU based terminal. In versions 0.46.2 and below, the `handle_compose_command()` function in `kitty/graphics.c` performs bounds validation on composition offsets using unsigned 32-bit arithmetic that is subject to integer wrapping, potentially leading to Heap Buffer Over-Read/Write. An attacker who can write escape sequences to a kitty terminal (e.g., via a malicious file,...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:L/I:L/A:H

Tipo: CWE-125

Tecnología: No especificado

Publicado el: 2026-05-19



## CVE-2026-6555

Descripción: The ProSolution WP Client plugin for WordPress is vulnerable to Arbitrary File Upload in versions up to, and including, 2.0.0. This is due to an array validation mismatch where only the first file in the upload array undergoes extension and MIME type validation, while all files are processed and uploaded to a web-accessible directory. This makes it possible for unauthenticated attackers to uplo...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-434

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-7284

Descripción: The Easy Elements for Elementor – Addons & Website Templates plugin for WordPress is vulnerable to privilege escalation via user registration in all versions up to, and including, 1.4.4. This is due to the 'easyel\_handle\_register' function not restricting what user roles a user can register with. This makes it possible for unauthenticated attackers to supply the 'administrator' role during regi...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-269

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2025-33255

Descripción: NVIDIA TRT-LLM for any platform contains a vulnerability in MPI server, where an attacker could cause an unsafe deserialization. A successful exploit of this vulnerability might lead to code execution, denial of service, data tampering, and information disclosure.

CVSS: 7.5 (HIGH)

Vector: CVSS:3.1/AV:L/AC:H/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-05-20





## CVE-2026-24142

Descripción: NVIDIA TRT-LLM for any platform contains a deserialization vulnerability and unsafe serialized handle. A successful exploit of this vulnerability might lead to code execution, data tampering, and information disclosure.

CVSS: 6.3 (MEDIUM)

Vector: CVSS:3.1/AV:L/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-24163

Descripción: NVIDIA TRT-LLM for any platform contains a vulnerability in RPC testing, where an attacker could cause an unsafe deserialization. A successful exploit of this vulnerability might lead to code execution, denial of service, data tampering, and information disclosure.

CVSS: 7.5 (HIGH)

Vector: CVSS:3.1/AV:L/AC:H/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-24206

Descripción: NVIDIA Triton Inference Server contains a vulnerability where an attacker could cause an authentication bypass. A successful exploit of this vulnerability might lead to escalation of privileges, denial of service, or information disclosure.

CVSS: 7.3 (HIGH)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L

Tipo: CWE-288

Tecnología: No especificado

Publicado el: 2026-05-20





## CVE-2026-24213

Descripción: NVIDIA Triton Inference Server contains a vulnerability in the DALI backend where an attacker could cause an out-of-bounds read. A successful exploit of this vulnerability might lead to code execution, data tampering, denial of service, or information disclosure.

CVSS: 8.0 (HIGH)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:R/S:U/C:H/I:H/A:H

Tipo: CWE-125

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-24214

Descripción: NVIDIA Triton Inference Server contains a vulnerability in the DALI backend where an attacker could cause an integer overflow. A successful exploit of this vulnerability might lead to code execution, data tampering, or denial of service.

CVSS: 8.0 (HIGH)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:R/S:U/C:H/I:H/A:H

Tipo: CWE-190

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-7637

Descripción: The Boost plugin for WordPress is vulnerable to PHP Object Injection in versions up to, and including, 2.0.3 via deserialization of untrusted input in the STYXKEY-BOOST\_USER\_LOCATION cookie. This makes it possible for unauthenticated attackers to inject a PHP Object. No known POP chain is present in the vulnerable software, which means this vulnerability has no impact unless another plugin or t...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-33278

Descripción: NLnet Labs Unbound 1.19.1 up to and including version 1.25.0 has a vulnerability in the DNSSEC validator that enables denial of service and possible remote code execution as a result of deep copying a data structure and erroneously overwriting a destination pointer. An adversary can exploit the vulnerability by controlling a malicious signed zone and querying a vulnerable Unbound. When DS sub-q...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-42960

Descripción: NLnet Labs Unbound up to and including version 1.25.0 is vulnerable to poisoning via promiscuous records for the authority section. Promiscuous RRSets that complement DNS replies in the authority section can be used to trick Unbound to cache such records. If an adversary is able to attach such records in a reply (i.e., spoofed packet, fragmentation attack) he would be able to poison Unbound's c...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:H

Tipo: CWE-349

Tecnología: No especificado

Publicado el: 2026-05-20





## CVE-2025-31973

Descripción: HCL BigFix Service Management (SM) is susceptible to a Configuration – 'Insecure Use of Base Image Version'. Using outdated or insecure base images may introduce known vulnerabilities, potentially increasing the risk of exploitation in the application environment.

CVSS: 4.0 (MEDIUM)

Vector: CVSS:3.1/AV:L/AC:L/PR:H/UI:R/S:U/C:L/I:L/A:L

Tipo: NVD-CWE-noinfo

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-3593

Descripción: A use-after-free vulnerability exists within the DNS-over-HTTPS implementation. This issue affects BIND 9 versions 9.20.0 through 9.20.22, 9.21.0 through 9.21.21, and 9.20.9-S1 through 9.20.22-S1. BIND 9 versions 9.18.0 through 9.18.48 and 9.18.11-S1 through 9.18.48-S1 are NOT affected.

CVSS: 7.4 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-20223

Descripción: A vulnerability in the access validation of internal REST APIs of Cisco Secure Workload could allow an unauthenticated, remote attacker to access site resources with the privileges of the Site Admin role. This vulnerability is due to insufficient validation and authentication when accessing REST API endpoints. An attacker could exploit this vulnerability if they are able to send a ...

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-05-20





## CVE-2026-9139

Descripción: Taiko AG1000-01A SMS Alert Gateway Rev 7.3 and Rev 8 contains a hard-coded credential vulnerability in the embedded web configuration interface where authentication is implemented entirely in client-side JavaScript in login.zh.html, exposing static plaintext credentials in the page source. Unauthenticated attackers with network access can recover administrative credentials directly from the client...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-798

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-8631

Descripción: A potential security vulnerability has been identified in the HP Linux Imaging and Printing Software. This potential vulnerability may allow escalation of privileges and/or arbitrary code execution via an integer overflow in the hpcups processing path when handling crafted print data.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-05-20



## CVE-2026-6279

Descripción: The Avada Builder (fusion-builder) plugin for WordPress is vulnerable to Unauthenticated Remote Code Execution via PHP Function Injection in versions up to and including 3.15.2. This is due to the `wp\_conditional\_tags` case in `Fusion\_Builder\_Conditional\_Render\_Helper::get\_value()` passing attacker-controlled values from a base64-decoded JSON blob directly to `call\_user\_func()` without any allo...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-74

Tecnología: No especificado

Publicado el: 2026-05-21



## CVE-2026-4858

Descripción: Mattermost versions 11.6.x <= 11.6.0, 11.5.x <= 11.5.3, 11.4.x <= 11.4.4, 10.11.x <= 10.11.14 fail to check integration URL for path traversal which allows an malicious authenticated user to call an arbitrary API via system admin Mattermost auth token using via path traversal in integration action URL.. Mattermost Advisory ID: MMSA-2026-00640

CVSS: 8.0 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:L/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-05-21



## CVE-2026-5118

Descripción: The Divi Form Builder plugin for WordPress is vulnerable to privilege escalation in versions up to, and including, 5.1.2. This is due to the plugin accepting a user-controlled 'role' parameter from POST data during user registration without validating it against the form's configured default\_user\_role setting. This makes it possible for unauthenticated attackers to create administrator accounts...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-269

Tecnología: No especificado

Publicado el: 2026-05-21





## CVE-2026-6960

Descripción: The BookingPress Pro plugin for WordPress is vulnerable to arbitrary file uploads due to missing file type validation in the 'bookingpress\_validate\_submitted\_booking\_form\_func' function in all versions up to, and including, 5.6. This makes it possible for unauthenticated attackers to upload arbitrary files on the affected site's server which may make remote code execution possible. Note: The vu...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-434

Tecnología: No especificado

Publicado el: 2026-05-21



## CVE-2026-44930

Descripción: An LDAP injection vulnerability in the LDAP Certificate repository of the XKMS server in Apache CXF may allow an attacker to retrieve arbitrary certificates from the repository. Users are recommended to upgrade to versions 4.2.1, 4.1.6 or 3.6.11, which fix this issue.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-90

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2026-23652

Descripción: Improper neutralization of special elements used in a command ('command injection') in Microsoft Power Pages allows an unauthorized attacker to execute code over a network.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-22





## CVE-2026-33843

Descripción: Authentication bypass using an alternate path or channel in Microsoft Azure Active Directory B2C allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-288

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2026-40411

Descripción: Improper input validation in Azure Virtual Network Gateway allows an authorized attacker to execute code over a network.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2026-40412

Descripción: Unrestricted upload of file with dangerous type in Azure Orbital Spatio allows an unauthorized attacker to execute code over a network.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-434

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2026-41090

Descripción: Improper neutralization of special elements used in a command ('command injection') in Microsoft Copilot allows an unauthorized attacker to perform tampering over a network.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2026-41104

Descripción: Deserialization of untrusted data in Microsoft Planetary Computer Pro allows an unauthorized attacker to disclose information over a network.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-05-22





## CVE-2026-42901

Descripción: Origin validation error in Microsoft Entra ID allows an unauthorized attacker to elevate privileges over a network.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-346

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2026-47280

Descripción: Improper authentication in Azure Resource Manager (ARM) allows an unauthorized attacker to elevate privileges over a network.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-287

Tecnología: No especificado

Publicado el: 2026-05-22



## CVE-2018-25350

Descripción: userSpice 4.3.24 contains a username enumeration vulnerability that allows unauthenticated attackers to discover valid usernames by sending POST requests to the existingUsernameCheck.php endpoint. Attackers can submit usernames and analyze response text for the 'taken' string to identify existing accounts in the system.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-204

Tecnología: No especificado

Publicado el: 2026-05-23





## CVE-2026-9384

Descripción: A vulnerability was found in Totolink A8000RU 7.1cu.643\_b20200521. This vulnerability affects the function setDiagnosisCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. The manipulation of the argument ip results in os command injection. The attack can be executed remotely. The exploit has been made public and could be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-24



## CVE-2026-9385

Descripción: A vulnerability was determined in Totolink A8000RU 7.1cu.643\_b20200521. This issue affects the function setTracerouteCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. This manipulation of the argument command causes os command injection. The attack is possible to be carried out remotely. The exploit has been publicly disclosed and may be utilized.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-24



## CVE-2026-9386

Descripción: A vulnerability was identified in Totolink A8000RU 7.1cu.643\_b20200521. Impacted is the function setLanguageCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Such manipulation of the argument lang leads to os command injection. The attack may be performed from remote. The exploit is publicly available and might be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-24



## CVE-2026-9387

Descripción: A security flaw has been discovered in Totolink A8000RU 7.1cu.643\_b20200521. The affected element is the function setUpgradeFW of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Performing a manipulation of the argument resetFlags results in os command injection. It is possible to initiate the attack remotely. The exploit has been released to the public and may be used ...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-24



## CVE-2026-9388

Descripción: A weakness has been identified in Totolink A8000RU 7.1cu.643\_b20200521. The impacted element is the function setScheduleCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Executing a manipulation of the argument mode can lead to os command injection. It is possible to launch the attack remotely. The exploit has been made available to the public and could be used for...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-24





## CVE-2026-9404

Descripción: A vulnerability was identified in Totolink A8000RU 7.1cu.643\_b20200521. This affects the function setDdnsCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Such manipulation of the argument provider leads to os command injection. The attack may be launched remotely. The exploit is publicly available and might be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-24



## CVE-2026-9405

Descripción: A security flaw has been discovered in Totolink A8000RU 7.1cu.643\_b20200521. This impacts the function setGameSpeedCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Performing a manipulation of the argument enable results in os command injection. Remote exploitation of the attack is possible. The exploit has been released to the public and may be used for attacks.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9406

Descripción: A weakness has been identified in Totolink A8000RU 7.1cu.643\_b20200521. Affected is the function setRemoteCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Executing a manipulation of the argument enable can lead to os command injection. The attack can be executed remotely. The exploit has been made available to the public and could be used for attacks.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25





## CVE-2026-9407

Descripción: A security vulnerability has been detected in Totolink A8000RU 7.1cu.643\_b20200521. Affected by this vulnerability is the function setFirewallType of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. The manipulation of the argument firewallType leads to os command injection. The attack is possible to be carried out remotely. The exploit has been disclosed publicly and ma...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9408

Descripción: A vulnerability was detected in Totolink A8000RU 7.1cu.643\_b20200521. Affected by this issue is the function setStaticDhcpRules of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. The manipulation of the argument enable results in os command injection. The attack may be performed from remote. The exploit is now public and may be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9432

Descripción: A security flaw has been discovered in Totolink A8000RU 7.1cu.643\_b20200521. This vulnerability affects the function setWiFiAdvancedCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. The manipulation of the argument bgProtection results in os command injection. The attack can be launched remotely. The exploit has been released to the public and may be used for attacks.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9433

Descripción: A weakness has been identified in Totolink A8000RU 7.1cu.643\_b20200521. This issue affects the function setMacFilterRules of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. This manipulation of the argument enable causes os command injection. The attack may be initiated remotely. The exploit has been made available to the public and could be used for attacks.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9434

Descripción: A security vulnerability has been detected in Totolink A8000RU 7.1cu.643\_b20200521. Impacted is the function setWiFiWpsCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Such manipulation of the argument wscDisabled leads to os command injection. The attack may be launched remotely. The exploit has been disclosed publicly and may be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25





## CVE-2026-9435

Descripción: A vulnerability was detected in Totolink A8000RU 7.1cu.643\_b20200521. The affected element is the function setQosCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Performing a manipulation of the argument enable results in os command injection. Remote exploitation of the attack is possible. The exploit is now public and may be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9436

Descripción: A flaw has been found in Totolink A8000RU 7.1cu.643\_b20200521. The impacted element is the function setL2tpServerCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Executing a manipulation of the argument enable can lead to os command injection. The attack can be executed remotely. The exploit has been published and may be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9454

Descripción: A flaw has been found in Totolink A8000RU 7.1cu.643\_b20200521. This vulnerability affects the function setOpenVpnCertGenerationCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Executing a manipulation of the argument servername can lead to os command injection. The attack may be launched remotely. The exploit has been published and may be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25





## CVE-2026-9455

Descripción: A vulnerability has been found in Totolink A8000RU 7.1cu.643\_b20200521. This issue affects the function UploadOpenVpnCert of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. The manipulation of the argument FileName leads to os command injection. Remote exploitation of the attack is possible. The exploit has been disclosed to the public and may be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9456

Descripción: A vulnerability was found in Totolink A8000RU 7.1cu.643\_b20200521. Impacted is the function setOpenVpnCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. The manipulation of the argument enabled results in os command injection. The attack can be executed remotely. The exploit has been made public and could be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9457

Descripción: A vulnerability was determined in Totolink A8000RU 7.1cu.643\_b20200521. The affected element is the function UploadFirmwareFile of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. This manipulation of the argument FileName causes os command injection. The attack is possible to be carried out remotely. The exploit has been publicly disclosed and may be utilized.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9458

Descripción: A vulnerability was identified in Totolink A8000RU 7.1cu.643\_b20200521. The impacted element is the function setWanCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Such manipulation of the argument enabled leads to os command injection. The attack may be performed from remote. The exploit is publicly available and might be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9475

Descripción: A vulnerability was determined in Totolink A8000RU 7.1cu.643\_b20200521. This affects the function setIpQosRules of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. This manipulation of the argument Comment causes os command injection. Remote exploitation of the attack is possible. The exploit has been publicly disclosed and may be utilized.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25





## CVE-2026-9476

Descripción: A vulnerability was identified in Totolink A8000RU 7.1cu.643\_b20200521. This vulnerability affects the function setPasswordCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Such manipulation of the argument admpass leads to os command injection. The attack can be executed remotely. The exploit is publicly available and might be used.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9477

Descripción: A security flaw has been discovered in Totolink A8000RU 7.1cu.643\_b20200521. This issue affects the function setAccessDeviceCfg of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Performing a manipulation of the argument mac results in os command injection. The attack is possible to be carried out remotely. The exploit has been released to the public and may be used for...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25



## CVE-2026-9478

Descripción: A weakness has been identified in Totolink A8000RU 7.1cu.643\_b20200521. Impacted is the function setParentalRules of the file /cgi-bin/cstecgi.cgi of the component Web Management Interface. Executing a manipulation of the argument enable can lead to os command injection. The attack may be performed from remote. The exploit has been made available to the public and could be used for attacks.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-05-25





## CVE-2026-7374

Descripción: A flaw was found in KubeVirt's virt-handler component. This vulnerability allows an authenticated OpenShift user with edit permissions in a single namespace to exploit improper symlink validation when connecting to virtual machine console sockets. By replacing the console socket with a symlink to the host's container runtime (CRI-O) socket, an attacker can hijack virt-handler's privileged conne...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-59

Tecnología: No especificado

Publicado el: 2026-05-26



## CVE-2026-45247

Descripción: Mirasvit Full Page Cache Warmer for Magento 2 before version 1.11.12 contains a PHP object injection vulnerability that allows unauthenticated attackers to achieve remote code execution by supplying a crafted serialized PHP object in the CacheWarmer cookie. Attackers can exploit the unrestricted call to PHP's native unserialize() function combined with gadget chains available in Magento and its...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-502

Tecnología: No especificado

Publicado el: 2026-05-26



## CVE-2026-8633

Descripción: IBM Web Server Plug-ins for WebSphere Application Server and WebSphere Liberty 8.5, 9.0 IBM WebSphere Application Server and WebSphere Application Server Liberty are vulnerable to remote code execution in the Web Server Plug-ins, through a specially crafted request.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-94

Tecnología: No especificado

Publicado el: 2026-05-26



## Resumen del Reporte

CVEs analizados: 58

Promedio CVSS: 9.39

Fuente: [nvd.nist.gov](https://nvd.nist.gov)

Nos vemos la próxima semana. Hack the Cat ☹

