

CVEs más relevantes de la semana

Del 01/09/2026 al 08/09/2026

Porque el primer paso para defender es conocer las amenazas.



CVE-2026-85031

Descripción: A vulnerability was found in TOTOLINK CP450 4.1.0. The impacted element is an unknown function of the file /cgi-bin/cstecgi.cgi. Performing a manipulation of the argument topicurl results in buffer overflow. Remote exploitation of the attack is possible.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-85183

Descripción: Taipy configures its socket.io server with wildcard CORS origin and credential flag enabled, allowing any web page to establish credentialed WebSocket connections to victim applications. Attackers can open socket.io sessions from arbitrary domains and invoke state variable modifications and action callbacks without CSRF protection.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-1385

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-85394

Descripción: python-jose through 3.5.0 fails to properly validate asymmetric keys in HMAC initialization, accepting DER-encoded public keys that lack PEM armor or SSH prefixes. Attackers holding the service's public key can forge HS256 tokens that pass verification when algorithms are not explicitly restricted. This is an incomplete fix for CVE-2024-33663.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-347

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-62916

Descripción: Authentication bypass using an alternate path or channel in Microsoft Entra ID allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-288

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-65818

Descripción: Server-side request forgery (ssrf) in Power Automate allows an authorized attacker to elevate privileges over a network.

CVSS: 8.5 (HIGH)

Vector: CVSS:3.1/AV:N/AC:H/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-918

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-80098

Descripción: Improper verification of cryptographic signature in Copilot Studio allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:L/I:H/A:N

Tipo: CWE-347

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-85428

Descripción: MOOS core-moos through 10.4.0 contains an authentication bypass vulnerability in the optional MOOSDB HTTP server that allows unauthenticated clients to write variables. Attackers can send HTTP requests with variable names and values to the MOOSDB HTTP server port to modify MOOS variables including actuator and override commands without authentication.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-85433

Descripción: MOOS essential-moos pShare through 10.0.1 fails to properly authorize PSHARE_CMD messages, allowing any publisher to reconfigure network routes and listeners at runtime. Attackers can send crafted PSHARE_CMD messages with cmd=output or cmd=input parameters to open new listeners on arbitrary addresses and redirect or duplicate bus traffic to attacker-controlled destinations.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-862

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-85438

Descripción: MOOS-IvP through 24.8.1 contains a buffer overflow vulnerability in StringToIvPFunction() where dimension, piece, and degree counts from encoded BHV_IPF payloads are used as allocation sizes and loop bounds without validation. Attackers can supply crafted payloads with mismatched dimension values to write attacker-controlled doubles past the end of the IvPBox weight array, causing memory corrup...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-190

Tecnología: No especificado

Publicado el: 2026-09-03



CVE-2026-85661

Descripción: excel-mcp-server 0.1.8 fails to enforce path confinement in stdio mode when EXCEL_FILES_PATH is unset, allowing attackers to read and write arbitrary files. Attackers can supply unchecked file paths to read and write tools to access any file accessible to the process.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-22

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-85688

Descripción: TEN Framework 0.11.71 contains unauthenticated arbitrary file read and write vulnerabilities in the TMAN Designer file-content API endpoints. Attackers can submit POST and PUT requests to the `/api/designer/v1/file-content` endpoints to read arbitrary files or write malicious content to system paths, enabling code execution through `authorized_keys`, cron files, or executable graph files.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-85695

Descripción: FastChat contains an authentication bypass vulnerability in the /register_worker endpoint that allows unauthenticated attackers to register arbitrary worker addresses and perform server-side request forgery. Attackers can register malicious workers under victim model names to intercept user prompts, images, and responses, or probe internal network ports across the worker mesh.

CVSS: 9.4 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:L

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-85696

Descripción: SadTalker contains an OS command injection vulnerability in the video muxing process where uploaded audio filenames are interpolated into ffmpeg commands without proper escaping. Attackers can upload audio files with shell metacharacters in the filename to break out of quoted arguments and execute arbitrary system commands when video generation occurs.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-78

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-18658

Descripción: IBM Operational Decision Manager 9.6.0.0, 9.5.0.0, 8.11.1.0, 8.11.0.1, 8.12.0.1, 9.5.0.1, and 9.0.0.1 is vulnerable to SQL injection. An unauthenticated attacker can execute arbitrary SQL statements and leverage database functionality to write a web shell to the application web root, resulting in remote code execution.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-89

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-17057

Descripción: IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote attacker to cause a denial of service and affect data integrity due to missing authentication for critical functions.

CVSS: 6.5 (MEDIUM)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:L

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-17207

Descripción: IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote attacker to cause a denial of service and compromise integrity due to a buffer overflow.

CVSS: 6.5 (MEDIUM)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:L

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-09-04



CVE-2026-86124

Descripción: AutoAgent contains an unauthenticated remote code execution vulnerability in the TCP server that binds to all interfaces and executes attacker-supplied commands as root. Attackers can connect to the exposed communication port and execute arbitrary bash commands within the container, gaining access to bind-mounted host workspace directories.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-05



CVE-2026-86184

Descripción: Lara Dashboard before 1.3.0 contains an authentication bypass vulnerability in the screenshot-login route that allows unauthenticated attackers to authenticate as any user by email when APP_ENV is not production. Attackers can request the GET /screenshot-login/{email} endpoint with a registered email address to receive a fully authenticated session, enabling access to user administration, setti...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-05



CVE-2026-86189

Descripción: WBN AVideo contains a path traversal vulnerability in notify.ffmpeg.json.php that allows unauthenticated attackers to write files to arbitrary locations by supplying a caller-chosen path in the avideoRelativePath parameter. Attackers can replay any previously issued ciphertext as a notifyCode token, which is decrypted but never validated, to bypass authentication and write files to the applica...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-73

Tecnología: No especificado

Publicado el: 2026-09-05



CVE-2026-86190

Descripción: WWBN AVideo contains a broken access control vulnerability in videoViewsInfo endpoints that returns complete user records including password hashes, recovery tokens, and live session identifiers to unauthenticated callers when a hash parameter is provided. Attackers can use the disclosed session identifier to hijack viewer sessions, including administrator accounts, and obtain sensitive persona...

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N

Tipo: CWE-200

Tecnología: No especificado

Publicado el: 2026-09-05



CVE-2026-86149

Descripción: A weakness has been identified in Tenda CP3 27.5.57.101. This issue affects some unknown processing of the file Net/NetCheckPing.cpp. This manipulation of the argument interface_name/host causes os command injection. The attack can be initiated remotely.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-09-05



CVE-2026-86151

Descripción: A vulnerability was detected in Tenda CP3 27.5.57.101. The affected element is the function sub_2F77E8 of the file Apis/system.c of the component Network Configuration Management. Performing a manipulation results in os command injection. The attack may be initiated remotely.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-09-06



CVE-2026-86152

Descripción: A flaw has been found in Tenda CP3 27.5.57.101. The impacted element is the function CAutoAddWifi::ThreadProc of the file Functions/AutoAddWifi.cpp of the component Kylin. Executing a manipulation can lead to os command injection. The attack may be launched remotely.

CVSS: 10.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-09-06



CVE-2026-79698

Descripción: A vulnerability was identified in Advantech WISE-6610-NB, WISE-6610-EB, WISE-6610-TB, WISE-6610-JB, WISE-6610-CB, WISE-6610-EL-NB, WISE-6610-EL-EB, WISE-6610-EL-TB, WISE-6610-EL-JB, WISE-6610-EL-CB, WISE-6610P-DEA, WISE-6610P-DNA and WISE-6610P-DTA 1.2.1_20251110. This vulnerability affects the function `nodered_lib_apply` of the component Node-RED Library. Such manipulation of the argument `act` l...

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-74

Tecnología: No especificado

Publicado el: 2026-09-07



CVE-2026-86299

Descripción: A vulnerability was detected in Linksys RE7000 2.0.15. This affects the function platform_event_pingTest of the file /cgi-bin/json.cgi?PingTest of the component PingTest Handler. The manipulation of the argument pingTestIp/pingTestPktSize/pingTestTimes results in os command injection. The attack can be launched remotely. The exploit is now public and may be used.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-77

Tecnología: No especificado

Publicado el: 2026-09-07



CVE-2026-86543

Descripción: knowns versions before 0.30.0 serve the management API without authentication on all network interfaces by default, with no password required on fresh installations. Attackers can access the unauthenticated /api/tunnel/start endpoint to provision a public tunnel and republish the API at a publicly accessible address.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-306

Tecnología: No especificado

Publicado el: 2026-09-07



CVE-2026-86509

Descripción: A flaw has been found in D-Link DIR-895L A1_102b07. This impacts the function sendOffer/sendACK of the file udhcpd/serverpacket.c of the component udhcpd. This manipulation causes stack-based buffer overflow. The attack can only be done within the local network. The exploit has been published and may be used.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:A/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-119

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-61516

Descripción: Netis NX10 firmware V4.0.1.5808 and V3.0.0.4142 contain an information disclosure vulnerability that allows unauthenticated attackers to retrieve the administrator password by sending a request to the sysinfo action in the web management interface without a valid session. Attackers can replay the exposed credential against the login handler to establish a fully authenticated administrator sessi...

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-522

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-65669

Descripción: Improper neutralization of special elements in output used by a downstream component ('injection') in SQL Server allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-74

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-68839

Descripción: Heap-based buffer overflow in Windows USB Mass Storage Class Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69276

Descripción: Integer underflow (wrap or wraparound) in Microsoft UxTheme Library (uxtheme.dll) allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69356

Descripción: Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Exchange Server allows an unauthorized attacker to perform spoofing over a network.

CVSS: 9.3 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:N

Tipo: CWE-79

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69408

Descripción: Integer overflow or wraparound in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69431

Descripción: Heap-based buffer overflow in Telnet Client allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69463

Descripción: Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69491

Descripción: Heap-based buffer overflow in Windows Microsoft DirectMusic allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69493

Descripción: Out-of-bounds read in Windows Event Logging Service allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69496

Descripción: Heap-based buffer overflow in Windows Compressed Folder allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69525

Descripción: Use after free in Windows Remote Desktop Services allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69579

Descripción: Use after free in Windows Message Queuing allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69586

Descripción: Integer overflow or wraparound in Microsoft Windows PDF allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69590

Descripción: Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69595

Descripción: Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69641

Descripción: Missing authorization in Microsoft Exchange Server allows an authorized attacker to elevate privileges over a network.

CVSS: 9.1 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-862

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69669

Descripción: Heap-based buffer overflow in Windows Kernel allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69715

Descripción: Out-of-bounds read in Windows Direct Show allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69730

Descripción: Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69768

Descripción: Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69769

Descripción: Heap-based buffer overflow in Windows HTTP Print Provider allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69819

Descripción: Out-of-bounds write in RPC Runtime allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69824

Descripción: Integer underflow (wrap or wraparound) in Microsoft Standard XPS allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69829

Descripción: Heap-based buffer overflow in Windows Shell allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69845

Descripción: Heap-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-20

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69854

Descripción: Improper authentication in Spring Cloud Azure allows an unauthorized attacker to elevate privileges over a network.

CVSS: 9.0 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H

Tipo: CWE-287

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-69910

Descripción: Stack-based buffer overflow in Windows Hyper-V allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-121

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-70296

Descripción: Out-of-bounds write in Windows Imaging Component allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-787

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-72979

Descripción: Use after free in Windows DHCP Server allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-72982

Descripción: Stack-based buffer overflow in Windows Netlogon allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-121

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-72983

Descripción: Use after free in Windows Internet Connection Sharing (ICS) allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-73009

Descripción: Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-73010

Descripción: Use after free in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-73025

Descripción: Weak authentication in Windows iSCSI allows an unauthorized attacker to bypass a security feature over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-1390

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-77493

Descripción: Double free in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-415

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-78445

Descripción: Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-416

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-78509

Descripción: Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-78510

Descripción: Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-122

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-81376

Descripción: Incomplete comparison with missing factors in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.

CVSS: 9.6 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:R/S:C/C:H/I:H/A:H

Tipo: CWE-693

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-83941

Descripción: Missing authorization in Entra ID allows an authorized attacker to elevate privileges over a network.

CVSS: 9.9 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:L

Tipo: CWE-862

Tecnología: No especificado

Publicado el: 2026-09-08



CVE-2026-66302

Descripción: External control of file name or path in Skype for Business allows an unauthorized attacker to execute code over a network.

CVSS: 9.8 (CRITICAL)

Vector: CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H

Tipo: CWE-73

Tecnología: No especificado

Publicado el: 2026-09-08



Resumen del Reporte

CVEs analizados: 69

Promedio CVSS: 9.59

Fuente: nvd.nist.gov

Nos vemos la próxima semana. Hack the Cat ☺

