

Nama : Sukma Nindi Listyarini

NIM : L200170147


Kelas : D

---

## Laporan Praktikum - Jaringan Komputer

### Modul 11

1. Membuat topologi menggunakan cisco packet tracer



2. Konfigurasi router 1 (Jarkom)

```
Router>en
Router#config term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname Jarkom
Jarkom(config)#int fa 0/0
Jarkom(config-if)#ip address 172.16.0.1 255.255.255.0
Jarkom(config-if)#no shutdown

Jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Jarkom(config-if)#exit
Jarkom(config)#int fa 1/0
Jarkom(config-if)#ip address 172.15.0.1 255.255.255.0
Jarkom(config-if)#no shutdown

Jarkom(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

Jarkom(config-if)#exit
Jarkom(config)#
```

## Mengatur ip address Sistem Informasi

```
Router>en
Router#config term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname SistemInformasi
SistemInformasi(config)#int fa 0/0
SistemInformasi(config-if)#ip address 172.15.0.2 255.255.255.0
SistemInformasi(config-if)#no shutdown

SistemInformasi(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

SistemInformasi(config-if)#exit
SistemInformasi(config)#int fa 1/0
SistemInformasi(config-if)#ip address 172.18.0.1 255.255.255.0
SistemInformasi(config-if)#no shutdown

SistemInformasi(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

SistemInformasi(config-if)#exit
SistemInformasi(config)#
SistemInformasi(config)#interface FastEthernet0/0
SistemInformasi(config-if)#
SistemInformasi(config-if)#exit
SistemInformasi(config)#interface FastEthernet0/0
SistemInformasi(config-if)#
SistemInformasi(config-if)#exit
SistemInformasi(config)#interface FastEthernet1/0
SistemInformasi(config-if)#ip address 172.17.0.1 255.255.255.0
SistemInformasi(config-if)#ip address 172.17.0.1 255.255.255.0
SistemInformasi(config-if)#
```

## Mengatur ip address RPL

```
Router(config)#hostname RPL
RPL(config)#int fa 1/0
RPL(config-if)#172.15.0.3 255.255.255.0
^
% Invalid input detected at '^' marker.

RPL(config-if)#no shutdown

RPL(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

RPL(config-if)#exit
RPL(config)#int fa 1/0
RPL(config-if)#172.18.0.1 255.255.255.0
^
% Invalid input detected at '^' marker.

RPL(config-if)#no shutdown
RPL(config-if)#exit
RPL(config)#int fa 0/0
RPL(config-if)#ip address 172.15.0.3 255.255.255.0
RPL(config-if)#no shutdown

RPL(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

RPL(config-if)#exit
RPL(config)#
```

## Mengatur ip address UM

```
Router>en
Router#config term
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname UMS
UMS(config)#int fa 1/0
UMS(config-if)#ip address 172.15.0.4 255.255.255.0
UMS(config-if)#no shutdown

UMS(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up

UMS(config-if)#exit
UMS(config)#int fa 0/0
UMS(config-if)#ip address 172.19.0.1 255.255.255.0
UMS(config-if)#no shutdown

UMS(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

UMS(config-if)#exit
UMS(config)#
```

## 3. Mengkonfigurasi Routing Table

### Jarkom

```
Jarkom>en
Jarkom#config term
Enter configuration commands, one per line. End with CNTL/Z.
Jarkom(config)#router rip
Jarkom(config-router)#network 172.15.0.0
Jarkom(config-router)#network 172.16.0.0
Jarkom(config-router)#network 172.17.0.0
Jarkom(config-router)#network 172.18.0.0
Jarkom(config-router)#network 172.19.0.0
Jarkom(config-router)#
Jarkom#
%SYS-5-CONFIG_I: Configured from console by console
```

### Sistem informasi

```
SistemInformasi(config)#router rip
SistemInformasi(config-router)#network 172.15.0.0
SistemInformasi(config-router)#network 172.16.0.0
SistemInformasi(config-router)#network 172.17.0.0
SistemInformasi(config-router)#network 172.18.0.0
SistemInformasi(config-router)#network 172.19.0.0
SistemInformasi(config-router)#
```


## RPL

```
RPL>en
RPL#config term
Enter configuration commands, one per line. End with CNTL/Z.
RPL(config)#router rip
RPL(config-router)#network 172.15.0.0
RPL(config-router)#network 172.16.0.0
RPL(config-router)#network 172.17.0.0
RPL(config-router)#network 172.18.0.0
RPL(config-router)#network 172.19.0.0
RPL(config-router)#exit
RPL(config)#
```

## UMS

```
UMS#en
UMS#config term
Enter configuration commands, one per line. End with CNTL/Z.
UMS(config)#router rip
UMS(config-router)#network 172.15.0.0
UMS(config-router)#network 172.16.0.0
UMS(config-router)#network 172.17.0.0
UMS(config-router)#network 172.18.0.0
UMS(config-router)#network 172.19.0.0
UMS(config-router)#exit
UMS(config)#
```

## 4. Melakukan Konfigurasi



PC SI

Physical Config Desktop Programming Attributes

IP Configuration

IP Configuration

☐ DHCP ☒ Static

IP Address 172.17.0.2

Subnet Mask 255.255.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address /

Link Local Address FE80::20A:41FF:FE87:CAD5

IPv6 Gateway

IPv6 DNS Server

Top

PC RPL

Physical Config Desktop Programming Attributes

IP Configuration

IP Configuration

☐ DHCP ☒ Static

IP Address 172.18.0.2

Subnet Mask 255.255.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static


IPv6 Address /

Link Local Address FE80::2D0:D3FF:FE02:3D5B

IPv6 Gateway

IPv6 DNS Server

Top



5. Melakukan pengujian untuk tes koneksi

#### PC UMS ke PC Jarkom

```
C:\>ping 172.16.0.2

Pinging 172.16.0.2 with 32 bytes of data:

Reply from 172.16.0.2: bytes=32 time=1ms TTL=126
Reply from 172.16.0.2: bytes=32 time=12ms TTL=126
Reply from 172.16.0.2: bytes=32 time=12ms TTL=126
Reply from 172.16.0.2: bytes=32 time=12ms TTL=126

Ping statistics for 172.16.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
```

#### PC UMS ke PC Si

```
C:\>ping 172.18.0.2

Pinging 172.18.0.2 with 32 bytes of data:

Reply from 172.18.0.2: bytes=32 time<1ms TTL=126
Reply from 172.18.0.2: bytes=32 time=15ms TTL=126
Reply from 172.18.0.2: bytes=32 time=19ms TTL=126
Reply from 172.18.0.2: bytes=32 time=12ms TTL=126

Ping statistics for 172.18.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 19ms, Average = 11ms

C:\>
```

#### PC UMS ke PC RPL

```
C:\>ping 172.17.0.2

Pinging 172.17.0.2 with 32 bytes of data:

Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time=19ms TTL=126
Reply from 172.17.0.2: bytes=32 time=10ms TTL=126
Reply from 172.17.0.2: bytes=32 time=12ms TTL=126

Ping statistics for 172.17.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 19ms, Average = 10ms
```