

Nama : Aldo Brian Granada


NIM : L200170182

Kelas : D


Laporan Praktikum Jaringan Komputer

Tugas Modul 7

1. Gambar Topologi



2. Konfigurasi masing masing router.



Puma

Physical Config CLI Attributes

IOS Command Line Interface

```
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#no ip address
Router(config-if)#ip address 172.21.20.10 255.255.0.0
Router(config-if)#ip address 172.21.20.10 255.255.0.0
Router(config-if)#ip address 172.21.20.10 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet1/0
Router(config-if)#ip address 172.21.30.20 255.255.255.0
Router(config-if)#ip address 172.21.30.20 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet1/0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface Serial2/0
Router(config-if)#ip address 172.21.1.3 255.255.255.0
Router(config-if)#ip address 172.21.1.3 255.255.255.0
```

Ctrl+F6 to exit CLI focus

Copy Paste

Top

Tiger

Physical Config CLI Attributes

IOS Command Line Interface

```
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address 172.21.30.10 255.255.0.0
Router(config-if)#ip address 172.21.30.10 255.255.0.0
Router(config-if)#ip address 172.21.30.10 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet1/0
Router(config-if)#ip address 172.21.40.20 255.255.255.0
Router(config-if)#ip address 172.21.40.20 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface Serial2/0
Router(config-if)#ip address 172.21.1.3 255.255.255.0
Router(config-if)#ip address 172.21.1.3 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface Serial3/0
Router(config-if)#ip address 172.21.4.1 255.255.255.0
Router(config-if)#ip address 172.21.4.1 255.255.255.0
Router(config-if)#
```

Ctrl+F6 to exit CLI focus

Copy Paste

Top

Lion

Physical Config CLI Attributes

IOS Command Line Interface


```
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address 172.21.40.10 255.255.0.0
Router(config-if)#ip address 172.21.40.10 255.255.0.0
Router(config-if)#ip address 172.21.40.10 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet1/0
Router(config-if)#ip address 172.21.50.20 255.255.255.0
Router(config-if)#ip address 172.21.50.20 255.255.255.0
Router(config-if)#ip address 172.21.50.20 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface Serial2/0
Router(config-if)#ip address 172.21.1.4 255.255.255.0
Router(config-if)#ip address 172.21.1.4 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface Serial3/0
Router(config-if)#ip address 172.21.5.1 255.255.255.0
Router(config-if)#ip address 172.21.5.1 255.255.255.0
Router(config-if)#
```

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top

3. Konfigurasi pada setiap PC.



4. Cek koneksi

dari PC Aquarius ke Router Elang.

```
C:\>ping 172.21.10.10

Pinging 172.21.10.10 with 32 bytes of data:

Reply from 172.21.10.10: bytes=32 time=108ms TTL=255
Reply from 172.21.10.10: bytes=32 time<1ms TTL=255
Reply from 172.21.10.10: bytes=32 time<1ms TTL=255
Reply from 172.21.10.10: bytes=32 time<1ms TTL=255


Ping statistics for 172.21.10.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 108ms, Average = 27ms
```

dari Router Elang ke Router Puma.


```
Router#ping 172.21.1.2

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.21.1.2, timeout is 2
seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max =
1/3/11 ms
```

5. Melakukan routing



6. Show ip route



7. PING PC Pisces ke Libra

