WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/21L-6114_A1.cpp/22I%207957%20%20assignment%201.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
21L-6114_A1.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
24.65

Submission 1 File 1	Submission 2 File 2	Tokens
21L-6114_A1.cpp\21L-6114_A1.cpp (71 - 88)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (56 - 70)	18
21L-6114_A1.cpp\21L-6114_A1.cpp (192 - 201)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (19 - 25)	14
21L-6114_A1.cpp\21L-6114_A1.cpp (66 - 69)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (51 - 55)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (211 - 215)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (166 - 172)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (115 - 122)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (175 - 181)	12

Files of 21L-6114_A1.cpp

21L-6114_A1.cpp\21L-6114_A1.cpp

```cpp
/*

Laiba Tariq
21L-6114
BS-SE
2C
*/

#include <iostream>
#include <string>
#include <string.h>
#include <cstring>
using namespace std;

void tokenize(char* str, char**& dictionary, int& dictSize) {
    // initialize variables
    int i = 0, j = 0, k = 0;
    dictSize = 0;
    char* word = new char[50]; // assume max word length is 50 characters

    // loop through string character array
    while (str[i] != '\0' && k < 3000) {
        if (str[i] == ' ' || str[i] == '.') { // check for end of word
            if (j > 0) { // if word has been formed
                word[j] = '\0'; // add null terminator
                bool duplicate = false;
                // check if word is already in dictionary
                for (int l = 0; l < dictSize; l++) {

                    if (strcmp(word, dictionary[l]) == 0) {                    // CHANG
                        duplicate = true;
                        break;
                    }
                }
                // add word to dictionary if not a duplicate
                if (!duplicate) {
                    dictionary[dictSize] = new char[j + 1]; // allocate memory for wo

                    //                    for(int i=0; i<dictSize; i++)
                    //                    {
                    //
                    //                                                    }

                    strcpy_s(dictionary[dictSize], j + 1, word); // copy word to dict
                    dictSize++; // increment dictionary size
                }
            }
            // reset variables for next word
            j = 0;
            delete[] word;
            word = new char[50];
        }
        else {
            word[j] = str[i]; // add character to word
            j++;
        }
        i++;
```

Files of 22I 7957 assignment 1.cpp

..ignment 1.cpp\22I 7957 assignment 1.cpp

```cpp
#include<iostream>
#include<cstring>
using namespace std;
bool areEqual(char* w1, char* w2)
{
    int i = 0;
    while (w1[i] && w2[i])
    {
        if (w1[i] != w2[i])
        {
            return false;
        }
        i++;
    }
    return (w1[i] == '\0' && w2[i] == '\0');
}
void checkunique(char**& data_dictionary, int& row)
{
    int count = 0;
    for (int i = 0; i < row; i++)
    {
        for (int j = i + 1; j < row; j++)
        {
            if (areEqual(data_dictionary[i], data_dictionary[j]))
            {
                count++;
                for (int k = 0;k < strlen(data_dictionary[i]); k++)
                {
                    data_dictionary[i][k] = ' ';
                }
            }
        }
    }
    row = row - count;
}
int main()
{
    //task 1
    const int Size = 2000;
    char arr[Size];
    cin.getline(arr, Size);
    int row = 2, col = 1;
    int s = strlen(arr);
    for (int i = 0;i < s;i++)
    {
        if (arr[i] == ' ' || arr[i] == '.')
        {
            row++;
        }
    }
    char** data_dictionary = new char* [row];
    for (int j = 0;j < row;j++)
    {
        data_dictionary[j] = new char[20];   // set maximum length of each word
    }
```

1:19 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/21L-6114_A1.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
21L-6114_A1.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
24.65

Submission 1 File 1	Submission 2 File 2	Tokens
21L-6114_A1.cpp\21L-6114_A1.cpp (71 - 86)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (56 - 70)	18
21L-6114_A1.cpp\21L-6114_A1.cpp (192 - 201)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (19 - 25)	14
21L-6114_A1.cpp\21L-6114_A1.cpp (66 - 69)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (51 - 55)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (211 - 215)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (166 - 172)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (115 - 122)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (175 - 181)	12

```cpp
    int j = 0;
    for (int i = 0; i <= (strlen(str)); i++)
    {
        // if space or NULL found, assign NULL into newString[ctr]
        if (str[i] == ' ' || str[i] == '\0')
        {
            newString[ctr][j] = '\0';
            ctr++;  //for next word
            j = 0;   //for next word, init index to 0
        }
        else
        {
            newString[ctr][j] = str[i];
            j++;
        }
    }

    return newString;
}

void inputSynonym(string++& syn, int& s, char++& dictionary, int& dictSize)
{
    syn = new string * [dictSize];
    s = 0;  //s will be size of total number of synonyms stored

    int option, SynNum;

    for (int i = 0; i < dictSize; i++) {
        cout << "Enter 1 to store Synonyms for the word: " << dictionary[i] << endl;
        cin >> option;

         if (option == 1)
         {
             cout << "How many Synonyms you want to store" << endl;
             cin >> SynNum;
             syn[s] = new string[SynNum + 2]; // 2 extra indexes, 1 for word and other
             //copting word at 0 index
             syn[s][0] = dictionary[i];
             cout << "Word: " << syn[s][0] << endl;
             for (int j = 1; j < SynNum + 1; j++) {
                 cout << "Enter synonym " << j << " :";
                 cin >> syn[s][j];
             }
             syn[s][SynNum + 1] = "#";
             s++;

         }
    }

    cout << "Words and Synonyms" << endl;
    for (int i = 0; i < s; i++)
    {
        for (int j = 0; syn[i][j] != "#"; j++)
        {

            cout << syn[i][j] << " ";
        }
        cout << endl;
    }

}

//void search(string++ syn, int s)
//{
//    string arr2;
//    int j = 0;
//    string* arr3 = new string;
//    int count = 0;
//    cout << "Input word(function): ";
//    cin.ignore(); //to clear buffer
```

```cpp
    int r = 0, c = 0;
    for (int i = 0; arr[i] != '\0'; i++)
    {
            if (arr[i] == ' ' || arr[i] == '.')
            {
                    data_dictionary[r][c] = '\0'; // end of word
                    r++;
                    c = 0;
            }
            else
            {
                    data_dictionary[r][c] = arr[i];
                    c++;
            }
    }

    data_dictionary[r][c] = '\0';
    //check for unique words
    checkunique(data_dictionary, row);
    cout << endl;
    cout << "____________Tokens:_____________ " << endl;
    for (int i = 0; i < row - 1; i++)
    {
            cout << data_dictionary[i] << endl;
    }
    cout << endl;
    //task 2
    char+++ synonyms = new char++ [row];
    for (int i = 0;i < row;i++)
    {
            synonyms[i] = new char* [row];
            for (int j = 0;j < row;j++)
            {
                    synonyms[i][j] = new char[row];

                    for (int k = 0;k < row;k++)
                    {
                            synonyms[i][j][k] = NULL;
                    }
            }
    }
    const int x = 100;
    int counts[x];
    for (int i = 0; i < row; i++)
    {
            counts[i] = 0;
            {
                    cout << "the " << i + 1 << " word of data dictionary is : " << da
                    char response;
                    cout << "Do you want to store synonyms for this word? (y/n): ";
                    cin >> response;

                    if (response == 'y')
                    {
                            cout << "Enter the number of synonyms: ";
                            cin >> counts[i];
                            for (int j = 0; j < counts[i]; j++)
                            {
                                    char temp[x];
                                    cout << "Enter synonym " << j + 1 << ": ";
                                    cin >> temp;

                                    // Allocate memory for synonym in 3D array
                                    synonyms[i][j] = new char[strlen(temp) + 1];
                                    synonyms[i][j] = data_dictionary[i];
                                    for (int k = 0;k < counts[i];k++)
                                    {
                                            synonyms[i][j][k] = temp[k];
                                    }
                            }
```

1:19 PM
4/14/2023

WhatsA × report-v × Lab Mar × Downlo × BDS - 4 × New Tal × Convert × +
jplag.github.io/JPlag/comparison/21L-6114_A1.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
21L-6114_A1.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
24.65

Submission 1 File 1	Submission 2 File 2	Tokens
21L-6114_A1.cpp\21L-6114_A1.cpp (71 - 88)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (56 - 70)	18
21L-6114_A1.cpp\21L-6114_A1.cpp (192 - 201)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (19 - 25)	14
21L-6114_A1.cpp\21L-6114_A1.cpp (66 - 69)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (51 - 55)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (211 - 215)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (166 - 172)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (115 - 122)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (175 - 181)	12

```cpp
    int arrSize = 0;
    //creating 2D array of uniqueWords form useCase Array
    tokenize(input, uniqueWords, arrSize);

    cout << endl << endl;
    cout << "Displaying useCase1 Words in Dictionary" << endl;
    for (int i = 0; i < arrSize; i++) {
        for (int j = 0; j < dictSize; j++) {
            //comparing and displaying if similar
            if (!strcmp(uniqueWords[i], dictionary[j])) {
                cout << uniqueWords[i] << endl;
                break;
            }
        }
    }

    //task4
    int sizeTokenizedInput;
    //Tokenizing without removing repeated words.
    char** tokenizedInput = tokenize(input, sizeTokenizedInput);
    cout << endl << endl;
    for (int i = 0; i < sizeTokenizedInput; i++) {
        for (int j = 0; j < s; j++) {
            if (tokenizedInput[i] == syn[j][0]) {
                int k = 1;
                cout << syn[j][0] << " has Synonyms:  ";
                while (syn[j][k] != "#")
                    cout << syn[j][k++] << " ";
                cout << endl;
                //changing the word with Synonym by Coping the 1st synonym
                Copy(tokenizedInput[i], syn[j][1]);
                break;
            }
        }
    }
    //Displaying final output
    cout << "Replacing with Synonyms" << endl;
    for (int i = 0; i < sizeTokenizedInput; i++) {
        cout << tokenizedInput[i] << " ";
    }
    cout << endl;

    //deallocation
    for (int i = 0; i < sizeTokenizedInput; i++)
        delete[]tokenizedInput[i];
    delete[]tokenizedInput;
    for (int i = 0; i < arrSize; i++)
        delete[]uniqueWords[i];
    delete[]uniqueWords;
    delete[]input;
}

int main() {
    // get input from user
    char* input = new char[3001]; // assume max input length is 3000 characters
    cout << "Enter Sentence to be tokenized: ";
    cin.getline(input, 3001);

    // tokenize input and store in data dictionary
    char** dictionary = new char* [1000]; // assume max unique words is 1000
    int dictSize = 0;
    tokenize(input, dictionary, dictSize);

    // print data dictionary
    cout << "\nOutput Data Dictionary:\n";
    for (int i = 0; i < dictSize; i++)
    {
```

```cpp
    int count = 0;
    for (int i = 0; i < row; i++)
    {
            for (int j = i + 1; j < row; j++)
            {
                    if (areEqual(data_dictionary[i], data_dictionary[j]))
                    {
                            count++;
                            for (int k = 0;k < strlen(data_dictionary[i]); k++)
                            {
                                    data_dictionary[i][k] = ' ';
                            }
                    }
            }
    }
    row = row - count;
}
int main()
{
    //task 1
    const int Size = 2000;
    char arr[Size];
    cin.getline(arr, Size);
    int row = 2, col = 1;
    int s = strlen(arr);
    for (int i = 0;i < s;i++)
    {
            if (arr[i] == ' ' || arr[i] == '.')
            {
                    row++;
            }
    }
    char** data_dictionary = new char* [row];
    for (int j = 0;j < row;j++)
    {
            data_dictionary[j] = new char[20];   // set maximum length of each word t
    }

    int r = 0, c = 0;
    for (int i = 0; arr[i] != '\0'; i++)
    {
            if (arr[i] == ' ' || arr[i] == '.')
            {
                    data_dictionary[r][c] = '\0'; // end of word
                    r++;
                    c = 0;
            }
            else
            {
                    data_dictionary[r][c] = arr[i];
                    c++;
            }
    }
    data_dictionary[r][c] = '\0';
    //check for unique words
    checkunique(data_dictionary, row);
    cout << endl;
    cout << "_____Tokens:_____ " << endl;
    for (int i = 0; i < row - 1; i++)
    {
            cout << data_dictionary[i] << endl;
    }
    cout << endl;
    //task 2
    char*** synonyms = new char** [row];
    for (int i = 0;i < row;i++)
    {
```

1:19 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/21L-6114_A1.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
21L-6114_A1.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
24.65

Submission 1 File 1	Submission 2 File 2	Tokens
21L-6114_A1.cpp\21L-6114_A1.cpp (71 - 86)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (56 - 70)	18
21L-6114_A1.cpp\21L-6114_A1.cpp (192 - 201)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (19 - 25)	14
21L-6114_A1.cpp\21L-6114_A1.cpp (66 - 69)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (51 - 55)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (211 - 215)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (166 - 172)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (115 - 122)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (175 - 181)	12

```cpp
    char** newString = new char* [1000]; //max words 1000
    for (int i = 0; i < 10; i++) {
        newString[i] = new char[50];
    }

    ctr = 0;

    int j = 0;
    for (int i = 0; i <= (strlen(str)); i++)
    {
        // if space or NULL found, assign NULL into newString[ctr]
        if (str[i] == ' ' || str[i] == '\0')
        {
            newString[ctr][j] = '\0';
            ctr++;  //for next word
            j = 0;   //for next word, init index to 0
        }
        else
        {
            newString[ctr][j] = str[i];
            j++;
        }
    }

    return newString;
}

void inputSynonym(string**& syn, int& s, char**& dictionary, int& dictSize)
{
    syn = new string * [dictSize];
    s = 0;  //s will be size of total number of synonyms stored

    int option, SynNum;

    for (int i = 0; i < dictSize; i++) {
        cout << "Enter 1 to store Synonyms for the word: " << dictionary[i] << endl;
        cin >> option;

         if (option == 1)
         {
             cout << "How many Synonyms you want to store" << endl;
             cin >> SynNum;
             syn[s] = new string[SynNum + 2]; // 2 extra indexes, 1 for word and other
             //copting word at 0 index
             syn[s][0] = dictionary[i];
             cout << "Word: " << syn[s][0] << endl;
             for (int j = 1; j < SynNum + 1; j++) {
                 cout << "Enter synonym " << j << " :";
                 cin >> syn[s][j];
             }
             syn[s][SynNum + 1] = "#";
             s++;

         }
     }

     cout << "Words and Synonyms" << endl;
     for (int i = 0; i < s; i++)
     {
         for (int j = 0; syn[i][j] != "#"; j++)
         {

             cout << syn[i][j] << " ";
         }
         cout << endl;
     }

}

//void search(string** syn, int s)
///
```

```cpp
    char** data_dictionary = new char* [row];
    for (int j = 0;j < row;j++)
    {
            data_dictionary[j] = new char[20];   // set maximum length of each word t
    }

    int r = 0, c = 0;
    for (int i = 0; arr[i] != '\0'; i++)
    {
            if (arr[i] == ' ' || arr[i] == '.')
            {
                    data_dictionary[r][c] = '\0'; // end of word
                    r++;
                    c = 0;
            }
            else
            {
                    data_dictionary[r][c] = arr[i];
                    c++;
            }
    }

    data_dictionary[r][c] = '\0';
    //check for unique words
    checkunique(data_dictionary, row);
    cout << endl;
    cout << "_____________Tokens:_____________ " << endl;
    for (int i = 0; i < row - 1; i++)
    {
            cout << data_dictionary[i] << endl;
    }
    cout << endl;
    //task 2
    char*** synonyms = new char** [row];
    for (int i = 0;i < row;i++)
    {
            synonyms[i] = new char* [row];
            for (int j = 0;j < row;j++)
            {
                    synonyms[i][j] = new char[row];

                    for (int k = 0;k < row;k++)
                    {
                            synonyms[i][j][k] = NULL;
                    }
            }
    }
    const int x = 100;
    int counts[x];
    for (int i = 0; i < row; i++)
    {
            counts[i] = 0;
            {
                    cout << "the " << i + 1 << " word of data dictionary is : " << da
                    char response;
                    cout << "Do you want to store synonyms for this word? (y/n): ";
                    cin >> response;

                    if (response == 'y')
                    {
                            cout << "Enter the number of synonyms: ";
                            cin >> counts[i];
                            for (int j = 0; j < counts[i]; j++)
                            {
                                    char temp[x];
                                    cout << "Enter synonym " << j + 1 << ": ";
                                    cin >> temp;

                                    // Allocate memory for synonym in 3D array
```

1:19 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/21L-6114_A1.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
21L-6114_A1.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
24.65

Submission 1 File 1	Submission 2 File 2	Tokens
21L-6114_A1.cpp\21L-6114_A1.cpp (71 - 88)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (56 - 70)	18
21L-6114_A1.cpp\21L-6114_A1.cpp (192 - 201)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (19 - 25)	14
21L-6114_A1.cpp\21L-6114_A1.cpp (66 - 69)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (51 - 55)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (211 - 215)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (166 - 172)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (115 - 122)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (175 - 181)	12

```
211     char** tokenizedInput = tokenize(input, sizeTokenizedInput);
212     cout << endl << endl;
213     for (int i = 0; i < sizeTokenizedInput; i++) {
214         for (int j = 0; j < s; j++) {
215             if (tokenizedInput[i] == syn[j][0]) {
216                 int k = 1;
217                 cout << syn[j][0] << " has Synonyms:  ";
218                 while (syn[j][k] != "#")
219                     cout << syn[j][k++] << " ";
220                 cout << endl;
221                 //changing the word with Synonym by Coping the 1st synonym
222                 Copy(tokenizedInput[i], syn[j][1]);
223                 break;
224             }
225         }
226     }
227     //Displaying final output
228     cout << "Replacing with Synonyms" << endl;
229     for (int i = 0; i < sizeTokenizedInput; i++) {
230         cout << tokenizedInput[i] << " ";
231     }
232     cout << endl;
233
234     //deallocation
235     for (int i = 0; i < sizeTokenizedInput; i++)
236         delete[]tokenizedInput[i];
237     delete[]tokenizedInput;
238     for (int i = 0; i < arrSize; i++)
239         delete[]uniqueWords[i];
240     delete[]uniqueWords;
241     delete[]input;
242 }
243
244 int main() {
245     // get input from user
246     char* input = new char[3001]; // assume max input length is 3000 characters
247     cout << "Enter Sentence to be tokenized: ";
248     cin.getline(input, 3001);
249
250     // tokenize input and store in data dictionary
251     char** dictionary = new char* [1000]; // assume max unique words is 1000
252     int dictSize = 0;
253     tokenize(input, dictionary, dictSize);
254
255     // print data dictionary
256     cout << "\nOutput Data Dictionary:\n";
257     for (int i = 0; i < dictSize; i++)
258     {
259         cout << dictionary[i] << endl;
260     }
261
262     //s should be equal to dictSize
263     int s = 0;
264     string** syn;
265     inputSynonym(syn, s, dictionary, dictSize);
266     //myToken(data, list, rows);
267     search(syn, s, dictionary, dictSize);
268
269
270     // memory deallocation of input and data dictionary
271     delete[] input;
272     for (int i = 0; i < dictSize; i++) {
273         delete[] dictionary[i];
274         //delete[] syn[i];
275     }
276     for (int i = 0; i < s; i++)
277         delete[]syn[i];
278     delete[] dictionary;
279     delete[] syn;
```

```
162                 n++;
163         }
164     }
165     temp[n][m] = '\0';
166     int count = 0;
167     for (int i = 0; i < n; i++)
168     {
169             for (int j = 0; j < row; j++)
170             {
171                     if (areEqual(temp[i], data_dictionary[j]))
172                     {
173                             count++;
174                     }
175             }
176     }
177     cout << "these are " << count << " words in data dictionary" << endl;
178     for (int i = 0; i < n; i++)
179     {
180             for (int j = 0; j < row; j++)
181             {
182                     if (areEqual(temp[i], data_dictionary[j]))
183                     {
184                             cout << temp[i] << endl;
185                     }
186             }
187     }
188     //task 4
189     char resp;
190     for (int i = 0; i < n; i++)
191     {
192             for (int j = 0; j < row; j++)
193             {
194                     if (areEqual(temp[i], data_dictionary[j]))
195                     {
196                             resp = 'y';
197                     }
198                     else
199                     {
200                             resp = 'n';
201                     }
202             }
203             if(resp=='y')
204             {
205                     for (int i = 0;i < row;i++)
206                     {
207                             for (int j = 0;j < row;j++)
208
209                                     if(synonyms[i][j]=data_dictionary[i])
210                                             {
211                                             for (int k = 0;synonyms[i][j][k]
212                                             {
213                                                     cout << "the word is " <<
214                                                 }
215                                             }
216                             cout << endl;
217                     }
218             }
219     }
220
221     system("pause");
222     return 0;
223 }
```

1:19 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/21L-6114_A1.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
21L-6114_A1.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
24.65

Submission 1 File 1	Submission 2 File 2	Tokens
21L-6114_A1.cpp\21L-6114_A1.cpp (71 - 88)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (56 - 70)	18
21L-6114_A1.cpp\21L-6114_A1.cpp (192 - 201)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (19 - 25)	14
21L-6114_A1.cpp\21L-6114_A1.cpp (66 - 69)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (51 - 55)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (211 - 215)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (166 - 172)	13
21L-6114_A1.cpp\21L-6114_A1.cpp (115 - 122)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (175 - 181)	12

```
115         }
116     }
117
118     cout << "Words and Synonyms" << endl;
119     for (int i = 0; i < s; i++)
120     {
121         for (int j = 0; syn[i][j] != "#"; j++)
122         {
123             cout << syn[i][j] << " ";
124         }
125         cout << endl;
126     }
127
128 }
129
130 //void search(string* syn, int s)
131 //{
132 //    string arr2;
133 //    int j = 0;
134 //    string* arr3 = new string;
135 //    int count = 0;
136 //    cout << "Input word(function): ";
137 //    cin.ignore(); //to clear buffer
138 //    getline(cin, arr2);
139 //    for (int i = 0; arr2[i] != '\0'; i++)
140 //    {
141 //        if (arr2[i] == ' ')
142 //        {
143 //            continue;
144 //        }
145 //        else
146 //        {
147 //            (*arr3)[count] = arr2[i];
148 //            cout << endl;
149 //            count++;
150 //        }
151 //    }
152 //    (*arr3)[count] = '\0';
153 //    cout << *arr3 << endl;
154 //    _getch();
155 //    count = 0;
156 //    for (int i = 0; i < count; i++)
157 //    {
158 //        for (int j = 0; j < s; j++)
159 //        {
160 //            if (arr3 == syn[j])
161 //            {
162 //                count++;
163 //
164 //                cout << "The synonym of ";
165 //                cout << syn[j][0] << " is: " << syn[j][1];
166 //            }
167 //        }
168 //    }
169 //    if (count == 0)
170 //    {
171 //        cout << "No synonyms found";
172 //    }
173 //}
174
175 void Copy(char*& arr, string& s) {
176     int i;
177     for (i = 0; i < s.size(); i++) {
178         arr[i] = s[i];
179     }
180     arr[i] = '\0';
181 }
182
183 void search(string* syn, int s, char*& dictionary, const int dictSize)
```

```
162                 m++;
163         }
164     }
165     temp[n][m] = '\0';
166     int count = 0;
167     for (int i = 0; i < n; i++)
168     {
169             for (int j = 0; j < row; j++)
170             {
171                     if (areEqual(temp[i], data_dictionary[j]))
172                     {
173                             count++;
174                     }
175             }
176     }
177     cout << "these are " << count << " words in data dictionary" << endl;
178     for (int i = 0; i < n; i++)
179     {
180             for (int j = 0; j < row; j++)
181             {
182                     if (areEqual(temp[i], data_dictionary[j]))
183                     {
184                             cout << temp[i] << endl;
185                     }
186             }
187     }
188     //task 4
189     char resp;
190     for (int i = 0; i < n; i++)
191     {
192             for (int j = 0; j < row; j++)
193             {
194                     if (areEqual(temp[i], data_dictionary[j]))
195                     {
196                             resp = 'y';
197                     }
198                     else
199                     {
200                             resp = 'n';
201                     }
202             }
203             if(resp=='y')
204             {
205                     for (int i = 0;i < row;i++)
206                     {
207                             for (int j = 0;j < row;j++)
208
209                                     if(synonyms[i][j]=data_dictionary[i])
210                                             {
211                                             for (int k = 0;synonyms[i][j][k]
212                                             {
213                                                     cout << "the word is " <<
214                                             }
215                                             }
216                             cout << endl;
217                     }
218             }
219     }
220
221     system("pause");
222     return 0;
223 }
```

1:19 PM
4/14/2023