WhatsA report- Lab Mar Downlo BDS - 4 New Tal Convert
jplag.github.io/JPlag/comparison/22L-6194.cpp/22L-7857.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

# JPlag Comparison

back

Submission 1
**22L-6194.cpp**

Submission 2
**22L-7857.cpp**

Match %
**28.86**

| Submission 1 File 1 | Submission 2 File 2 | Tokens |
|---|---|---|
| 22L-6194.cpp\22L-6194.cpp (138 - 209) | 22L-7857.cpp\22L-7857.cpp (223 - 295) | 89 |
| 22L-6194.cpp\22L-6194.cpp (87 - 93) | 22L-7857.cpp\22L-7857.cpp (162 - 169) | 12 |

## Files of 22L-6194.cpp

22L-6194.cpp\22L-6194.cpp

```cpp
#include <iostream>
#include <cstring>
using namespace std;

void Tokenization(char input[], char** dataDictionary,int&numWords) {

    int startIndex = 0;
    for (int i = 0; i < strlen(input); i++) {
        if (input[i] == ' ' || input[i] == '.') {
            int length = i - startIndex;
            if (length > 0) {
                char* word = new char[length + 1];
                for (int j = 0; j < length; j++) {
                    word[j] = input[startIndex + j];
                }
                word[length] = '\0';
                // Check for duplicates
                bool found = false;
                for (int j = 0; j < numWords; j++) {
                    if (strcmp(word, dataDictionary[j]) == 0) {
                        found = true;
                        break;
                    }
                }

                if (!found) {
                    dataDictionary[numWords] = word;
                    numWords++;
                }
                else {
                    delete[] word;
                }
            }
            startIndex = i + 1;
        }
    }


    cout << "Data Dictionary:" << endl;
    for (int i = 0; i < numWords; i++) {
        cout << dataDictionary[i] << endl;
    }
}
void getsynonyms(char***synonyms,char**dataDictionary,int&numWords) {
    for (int i = 0; i < numWords; i++) {
        synonyms[i] = nullptr;
    }


    for (int i = 0; i < numWords; i++) {
        char* word = dataDictionary[i];


        cout << "Do you want to store synonyms for " << word << "? (y/n): ";
        char choice;
        cin >> choice;
```

## Files of 22L-7857.cpp

22L-7857.cpp\22L-7857.cpp

```cpp
#include <iostream>
#include <fstream>
#include<string>

using namespace std;

void inputValidation(int& num)
{
    while (!(cin >> num && num > 0))
    {
        cout << "please enter a positive integer: ";
        cin.clear();
        cin.ignore(123, '\n');
    }
}

bool checkUnique(char* arr1D, int i)
{
    bool flag = false;
    int temp = i, j = 0;
    while (j < i)
    {
        for (j; arr1D[j] != ' ' && arr1D[j] != '.'; j++)
        {
            if (arr1D[i] == arr1D[j])
            {
                flag = false;
                continue;
            }
            else
            {
                flag = true;
                break;
            }
            i++;
        }
        i = temp;
        j++;
    }
    return flag;
}

void readData(fstream& myData, char*& arr1D)
{
    arr1D = new char[2500];
    int i = 0;
    myData.open("Data.txt", ios::in);
    while (!myData.eof())
    {
        arr1D[i] = myData.get();
        i++;
    }
    arr1D[i - 1] = '\0';
}

int input2D(char*& arr1D, char**& arr2D)
{
```

1:18 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/22L-6194.cpp/22L-7857.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

# JPlag Comparison

back

Submission 1
**22L-6194.cpp**

Submission 2
**22L-7857.cpp**

Match %
**28.86**

| Submission 1 File 1 | Submission 2 File 2 | Tokens |
|---|---|---|
| 22L-6194.cpp\22L-6194.cpp (138 - 209) | 22L-7857.cpp\22L-7857.cpp (223 - 295) | 89 |
| 22L-6194.cpp\22L-6194.cpp (87 - 93) | 22L-7857.cpp\22L-7857.cpp (162 - 169) | 12 |

```cpp
138 }
139 void replaceSynonyms(char*** synonyms, char** dataDictionary, int wordCount)
140 {
141     bool isPresent = true;
142     char* useCase1 = new char[2500];
143     char* temp = new char[2500];
144     int i = 0,j=0,forTemp=0;
145     cout << "enter sentence(s) to replace synonyms: ";
146     cin.getline(useCase1, 2500);
147     while (useCase1[i] != '\0')
148     {
149             if (i == 0 || useCase1[i] == ' ' || useCase1[i] == '.')
150             {
151                     if (i != 0)
152                             i++;
153                     int temp1 = i;
154                     j = 0;
155                     while (j < wordCount)
156                     {
157                             int characters = 0;
158                             temp1 = i;
159                             while (useCase1[temp1] != ' ' && useCase1[temp1] != '.' &
160                             {
161
162                                     if (useCase1[temp1++] == dataDictionary[j][charac
163                                     {
164                                             isPresent = true;
165                                     }
166                                     else
167                                     {
168                                             isPresent = false;
169                                             break;
170                                     }
171                             }
172                             if (isPresent)
173                             {
174                                     if (synonyms[j][0][0] == '\0')
175                                             isPresent = false;
176                                     break;
177                             }
178                             j++;
179                     }
180
181                     if (isPresent)
182                     {
183                             int h = 0;
184                             while (synonyms[j][0][h] != '\0')
185                             {
186                                     temp[forTemp++] = synonyms[j][0][h++];
187                             }
188                             while (useCase1[i] != ' ' && useCase1[i] != '.' && useCas
189                             {
190                                     i++;
191                             }
192                     }
193                     else
194                     {
195                             while (useCase1[i] != ' ' && useCase1[i] != '.' && useCas
196                             {
197                                     temp[forTemp++] = useCase1[i++];
198                             }
199                     }
200                     if (useCase1[i] == ' ')
201                             temp[forTemp++] = ' ';
202                     else
203                             temp[forTemp++] = '.';
204             }
205
206     }
```

```cpp
223 }
224
225 void replaceSynonyms(char*** arr3D, char** arr2D, int wordCount)
226 {
227     bool isPresent = true;
228     char* useCase1 = new char[2500];
229     char* temp = new char[2500];
230     int i = 0,j=0,forTemp=0;
231     cout << "enter sentence(s) to replace synonyms: ";
232     cin.getline(useCase1, 2500);
233     while (useCase1[i] != '\0')
234     {
235             if (i == 0 || useCase1[i] == ' ' || useCase1[i] == '.')
236             {
237                     if (i != 0)
238                             i++;
239                     int temp1 = i;
240                     j = 0;
241                     while (j < wordCount)
242                     {
243                             int characters = 0;
244                             temp1 = i;
245                             while (useCase1[temp1] != ' ' && useCase1[temp1] != '.' &
246                             {
247
248                                     if (useCase1[temp1++] == arr2D[j][characters++])
249                                     {
250                                             isPresent = true;
251                                     }
252                                     else
253                                     {
254                                             isPresent = false;
255                                             break;
256                                     }
257                             }
258                             if (isPresent)
259                             {
260                                     if (arr3D[j][0][0] == '\0')
261                                             isPresent = false;
262                                     break;
263                             }
264                             j++;
265                     }
266
267                     if (isPresent)
268                     {
269                             int h = 0;
270                             while (arr3D[j][0][h] != '\0')
271                             {
272                                     temp[forTemp++] = arr3D[j][0][h++];
273                             }
274                             while (useCase1[i] != ' ' && useCase1[i] != '.' && useCas
275                             {
276                                     i++;
277                             }
278                     }
279                     else
280                     {
281                             while (useCase1[i] != ' ' && useCase1[i] != '.' && useCas
282                             {
283                                     temp[forTemp++] = useCase1[i++];
284                             }
285                     }
286                     if (useCase1[i] == ' ')
287                             temp[forTemp++] = ' ';
288                     else
289                             temp[forTemp++] = '.';
290             }
291
```

1:18 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/22L-6194.cpp/22L-7857.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

# JPlag Comparison

back

Submission 1
**22L-6194.cpp**

Submission 2
**22L-7857.cpp**

Match %
**28.86**

| Submission 1 File 1 | Submission 2 File 2 | Tokens |
|---|---|---|
| 22L-6194.cpp\22L-6194.cpp (138 - 209) | 22L-7857.cpp\22L-7857.cpp (223 - 295) | 89 |
| 22L-6194.cpp\22L-6194.cpp (87 - 93) | 22L-7857.cpp\22L-7857.cpp (162 - 169) | 12 |

```cpp
            for (int j = 0; j < count; j++) {

                static char temp[100];

                cout << "Enter synonym #" << j + 1 << " for " << word << ": ";
                cin >> temp;

                // Allocate memory for the synonym at this index
                synonyms[i][j] = new char[strlen(temp) + 1];

                // Copy the data character by character
                for (int k = 0; k < strlen(temp); k++) {
                    synonyms[i][j][k] = temp[k];
                }
                synonyms[i][j][strlen(temp)] = '\0';
            }
        }
        else if (choice == 'n' || choice == 'N')
        {

            synonyms[i] = new char* [1];
            synonyms[i][0] = new char[10];
            synonyms[i][0][0] = '\0';
        }
    }
}
void SearchWord(char* UseCase1, char** dataDictionary, int numWords) {

    const int WORD_LEN = 1000;
    char word[WORD_LEN];

    int startIndex = 0;
    int count = 0;

     cout << "Matched words:" << endl;

     for (int i = 0; i <= strlen(UseCase1); i++) {
         if (UseCase1[i] == ' ' || UseCase1[i] == '.') {
             int length = i - startIndex;
             if (length > 0) {
                 if (length >=WORD_LEN) {
                     cout << "Error: word length exceeds maximum length." << endl;
                     return;
                 }
                 for (int j = 0; j < length; j++) {
                     word[j] = UseCase1[startIndex + j];
                 }
                 word[length] = '\0';

                 bool found = false;
                 for (int j = 0; j < numWords; j++) {
                     if (strcmp(word, dataDictionary[j]) == 0) {
                         found = true;
                         break;
                     }
                 }
                 if (found) {
                     cout << word << endl;
                     count++;
                 }

             }
             startIndex = i + 1;
         }
     }

     if (count == 0) {
```

```cpp
    int synonymCount, len,j;
    string synonym;
    for (int i = 0; i < wordcount; i++)
    {
            cout << arr2D[i] << endl;
            do {
                    cout << "would you like to enter synonyms of this word(y or n) ?
                    cin >> entersynonym;
            }while(entersynonym!='y' && entersynonym!='n');
            if (entersynonym == 'y')
        {
                    cout << "how many synonyms would you like to enter for the word:
                    inputValidation(synonymCount);
                    arr3D[i] = new char* [synonymCount+1];
                    for (j = 0; j < synonymCount; j++)
                    {
                            int x;
                            cout << "enter synonym: ";
                            cin >> synonym;
                            len = synonym.size();
                            arr3D[i][j] = new char[len + 1];
                            for (x = 0; x <= len; x++)
                            {
                                    arr3D[i][j][x] = synonym[x];
                            }
                            arr3D[i][j][x] = '\0';
                    }
                    arr3D[i][j] = new char[1];
                    arr3D[i][j][0] = '\0';
            }
            else if (entersynonym == 'n')
            {
                    synonymCount = 1;

                    arr3D[i] = new char* [synonymCount];
                    arr3D[i][0] = new char[1];
                    arr3D[i][0][0] = '\0';
            }
    }
}

void findInDictionary(char** arr2D, int wordCount)
{
    int i = 0, len, temp, x = 0, sinNum = 0;
    bool isFound;
    char* useCase1 = new char[2500];
    cout << "enter sentence(s) to check: ";
    cin.ignore();
    cin.getline(useCase1, 2500);
    while (useCase1[i] != '\0')
    {
            x = 0;
            len = 0;
            temp = i;
            while (useCase1[i] != ' ' && useCase1[i] != '.' && i<=strlen(useCase1))
            {
                    len++;
                    i++;
            }
            for (int j = 0; j < wordCount; j++)
            {

                    if (len == strlen(arr2D[j]))
                    {
                            i = temp;
                            while (arr2D[j][x] != '\0')
                            {
                                    if (arr2D[j][x] == useCase1[i])
                                    {
```

1:19 PM
4/14/2023