What × | Lab M × | Pyth × | GDB × | Class × | repor × | L × | New ×
jplag.github.io/JPlag/comparison/22L_7832.cpp/Source.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L_7832.cpp

Submission 2
Source.cpp

Match %
33.90

Submission 1 File 1	Submission 2 File 2	Tokens
22L_7832.cpp\22L_7832.cpp (44 - 80)	Source.cpp\L22-7904.cpp (52 - 87)	28
22L_7832.cpp\22L_7832.cpp (94 - 102)	Source.cpp\L22-7904.cpp (86 - 95)	20
22L_7832.cpp\22L_7832.cpp (149 - 161)	Source.cpp\L22-7904.cpp (160 - 171)	19
22L_7832.cpp\22L_7832.cpp (32 - 42)	Source.cpp\L22-7904.cpp (43 - 51)	13

Files of 22L_7832.cpp

22L_7832.cpp\22L_7832.cpp

```
1 #include<iostream>
2 using namespace std;
3
4 void getInput(char* words, const int size);
5 int Dictionary(char*& words, const int& size,char**&data_dictionary);
6 void Synonyms(char*& words, const int& size, char** data_dictionary,const int unique_w
7 void use_Case(char** data_dictionary);
8 int main()
9 {
10      int unique_words;
11      const int size = 3000;
12      char*words=new char[size];
13      getInput(words, size);
14      char** data_dictionary = NULL;
15      unique_words=Dictionary(words, size,data_dictionary);
16      Synonyms(words, size,data_dictionary, unique_words);
17      use_Case(data_dictionary);
18
19 }
20
21 void getInput(char * words,const int size)
22 {
23      cout << "Enter a sentence: " << endl;
24      cin.getline(words, size);
25 }
26
27
28
29 int Dictionary(char*& words, const int& size,char**&data_dictionary)
30 {
31
32      int count = 1;
33      int len;
34      len = strlen(words);
35
36      for (int i = 0; i < len; i++)
37      {
38              if (*(words + i) == ' ')
39              {
40                      count++;
41              }
42      }
43
44      data_dictionary = new char* [count];
45      for (int i = 0; i < count; i++) {
46              *(data_dictionary+i) = new char[len];
47      }
48
49      int row = 0, col = 0;
50
51      for (int i = 0; i < len; i++)
52      {
53              if (*(words + i) == ' ')
54              {
55                      data_dictionary[row][col] = '\0';
```

Files of Source.cpp

Source.cpp\L22-7904.cpp

```
1 #include<iostream>
2 #include<cstring>
3 using namespace std;
4 bool areEqual(char* w1, char* w2)
5 {
6       int i = 0;
7       while (w1[i] && w2[i])
8       {
9               if (w1[i] != w2[i])
10              {
11                      return false;
12              }
13              i++;
14      }
15      return (w1[i] == '\0' && w2[i] == '\0');
16 }
17 void checkunique(char**& data_dictionary, int& row)
18 {
19      int count = 0;
20      for (int i = 0; i < row; i++)
21      {
22              for (int j = i + 1; j < row; j++)
23              {
24                      if (areEqual(data_dictionary[i], data_dictionary[j]))
25                      {
26                              count++;
27                              for (int k = 0;k < strlen(data_dictionary[i]); k++)
28                              {
29                                      data_dictionary[i][k] = ' ';
30                              }
31                      }
32              }
33      }
34      row = row - count;
35 }
36
37 int main()
38 {
39      //task 1
40      const int Size = 2000;
41      char arr[Size];
42      cin.getline(arr, Size);
43      int row = 2, col = 1;
44      int s = strlen(arr);
45      for (int i = 0;i < s;i++)
46      {
47              if (arr[i] == ' ' || arr[i] == '.')
48              {
49                      row++;
50              }
51      }
52      char** data_dictionary = new char* [row];
53      for (int j = 0;j < row;j++)
54      {
55              data_dictionary[j] = new char[20];   // set maximus length of each word
```

4:51 PM
4/14/2023

What × | Lab M × | Pytho × | GDB × | Class × | repor × | L × | New ×
jplag.github.io/JPlag/comparison/22L_7832.cpp/Source.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L_7832.cpp

Submission 2
Source.cpp

Match %
33.90

Submission 1 File 1	Submission 2 File 2	Tokens
22L_7832.cpp\22L_7832.cpp (44 - 80)	Source.cpp\L22-7904.cpp (52 - 87)	28
22L_7832.cpp\22L_7832.cpp (94 - 102)	Source.cpp\L22-7904.cpp (86 - 95)	20
22L_7832.cpp\22L_7832.cpp (149 - 161)	Source.cpp\L22-7904.cpp (160 - 171)	19
22L_7832.cpp\22L_7832.cpp (32 - 42)	Source.cpp\L22-7904.cpp (43 - 51)	13

```cpp
44      data_dictionary = new char* [count];
45      for (int i = 0; i < count; i++) {
46              *(data_dictionary+i) = new char[len];
47      }
48
49      int row = 0, col = 0;
50
51      for (int i = 0; i < len; i++)
52      {
53              if (*(words + i) == ' ')
54              {
55                      data_dictionary[row][col] = '\0';
56                      row++;
57                      col = 0;
58              }
59              else
60              {
61                      if (col == 0)
62                      {
63                              data_dictionary[row] = new char[len];
64                      }
65                      data_dictionary[row][col] = *(words + i);
66                      col++;
67              }
68      }
69      data_dictionary[row][col] = '\0';
70      char choice;
71      cout << endl << "Do you want to see the data in the Dictionary:(y/n)\n";
72      cin >> choice;
73      if (choice == 'y')
74      {
75              cout << endl;
76              for (int i = 0; i < count; i++)
77              {
78                      cout << *(data_dictionary + i) << endl;
79              }
80      }
81      else
82      {
83              cout << "THANK YOU" << endl;
84      }
85      /*use_Case(data_dictionary);
86      Synonyms(words, size, len,data_dictionary,count);*/
87      return count;
88 }
89
90 void Synonyms(char*& words, const int& size,char**data_dictionary, const int unique_wo
91 {
92      char*** synonym;
93
94      synonym = new char** [size];
95      for (int i = 0; i < size; i++)
96      {
97              *(synonym + i) = new char* [unique_words];
98              for (int j = 0; j < unique_words; j++)
99              {
100                     *(*(synonym + i) + j) = NULL;
101             }
102     }
103     char choice;
104     char  temp[10];
105     int s_count;
106     int s_Len;
107     for (int i = 0; i < size; i++)
108     {
109
110             cout << "Do you want to store a synonym for the word '" << data_dictionar
```

```cpp
52      char** data_dictionary = new char* [row];
53      for (int j = 0;j < row;j++)
54      {
55              data_dictionary[j] = new char[20];   // set maximum length of each word t
56      }
57      int r = 0, c = 0;
58      for (int i = 0; arr[i] != '\0'; i++)
59      {
60              if (arr[i] == ' ' || arr[i] == '.')
61              {
62                      data_dictionary[r][c] = '\0'; // end of word
63                      r++;
64                      c = 0;
65              }
66              else
67              {
68                      data_dictionary[r][c] = arr[i];
69                      c++;
70              }
71      }
72      data_dictionary[r][c] = '\0';
73      //check for unique words
74      checkunique(data_dictionary, row);
75      cout << endl;
76      cout << "____________Tokens:_____________ " << endl;
77      for (int i = 0; i < row-1; i++)
78      {
79              cout << data_dictionary[i] << endl;
80      }
81      cout << endl;
82      //task 2
83      char*** synonyms = new char** [row];
84      for (int i = 0;i < row;i++)
85      {
86              synonyms[i] = new char* [row];
87              for (int j = 0;j < row;j++)
88              {
89                      synonyms[i][j] = new char[row];
90
91                      for (int k = 0;k < row;k++)
92                      {
93                              synonyms[i][j][k] = NULL;
94                      }
95              }
96      }
97      const int x = 100;
98      int counts[x];
99      for (int i = 0; i < row; i++)
100     {
101             counts[i] = 0;
102             cout << "the " << i + 1 << " word of data dictionary is : " << data_dicti
103             char response;
104             cout << "Do you want to store synonyms for this word? (y/n): ";
105             cin >> response;
106
107             if (response == 'y')
108             {
109                     cout << "Enter the number of synonyms: ";
110                     cin >> counts[i];
111                     for (int j = 0; j < counts[i]; j++)
112                     {
113                             char temp[x];
114                             cout << "Enter synonym " << j + 1 << ": ";
115                             cin >> temp;
116
117                             // Allocate memory for synonym in 3D array
118                             synonyms[i][j] = new char[strlen(temp) + 1];
```

4:51 PM
4/14/2023

jplag.github.io/JPlag/comparison/22L_7832.cpp/Source.cpp

JPlag Comparison

back

Submission 1
22L_7832.cpp

Submission 2
Source.cpp

Match %
33.90

Submission 1 File 1	Submission 2 File 2	Tokens
22L_7832.cpp\22L_7832.cpp (44 - 80)	Source.cpp\L22-7904.cpp (52 - 87)	28
22L_7832.cpp\22L_7832.cpp (94 - 102)	Source.cpp\L22-7904.cpp (86 - 95)	20
22L_7832.cpp\22L_7832.cpp (149 - 161)	Source.cpp\L22-7904.cpp (160 - 171)	19
22L_7832.cpp\22L_7832.cpp (32 - 42)	Source.cpp\L22-7904.cpp (43 - 51)	13

```
100                 *(*(synonym + i) + j) = NULL;
101             }
102     }
103     char choice;
104     char  temp[10];
105     int s_count;
106     int s_Len;
107     for (int i = 0; i < size; i++)
108     {
109
110             cout << "Do you want to store a synonym for the word '" << data_dictionar
111             cin >> choice;
112             if (choice == 'y')
113             {
114                     cout << "How many synonyms do you want to enter:\n";
115                     cin >> s_count;
116                     for (int j = 0; j < s_count; j++)
117                     {
118                             cout << "Please enter the synonym of the word " << data_d
119                             cin >> temp;
120                             s_Len = strlen(temp+1);
121                             *(*(synonym + i) + j) = new char[s_Len];
122                             *(*(synonym + i) + j) = temp;
123                     }
124
125             }
126     }
127
128     /*for (int i = 0; i < size; i++) {
129             cout << data_dictionary[i] << ": ";
130             for (int j = 0; j < unique_Words; j++) {
131                     if (synonym[i][j] != nullptr) {
132                             cout << synonym[i][j] << " ";
133                     }
134             }
135             cout << endl;
136     }*/
137
138
139 }
140
141 void use_Case(char** data_dictionary)
142 {
143     const int max_words = 3000;
144     char* useCase1 = new char[max_words];
145     /*cout << "Please enter a long sentence:\n";
146     cin.getline(useCase1, max_words);*/
147     getInput(useCase1, max_words);
148     int use_len;
149     use_len = strlen(useCase1);
150     int use_count = 0;
151     for (int i = 0; i < use_len; i++)
152     {
153             for (int j = 0; j < use_len; j++)
154             {
155                     if (useCase1[j] == data_dictionary[i][j])
156                     {
157                             use_count++;
158                             cout << useCase1[i] << endl;
159                     }
160             }
161     }
162 }
```

```
139     for (int j = 0;j < row;j++)
140     {
141             temp[j] = new char[20];
142     }
143
144
145     int n = 0, m = 0;
146     for (int i = 0; useCase1[i] != '\0'; i++)
147     {
148             if (useCase1[i] == ' ' || useCase1[i] == '.')
149             {
150                     temp[n][m] = '\0';
151                     n++;
152                     m = 0;
153             }
154             else
155             {
156                     temp[n][m] = useCase1[i];
157                     m++;
158             }
159     }
160     temp[n][m] = '\0';
161     int count = 0;
162     for (int i = 0; i < n; i++)
163     {
164             for (int j = 0; j < row; j++)
165             {
166                     if (areEqual(temp[i], data_dictionary[j]))
167                     {
168                             count++;
169                     }
170             }
171     }
172     cout << "these are " << count << " words in data dictionary" << endl;
173     for (int i = 0; i < n; i++)
174     {
175             for (int j = 0; j < row; j++)
176             {
177                     if (areEqual(temp[i], data_dictionary[j]))
178                     {
179                             cout << temp[i] << endl;
180                     }
181             }
182     }
183     //task 4
184     char resp;
185     for (int i = 0; i < n; i++)
186     {
187             for (int j = 0; j < row; j++)
188             {
189                     if (areEqual(temp[i], data_dictionary[j]))
190                     {
191                             resp = 'y';
192                     }
193                     else
194                     {
195                             resp = 'n';
196                     }
197             }
198     }
199
200     system("pause");
201     return 0;
202 }
```

4:51 PM
4/14/2023

What × | Lab M × | Pyth × | GDB × | Class × | repor × | L × | New ×

jplag.github.io/JPlag/comparison/22L_7832.cpp/Source.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L_7832.cpp

Submission 2
Source.cpp

Match %
33.90

Submission 1 File 1	Submission 2 File 2	Tokens
22L_7832.cpp\22L_7832.cpp (44 - 80)	Source.cpp\L22-7904.cpp (52 - 87)	28
22L_7832.cpp\22L_7832.cpp (94 - 102)	Source.cpp\L22-7904.cpp (86 - 95)	20
22L_7832.cpp\22L_7832.cpp (149 - 161)	Source.cpp\L22-7904.cpp (160 - 171)	19
22L_7832.cpp\22L_7832.cpp (32 - 42)	Source.cpp\L22-7904.cpp (43 - 51)	13

```
52      int count = 1;
53      int len;
54      len = strlen(words);
55
56      for (int i = 0; i < len; i++)
57      {
58              if (*(words + i) == ' ')
59              {
60                      count++;
61              }
62      }
43
44      data_dictionary = new char* [count];
45      for (int i = 0; i < count; i++) {
46              *(data_dictionary+i) = new char[len];
47      }
48
49      int row = 0, col = 0;
50
51      for (int i = 0; i < len; i++)
52      {
53              if (*(words + i) == ' ')
54              {
55                      data_dictionary[row][col] = '\0';
56                      row++;
57                      col = 0;
58              }
59              else
60              {
61                      if (col == 0)
62                      {
63                              data_dictionary[row] = new char[len];
64                      }
65                      data_dictionary[row][col] = *(words + i);
66                      col++;
67              }
68      }
69      data_dictionary[row][col] = '\0';
70      char choice;
71      cout << endl << "Do you want to see the data in the Dictionary:(y/n)\n";
72      cin >> choice;
73      if (choice == 'y')
74      {
75              cout << endl;
76              for (int i = 0; i < count; i++)
77              {
78                      cout << *(data_dictionary + i) << endl;
79              }
80      }
81      else
82      {
83              cout << "THANK YOU" << endl;
84      }
85      /*use_Case(data_dictionary);
86      Synonyms(words, size, len,data_dictionary,count);*/
87      return count;
88 }
89
90 void Synonyms(char& words, const int& size,char**data_dictionary, const int unique_wo
91 {
92      char*** synonym;
93
94      synonym = new char** [size];
95      for (int i = 0; i < size; i++)
96      {
97              *(synonym + i) = new char* [unique_words];
```

```
43      int row = 2, col = 1;
44      int s = strlen(arr);
45      for (int i = 0;i < s;i++)
46      {
47              if (arr[i] == ' ' || arr[i] == '.')
48              {
49                      row++;
50              }
51      }
52      char** data_dictionary = new char* [row];
53      for (int j = 0;j < row;j++)
54      {
55              data_dictionary[j] = new char[20];   // set maximum length of each word t
56      }
57      int r = 0, c = 0;
58      for (int i = 0; arr[i] != '\0'; i++)
59      {
60              if (arr[i] == ' ' || arr[i] == '.')
61              {
62                      data_dictionary[r][c] = '\0'; // end of word
63                      r++;
64                      c = 0;
65              }
66              else
67              {
68                      data_dictionary[r][c] = arr[i];
69                      c++;
70              }
71      }
72      data_dictionary[r][c] = '\0';
73      //check for unique words
74      checkunique(data_dictionary, row);
75      cout << endl;
76      cout << "_____Tokens:_____ " << endl;
77      for (int i = 0; i < row-1; i++)
78      {
79              cout << data_dictionary[i] << endl;
80      }
81      cout << endl;
82      //task 2
83      char*** synonyms = new char** [row];
84      for (int i = 0;i < row;i++)
85      {
86              synonyms[i] = new char* [row];
87              for (int j = 0;j < row;j++)
88              {
89                      synonyms[i][j] = new char[row];
90
91                      for (int k = 0;k < row;k++)
92                      {
93                              synonyms[i][j][k] = NULL;
94                      }
95              }
96      }
97      const int x = 100;
98      int counts[x];
99      for (int i = 0; i < row; i++)
100     {
101             counts[i] = 0;
102             cout << "the " << i + 1 << " word of data dictionary is : " << data_dicti
103             char response;
104             cout << "Do you want to store synonyms for this word? (y/n): ";
105             cin >> response;
106
107             if (response == 'y')
```

4:51 PM
4/14/2023