What Lab M Pyth GDB Class repor L New
jplag.github.io/JPlag/comparison/Source.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
Source.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
93.45

Submission 1 File 1	Submission 2 File 2	Tokens
Source.cpp\L22-7904.cpp (4 - 101)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (4 - 100)	147
Source.cpp\L22-7904.cpp (120 - 197)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (125 - 202)	111
Source.cpp\L22-7904.cpp (103 - 119)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (103 - 119)	13

Files of Source.cpp

Source.cpp\L22-7904.cpp

```cpp
#include<iostream>
#include<cstring>
using namespace std;
bool areEqual(char* w1, char* w2)
{
	int i = 0;
	while (w1[i] && w2[i])
	{
		if (w1[i] != w2[i])
		{
			return false;
		}
		i++;
	}
	return (w1[i] == '\0' && w2[i] == '\0');
}
void checkunique(char**& data_dictionary, int& row)
{
	int count = 0;
	for (int i = 0; i < row; i++)
	{
		for (int j = i + 1; j < row; j++)
		{
			if (areEqual(data_dictionary[i], data_dictionary[j]))
			{
				count++;
				for (int k = 0;k < strlen(data_dictionary[i]); k++)
				{
					data_dictionary[i][k] = ' ';
				}
			}
		}
	}
	row = row - count;
}

int main()
{
	//task 1
	const int Size = 2000;
	char arr[Size];
	cin.getline(arr, Size);
	int row = 2, col = 1;
	int s = strlen(arr);
	for (int i = 0;i < s;i++)
	{
		if (arr[i] == ' ' || arr[i] == '.')
		{
			row++;
		}
	}
	char** data_dictionary = new char* [row];
	for (int j = 0;j < row;j++)
	{
		data_dictionary[j] = new char[20];   // set maximum length of each word t
	}
```

Files of 22I 7957 assignment 1.cpp

..ignment 1.cpp\22I 7957 assignment 1.cpp

```cpp
#include<iostream>
#include<cstring>
using namespace std;
bool areEqual(char* w1, char* w2)
{
	int i = 0;
	while (w1[i] && w2[i])
	{
		if (w1[i] != w2[i])
		{
			return false;
		}
		i++;
	}
	return (w1[i] == '\0' && w2[i] == '\0');
}
void checkunique(char**& data_dictionary, int& row)
{
	int count = 0;
	for (int i = 0; i < row; i++)
	{
		for (int j = i + 1; j < row; j++)
		{
			if (areEqual(data_dictionary[i], data_dictionary[j]))
			{
				count++;
				for (int k = 0;k < strlen(data_dictionary[i]); k++)
				{
					data_dictionary[i][k] = ' ';
				}
			}
		}
	}
	row = row - count;
}
int main()
{
	//task 1
	const int Size = 2000;
	char arr[Size];
	cin.getline(arr, Size);
	int row = 2, col = 1;
	int s = strlen(arr);
	for (int i = 0;i < s;i++)
	{
		if (arr[i] == ' ' || arr[i] == '.')
		{
			row++;
		}
	}
	char** data_dictionary = new char* [row];
	for (int j = 0;j < row;j++)
	{
		data_dictionary[j] = new char[20];   // set maximum length of each word t
	}
	int r = 0, c = 0;
```

4:51 PM
4/14/2023

What × | Lab M × | Pyth × | GDB × | Class × | repor × | L × | New ×

jplag.github.io/JPlag/comparison/Source.cpp/22I%207957%20%20assignment%201.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
Source.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
93.45

Submission 1 File 1	Submission 2 File 2	Tokens
Source.cpp\L22-7904.cpp (4 - 101)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (4 - 100)	147
Source.cpp\L22-7904.cpp (120 - 197)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (125 - 202)	111
Source.cpp\L22-7904.cpp (103 - 119)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (103 - 119)	13

```cpp
bool areEqual(char* w1, char* w2)
{
    int i = 0;
    while (w1[i] && w2[i])
    {
        if (w1[i] != w2[i])
        {
            return false;
        }
        i++;
    }
    return (w1[i] == '\0' && w2[i] == '\0');
}
void checkunique(char**& data_dictionary, int& row)
{
    int count = 0;
    for (int i = 0; i < row; i++)
    {
        for (int j = i + 1; j < row; j++)
        {
            if (areEqual(data_dictionary[i], data_dictionary[j]))
            {
                count++;
                for (int k = 0;k < strlen(data_dictionary[i]); k++)
                {
                    data_dictionary[i][k] = ' ';
                }
            }
        }
    }
    row = row - count;
}

int main()
{
    //task 1
    const int Size = 2000;
    char arr[Size];
    cin.getline(arr, Size);
    int row = 2, col = 1;
    int s = strlen(arr);
    for (int i = 0;i < s;i++)
    {
        if (arr[i] == ' ' || arr[i] == '.')
        {
            row++;
        }
    }
    char** data_dictionary = new char* [row];
    for (int j = 0;j < row;j++)
    {
        data_dictionary[j] = new char[20];   // set maximum length of each word t
    }
    int r = 0, c = 0;
    for (int i = 0; arr[i] != '\0'; i++)
    {
        if (arr[i] == ' ' || arr[i] == '.')
        {
            data_dictionary[r][c] = '\0'; // end of word
            r++;
            c = 0;
        }
        else
        {
            data_dictionary[r][c] = arr[i];
            c++;
        }
    }
    data_dictionary[r][c] = '\0';
```

```cpp
bool areEqual(char* w1, char* w2)
{
    int i = 0;
    while (w1[i] && w2[i])
    {
        if (w1[i] != w2[i])
        {
            return false;
        }
        i++;
    }
    return (w1[i] == '\0' && w2[i] == '\0');
}
void checkunique(char**& data_dictionary, int& row)
{
    int count = 0;
    for (int i = 0; i < row; i++)
    {
        for (int j = i + 1; j < row; j++)
        {
            if (areEqual(data_dictionary[i], data_dictionary[j]))
            {
                count++;
                for (int k = 0;k < strlen(data_dictionary[i]); k++)
                {
                    data_dictionary[i][k] = ' ';
                }
            }
        }
    }
    row = row - count;
}
int main()
{
    //task 1
    const int Size = 2000;
    char arr[Size];
    cin.getline(arr, Size);
    int row = 2, col = 1;
    int s = strlen(arr);
    for (int i = 0;i < s;i++)
    {
        if (arr[i] == ' ' || arr[i] == '.')
        {
            row++;
        }
    }
    char** data_dictionary = new char* [row];
    for (int j = 0;j < row;j++)
    {
        data_dictionary[j] = new char[20];   // set maximum length of each word t
    }
    int r = 0, c = 0;
    for (int i = 0; arr[i] != '\0'; i++)
    {
        if (arr[i] == ' ' || arr[i] == '.')
        {
            data_dictionary[r][c] = '\0'; // end of word
            r++;
            c = 0;
        }
        else
        {
            data_dictionary[r][c] = arr[i];
            c++;
        }
    }
    data_dictionary[r][c] = '\0';
    //check for unique words
```

4:51 PM
4/14/2023

What × | Lab M × | Pyth × | GDB × | Class × | repor × | L × | New ×

jplag.github.io/JPlag/comparison/Source.cpp/22I%207957%20%20assignment%201.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
Source.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
93.45

Submission 1 File 1	Submission 2 File 2	Tokens
Source.cpp\L22-7904.cpp (4 - 101)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (4 - 100)	147
Source.cpp\L22-7904.cpp (120 - 197)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (125 - 202)	111
Source.cpp\L22-7904.cpp (103 - 119)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (103 - 119)	13

```
120                 }
121         }
122 }
123 //task 3
124 int Siz = 2000;
125 char* useCase1 = new char[Siz];
126 cout << "Enter Sentence : " << endl;
127 cin.ignore();
128 cin.getline(useCase1, Siz);
129 int S = strlen(useCase1);
130 int rw = 1, cl = 1;
131 for (int i = 0;i < S;i++)
132 {
133         if (useCase1[i] == ' ' || useCase1[i] == '.')
134         {
135                 rw++;
136         }
137 }
138 char** temp = new char* [rw];
139 for (int j = 0;j < row;j++)
140 {
141         temp[j] = new char[20];
142 }
143
144
145 int n = 0, m = 0;
146 for (int i = 0; useCase1[i] != '\0'; i++)
147 {
148         if (useCase1[i] == ' ' || useCase1[i] == '.')
149         {
150                 temp[n][m] = '\0';
151                 n++;
152                 m = 0;
153         }
154         else
155         {
156                 temp[n][m] = useCase1[i];
157                 m++;
158         }
159 }
160 temp[n][m] = '\0';
161 int count = 0;
162 for (int i = 0; i < n; i++)
163 {
164         for (int j = 0; j < row; j++)
165         {
166                 if (areEqual(temp[i], data_dictionary[j]))
167                 {
168                         count++;
169                 }
170         }
171 }
172 cout << "these are " << count << " words in data dictionary" << endl;
173 for (int i = 0; i < n; i++)
174 {
175         for (int j = 0; j < row; j++)
176         {
177                 if (areEqual(temp[i], data_dictionary[j]))
178                 {
179                         cout << temp[i] << endl;
180                 }
181         }
182 }
183 //task 4
184 char resp;
185 for (int i = 0; i < n; i++)
186 {
187         for (int j = 0; j < row; j++)
188         {
```

```
125                 }
126         }
127 }
128 //task 3
129 int Siz = 2000;
130 char* useCase1 = new char[Siz];
131 cout << "Enter Sentence : " << endl;
132 cin.ignore();
133 cin.getline(useCase1, Siz);
134 int S = strlen(useCase1);
135 int rw = 1, cl = 1;
136 for (int i = 0;i < S;i++)
137 {
138         if (useCase1[i] == ' ' || useCase1[i] == '.')
139         {
140                 rw++;
141         }
142 }
143 char** temp = new char* [rw];
144 for (int j = 0;j < row;j++)
145 {
146         temp[j] = new char[20];
147 }
148
149
150 int n = 0, m = 0;
151 for (int i = 0; useCase1[i] != '\0'; i++)
152 {
153         if (useCase1[i] == ' ' || useCase1[i] == '.')
154         {
155                 temp[n][m] = '\0';
156                 n++;
157                 m = 0;
158         }
159         else
160         {
161                 temp[n][m] = useCase1[i];
162                 m++;
163         }
164 }
165 temp[n][m] = '\0';
166 int count = 0;
167 for (int i = 0; i < n; i++)
168 {
169         for (int j = 0; j < row; j++)
170         {
171                 if (areEqual(temp[i], data_dictionary[j]))
172                 {
173                         count++;
174                 }
175         }
176 }
177 cout << "these are " << count << " words in data dictionary" << endl;
178 for (int i = 0; i < n; i++)
179 {
180         for (int j = 0; j < row; j++)
181         {
182                 if (areEqual(temp[i], data_dictionary[j]))
183                 {
184                         cout << temp[i] << endl;
185                 }
186         }
187 }
188 //task 4
189 char resp;
190 for (int i = 0; i < n; i++)
191 {
192         for (int j = 0; j < row; j++)
193         {
```

4:51 PM
4/14/2023

What × | Lab M × | Pytho × | GDB × | Class × | repor × | L × | New ×
jplag.github.io/JPlag/comparison/Source.cpp/22I%207957%20%20assignment%201.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
Source.cpp

Submission 2
22I 7957 assignment 1.cpp

Match %
93.45

Submission 1 File 1	Submission 2 File 2	Tokens
Source.cpp\L22-7904.cpp (4 - 101)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (4 - 100)	147
Source.cpp\L22-7904.cpp (120 - 197)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (125 - 202)	111
Source.cpp\L22-7904.cpp (103 - 119)	22I 7957 assignment 1.cpp\22I 7957 assignment 1.cpp (103 - 119)	13

```
103             char response;
104             cout << "Do you want to store synonyms for this word? (y/n): ";
105             cin >> response;
106
107             if (response == 'y')
108             {
109                     cout << "Enter the number of synonyms: ";
110                     cin >> counts[i];
111                     for (int j = 0; j < counts[i]; j++)
112                     {
113                             char temp[x];
114                             cout << "Enter synonym " << j + 1 << ": ";
115                             cin >> temp;
116
117                             // Allocate memory for synonym in 3D array
118                             synonyms[i][j] = new char[strlen(temp) + 1];
119                             synonyms[i][j] = temp;
120                     }
121             }
122     }
123     //task 3
124     int Siz = 2000;
125     char* useCase1 = new char[Siz];
126     cout << "Enter Sentence : " << endl;
127     cin.ignore();
128     cin.getline(useCase1, Siz);
129     int S = strlen(useCase1);
130     int rw = 1, cl = 1;
131     for (int i = 0;i < S;i++)
132     {
133             if (useCase1[i] == ' ' || useCase1[i] == '.')
134             {
135                     rw++;
136             }
137     }
138     char** temp = new char* [rw];
139     for (int j = 0;j < row;j++)
140     {
141             temp[j] = new char[20];
142     }
143
144
145     int n = 0, m = 0;
146     for (int i = 0; useCase1[i] != '\0'; i++)
147     {
148             if (useCase1[i] == ' ' || useCase1[i] == '.')
149             {
150                     temp[n][m] = '\0';
151                     n++;
152                     m = 0;
153             }
154             else
155             {
156                     temp[n][m] = useCase1[i];
157                     m++;
158             }
159     }
160     temp[n][m] = '\0';
161     int count = 0;
162     for (int i = 0; i < n; i++)
163     {
164             for (int j = 0; j < row; j++)
165             {
166                     if (areEqual(temp[i], data_dictionary[j]))
167                     {
168                             count++;
169                     }
170             }
```

```
103             char response;
104             cout << "Do you want to store synonyms for this word? (y/n): ";
105             cin >> response;
106
107             if (response == 'y')
108             {
109                     cout << "Enter the number of synonyms: ";
110                     cin >> counts[i];
111                     for (int j = 0; j < counts[i]; j++)
112                     {
113                             char temp[x];
114                             cout << "Enter synonym " << j + 1 << ": ";
115                             cin >> temp;
116
117                             // Allocate memory for synonym in 3D array
118                             synonyms[i][j] = new char[strlen(temp) + 1];
119                             synonyms[i][j] = data_dictionary[i];
120                             for (int k = 0;k < counts[i];k++)
121                             {
122                                     synonyms[i][j][k] = temp[k];
123                             }
124                     }
125             }
126     }
127     //task 3
128     int Siz = 2000;
129     char* useCase1 = new char[Siz];
130     cout << "Enter Sentence : " << endl;
131     cin.ignore();
132     cin.getline(useCase1, Siz);
133     int S = strlen(useCase1);
134     int rw = 1, cl = 1;
135     for (int i = 0;i < S;i++)
136     {
137             if (useCase1[i] == ' ' || useCase1[i] == '.')
138             {
139                     rw++;
140             }
141     }
142     char** temp = new char* [rw];
143     for (int j = 0;j < row;j++)
144     {
145             temp[j] = new char[20];
146     }
147
148
149     int n = 0, m = 0;
150     for (int i = 0; useCase1[i] != '\0'; i++)
151     {
152             if (useCase1[i] == ' ' || useCase1[i] == '.')
153             {
154                     temp[n][m] = '\0';
155                     n++;
156                     m = 0;
157             }
158             else
159             {
160                     temp[n][m] = useCase1[i];
161                     m++;
162             }
163     }
164     temp[n][m] = '\0';
165     int count = 0;
166     for (int i = 0; i < n; i++)
167     {
168             for (int j = 0; j < row; j++)
169             {
170
```

4:51 PM
4/14/2023