WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022l-7906.cpp/22L-6194.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22l-7906.cpp

Submission 2
22L-6194.cpp

Match %
22.19

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (235 - 248)	22L-6194.cpp\22L-6194.cpp (211 - 220)	19
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (120 - 128)	22L-6194.cpp\22L-6194.cpp (76 - 85)	14
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (66 - 72)	22L-6194.cpp\22L-6194.cpp (12 - 18)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (90 - 96)	22L-6194.cpp\22L-6194.cpp (45 - 50)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (158 - 166)	22L-6194.cpp\22L-6194.cpp (95 - 103)	12

Files of assignment 1 22l-7906.cpp

..1 22l-7906.cpp\assignment 1 22l-7906.cpp

```cpp
#include <iostream>
#include<fstream>
using namespace std;
char choice;
int synonym_count;
char temp[1000];
int ft = 0;
int t = 0;


bool SearchUnique(char** data_dict, int data_count, char* word,int &f_index )
{
    for (int i = 0; i < data_count; i++)
    {
        int j = 0;
        while (data_dict[i][j] != '\0' && word[j] != '\0')
        {
            if (data_dict[i][j] != word[j])
            {
                break;
            }
            j++;
        }
        if (data_dict[i][j] == '\0' && word[j] == '\0')
        {
            f_index = i;
            return true;
        }
    }
    return false;
}
bool checkSynonum(char*** synonym, char* word, int data_count,int f_index)
{
    for (int i = 0; i < data_count && f_index!=-1; i++)
    {
        if (synonym[f_index] != nullptr)
        {
            return true;
        }
    }
    return false;
}
int main()
{
    char text[3000];
    cout << "Enter data\n ";
    cin.getline(text, 3000);
    char** data_dict = new char* [3000];
    int data_count = 0, start = 0,f_index=-1;
    for (int i = 0; text[i] != '\0'; i++)
    {
        if (text[i] == ' ' || text[i] == '.')
        {
            char* word = new char[(i - start) + 1];
            int j = 0;
            for (int k = start; k < i; k++)
            {
```

Files of 22L-6194.cpp

22L-6194.cpp\22L-6194.cpp

```cpp
#include <iostream>
#include <cstring>
using namespace std;

void Tokenization(char input[], char** dataDictionary,int&numWords) {

    int startIndex = 0;
    for (int i = 0; i < strlen(input); i++) {
        if (input[i] == ' ' || input[i] == '.') {
            int length = i - startIndex;
            if (length > 0) {
                char* word = new char[length + 1];
                for (int j = 0; j < length; j++) {
                    word[j] = input[startIndex + j];
                }
                word[length] = '\0';
                // Check for duplicates
                bool found = false;
                for (int j = 0; j < numWords; j++) {
                    if (strcmp(word, dataDictionary[j]) == 0) {
                        found = true;
                        break;
                    }
                }

                if (!found) {
                    dataDictionary[numWords] = word;
                    numWords++;
                }
                else {
                    delete[] word;
                }
            }
            startIndex = i + 1;
        }
    }


    cout << "Data Dictionary:" << endl;
    for (int i = 0; i < numWords; i++) {
        cout << dataDictionary[i] << endl;
    }
}
void getsynonyms(char***synonyms,char**dataDictionary,int&numWords) {

    for (int i = 0; i < numWords; i++) {
        synonyms[i] = nullptr;
    }


    for (int i = 0; i < numWords; i++) {

        char* word = dataDictionary[i];


        cout << "Do you want to store synonyms for " << word << "? (y/n): ";
```

1:20 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022l-7906.cpp/22L-6194.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22l-7906.cpp

Submission 2
22L-6194.cpp

Match %
22.19

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (235 - 248)	22L-6194.cpp\22L-6194.cpp (211 - 220)	19
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (120 - 128)	22L-6194.cpp\22L-6194.cpp (76 - 85)	14
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (66 - 72)	22L-6194.cpp\22L-6194.cpp (12 - 18)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (90 - 96)	22L-6194.cpp\22L-6194.cpp (45 - 50)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (158 - 166)	22L-6194.cpp\22L-6194.cpp (95 - 103)	12

```cpp
    char useCase2[2000];
    char f_text[1000];
    cout << "Input:";
    cin.getline(useCase2, 2000);
    index = 0;
    int text_c = 0;
    for (int i = 0; useCase2[i] != '\0'; i++)
    {
        if (useCase2[i] == ' ' || useCase2[i] == '.')
        {
            char* word = new char[(i - index) + 1];
            int j = 0;
            for (int k = index; k < i; k++)
            {
                word[j] = useCase2[k];
                j++;
            }
            word[j] = '\0';

            if (SearchUnique(data_dict, data_count, word,f_index))
            {
                if (checkSynonum(synonym, word, data_count,f_index))
                {
                    for (; temp[t] != '#'; t++)
                    {
                        cout << temp[t];
                    }
                    t++;
                    cout << " ";

                }
                else
               cout<< word << " ";
            }
            else
            {
                cout << word<<" ";
            }
            delete[] word;
            index = i + 1;
        }
    }



    for (int i = 0; i < data_count; i++)
    {
        delete[] data_dict[i];
        if (synonym[i] != nullptr)
        {
            for (int j = 0; j < synonym_count; j++)
            {
                delete[] synonym[i][j];
            }
            delete[] synonym[i];
        }
    }

    delete[] data_dict;

    delete[] synonym;
    system("Pause>0");
    return 0;
}
```

```cpp
                        temp[forTemp++] = synonyms[j][0][n++];
                    }
                    while (useCase1[i] != ' ' && useCase1[i] != '.' && useCas
                    {
                        i++;
                    }
                }
                else
                {
                    while (useCase1[i] != ' ' && useCase1[i] != '.' && useCas
                    {
                        temp[forTemp++] = useCase1[i++];
                    }
                }
                if (useCase1[i] == ' ')
                    temp[forTemp++] = ' ';
                else
                    temp[forTemp++] = '.';
            }

    }
    temp[forTemp] = '\0';
    cout << temp;
}
void deallocation(char*** &synonyms, char** &dataDictionary, char* &UseCase1,int numW

    for (int i = 0; i < numWords; i++) {
        delete[] dataDictionary[i];
        if (synonyms[i] != nullptr) {
            for (int j = 0; synonyms[i][j] != nullptr; j++) {
                delete[] synonyms[i][j];
            }
            delete[] synonyms[i];
        }
    }
    delete[] dataDictionary;

    dataDictionary = NULL;
    delete[] synonyms;
    synonyms = NULL;
    delete[]UseCase1;
    UseCase1 = NULL;
}

int main() {

    char input[3000];
    char** dataDictionary = new char* [3000];
    cout << "Enter data (at least 4-5 sentences, each sentence ending with a fullstop

    cin.getline(input, 3000);
    int numWords = 0;
    Tokenization(input, dataDictionary,numWords);
    char*** synonyms = new char** [numWords];
    getsynonyms(synonyms, dataDictionary,numWords);
    char* UseCase1 = new char[3000];
    cout << "Enter string (each sentence ending with a fullstop): ";
    cin.ignore();
    cin.getline(UseCase1, 3000);
    SearchWord(UseCase1, dataDictionary, numWords);
    replaceSynonyms( synonyms, dataDictionary, numWords);
    deallocation(synonyms, dataDictionary, UseCase1,numWords);


    return 0;
}
```

1:20 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22L-6194.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22L-6194.cpp

Match %
22.19

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (235 - 248)	22L-6194.cpp\22L-6194.cpp (211 - 220)	19
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (120 - 128)	22L-6194.cpp\22L-6194.cpp (76 - 85)	14
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (66 - 72)	22L-6194.cpp\22L-6194.cpp (12 - 18)	12
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (90 - 96)	22L-6194.cpp\22L-6194.cpp (45 - 50)	12
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (158 - 166)	22L-6194.cpp\22L-6194.cpp (95 - 103)	12

```
                synonym[i][j] = new char[strlen(user_synonym) + 1];
                for (int k = 0; k < strlen(user_synonym); k++)
                {
                    synonym[i][j][k] = user_synonym[k];
                }
                synonym[i][j][strlen(user_synonym)] = '\0';
            }
        }
        else
            synonym[i] = nullptr;
        if (choice != 'n' && choice != 'N' && choice != 'Y' && choice != 'y')
        {
            cout << "Enter correct choice:\n";
                goto again;
        }


    }

    for (int i = 0; i < counter; i++)
    {
        cout << "Input word : " << data_dict[i] << endl;
        if (synonym[i] != nullptr)
        {
            for (int j = 0; j < synonym_count; j++)
            {
                cout << "Synonym: ";
                for (int k = 0; synonym[i][j][k] != '\0'; k++)
                {
                    cout << synonym[i][j][k];
                }
                cout << endl;
            }
        }
        cout << endl;
    }

            //++task 3++//

      char useCase1[2000];
    cout << "Enter use case: ";
    cin.getline(useCase1, 2000);
    int c= 0;
    int index = 0;
    for (int i = 0; useCase1[i] != '\0'; i++)
    {
        if (useCase1[i] == ' '||useCase1[i]=='.')
        {
            char* word = new char[(i - index) + 1];
            int j = 0;
            for (int k = index; k < i; k++)
            {
                word[j] = useCase1[k];
                j++;
            }
            word[j] = '\0';

            if (SearchUnique(data_dict, data_count, word,f_index))
            {
                cout << "Word: " << word << endl;
                index++;
                c++;
            }
            delete[] word;
            index = i + 1;
        }
    }
    cout << "There were " << c << " words\n";
```

```
                synonyms[i][j] = new char[strlen(temp) + 1];

                // Copy the data character by character
                for (int k = 0; k < strlen(temp); k++) {
                    synonyms[i][j][k] = temp[k];
                }
                synonyms[i][j][strlen(temp)] = '\0';
            }
        }
        else if (choice == 'n' || choice == 'N')
        {
            synonyms[i] = new char* [1];
            synonyms[i][0] = new char[10];
            synonyms[i][0][0] = '\0';
        }
    }
}
void SearchWord(char* UseCase1, char** dataDictionary, int numWords) {
    const int WORD_LEN = 1000;

    char word[WORD_LEN];

    int startIndex = 0;
    int count = 0;

     cout << "Matched words:" << endl;

     for (int i = 0; i <= strlen(UseCase1); i++) {
         if (UseCase1[i] == ' ' || UseCase1[i] == '.') {
            int length = i - startIndex;
            if (length > 0) {
                if (length >=WORD_LEN) {
                    cout << "Error: word length exceeds maximum length." << endl;
                    return;
                }
                for (int j = 0; j < length; j++) {
                    word[j] = UseCase1[startIndex + j];
                }
                word[length] = '\0';

                bool found = false;
                for (int j = 0; j < numWords; j++) {
                    if (strcmp(word, dataDictionary[j]) == 0) {
                        found = true;
                        break;
                    }
                }
                if (found) {
                    cout << word << endl;
                    count++;
                }

            }
            startIndex = i + 1;
        }
    }

    if (count == 0) {
        cout << "No words found in data dictionary." << endl;
    }
    else {
        cout << "Total matched words: " << count << endl;
    }
}
void replaceSynonyms(char*** synonyms, char** dataDictionary, int wordCount)
{
    bool isPresent = true;
    char* useCase1 = new char[2000];
```

1:20 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022l-7906.cpp/22L-6194.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22l-7906.cpp

Submission 2
22L-6194.cpp

Match %
22.19

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (235 - 248)	22L-6194.cpp\22L-6194.cpp (211 - 220)	19
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (120 - 128)	22L-6194.cpp\22L-6194.cpp (76 - 85)	14
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (66 - 72)	22L-6194.cpp\22L-6194.cpp (12 - 18)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (90 - 96)	22L-6194.cpp\22L-6194.cpp (45 - 50)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (158 - 166)	22L-6194.cpp\22L-6194.cpp (95 - 103)	12

```cpp
66                  date_dict[data_count] = new char[word_length + 1];
67                  for (int k = 0; k < word_length; k++)
68                  {
69                      data_dict[data_count][k] = word[k];
70                  }
71                  data_dict[data_count][word_length] = '\0';
72                  data_count++;
73              }
74
75              start = i + 1;
76              delete[] word;
77          }
78      }
79
80
81                      ///+++Task 2+++///
82
83      int counter = 0;
84      for (int i = 0; i < data_count; i++)
85      {
86          cout << data_dict[i] << endl;
87          counter++;
88      }
89      char+++ synonym = new char++ [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
99          cin >> choice;
100         if (choice == 'Y' || choice == 'y')
101         {
102             cout << "How many synonyms do you want to store for " << data_dict[i] <<
103
104             cin >> synonym_count;
105             cin.ignore();
106             synonym[i] = new char+ [synonym_count];
107             for (int j = 0; j < synonym_count; j++)
108             {
109                 cout << "Enter synonym for " << data_dict[i] << endl;
110                 char user_synonym[30];
111                 cin.getline(user_synonym, 30);
112                 for (int i = 0; user_synonym[i] != '\0'; i++)
113                 {
114                     temp[ft++] = user_synonym[i];
115                 }
116                 temp[ft++]='#';
117
118
119
120                 synonym[i][j] = new char[strlen(user_synonym) + 1];
121                 for (int k = 0; k < strlen(user_synonym); k++)
122                 {
123                     synonym[i][j][k] = user_synonym[k];
124                 }
125                 synonym[i][j][strlen(user_synonym)] = '\0';
126             }
127         }
128         else
129             synonym[i] = nullptr;
130         if (choice != 'n' && choice != 'N' && choice != 'Y' && choice != 'y')
```

```cpp
12                  char+ word = new char[length + 1];
13                  for (int j = 0; j < length; j++) {
14                      word[j] = input[startIndex + j];
15                  }
16                  word[length] = '\0';
17                  // Check for duplicates
18                  bool found = false;
19                  for (int j = 0; j < numWords; j++) {
20                      if (strcmp(word, dataDictionary[j]) == 0) {
21                          found = true;
22                          break;
23                      }
24                  }
25
26                  if (!found) {
27                      dataDictionary[numWords] = word;
28                      numWords++;
29                  }
30                  else {
31                      delete[] word;
32                  }
33              }
34              startIndex = i + 1;
35          }
36      }
37
38
39      cout << "Data Dictionary:" << endl;
40      for (int i = 0; i < numWords; i++) {
41          cout << dataDictionary[i] << endl;
42      }
43  }
44  void getsynonyms(char+++synonyms,char++dataDictionary,int&numWords) {
45      for (int i = 0; i < numWords; i++) {
46          synonyms[i] = nullptr;
47      }
48
49
50      for (int i = 0; i < numWords; i++) {
51          char+ word = dataDictionary[i];
52
53
54          cout << "Do you want to store synonyms for " << word << "? (y/n): ";
55          char choice;
56          cin >> choice;
57
58          if (choice == 'Y' || choice == 'Y') {
59
60              int count;
61              cout << "How many synonyms do you want to store? ";
62              cin >> count;
63
64              // Allocate memory for the synonyms at this index
65              synonyms[i] = new char+ [count];
66
67
68              for (int j = 0; j < count; j++) {
69
70                  static char temp[100];
71
72                  cout << "Enter synonym #" << j + 1 << " for " << word << ": ";
73                  cin >> temp;
74
75                  // Allocate memory for the synonym at this index
76                  synonyms[i][j] = new char[strlen(temp) + 1];
77
```

1:20 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022l-7906.cpp/22L-6194.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22l-7906.cpp

Submission 2
22L-6194.cpp

Match %
22.19

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (235 - 248)	22L-6194.cpp\22L-6194.cpp (211 - 220)	19
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (120 - 128)	22L-6194.cpp\22L-6194.cpp (76 - 85)	14
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (66 - 72)	22L-6194.cpp\22L-6194.cpp (12 - 18)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (90 - 96)	22L-6194.cpp\22L-6194.cpp (45 - 50)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (158 - 166)	22L-6194.cpp\22L-6194.cpp (95 - 103)	12

```cpp
    for (int i = 0; i < counter; i++)
    {
        synonym[i] = nullptr;
    }

    for (int i = 0; i < counter; i++)
    {

        again:
        cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
        cin >> choice;
         if (choice == 'Y' || choice == 'y')
         {
             cout << "How many synonyms do you want to store for " << data_dict[i] <<

             cin >> synonym_count;
             cin.ignore();
             synonym[i] = new char* [synonym_count];
             for (int j = 0; j < synonym_count; j++)
             {
                 cout << "Enter synonym for " << data_dict[i] << endl;
                 char user_synonym[30];
                 cin.getline(user_synonym, 30);
                 for (int i = 0; user_synonym[i] != '\0'; i++)
                 {
                     temp[ft++] = user_synonym[i];
                 }
                 temp[ft++]='#';



                 synonym[i][j] = new char[strlen(user_synonym) + 1];
                 for (int k = 0; k < strlen(user_synonym); k++)
                 {
                     synonym[i][j][k] = user_synonym[k];
                 }
                 synonym[i][j][strlen(user_synonym)] = '\0';
             }
         }
         else
             synonym[i] = nullptr;
         if (choice != 'n' && choice != 'N' && choice != 'Y' && choice != 'y')
         {
             cout << "Enter correct choice:\n";
                 goto again;
         }


    }

    for (int i = 0; i < counter; i++)
    {
        cout << "Input word : " << data_dict[i] << endl;
        if (synonym[i] != nullptr)
        {
            for (int j = 0; j < synonym_count; j++)
            {
                cout << "Synonyn: ";
                for (int k = 0; synonym[i][j][k] != '\0'; k++)
                {
                    cout << synonym[i][j][k];
                }
                cout << endl;
            }
        }
        cout << endl;
    }

```

```cpp
    for (int i = 0; i < numWords; i++) {
        synonyms[i] = nullptr;
    }


    for (int i = 0; i < numWords; i++) {

        char* word = dataDictionary[i];


        cout << "Do you want to store synonyms for " << word << "? (y/n): ";
        char choice;
        cin >> choice;

        if (choice == 'y' || choice == 'Y') {

            int count;
            cout << "How many synonyms do you want to store? ";
            cin >> count;

            // Allocate memory for the synonyms at this index
            synonyms[i] = new char* [count];


            for (int j = 0; j < count; j++) {

                static char temp[100];

                cout << "Enter synonyn #" << j + 1 << " for " << word << ": ";
                cin >> temp;

                // Allocate memory for the synonym at this index

                synonyms[i][j] = new char[strlen(temp) + 1];

                // Copy the data character by character
                for (int k = 0; k < strlen(temp); k++) {
                    synonyms[i][j][k] = temp[k];
                }
                synonyms[i][j][strlen(temp)] = '\0';
            }
        }
        else if (choice == 'n' || choice == 'N')

        {
            synonyms[i] = new char* [1];
            synonyms[i][0] = new char[10];
            synonyms[i][0][0] = '\0';
        }
    }
}
void SearchWord(char* UseCase1, char** dataDictionary, int numWords) {
    const int WORD_LEN = 1000;

    char word[WORD_LEN];

    int startIndex = 0;
    int count = 0;

     cout << "Matched words:" << endl;

     for (int i = 0; i <= strlen(UseCase1); i++) {
         if (UseCase1[i] == ' ' || UseCase1[i] == '.') {

             int length = i - startIndex;
             if (length > 0) {
                 if (length >=WORD_LEN) {
                     cout << "Error: word length exceeds maximum length." << endl;
                     return;
                 }
```

1:20 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022l-7906.cpp/22L-6194.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22l-7906.cpp

Submission 2
22L-6194.cpp

Match %
22.19

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (235 - 248)	22L-6194.cpp\22L-6194.cpp (211 - 220)	19
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (120 - 128)	22L-6194.cpp\22L-6194.cpp (76 - 85)	14
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (66 - 72)	22L-6194.cpp\22L-6194.cpp (12 - 18)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (90 - 96)	22L-6194.cpp\22L-6194.cpp (45 - 50)	12
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (158 - 166)	22L-6194.cpp\22L-6194.cpp (95 - 103)	12

```
158     char useCase1[2000];
159    cout << "Enter use case: ";
160    cin.getline(useCase1, 2000);
161    int c= 0;
162    int index = 0;
163    for (int i = 0; useCase1[i] != '\0'; i++)
164    {
165        if (useCase1[i] == ' '||useCase1[i]=='.')
166        {
167            char* word = new char[(i - index) + 1];
168            int j = 0;
169            for (int k = index; k < i; k++)
170            {
171                word[j] = useCase1[k];
172                j++;
173            }
174            word[j] = '\0';
175
176            if (SearchUnique(data_dict, data_count, word,f_index))
177            {
178                cout << "Word: " << word << endl;
179                index++;
180                c++;
181            }
182            delete[] word;
183            index = i + 1;
184        }
185    }
186    cout << "There were " << c << " words\n";
187
188                    //++task 4++//
189
190    char useCase2[2000];
191    char f_text[1000];
192    cout << "Input:";
193    cin.getline(useCase2, 2000);
194    index = 0;
195    int text_c = 0;
196    for (int i = 0; useCase2[i] != '\0'; i++)
197    {
198        if (useCase2[i] == ' ' || useCase2[i] == '.')
199        {
200            char* word = new char[(i - index) + 1];
201            int j = 0;
202            for (int k = index; k < i; k++)
203            {
204                word[j] = useCase2[k];
205                j++;
206            }
207            word[j] = '\0';
208
209            if (SearchUnique(data_dict, data_count, word,f_index))
210            {
211                if (checkSynonum(synonym, word, data_count,f_index))
212                {
213                    for (; temp[t] != '#'; t++)
214                    {
215                        cout << temp[t];
216                    }
217                    t++;
218                    cout << " ";
219
220                }
221                else
222                cout<< word << " ";
223            }
224            else
225            {
226                cout << word<< " ";
```

```
95     char word[WORD_LEN];
96
97     int startIndex = 0;
98     int count = 0;
99
100     cout << "Matched words:" << endl;
101
102     for (int i = 0; i <= strlen(UseCase1); i++) {
103         if (UseCase1[i] == ' ' || UseCase1[i] == '.') {
104             int length = i - startIndex;
105             if (length > 0) {
106                 if (length >=WORD_LEN) {
107                     cout << "Error: word length exceeds maximum length." << endl;
108                     return;
109                 }
110                 for (int j = 0; j < length; j++) {
111                     word[j] = UseCase1[startIndex + j];
112                 }
113                 word[length] = '\0';
114
115                 bool found = false;
116                 for (int j = 0; j < numWords; j++) {
117                     if (strcmp(word, dataDictionary[j]) == 0) {
118                         found = true;
119                         break;
120                     }
121                 }
122                 if (found) {
123                     cout << word << endl;
124                     count++;
125                 }
126
127             }
128             startIndex = i + 1;
129         }
130     }
131
132     if (count == 0) {
133         cout << "No words found in data dictionary." << endl;
134     }
135     else {
136         cout << "Total matched words: " << count << endl;
137     }
138 }
139 void replaceSynonyms(char*** synonyms, char** dataDictionary, int wordCount)
140 {
141     bool isPresent = true;
142     char* useCase1 = new char[2500];
143     char* temp = new char[2500];
144     int i = 0,j=0,forTemp=0;
145     cout << "enter sentence(s) to replace synonyms: ";
146     cin.getline(useCase1, 2500);
147     while (useCase1[i] != '\0')
148     {
149             if (i == 0 || useCase1[i] == ' ' || useCase1[i] == '.')
150             {
151                     if (i != 0)
152                             i++;
153                     int temp1 = i;
154                     j = 0;
155                     while (j < wordCount)
156                     {
157                             int characters = 0;
158                             temp1 = i;
159                             while (useCase1[temp1] != ' ' && useCase1[temp1] != '.' &
160                             {
161
162                                     if (useCase1[temp1++] == dataDictionary[j][charac
163                                     {
```

1:20 PM
4/14/2023