WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22I7944_assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22I7944_assignment1.cpp

Match %
20.47

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (89 - 96)	22I7944_assignment1.cpp\22I7944_assignment1.cpp (178 - 182)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (161 - 167)	22I7944_assignment1.cpp\22I7944_assignment1.cpp (59 - 65)	14
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 72)	22I7944_assignment1.cpp\22I7944_assignment1.cpp (281 - 287)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (195 - 200)	22I7944_assignment1.cpp\22I7944_assignment1.cpp (248 - 252)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	22I7944_assignment1.cpp\22I7944_assignment1.cpp (354 - 361)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (116 - 125)	22I7944_assignment1.cpp\22I7944_assignment1.cpp (320 - 326)	12

Files of assignment 1 22I-7906.cpp

..1 22I-7906.cpp\assignment 1 22I-7906.cpp

```cpp
#include <iostream>
#include<fstream>
using namespace std;
char choice;
int synonym_count;
char temp[1000];
int ft = 0;
int t = 0;


bool SearchUnique(char** data_dict, int data_count, char* word,int &f_ir
{
    for (int i = 0; i < data_count; i++)
    {
        int j = 0;
        while (data_dict[i][j] != '\0' && word[j] != '\0')
        {
            if (data_dict[i][j] != word[j])
            {
                break;
            }
            j++;
        }
        if (data_dict[i][j] == '\0' && word[j] == '\0')
        {
            f_index = i;
            return true;
        }
    }
    return false;
}
bool checkSynonym(char*** synonym, char* word, int data_count,int f_inde
{
    for (int i = 0; i < data_count && f_index!=-1; i++)
    {
        if (synonym[f_index] != nullptr)
        {
            return true;
        }
    }
    return false;
}
int main()
{
    char text[3000];
    cout << "Enter data\n ";
    cin.getline(text, 3000);
    char** data_dict = new char* [3000];
    int data_count = 0, start = 0,f_index=-1;
    for (int i = 0; text[i] != '\0'; i++)
    {
        if (text[i] == ' ' || text[i] == '.')
        {
            char* word = new char[(i - start) + 1];
            int j = 0;
```

Files of 22I7944_assignment1.cpp

..._assignment1.cpp\22I7944_assignment1.cpp

```cpp
#include <iostream>
#include <fstream>
#include <cstring>
#include <limits>

void replaceWord(char*& sentence, const char* const& synonym, const int s
int fetchSynonym(char * &word, char ** &data_dict, char *** &synonyms);
void synonify(char *&useCase1, char *** &synonyms, char ** &data_dict);
void getWordMatches(char *&useCase1, char ** &data_dict);
void getSynonyms(char***& synonyms, const char* const* const &data_dict,
void displaySynonyms(char***& synonyms, char**& data_dict, const int &cc
void generateDataDict(char**& data_dict);
bool checkRepitition(const char* word, char** &data_dict);
void makeWord(char*& arr, const char& val);
void addWord(char*& word, char**& data_dict);
void display(const char* const* const& data);
void deallocate(char ** &data_dict, char *** &synonyms, char * &useCase1

using namespace std;

int main() {
    char** data_dict = new char* [1];
    data_dict[0] = new char[1];
    data_dict[0][0] = '\0';

    generateDataDict(data_dict);
    cout << endl << "Data Dictionary: " << endl;
    display(const_cast<const char**>(data_dict));

    int count = 0;
    for (; data_dict[count][0] != '\0'; count++);

    char*** synonyms = nullptr;
    getSynonyms(synonyms, const_cast<const char**>(data_dict), count);
    displaySynonyms(synonyms, data_dict, count);

    char * useCase1 = new char [1];
    useCase1[0] = '\0';
    getWordMatches(useCase1, data_dict);

    cout << endl << "Data Dictionary: " << endl;
    display(const_cast<const char**>(data_dict));

    cout << endl << "Original 'useCase1' Sentence: " << endl << useCase1
    synonify(useCase1, synonyms, data_dict);
    cout << "Updated 'useCase1' Sentence: " << endl << useCase1 << endl

    // Deallocation
    try {
        deallocate(data_dict, synonyms, useCase1, --count);
    } catch (...) {
        cout << "Error occurred." << endl;
    }

    return 0; // exit program with success status
```

1:21 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22I7944_assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22I7944_assignment1.cpp

Match %
20.47

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (89 - 96)	(178 - 182)	15
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (161 - 167)	(59 - 65)	14
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (65 - 72)	(281 - 287)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (195 - 200)	(248 - 252)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (238 - 248)	(354 - 361)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (116 - 125)	(320 - 326)	12

```
89      char*** synonym = new char** [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " 
99          cin >> choice;
100         if (choice == 'Y' || choice == 'y')
101         {
102             cout << "How many synonyms do you want to store for " << da
103
104             cin >> synonym_count;
105             cin.ignore();
106             synonym[i] = new char* [synonym_count];
107             for (int j = 0; j < synonym_count; j++)
108             {
109                 cout << "Enter synonym for " << data_dict[i] << endl;
110                 char user_synonym[30];
111                 cin.getline(user_synonym, 30);
112                 for (int i = 0; user_synonym[i] != '\0'; i++)
113                 {
114                     temp[ft++] = user_synonym[i];
115                 }
116                 temp[ft++]='#';
117
118
119
120                 synonym[i][j] = new char[strlen(user_synonym) + 1];
121                 for (int k = 0; k < strlen(user_synonym); k++)
122                 {
123                     synonym[i][j][k] = user_synonym[k];
124                 }
125                 synonym[i][j][strlen(user_synonym)] = '\0';
126             }
127         }
128         else
129             synonym[i] = nullptr;
130         if (choice != 'n' && choice != 'N' && choice != 'Y' && choice !
131         {
132             cout << "Enter correct choice:\n";
133                 goto again;
134         }
135
136
137     }
138
139     for (int i = 0; i < counter; i++)
140     {
141         cout << "Input word : " << data_dict[i] << endl;
142         if (synonym[i] != nullptr)
143         {
144             for (int j = 0; j < synonym_count; j++)
145             {
146                 cout << "Synonym: ";
147                 for (int k = 0; synonym[i][j][k] != '\0'; k++)
148                 {
149                     cout << synonym[i][j][k];
150                 }
151                 cout << endl;
152             }
153         }
154         cout << endl;
```

```
178     synonyms = new char** [count];
179     for (int i = 0; i < count; i++) {
180         synonyms[i] = nullptr;
181     }
182     for (int w = 0; w < count; w++) {
183         int choice;
184         while (
185             cout << endl << "Do you want to enter a synonym for '" << da
186             << "Press 1 to do it and any other to continue elsewise: "
187             && !(cin >> choice)
188             ) {
189             cout << "Invalid input. Please enter a number.\n";
190             cin.clear();
191             cin.ignore(numeric_limits<streamsize>::max(), '\n');
192         }
193
194         if (choice == 1) {
195             int synCount = 0;
196             while (
197             cout << endl << "How many synonyms do you want to enter?: "
198             cin >> synCount && synCount <= 0
199             ) {
200                 cout << "Invalid input. Please enter a number.\n";
201                 cin.clear();
202                 cin.ignore(numeric_limits<streamsize>::max(), '\n');
203             }
204
205             synonyms[w] = new char* [synCount+1];
206
207             cin.ignore(); cout << endl;
208             for (int i = 0; i < synCount; i++) {
209                 char input[3000];
210                 cout << "Enter synonym " << i + 1 << ": ";
211                 cin.getline(input, 3000);
212                 int len = strlen(input) + 1;
213                 synonyms[w][i] = new char[len];
214                 for (int j = 0; j < len; j++) {
215                     synonyms[w][i][j] = input[j];
216                 }
217             }
218             synonyms[w][synCount] = new char [1];
219             synonyms[w][synCount][0] = '\0';
220
221         } else {
222             synonyms[w] = nullptr;
223         }
224     }
225 }
226
227 void displaySynonyms(char***& synonyms, char **&data_dict, const int &c
228     cout << endl << "Synonyms: " << endl << endl;
229     for (int w = 0; w < count; w++) {
230         cout << "'" << data_dict[w] << "' synonyms --> ";
231         if (synonyms[w] != nullptr) {
232             for (int x = 0; synonyms[w][x][0] != '\0'; x++) {
233                 cout << "(" << x+1 << ") " << synonyms[w][x] << " ";
234             } cout << endl;
235         } else {
236             cout << "no synonyms" << endl;
237         }
238     }
239 }
240
241 void generateDataDict(char ** &data_dict) {
242     char input[3000];
243     ifstream data("data.txt");
244     if (!data) {
```

1:21 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22I7944_assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22I7944_assignment1.cpp

Match %
20.47

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (89 - 96)	(178 - 182)	15
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (161 - 167)	(59 - 65)	14
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (65 - 72)	(281 - 287)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (195 - 200)	(248 - 252)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (238 - 248)	(354 - 361)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (116 - 125)	(320 - 326)	12

```cpp
    int c= 0;
    int index = 0;
    for (int i = 0; useCase1[i] != '\0'; i++)
    {
        if (useCase1[i] == ' '||useCase1[i]=='.')
        {
            char* word = new char[(i - index) + 1];
            int j = 0;
            for (int k = index; k < i; k++)
            {
                word[j] = useCase1[k];
                j++;
            }
            word[j] = '\0';

            if (SearchUnique(data_dict, data_count, word,f_index))
            {
                cout << "Word: " << word << endl;
                index++;
                c++;
            }
            delete[] word;
            index = i + 1;
        }
    }
    cout << "There were " << c << " words\n";

                    //++task 4++//

    char useCase2[2000];
    char f_text[1000];
    cout << "Input:";
    cin.getline(useCase2, 2000);
    index = 0;

    int text_c = 0;
    for (int i = 0; useCase2[i] != '\0'; i++)
    {
        if (useCase2[i] == ' ' || useCase2[i] == '.')
        {
            char* word = new char[(i - index) + 1];
            int j = 0;
            for (int k = index; k < i; k++)
            {
                word[j] = useCase2[k];
                j++;
            }
            word[j] = '\0';

            if (SearchUnique(data_dict, data_count, word,f_index))
            {
                if (checkSynonum(synonym, word, data_count,f_index))
                {
                    for (; temp[t] != '#'; t++)
                    {
                        cout << temp[t];
                    }
                    t++;
                    cout << " ";

                }
                else
               cout<< word << " ";
            }
            else
            {
                cout << word<<" ";
            }
```

```cpp
    int count = 0; for (; data_dict[count][0] != '\0'; count++);
    cout << endl;

    int j = 0;
    for (int c = 0; useCase1[c] != '\0'; c++) {
        if (useCase1[c] == ' ' || useCase1[c] == '.') {
            char * word = new char [1];
            word[0] = '\0';
            int x = j;
            for (; j < c; j++) {
                if (useCase1[j] != ' ') {
                    makeWord(word, useCase1[j]);
                }
            }
            if (word[0] == '.') c++;
            else if (checkRepitition(word, data_dict)) {
                int synonym = fetchSynonym(word, data_dict, synonyms);
                if (synonym != -1) {
                    replaceWord(useCase1, synonyms[synonym][0], x, c);
                }
            }

            delete[] word; word = nullptr;
        }
    }
    cout << endl;
}

void replaceWord(char*& sentence, const char* const& synonym, const int :
    int sencount = 0; for (; sentence[sencount] != '\0'; sencount++);
    int syncount = 0; for (; synonym[syncount] != '\0'; syncount++);
    int len = sencount + syncount - (end - start) + 1;

    char * temp = new char [len];
    int i = 0, j = 0;

    int starte = start; if (starte != 0) starte++;
    for (; i < starte; i++, j++) temp[j] = sentence[i];
    for (int k = 0; synonym[k] != '\0'; k++, j++) temp[j] = synonym[k];
    for (i = end; sentence[i] != '\0'; i++, j++) temp[j] = sentence[i];

     temp[j] = '\0';
     delete[] sentence;
     sentence = temp;
}


int fetchSynonym(char * &word, char ** &data_dict, char *** &synonyms) :
    int w = 0; bool match = false;
    for (; data_dict[w][0] != '\0' && !match; w++) {
        if (word[0] == data_dict[w][0]) {
            match = true;
            for (int c = 1; data_dict[c][0] != '\0' && match; c++) {
                if (word[c] != data_dict[w][c]) match = false;
            }
        }
    }

    if (match) {
        w--;
        if (synonyms[w] != nullptr) return w;
        else return -1;
    }
    else return -1;
}

// gets word matches
void getWordMatches(char * &useCase1, char ** &data_dict) {
    char input[3000];
```

1:21 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22I7944_assignment1.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22I7944_assignment1.cpp

Match %
20.47

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (89 - 96)	(178 - 182)	15
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (161 - 167)	(59 - 65)	14
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (65 - 72)	(281 - 287)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (195 - 200)	(248 - 252)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (238 - 248)	(354 - 361)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (116 - 125)	(320 - 326)	12

```
65              int word_length = strlen(word);
66              data_dict[data_count] = new char[word_length + 1];
67              for (int k = 0; k < word_length; k++)
68              {
69                  data_dict[data_count][k] = word[k];
70              }
71              data_dict[data_count][word_length] = '\0';
72              data_count++;
73          }
74
75          start = i + 1;
76          delete[] word;
77      }
78  }
79
80
81                      ///***Task 2***///
82
83  int counter = 0;
84  for (int i = 0; i < data_count; i++)
85  {
86      cout << data_dict[i] << endl;
87      counter++;
88  }
89  char*** synonym = new char** [counter];
90  for (int i = 0; i < counter; i++)
91  {
92      synonym[i] = nullptr;
93  }
94
95  for (int i = 0; i < counter; i++)
96  {
97      again:
98      cout << "Do you want to enter Synonym of " << data_dict[i] << "
99      cin >> choice;
100      if (choice == 'Y' || choice == 'y')
101      {
102          cout << "How many synonyms do you want to store for " << da
103
104          cin >> synonym_count;
105          cin.ignore();
106          synonym[i] = new char* [synonym_count];
107          for (int j = 0; j < synonym_count; j++)
108          {
109              cout << "Enter synonym for " << data_dict[i] << endl;
110              char user_synonym[30];
111              cin.getline(user_synonym, 30);
112              for (int i = 0; user_synonym[i] != '\0'; i++)
113              {
114                  temp[ft++] = user_synonym[i];
115              }
116              temp[ft++]='#';
117
118
119
120              synonym[i][j] = new char[strlen(user_synonym) + 1];
121              for (int k = 0; k < strlen(user_synonym); k++)
122              {
123                  synonym[i][j][k] = user_synonym[k];
124              }
125              synonym[i][j][strlen(user_synonym)] = '\0';
126          }
127      }
128      else
129          synonym[i] = nullptr;
130      if (choice != 'n' && choice != 'N' && choice != 'Y' && choice !=
```

```
281     char* temp = nullptr;
282     temp = new char[count + 2];
283     for (int i = 0; i < count; i++) {
284         temp[i] = arr[i];
285     }
286     temp[count] = val;
287     temp[count + 1] = '\0';
288     delete[] arr;
289     arr = temp;
290 }
291
292 bool checkRepitition(const char* word, char** &data_dict) {
293     bool match = false;
294     for (int r = 0; data_dict[r][0] != '\0' && !match; r++) {
295         if (word[0] == data_dict[r][0]) {
296             match = true;
297             for (int i = 1; data_dict[r][i] != '\0'  && match; i++) {
298                 if (word[i] != data_dict[r][i]) match = false;
299             }
300         }
301     }
302     return match;
303 }
304
305 // Adds the word to the data dictionary if it is unique
306 void addWord(char *&word, char **&data_dict) {
307     int words = 0;
308     for (; data_dict[words][0] != '\0'; words++);
309     char **temp = new char *[words + 2];
310     for (int r = 0; r < words; r++) {
311         int chars = 0;
312         for (; data_dict[r][chars] != '\0'; chars++);
313         temp[r] = new char[chars + 1];
314         for (int i = 0; i <= chars; i++) {
315             temp[r][i] = data_dict[r][i];
316         }
317     }
318
319     int chars = 0;
320     for (; word[chars] != '\0'; chars++);
321     temp[words] = new char[chars + 1];
322     for (int i = 0; i <= chars; i++) {
323         temp[words][i] = word[i];
324     }
325
326     temp[words + 1] = new char[1];
327     temp[words + 1][0] = '\0';
328
329     for (int i = 0; i < words; i++) {
330         delete[] data_dict[i];
331     }
332     delete[] data_dict;
333     data_dict = temp;
334 }
335
336 // displays the data dictionary
337 void display(const char* const* const& data) {
338     int i = 0;
339     while (data[i][0] != '\0') {
340         cout << data[i] << endl;
341         i++;
342     }
343 }
344
345 void deallocate(char ** &data_dict, char *** &synonyms, char * &useCase
346     delete[] useCase1;
347
```

1:21 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22I7944_assignment1.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22I7944_assignment1.cpp

Match %
20.47

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (89 - 96)	(178 - 182)	15
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (161 - 167)	(59 - 65)	14
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (65 - 72)	(281 - 287)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (195 - 200)	(248 - 252)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (238 - 248)	(354 - 361)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (116 - 125)	(320 - 326)	12

```
116                 temp[ft++]='#';
117
118
119
120                 synonym[i][j] = new char[strlen(user_synonym) + 1];
121                 for (int k = 0; k < strlen(user_synonym); k++)
122                 {
123                     synonym[i][j][k] = user_synonym[k];
124                 }
125                 synonym[i][j][strlen(user_synonym)] = '\0';
126             }
127         }
128         else
129             synonym[i] = nullptr;
130         if (choice != 'n' && choice != 'N' && choice != 'Y' && choice !=
131         {
132             cout << "Enter correct choice:\n";
133                 goto again;
134         }
135
136
137     }
138
139     for (int i = 0; i < counter; i++)
140     {
141         cout << "Input word : " << data_dict[i] << endl;
142         if (synonym[i] != nullptr)
143         {
144             for (int j = 0; j < synonym_count; j++)
145             {
146                 cout << "Synonym: ";
147                 for (int k = 0; synonym[i][j][k] != '\0'; k++)
148                 {
149                     cout << synonym[i][j][k];
150                 }
151                 cout << endl;
152             }
153         }
154         cout << endl;
155     }
156
157             //**task 3**//
158       char useCase1[2000];
159     cout << "Enter use case: ";
160     cin.getline(useCase1, 2000);
161     int c= 0;
162     int index = 0;
163     for (int i = 0; useCase1[i] != '\0'; i++)
164     {
165         if (useCase1[i] == ' '||useCase1[i]=='.')
166         {
167             char* word = new char[(i - index) + 1];
168             int j = 0;
169             for (int k = index; k < i; k++)
170             {
171                 word[j] = useCase1[k];
172                 j++;
173             }
174             word[j] = '\0';
175
176             if (SearchUnique(data_dict, data_count, word,f_index))
177             {
178                 cout << "Word: " << word << endl;
179                 index++;
180                 c++;
181             }
```

```
300         }
301     }
302     return match;
303 }
304
305 // Adds the word to the data dictionary if it is unique
306 void addWord(char *&word, char **&data_dict) {
307     int words = 0;
308     for (; data_dict[words][0] != '\0'; words++);
309     char **temp = new char *[words + 2];
310     for (int r = 0; r < words; r++) {
311         int chars = 0;
312         for (; data_dict[r][chars] != '\0'; chars++);
313         temp[r] = new char[chars + 1];
314         for (int i = 0; i <= chars; i++) {
315             temp[r][i] = data_dict[r][i];
316         }
317     }
318
319     int chars = 0;
320     for (; word[chars] != '\0'; chars++);
321     temp[words] = new char[chars + 1];
322     for (int i = 0; i <= chars; i++) {
323         temp[words][i] = word[i];
324     }
325
326     temp[words + 1] = new char[1];
327     temp[words + 1][0] = '\0';
328
329     for (int i = 0; i < words; i++) {
330         delete[] data_dict[i];
331     }
332     delete[] data_dict;
333     data_dict = temp;
334 }
335
336 // displays the data dictionary
337 void display(const char* const* const& data) {
338     int i = 0;
339     while (data[i][0] != '\0') {
340         cout << data[i] << endl;
341         i++;
342     }
343 }
344
345 void deallocate(char ** &data_dict, char *** &synonyms, char * &useCase1
346     delete[] useCase1;
347
348     for (int i = 0; data_dict[i][0] != '\0'; i++) {
349         delete[] data_dict[i];
350     }
351     delete[] data_dict;
352
353     for (int i = 0; i < count; i++) {
354         if (synonyms[i] != nullptr) {
355             for (int j = 0; synonyms[i][j][0] != '\0'; j++) {
356                 delete[] synonyms[i][j];
357             }
358             delete[] synonyms[i];
359         }
360     }
361     delete[] synonyms;
362 }
```

1:21 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/22I7944_assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
22I7944_assignment1.cpp

Match %
20.47

(89 - 96)		
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (161 - 167)	(59 - 65)	14
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (65 - 72)	(281 - 287)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (195 - 200)	(248 - 252)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (238 - 246)	(354 - 361)	13
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (116 - 125)	(320 - 328)	12
assignment 1 22I-7906.cpp\assignment22I7944_assignment1.cpp\22I7944_assignment1.cpp 1 22I-7906.cpp (139 - 146)	(229 - 232)	12

```
139     for (int i = 0; i < counter; i++)
140     {
141         cout << "Input word : " << data_dict[i] << endl;
142         if (synonym[i] != nullptr)
143         {
144             for (int j = 0; j < synonym_count; j++)
145             {
146                 cout << "Synonym: ";
147                 for (int k = 0; synonym[i][j][k] != '\0'; k++)
148                 {
149                     cout << synonym[i][j][k];
150                 }
151                 cout << endl;
152             }
153         }
154         cout << endl;
155     }
156
157             //**task 3**//
158       char useCase1[2000];
159     cout << "Enter use case: ";
160     cin.getline(useCase1, 2000);
161     int c= 0;
162     int index = 0;
163     for (int i = 0; useCase1[i] != '\0'; i++)
164     {
165         if (useCase1[i] == ' '||useCase1[i]=='.')
166         {
167             char* word = new char[(i - index) + 1];
168             int j = 0;
169             for (int k = index; k < i; k++)
170             {
171                 word[j] = useCase1[k];
172                 j++;
173             }
174             word[j] = '\0';
175
176             if (SearchUnique(data_dict, data_count, word,f_index))
177             {
178                 cout << "Word: " << word << endl;
179                 index++;
180                 c++;
181             }
182             delete[] word;
183             index = i + 1;
184         }
185     }
186     cout << "There were " << c << " words\n";
187
188                     //**task 4**//
189
190     char useCase2[2000];
191     char f_text[1000];
192     cout << "Input:";
193     cin.getline(useCase2, 2000);
194     index = 0;
195     int text_c = 0;
196     for (int i = 0; useCase2[i] != '\0'; i++)
197     {
198         if (useCase2[i] == ' ' || useCase2[i] == '.')
199         {
200             char* word = new char[(i - index) + 1];
201             int j = 0;
202             for (int k = index; k < i; k++)
203             {
204                 word[j] = useCase2[k];
```

```
229     for (int w = 0; w < count; w++) {
230         cout << "'" << data_dict[w] << "' synonyms --> ";
231         if (synonyms[w] != nullptr) {
232             for (int x = 0; synonyms[w][x][0] != '\0'; x++) {
233                 cout << "(" << x+1 << ") " << synonyms[w][x] << " ";
234             } cout << endl;
235         } else {
236             cout << "no synonyms" << endl;
237         }
238     }
239 }
240
241 void generateDataDict(char ** &data_dict) {
242     char input[3000];
243     ifstream data("data.txt");
244     if (!data) {
245         cout << "Error" << endl;
246     }
247
248     int j = 0;
249     for (int i = 0; data >> noskipws >> input[i]; i++) {
250         cout << input[i];
251         if (input[i] == ' ' || input[i] == '.') {
252             char* word = new char[1];
253             word[0] = '\0';
254             for (; j < i; j++) {
255                 if (input[j] != ' ' && input[j] != '.') makeWord(word, :
256             }
257             if (word[0] == '.') {
258                 delete[] word;
259                 i++;
260             }
261             else if (!checkRepitition(word, data_dict)) {
262                 addWord(word, data_dict);
263                 delete[] word;
264             }
265             else {
266                 delete[] word;
267             }
268         }
269     }
270     data.close();
271     cout << endl;
272 }
273
274 void makeWord(char*& arr, const char& val) {
275     if (!arr) {
276         arr = new char[1];
277         arr[0] = '\0';
278     }
279     int count = 0;
280     for (; arr[count] != '\0'; count++);
281     char* temp = nullptr;
282     temp = new char[count + 2];
283     for (int i = 0; i < count; i++) {
284         temp[i] = arr[i];
285     }
286     temp[count] = val;
287     temp[count + 1] = '\0';
288     delete[] arr;
289     arr = temp;
290 }
291
292 bool checkRepitition(const char* word, char** &data_dict) {
293     bool match = false;
294     for (int r = 0; data_dict[r][0] != '\0' && !match; r++) {
```

1:21 PM
4/14/2023