WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/I22-7974.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
I22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (11 - 25)	I22-7974.cpp\I22-7974.cpp (115 - 129)	20
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (88 - 96)	I22-7974.cpp\I22-7974.cpp (59 - 67)	17
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (48 - 53)	I22-7974.cpp\I22-7974.cpp (213 - 220)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 71)	I22-7974.cpp\I22-7974.cpp (82 - 88)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	I22-7974.cpp\I22-7974.cpp (199 - 208)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (139 - 145)	I22-7974.cpp\I22-7974.cpp (137 - 143)	12

Files of assignment 1 22I-7906.cpp

..1 22I-7906.cpp\assignment 1 22I-7906.cpp

```
1 #include <iostream>
2 #include<fstream>
3 using namespace std;
4 char choice;
5 int synonym_count;
6 char temp[1000];
7 int ft = 0;
8 int t = 0;
9
10
11 bool SearchUnique(char** data_dict, int data_count, char* word,int &f_index )
12 {
13     for (int i = 0; i < data_count; i++)
14     {
15         int j = 0;
16         while (data_dict[i][j] != '\0' && word[j] != '\0')
17         {
18             if (data_dict[i][j] != word[j])
19             {
20                 break;
21             }
22             j++;
23         }
24         if (data_dict[i][j] == '\0' && word[j] == '\0')
25         {
26             f_index = i;
27             return true;
28         }
29     }
30     return false;
31 }
32 bool checkSynonum(char*** synonym, char* word, int data_count,int f_index)
33 {
34     for (int i = 0; i < data_count && f_index!=-1; i++)
35     {
36         if (synonym[f_index] != nullptr)
37         {
38             return true;
39         }
40     }
41     return false;
42 }
43 int main()
44 {
45     char text[3000];
46     cout << "Enter data\n ";
47     cin.getline(text, 3000);
48     char** data_dict = new char* [3000];
49     int data_count = 0, start = 0,f_index=-1;
50     for (int i = 0; text[i] != '\0'; i++)
51     {
52         if (text[i] == ' ' || text[i] == '.')
53         {
54             char* word = new char[(i - start) + 1];
```

Files of I22-7974.cpp

I22-7974.cpp\I22-7974.cpp

```
1 #include <iostream>+68
2 #include <cstring>
3 #include<fstream>
4 using namespace std;
5 bool isUnique(char* str, char** arr, int index);
6 void displaySynonyms(char*** synonyms, char** arr, int row_count);
7 void searchword(char** data_dictionary, char* use_case1,int indx);
8 void deldatadict(char**data_dictionary, int row_count);
9 void delsyn(char*** synonyms, int row_count);
10 void replaceWithSynonyms(char** data_dictionary, char* useCase1, int row_count, char*
11 int getIndex(char** data_dictionary, char* word, int row_count);
12 bool isPresent(char** data_dictionary, char* word, int row_count);
13 int main()
14 {
15     cout << "\t --------------UNIQUE WORDS AND SYNONYM CHANGER-------------- \n";
16     char arr_0[2000];
17     //cout << "Enter Data:";
18     //cin.getline(arr_0, 1000);
19     ifstream fr("Text.txt");
20     fr.getline(arr_0, 1000);
21     cout << arr_0;
22     int tot_words = 0;
23     for (int i = 0; i < strlen(arr_0); i++) {
24             if (arr_0[i] == ' ') {
25                     tot_words++;
26             }
27     }
28     tot_words++;
29     char** data_dictionary = new char* [tot_words];
30     int row_count = 0;
31     int col_count = 0;
32     data_dictionary[row_count] = new char[strlen(arr_0) + 1];
33
34     for (int i = 0; i < strlen(arr_0); i++) {
35             if (arr_0[i] == ' ') {
36                     data_dictionary[row_count][col_count] = '\0';
37                     if (isUnique(data_dictionary[row_count], data_dictionary, row_co
38                             row_count++;
39                     }
40                     col_count = 0;
41                     data_dictionary[row_count] = new char[strlen(arr_0) + 1];
42             }
43             else {
44                     data_dictionary[row_count][col_count] = arr_0[i];
45                     col_count++;
46             }
47     }
48
49     data_dictionary[row_count][col_count] = '\0';
50
51     if (isUnique(data_dictionary[row_count], data_dictionary, row_count)) {
52             row_count++;
53     }
54     cout << endl << "Unique words are:" << row_count << endl;
55     cout << "Unique array is:\n";
56
57     for (int i = 0; i < row_count; i++) {
```

1:19 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/assignment%201%2022l-7906.cpp/l22-7974.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22l-7906.cpp

Submission 2
l22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (11 - 25)	l22-7974.cpp\l22-7974.cpp (115 - 129)	20
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (88 - 96)	l22-7974.cpp\l22-7974.cpp (59 - 67)	17
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (48 - 53)	l22-7974.cpp\l22-7974.cpp (213 - 220)	15
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (65 - 71)	l22-7974.cpp\l22-7974.cpp (82 - 88)	13
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (238 - 248)	l22-7974.cpp\l22-7974.cpp (199 - 208)	13
assignment 1 22l-7906.cpp\assignment 1 22l-7906.cpp (139 - 145)	l22-7974.cpp\l22-7974.cpp (137 - 143)	12

```
11 bool SearchUnique(char** data_dict, int data_count, char* word,int &f_index )
12 {
13     for (int i = 0; i < data_count; i++)
14     {
15         int j = 0;
16         while (data_dict[i][j] != '\0' && word[j] != '\0')
17         {
18             if (data_dict[i][j] != word[j])
19             {
20                 break;
21             }
22             j++;
23         }
24         if (data_dict[i][j] == '\0' && word[j] == '\0')
25         {
26             f_index = i;
27             return true;
28         }
29     }
30     return false;
31 }
32 bool checkSynonum(char*** synonym, char* word, int data_count,int f_index)
33 {
34     for (int i = 0; i < data_count && f_index!=-1; i++)
35     {
36         if (synonym[f_index] != nullptr)
37         {
38             return true;
39         }
40     }
41     return false;
42 }
43 int main()
44 {
45     char text[3000];
46     cout << "Enter data\n ";
47     cin.getline(text, 3000);
48     char** data_dict = new char* [3000];
49     int data_count = 0, start = 0,f_index=-1;
50     for (int i = 0; text[i] != '\0'; i++)
51     {
52         if (text[i] == ' ' || text[i] == '.')
53         {
54             char* word = new char[(i - start) + 1];
55             int j = 0;
56             for (int k = start; k < i; k++)
57             {
58                 word[j] = text[k];
59                 j++;
60             }
61             word[j] = '\0';
62
63             if (!SearchUnique(data_dict, data_count, word,f_index))
64             {
65                 int word_length = strlen(word);
66                 data_dict[data_count] = new char[word_length + 1];
67                 for (int k = 0; k < word_length; k++)
68                 {
69                     data_dict[data_count][k] = word[k];
70                 }
71                 data_dict[data_count][word_length] = '\0';
72                 data_count++;
73             }
74
75             start = i + 1;
```

```
115 bool isUnique(char* str, char** arr, int index)
116 {
117     for (int i = 0; i < index; i++)
118     {
119             int j = 0;
120             while (str[j] != '\0' && arr[i][j] != '\0')
121             {
122                     if (str[j] != arr[i][j])
123                     {
124                             break;
125                     }
126                     j++;
127             }
128             if (str[j] == '\0' && arr[i][j] == '\0')
129             {
130                     return false;
131             }
132     }
133     return true;
134 }
135 void displaySynonyms(char*** synonyms, char** arr, int row_count)
136 {
137     for (int i = 0; i < row_count; i++)
138     {
139             if (synonyms[i] != nullptr)
140             {
141                     cout << "Synonyms for " << arr[i] << ": ";
142                     for (int j = 0; synonyms[i][j][0] != '\0'; j++)
143                     {
144                             cout << synonyms[i][j]<<"      " ;
145
146                     }
147                     cout << endl;
148             }
149     }
150 }
151 void searchword(char** data_dictionary, char* use_case1, int indx)
152 {
153     bool found = false;
154     for (int i = 0; i < indx; i++)
155     {
156             int k = 0;
157             for (int j = 0; use_case1[j] != '\0'; j++)
158             {
159                     if (data_dictionary[i][k] == '\0')
160                     {
161                             if (use_case1[j] == ' ')
162                             {
163                                     k = 0;
164                             }
165                             else
166                             {
167                                     break;
168                             }
169                     }
170                     if (data_dictionary[i][k] == use_case1[j])
171                     {
172                             k++;
173                     }
174                     else
175                     {
176                             k = 0;
177                     }
178                     if (data_dictionary[i][k] == '\0' && (use_case1[j + 1] == ' ' ||
179                     {
180                             cout << "Similar Word: " << data_dictionary[i] << endl;
181                             found = true;
```

1:19 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/I22-7974.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
I22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (11 - 25)	I22-7974.cpp\I22-7974.cpp (115 - 129)	20
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (88 - 96)	I22-7974.cpp\I22-7974.cpp (59 - 67)	17
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (48 - 53)	I22-7974.cpp\I22-7974.cpp (213 - 220)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 71)	I22-7974.cpp\I22-7974.cpp (82 - 88)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	I22-7974.cpp\I22-7974.cpp (199 - 208)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (139 - 145)	I22-7974.cpp\I22-7974.cpp (137 - 143)	12

```
88      }
89      char** synonym = new char** [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
99          cin >> choice;
100          if (choice == 'Y' || choice == 'y')
101          {
102              cout << "How many synonyms do you want to store for " << data_dict[i] <<
103
104              cin >> synonym_count;
105              cin.ignore();
106              synonym[i] = new char* [synonym_count];
107              for (int j = 0; j < synonym_count; j++)
108              {
109                  cout << "Enter synonym for " << data_dict[i] << endl;
110                  char user_synonym[30];
111                  cin.getline(user_synonym, 30);
112                  for (int i = 0; user_synonym[i] != '\0'; i++)
113                  {
114                      temp[ft++] = user_synonym[i];
115                  }
116                  temp[ft++]='#';
117
118
119
120                  synonym[i][j] = new char[strlen(user_synonym) + 1];
121                  for (int k = 0; k < strlen(user_synonym); k++)
122                  {
123                      synonym[i][j][k] = user_synonym[k];
124                  }
125                  synonym[i][j][strlen(user_synonym)] = '\0';
126              }
127          }
128          else
129              synonym[i] = nullptr;
130          if (choice != 'n' && choice != 'N' && choice != 'Y' && choice != 'y')
131          {
132              cout << "Enter correct choice:\n";
133                  goto again;
134          }
135
136
137      }
138
139      for (int i = 0; i < counter; i++)
140      {
141          cout << "Input word : " << data_dict[i] << endl;
142          if (synonym[i] != nullptr)
143          {
144              for (int j = 0; j < synonym_count; j++)
145              {
146                  cout << "Synonym: ";
147                  for (int k = 0; synonym[i][j][k] != '\0'; k++)
148                  {
149                      cout << synonym[i][j][k];
150                  }
151                  cout << endl;
152              }
153          }
154          cout << endl;
```

```
59      }
60
61      char** synonyms = new char** [row_count];
62      for (int i = 0; i < row_count; i++) {
63              synonyms[i] = nullptr;
64      }
65
66      for (int i = 0; i < row_count; i++)
67      {
68              cout << "Do you want to store synonyms for " << data_dictionary[i] << "?
69              char choice;
70              cin >> choice;
71
72              if (choice == 'y') {
73                      int count;
74                      cout << "How many synonyms do you want to store?";
75                      cin >> count;
76                      synonyms[i] = new char* [count+1];
77                      for (int j = 0; j < count; j++)
78                      {
79                              char temp[100];
80                              cout << "Enter synonym #" << j + 1 << ": ";
81                              cin >> temp;
82                              int len = strlen(temp);
83                              synonyms[i][j] = new char[len + 1];
84                              for (int k = 0; k < len; k++) {
85                                      synonyms[i][j][k] = temp[k];
86                              }
87
88                              synonyms[i][j][len] = '\0';
89                      }
90                      synonyms[i][count] = new char[1];
91                      synonyms[i][count][0] = '\0';
92              }
93              if (choice == 'n')
94              {
95                      synonyms[i] = new char* [1];
96                      synonyms[i][0] = new char[1];
97                      synonyms[i][0][0] = '\0';
98              }
99      }
100     cout << endl << "Synonyms are:" << endl;
101     displaySynonyms(synonyms, data_dictionary, row_count);
102     char *use_case1 = new char[2000];
103     cout << "Enter data to check similar words:";
104     cin.ignore();
105     cin.getline(use_case1, 2000);
106     searchword(data_dictionary, use_case1,row_count);
107     replaceWithSynonyms(data_dictionary, use_case1, row_count,synonyms);
108     cout << endl;
109     cout << use_case1;
110     cout << endl;
111     deldatadict(data_dictionary, row_count);
112     delsyn(synonyms, row_count);
113     delete[] use_case1;
114 }
115 bool isUnique(char* str, char** arr, int index)
116 {
117     for (int i = 0; i < index; i++)
118     {
119             int j = 0;
120             while (str[j] != '\0' && arr[i][j] != '\0')
121             {
122                     if (str[j] != arr[i][j])
123                     {
124                             break;
```

1:19 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/I22-7974.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
I22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (11 - 25)	I22-7974.cpp\I22-7974.cpp (115 - 129)	20
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (88 - 96)	I22-7974.cpp\I22-7974.cpp (59 - 67)	17
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (48 - 53)	I22-7974.cpp\I22-7974.cpp (213 - 220)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 71)	I22-7974.cpp\I22-7974.cpp (82 - 88)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	I22-7974.cpp\I22-7974.cpp (199 - 208)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (139 - 145)	I22-7974.cpp\I22-7974.cpp (137 - 143)	12

```cpp
48      char** data_dict = new char* [3000];
49      int data_count = 0, start = 0,f_index=-1;
50      for (int i = 0; text[i] != '\0'; i++)
51      {
52          if (text[i] == ' ' || text[i] == '.')
53          {
54              char* word = new char[(i - start) + 1];
55              int j = 0;
56              for (int k = start; k < i; k++)
57              {
58                  word[j] = text[k];
59                  j++;
60              }
61              word[j] = '\0';
62
63              if (!SearchUnique(data_dict, data_count, word,f_index))
64              {
65                  int word_length = strlen(word);
66                  data_dict[data_count] = new char[word_length + 1];
67                  for (int k = 0; k < word_length; k++)
68                  {
69                      data_dict[data_count][k] = word[k];
70                  }
71                  data_dict[data_count][word_length] = '\0';
72                  data_count++;
73              }
74
75              start = i + 1;
76              delete[] word;
77          }
78      }
79
80
81                      ///***Task 2***///
82
83      int counter = 0;
84      for (int i = 0; i < data_count; i++)
85      {
86          cout << data_dict[i] << endl;
87          counter++;
88      }
89      char*** synonym = new char** [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
99          cin >> choice;
100          if (choice == 'Y' || choice == 'y')
101          {
102              cout << "How many synonyms do you want to store for " << data_dict[i] <<
103
104              cin >> synonym_count;
105              cin.ignore();
106              synonym[i] = new char* [synonym_count];
107              for (int j = 0; j < synonym_count; j++)
108              {
109                  cout << "Enter synonym for " << data_dict[i] << endl;
110                  char user_synonym[30];
111                  cin.getline(user_synonym, 30);
112                  for (int i = 0; user_synonym[i] != '\0'; i++)
```

```cpp
213     char* word = new char[100];
214     int word_index = 0;
215     bool word_found = false;
216     bool in_word = false;
217     for (int i = 0; useCase1[i] != '\0'; i++)
218     {
219             if (useCase1[i] == ' ')
220             {
221                     if (in_word)
222                     {
223                             word[word_index] = '\0';
224                             if (isPresent(data_dictionary, word, row_count))
225                             {
226                                     word_found = true;
227                                     int index = getIndex(data_dictionary, word, row_c
228                                     char** syns = synonyms[index];
229                                     if (syns != nullptr)
230                                     {
231
232                                             for (int j = 0; syns[0][j] != '\0'; j++)
233                                             {
234                                                     useCase1[i - word_index + j] = sy
235                                             }
236                                     }
237                             }
238                             word_index = 0;
239                             word_found = false;
240                             in_word = false;
241                     }
242             }
243             else {
244                     in_word = true;
245                     word[word_index] = useCase1[i];
246                     word_index++;
247             }
248     }
249     if (in_word)
250     {
251             word[word_index] = '\0';
252             if (isPresent(data_dictionary, word, row_count))
253             {
254                     word_found = true;
255                     int index = getIndex(data_dictionary, word, row_count);
256                     char** syns = synonyms[index];
257                     if (syns != nullptr) {
258                             for (int j = 0; syns[0][j] != '\0'; j++)
259                             {
260                                     useCase1[strlen(useCase1) - word_index + j] = syn
261                             }
262                     }
263             }
264     }
265     delete[] word;
266 }
267 bool isPresent(char** data_dictionary, char* word, int row_count)
268 {
269     for (int i = 0; i < row_count; i++) {
270             bool found = true;
271             for (int j = 0; data_dictionary[i][j] != '\0' && word[j] != '\0'; j++)
272             {
273                     if (data_dictionary[i][j] != word[j])
274                     {
275                             found = false;
276                             break;
277                     }
278             }
279             if (found && data_dictionary[i][strlen(word)] == '\0')
280             {
281                     return true;
```

1:19 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/I22-7974.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
I22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (11 - 25)	I22-7974.cpp\I22-7974.cpp (115 - 129)	20
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (88 - 96)	I22-7974.cpp\I22-7974.cpp (59 - 67)	17
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (48 - 53)	I22-7974.cpp\I22-7974.cpp (213 - 220)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 71)	I22-7974.cpp\I22-7974.cpp (82 - 88)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	I22-7974.cpp\I22-7974.cpp (199 - 208)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (139 - 145)	I22-7974.cpp\I22-7974.cpp (137 - 143)	12

```
65                  int word_length = strlen(word);
66                  data_dict[data_count] = new char[word_length + 1];
67                  for (int k = 0; k < word_length; k++)
68                  {
69                      data_dict[data_count][k] = word[k];
70                  }
71                  data_dict[data_count][word_length] = '\0';
72                  data_count++;
73              }
74
75              start = i + 1;
76              delete[] word;
77          }
78      }
79
80
81                      ///***Task 2***///
82
83      int counter = 0;
84      for (int i = 0; i < data_count; i++)
85      {
86          cout << data_dict[i] << endl;
87          counter++;
88      }
89      char** synonym = new char* [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
99          cin >> choice;
100          if (choice == 'Y' || choice == 'y')
101          {
102              cout << "How many synonyms do you want to store for " << data_dict[i] <<
103
104              cin >> synonym_count;
105              cin.ignore();
106              synonym[i] = new char* [synonym_count];
107              for (int j = 0; j < synonym_count; j++)
108              {
109                  cout << "Enter synonym for " << data_dict[i] << endl;
110                  char user_synonym[30];
111                  cin.getline(user_synonym, 30);
112                  for (int i = 0; user_synonym[i] != '\0'; i++)
113                  {
114                      temp[ft++] = user_synonym[i];
115                  }
116                  temp[ft++]='#';
117
118
119
120                  synonym[i][j] = new char[strlen(user_synonym) + 1];
121                  for (int k = 0; k < strlen(user_synonym); k++)
122                  {
123                      synonym[i][j][k] = user_synonym[k];
124                  }
125                  synonym[i][j][strlen(user_synonym)] = '\0';
126              }
127          }
128          else
129              synonym[i] = nullptr;
130          if (choice != 'n' && choice != 'N' && choice != 'Y' && choice != 'y')
131          {
132                      int len = strlen(temp);
133                      synonyms[i][j] = new char[len + 1];
134                      for (int k = 0; k < len; k++) {
135                              synonyms[i][j][k] = temp[k];
136                      }
137
138                      synonyms[i][j][len] = '\0';
139                  }
140                  synonyms[i][count] = new char[1];
141                  synonyms[i][count][0] = '\0';
142              }
143              if (choice == 'n')
144              {
145                  synonyms[i] = new char* [1];
146                  synonyms[i][0] = new char[1];
147                  synonyms[i][0][0] = '\0';
148              }
149      }
150      cout << endl << "Synonyms are:" << endl;
151      displaySynonyms(synonyms, data_dictionary, row_count);
152      char *use_case1 = new char[2000];
153      cout << "Enter data to check similar words:";
154      cin.ignore();
155      cin.getline(use_case1, 2000);
156      searchword(data_dictionary, use_case1,row_count);
157      replaceWithSynonyms(data_dictionary, use_case1, row_count,synonyms);
158      cout << endl;
159      cout << use_case1;
160      cout << endl;
161      deldatadict(data_dictionary, row_count);
162      delsyn(synonyms, row_count);
163      delete[] use_case1;
164  }
165  bool isUnique(char* str, char** arr, int index)
166  {
167      for (int i = 0; i < index; i++)
168      {
169              int j = 0;
170              while (str[j] != '\0' && arr[i][j] != '\0')
171              {
172                      if (str[j] != arr[i][j])
173                      {
174                              break;
175                      }
176                      j++;
177              }
178              if (str[j] == '\0' && arr[i][j] == '\0')
179              {
180                      return false;
181              }
182      }
183      return true;
184  }
185  void displaySynonyms(char*** synonyms, char** arr, int row_count)
186  {
187      for (int i = 0; i < row_count; i++)
188      {
189              if (synonyms[i] != nullptr)
190              {
191                      cout << "Synonyms for " << arr[i] << ": ";
192                      for (int j = 0; synonyms[i][j][0] != '\0'; j++)
193                      {
194                              cout << synonyms[i][j]<<"      " ;
195
196                      }
```

1:19 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/I22-7974.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
I22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (11 - 25)	I22-7974.cpp\I22-7974.cpp (115 - 129)	20
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (88 - 96)	I22-7974.cpp\I22-7974.cpp (59 - 67)	17
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (48 - 53)	I22-7974.cpp\I22-7974.cpp (213 - 220)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 71)	I22-7974.cpp\I22-7974.cpp (82 - 88)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	I22-7974.cpp\I22-7974.cpp (199 - 208)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (139 - 145)	I22-7974.cpp\I22-7974.cpp (137 - 143)	12

```cpp
    char useCase2[2000];
    char f_text[1000];
    cout << "Input:";
    cin.getline(useCase2, 2000);
    index = 0;
    int text_c = 0;
    for (int i = 0; useCase2[i] != '\0'; i++)
    {
        if (useCase2[i] == ' ' || useCase2[i] == ':')
        {
            char* word = new char[(i - index) + 1];
            int j = 0;
            for (int k = index; k < i; k++)
            {
                word[j] = useCase2[k];
                j++;
            }
            word[j] = '\0';

            if (SearchUnique(data_dict, data_count, word,f_index))
            {
                if (checkSynonym(synonym, word, data_count,f_index))
                {
                    for (; temp[t] != '#'; t++)
                    {
                        cout << temp[t];
                    }
                    t++;
                    cout << " ";

                }
                else
               cout<< word << " ";
            }
            else
            {
                cout << word<<" ";
            }
            delete[] word;
            index = i + 1;
        }
    }



    for (int i = 0; i < data_count; i++)
    {
        delete[] data_dict[i];

        if (synonym[i] != nullptr)
        {
            for (int j = 0; j < synonym_count; j++)
            {
                delete[] synonym[i][j];
            }
            delete[] synonym[i];
        }
    }

    delete[] data_dict;

    delete[] synonym;
    system("Pause>0");
    return 0;
}

            if (synonyms[i] != nullptr)
            {
                    for (int j = 0; synonyms[i][j][0] != '\0'; j++)
                    {
                            delete[] synonyms[i][j];
                    }
                    delete[] synonyms[i];
            }
    }
    delete[] synonyms;

}
void replaceWithSynonyms(char** data_dictionary, char* useCase1, int row_count, char*
{
    char* word = new char[100];
    int word_index = 0;
    bool word_found = false;
    bool in_word = false;
    for (int i = 0; useCase1[i] != '\0'; i++)
    {
            if (useCase1[i] == ' ')
            {
                    if (in_word)
                    {
                            word[word_index] = '\0';
                            if (isPresent(data_dictionary, word, row_count))
                            {
                                    word_found = true;
                                    int index = getIndex(data_dictionary, word, row_c
                                    char** syns = synonyms[index];
                                    if (syns != nullptr)
                                    {

                                            for (int j = 0; syns[0][j] != '\0'; j++)
                                            {
                                                    useCase1[i - word_index + j] = sy
                                            }
                                    }
                            }
                            word_index = 0;
                            word_found = false;
                            in_word = false;
                    }
            }
            else {
                    in_word = true;
                    word[word_index] = useCase1[i];
                    word_index++;
            }
    }
    if (in_word)
    {
            word[word_index] = '\0';
            if (isPresent(data_dictionary, word, row_count))
            {
                    word_found = true;
                    int index = getIndex(data_dictionary, word, row_count);
                    char** syns = synonyms[index];
                    if (syns != nullptr) {
                            for (int j = 0; syns[0][j] != '\0'; j++)
                            {
                                    useCase1[strlen(useCase1) - word_index + j] = syn
                            }
                    }
            }
    }
    delete[] word;
```

1:19 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/assignment%201%2022I-7906.cpp/I22-7974.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
assignment 1 22I-7906.cpp

Submission 2
I22-7974.cpp

Match %
25.21

Submission 1 File 1	Submission 2 File 2	Tokens
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (11 - 25)	I22-7974.cpp\I22-7974.cpp (115 - 129)	20
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (88 - 96)	I22-7974.cpp\I22-7974.cpp (59 - 67)	17
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (48 - 53)	I22-7974.cpp\I22-7974.cpp (213 - 220)	15
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (65 - 71)	I22-7974.cpp\I22-7974.cpp (82 - 88)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (238 - 248)	I22-7974.cpp\I22-7974.cpp (199 - 208)	13
assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (139 - 145)	I22-7974.cpp\I22-7974.cpp (137 - 143)	12

```
139     for (int i = 0; i < counter; i++)
140     {
141         cout << "Input word : " << data_dict[i] << endl;
142         if (synonym[i] != nullptr)
143         {
144             for (int j = 0; j < synonym_count; j++)
145             {
146                 cout << "Synonym: ";
147                 for (int k = 0; synonym[i][j][k] != '\0'; k++)
148                 {
149                     cout << synonym[i][j][k];
150                 }
151                 cout << endl;
152             }
153         }
154         cout << endl;
155     }
156
157             //**task 3**//
158       char useCase1[2000];
159     cout << "Enter use case: ";
160     cin.getline(useCase1, 2000);
161     int c= 0;
162     int index = 0;
163     for (int i = 0; useCase1[i] != '\0'; i++)
164     {
165         if (useCase1[i] == ' '||useCase1[i]=='.')
166         {
167             char* word = new char[(i - index) + 1];
168             int j = 0;
169             for (int k = index; k < i; k++)
170             {
171                 word[j] = useCase1[k];
172                 j++;
173             }
174             word[j] = '\0';
175
176             if (SearchUnique(data_dict, data_count, word,f_index))
177             {
178                 cout << "Word: " << word << endl;
179                 index++;
180                 c++;
181             }
182             delete[] word;
183             index = i + 1;
184         }
185     }
186     cout << "There were " << c << " words\n";
187
188                     //**task 4**//
189
190     char useCase2[2000];
191     char f_text[1000];
192     cout << "Input:";
193     cin.getline(useCase2, 2000);
194     index = 0;
195     int text_c = 0;
196     for (int i = 0; useCase2[i] != '\0'; i++)
197     {
198         if (useCase2[i] == ' ' || useCase2[i] == '.')
199         {
200             char* word = new char[(i - index) + 1];
201             int j = 0;
202             for (int k = index; k < i; k++)
203             {
204                 word[j] = useCase2[k];
205                 j++;
206             }
207             word[j] = '\0';
```

```
137     for (int i = 0; i < row_count; i++)
138     {
139             if (synonyms[i] != nullptr)
140             {
141                     cout << "Synonyms for " << arr[i] << ": ";
142                     for (int j = 0; synonyms[i][j][0] != '\0'; j++)
143                     {
144                             cout << synonyms[i][j]<<"      " ;
145
146                     }
147                     cout << endl;
148             }
149     }
150 }
151 void searchword(char** data_dictionary, char* use_case1, int indx)
152 {
153     bool found = false;
154     for (int i = 0; i < indx; i++)
155     {
156             int k = 0;
157             for (int j = 0; use_case1[j] != '\0'; j++)
158             {
159                     if (data_dictionary[i][k] == '\0')
160                     {
161                             if (use_case1[j] == ' ')
162                             {
163                                     k = 0;
164                             }
165                             else
166                             {
167                                     break;
168                             }
169                     }
170                     if (data_dictionary[i][k] == use_case1[j])
171                     {
172                             k++;
173                     }
174                     else
175                     {
176                             k = 0;
177                     }
178                     if (data_dictionary[i][k] == '\0' && (use_case1[j + 1] == ' ' ||
179                     {
180                             cout << "Similar Word: " << data_dictionary[i] << endl;
181                             found = true;
182                             break;
183                     }
184             }
185     }
186 }
187 void deldatadict(char** data_dictionary, int row_count)
188 {
189     for (int i = 0; i < row_count; i++)
190     {
191             delete[] data_dictionary[i];
192     }
193
194 }
195 void delsyn(char*** synonyms, int row_count)
196 {
197     for (int i = 0; i < row_count; i++)
198     {
199             if (synonyms[i] != nullptr)
200             {
201                     for (int j = 0; synonyms[i][j][0] != '\0'; j++)
202                     {
203                             delete[] synonyms[i][j];
204                     }
```

1:19 PM
4/14/2023