WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Downlo

jplag.github.io/JPlag/comparison/22L7916.cpp/22I7980assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L7916.cpp

Submission 2
22I7980assignment1.cpp

Match %
45.13

Submission 1 File 1	Submission 2 File 2	Tokens
22L7916.cpp\22L7916.cpp (215 - 258)	22I7980assignment1.cpp\22I7980assignment1.cpp (172 - 215)	79
22L7916.cpp\22L7916.cpp (262 - 298)	22I7980assignment1.cpp\22I7980assignment1.cpp (216 - 250)	50
22L7916.cpp\22L7916.cpp (59 - 84)	22I7980assignment1.cpp\22I7980assignment1.cpp (118 - 143)	46
22L7916.cpp\22L7916.cpp (96 - 111)	22I7980assignment1.cpp\22I7980assignment1.cpp (151 - 166)	29
22L7916.cpp\22L7916.cpp (7 - 13)	22I7980assignment1.cpp\22I7980assignment1.cpp (83 - 89)	18
22L7916.cpp\22L7916.cpp (48 - 55)	22I7980assignment1.cpp\22I7980assignment1.cpp (109 - 117)	14

Files of 22L7916.cpp

22L7916.cpp\22L7916.cpp

```
1 #include<iostream>
2 #include<fstream>
3 #include<string>
4 using namespace std;
5
6 void increaseSize(char**& dic, int& rows) {
7       char** newDic = new char* [rows + 1];
8       int count = 0;
9       for (int i = 0; i < rows; i++) {
10              count = 0;
11              for (int j = 0; dic[i][j] != '\0'; j++) {
12                      count++;
13              }
14              newDic[i] = new char[count + 2];
15              for (int j = 0; dic[i][j] != '\0'; j++) {
16                      newDic[i][j] = dic[i][j];
17              }
18              newDic[i][count] = '\0';
19              newDic[i][count + 1] = dic[i][count + 1];
20      }
21      newDic[rows] = NULL;
22      for (int i = 0; i < rows; i++) {
23              delete[]dic[i];
24      }
25      delete[]dic;
26      dic = newDic;
27      rows++;
28 }
29 void dictionary(char*& sen, char**& dic, int& rows) {
30      char temp[100];
31      int row = 0;
32      int counter = 0;
33      bool flag = false;
34      for (int i = 0; sen[i] != '\0'; i++) {
35              if (sen[i] == ' ' || sen[i] == '.') {
36                      temp[counter] = '\0';
37                      for (int j = 0; j < rows; j++) {
38                              flag = true;
39                              for (int k = 0; temp[k] != '\0' && dic[j][
40                                      if (toupper(temp[k]) != toupper(di
41                                              flag = false;
42                              }
43                      }
44                      if (flag) {
45                              break;
46                      }
47              }
48              if (!flag) {
```

Files of 22I7980assignment1.cpp

..80assignment1.cpp\22I7980assignment1.cpp

```
1 //bool wordExist(char** data_Dictionary, int count, char* word) {
2 //    for (int i = 0; i < count; i++) {
3 //            int j = 0;
4 //            while (true) {
5 //                    if (data_Dictionary[i][j] != word[j])
6 //                            break;
7 //                    if (data_Dictionary[i][j] == '\0' || word[j] == '\
8 //                            return true;
9 //                    j++;
10 //            }
11 //    }
12 //    return false;
13 //}
14 //
15 //void inputData(char** data_Dictionary, int& count, char* word) {
16 //    int tempLen = 0;
17 //    while (word[tempLen] != '\0')
18 //            tempLen++;
19 //
20 //    data_Dictionary[count] = new char[tempLen + 1];
21 //    for (int i = 0; i < tempLen; i++)
22 //            data_Dictionary[count][i] = word[i];
23 //    data_Dictionary[count][tempLen] = '\0';
24 //    count++;
25 //}
26 //void tokenize(char* input, char** data_dictionary, int& count) {
27 //    int initial_index = 0, final_index = 0;
28 //    char* begin = input;
29 //    for (int i = 0; input[i] != '\0'; i++)
30 //            final_index++;
31 //    char* ending = input + final_index;
32 //    while (begin < ending) {
33 //            char* i = begin;
34 //            while (*i != ' ' && *i != '\0' && *i != '.')
35 //                    i++;
36 //            if (*i == ' ' || *i == '.')
37 //                    *i = '\0';
38 //
39 //            if (*begin != '\0')
40 //                    if (!wordExist(data_dictionary, count, begin)) {
41 //                            inputData(data_dictionary, count, begin);
42 //                    }
43 //            begin = i + 1;
44 //            initial_index++;
45 //    }
46 //}
47 //#include <iostream>
48 //using namespace std;
```

Screenshot (205).pdf

Show all

1:12 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Downlo
jplag.github.io/JPlag/comparison/22L7916.cpp/22l7980assignment1.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L7916.cpp

Submission 2
22l7980assignment1.cpp

Match %
45.13

Submission 1 File 1	Submission 2 File 2	Tokens
22L7916.cpp\22L7916.cpp (215 - 258)	22l7980assignment1.cpp\22l7980assignment1.cpp (172 - 215)	79
22L7916.cpp\22L7916.cpp (262 - 298)	22l7980assignment1.cpp\22l7980assignment1.cpp (216 - 250)	50
22L7916.cpp\22L7916.cpp (59 - 84)	22l7980assignment1.cpp\22l7980assignment1.cpp (118 - 143)	46
22L7916.cpp\22L7916.cpp (96 - 111)	22l7980assignment1.cpp\22l7980assignment1.cpp (151 - 166)	29
22L7916.cpp\22L7916.cpp (7 - 13)	22l7980assignment1.cpp\22l7980assignment1.cpp (83 - 89)	18
22L7916.cpp\22L7916.cpp (48 - 55)	22l7980assignment1.cpp\22l7980assignment1.cpp (109 - 117)	14

```cpp
215             }
216     }
217 }
218 void foundWords(char*& useCase1, char**& dic, char***& syn, int& rows)
219     int i = 0;
220     int j = 0;
221     int count = 0;
222     bool flag;
223     int count2;
224     int r = 0;
225     char* temp = new char[100];
226     char** matched = new char*[0];
227     while (useCase1[i] != '\0') {
228             if (useCase1[i] == ' ' || useCase1[i] == '.') {
229                     temp[j] = '\0';
230                     for (int k = 0; k < rows; k++) {
231                             flag = true;
232                             for (int l = 0; temp[l] != '\0' && dic[k][
233                                     if (toupper(temp[l]) != toupper(di
234                                             flag = false;
235                                             break;
236                                     }
237                             }
238                             if (flag) {
239                                     count2 = 0;
240                                     increaseSize(matched, r);
241                                     for (int l = 0; temp[l] != '\0'; l
242                                             count2++;
243                                     }
244                                     matched[r-1] = new char[count2 + 2
245                                     for (int l = 0; temp[l] != '\0'; l
246                                             matched[r-1][l] = temp[l];
247                                     }
248                                     matched[r-1][count2] = '\0';
249                                     matched[r - 1][count2 + 1] = k + 4
250                                     count++;
251                                     break;
252                             }
253                             else {
254                                     //dictionary(temp, dic, rows);
255                             }
256                     }
257                     temp[0] = '\0';
258                     j = 0;
259                     if (useCase1[i] == '.' && useCase1[i+1] == ' ') {
260                             i++;
261                     }
262             }
263             else {
264                     temp[j] = useCase1[i];
265                     j++;
266             }
267             i++;
268     }
269     cout << "Total Words Found: " << count;
270     cout << "\nFound Words are as Follows: \n";
271     for (int i = 0; i < r; i++) {
272             for (int j = 0; matched[i][j] != '\0'; j++) {
273                     cout << matched[i][j];
274             }
275             cout << endl;
276     }
```

```cpp
172             }
173     }
174 }
175 void wordsfound(char*& firstcase, char*& dict, char**& synonym, int& r
176     int i = 0;
177     int j = 0;
178     int count = 0;
179     bool flag;
180     int count2;
181     int x = 0;
182     char* temporary = new char[100];
183     char** found = new char*[0];
184     while (firstcase[i] != '\0') {
185             if (firstcase[i] == ' ' || firstcase[i] == '.') {
186                     temporary[j] = '.';
187                     for (int k = 0; k < rows; k++) {
188                             flag = true;
189                             for (int l = 0; temporary[l] != '.' && dic
190                                     if (toup(temporary[l]) != toup(dic
191                                             flag = false;
192                                             break;
193                                     }
194                             }
195                             if (flag) {
196                                     count2 = 0;
197                                     growSize(found, x);
198                                     for (int l = 0; temporary[l] != '.
199                                             count2++;
200                                     }
201                                     found[x - 1] = new char[count2 + 2
202                                     for (int l = 0; temporary[l] != '.
203                                             found[x - 1][l] = temporar
204                                     }
205                                     found[x - 1][count2] = '\0';
206                                     found[x - 1][count2 + 1] = k;
207                                     count++;
208                                     break;
209                             }
210                             else {
211                                     //dictionary(temp, dic, rows);
212                             }
213                     }
214                     temporary[0] = '\0';
215                     j = 0;
216             }
217             else {
218                     temporary[j] = firstcase[i];
219                     j++;
220             }
221             i++;
222     }
223     cout << "Words Found: " << count;
224     cout << "Words :" << endl;
225     for (int i = 0; i < x; i++) {
226             for (int j = 0; found[i][j] != '\0'; j++) {
227                     cout << found[i][j];
228             }
229             cout << endl;
230     }
231
232 }
233 void main() {
```

Screenshot (205).pdf
Show all
1:12 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Downlo

jplag.github.io/JPlag/comparison/22L7916.cpp/22l7980assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L7916.cpp

Submission 2
22l7980assignment1.cpp

Match %
45.13

Submission 1 File 1	Submission 2 File 2	Tokens
22L7916.cpp\22L7916.cpp (216 - 258)	22l7980assignment1.cpp\22l7980assignment1.cpp (172 - 215)	79
22L7916.cpp\22L7916.cpp (262 - 298)	22l7980assignment1.cpp\22l7980assignment1.cpp (216 - 250)	50
22L7916.cpp\22L7916.cpp (59 - 84)	22l7980assignment1.cpp\22l7980assignment1.cpp (118 - 143)	46
22L7916.cpp\22L7916.cpp (96 - 111)	22l7980assignment1.cpp\22l7980assignment1.cpp (151 - 166)	29
22L7916.cpp\22L7916.cpp (7 - 13)	22l7980assignment1.cpp\22l7980assignment1.cpp (83 - 89)	18
22L7916.cpp\22L7916.cpp (48 - 55)	22l7980assignment1.cpp\22l7980assignment1.cpp (109 - 117)	14
22L7916.cpp\22L7916.cpp (27 - 32)	22l7980assignment1.cpp\22l7980assignment1.cpp (102 - 107)	12

```
246                                     matched[r-1][l] = temp[l];
247                                 }
248                                 matched[r-1][count2] = '\0';
249                                 matched[r - 1][count2 + 1] = k + 4
250                                 count++;
251                                 break;
252                             }
253                             else {
254                                     //dictionary(temp, dic, rows);
255                             }
256                     }
257                     temp[0] = '\0';
258                     j = 0;
259                     if (useCase1[i] == '.' && useCase1[i+1] == ' ') {
260                             i++;
261                     }
262             }
263             else {
264                     temp[j] = useCase1[i];
265                     j++;
266             }
267             i++;
268     }
269     cout << "Total Words Found: " << count;
270     cout << "\nFound Words are as Follows: \n";
271     for (int i = 0; i < r; i++) {
272             for (int j = 0; matched[i][j] != '\0'; j++) {
273                     cout << matched[i][j];
274             }
275             cout << endl;
276     }
277     replaceWords(syn, useCase1, matched, r);
278 }
279
280
281 void main() {
282     int rows = 0;
283     char* sen = new char[2000];
284     char** dic = NULL;
285     ifstream fr;
286     //ofstream fw("sentence.txt");
287     //fw << "This assignment is a piece of cake.";
288     //fw.close();
289     fr.open("sentence.txt");
290     int i;
291     fr.getline(sen, 2000);
292     dictionary(sen, dic, rows);
293     char*** syn = new char**[rows];
294     for (int i = 0; i < rows; i++) {
295             syn[i] = new char*[1];
296     }
297     synonyms(syn, dic, rows);
298     char* useCase1 = new char [2000];
299     cin.ignore();
300     cout << "Enter a Sentence: ";
301     cin.getline(useCase1, 2000);
302     foundWords(useCase1, dic, syn, rows);
303     for (int x = 0; useCase1[x] != '\0'; x++) {
304             cout << useCase1[x];
305     }
306 }
307
308
309
```

```
216             }
217             else {
218                     temporary[j] = firstcase[i];
219                     j++;
220             }
221             i++;
222     }
223     cout << "Words Found: " << count;
224     cout << "Words :" << endl;
225     for (int i = 0; i < x; i++) {
226             for (int j = 0; found[i][j] != '\0'; j++) {
227                     cout << found[i][j];
228             }
229             cout << endl;
230     }
231
232 }
233 void main() {
234     int row = 0;
235     char* sent = new char[2000];
236     char** dict = NULL;
237     ifstream fr;
238     ofstream fw("string.txt");
239     fw << "Hello World.";
240     fw.close();
241     fr.open("string.txt");
242     int i;
243     fr.getline(sent, 2000);
244     dictionary(sent, dict, row);
245     char** synonym = new char* [row];
246     for (int i = 0; i < row; i++) {
247             synonym[i] = new char* [1];
248     }
249     synonyms(synonym, dict, row);
250     char* firstcase = new char[2000];
251     cin.ignore();
252     cout << "Enter a String: ";
253     cin.getline(firstcase, 2000);
254     wordsfound(firstcase, dict, synonym, row);
255 }
256 //TASK 4
257 #include <iostream>
258 #include <cstring>
259 using namespace std;
260
261 const int MAX_DICT_SIZE = 1000;
262 const int MAX_WORD_SIZE = 50;
263 const int MAX_USECASE_SIZE = 3000;
264 const int MAX_SYN_SIZE = 10;
265
266 // function prototypes
267 bool isWordPresent(char** dateDictionary, int count, char* word);
268 void enterData(char** dateDictionary, int& count, char* word);
269 void tokenize(char* input, char** dateDictionary, int& count);
270 bool isSynPresent(char** synonymDict, int count, char* word);
271 void enterSynonym(char** synonymDict, char* word, char* syn, int& coun
272 void loadSynonyms(char** synonymDict, int& count);
273 void replaceWithSynonyms(char** dateDictionary, int dictCount, char**
274
275 // main function
276 int main() {
277     char* dateDictionary[MAX_DICT_SIZE];
278     int dictCount = 0;
279     loadDictionary(dateDictionary, dictCount);
280
281     char* synonymDict[MAX_DICT_SIZE];
282     int synCount = 0;
283     loadSynonyms(synonymDict, synCount);
284
```

1:12 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Downlo
jplag.github.io/JPlag/comparison/22L7916.cpp/22l7980assignment1.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L7916.cpp

Submission 2
22l7980assignment1.cpp

Match %
45.13

Submission 1 File 1	Submission 2 File 2	Tokens
22L7916.cpp\22L7916.cpp (216 - 258)	22l7980assignment1.cpp\22l7980assignment1.cpp (172 - 215)	79
22L7916.cpp\22L7916.cpp (262 - 298)	22l7980assignment1.cpp\22l7980assignment1.cpp (216 - 250)	50
22L7916.cpp\22L7916.cpp (59 - 84)	22l7980assignment1.cpp\22l7980assignment1.cpp (118 - 143)	46
22L7916.cpp\22L7916.cpp (96 - 111)	22l7980assignment1.cpp\22l7980assignment1.cpp (151 - 166)	29
22L7916.cpp\22L7916.cpp (7 - 13)	22l7980assignment1.cpp\22l7980assignment1.cpp (83 - 89)	18
22L7916.cpp\22L7916.cpp (48 - 55)	22l7980assignment1.cpp\22l7980assignment1.cpp (109 - 117)	14
22L7916.cpp\22L7916.cpp (27 - 32)	22l7980assignment1.cpp\22l7980assignment1.cpp (102 - 107)	12

```
59                      counter = 0;
60                      if (sen[i + 1] == ' ') {
61                              i++;
62                      }
63              }
64              else {
65                      temp[counter++] = sen[i];
66              }
67      }
68 }
69 void synonyms(char***& syn, char**& dic, int rows) {
70      char choice;
71      char temp[100];
72      int count = 0;
73      for (int i = 0; i < rows; i++) {
74              count = 0;
75              cout << "\nDo you want to write synonyms for \"";
76              for (int j = 0; dic[i][j] != '\0'; j++) {
77                      cout << dic[i][j];
78                      count++;
79              }
80              syn[i][0] = new char[count + 2];
81              for (int j = 0; dic[i][j] != '\0'; j++) {
82                      syn[i][0][j] = dic[i][j];
83              }
84              syn[i][0][count] = '\0';
85              cout << "\"? (y/n)";
86              choice:
87              cin >> choice;
88              char c_num;
89              int num = 0;
90              if (choice == 'y' || choice == 'Y') {
91                      cout << "How many Synonyms? : ";
92                      cin >> c_num;
93                      cin.ignore();
94                      num = int(c_num) - 48;
95                      syn[i][0][count + 1] = c_num;
96                      for (int k = 0; k < num; k++) {
97
98                              cout << "Enter Synonym: ";
99                              cin.getline(temp, 100);
100                             count = 0;
101                             for (int l = 0; temp[l] != '\0'; l++) {
102                                     count++;
103                             }
104                             syn[i][k + 1] = new char[count + 1];
105                             for (int l = 0; temp[l] != '\0'; l++) {
106                                     syn[i][k + 1][l] = temp[l];
107                             }
108                             syn[i][k + 1][count] = '\0';
109                     }
110             }
111             else if (choice == 'n' || choice == 'N') {
112                     syn[i][0][count + 1] = '0';
113                     continue;
114             }
115             else {
116                     cout << "Invalid! Try again\n";
117                     goto choice;
118             }
119     }
120 }
121 void replaceWords(char***& syn, char*& useCase1, char**& matched, int&
122     int index = 0;
123     int j = 0;
124     int l;
125     bool flag = true;
```

```
118                     x = 0;
119                     if (s[i + 1] == ' ') {
120                             i++;
121                     }
122             }
123             else {
124                     temporary[x++] = s[i];
125             }
126     }
127 }
128 void synonyms(char*& synonym, char& dict, int rows) {
129     char option;
130     char temp[100];
131     int count = 0;
132     for (int i = 0; i < rows; i++) {
133             count = 0;
134             cout << "\nDo you want to write synonyms for \"";
135             for (int j = 0; dict[i][j] != '\0'; j++) {
136                     cout << dict[i][j];
137                     count++;
138             }
139             synonym[i][0] = new char[count + 1];
140             for (int j = 0; dict[i][j] != '\0'; j++) {
141                     synonym[i][0][j] = dict[i][j];
142             }
143             synonym[i][0][count] = '\0';
144             cout << "\"? (y/n)";
145     option:
146             cin >> option;
147             int num = 0;
148             if (option == 'y' || option == 'Y') {
149                     cout << "Synonyms number? : ";
150                     cin >> num;
151                     for (int y = 0; y < num; y++) {
152                             cin.ignore();
153                             cout << "Enter Synonym: ";
154                             cin.getline(temp, 100);
155                             count = 0;
156                             for (int l = 0; temp[l] != '\0'; l++) {
157                                     count++;
158                             }
159                             synonym[i][y + 1] = new char[count + 1];
160                             for (int l = 0; temp[l] != '\0'; l++) {
161                                     synonym[i][y + 1][l] = temp[l];
162                             }
163                             synonym[i][y + 1][count] = '\0';
164                     }
165             }
166             else if (option == 'n' || option == 'N') {
167                     continue;
168             }
169             else {
170                     cout << "Invalid! Try again\n";
171                     goto option;
172             }
173     }
174 }
175 void wordsfound(char*& firstcase, char*& dict, char**& synonym, int& r
176     int i = 0;
177     int j = 0;
178     int count = 0;
179     bool flag;
180     int count2;
181     int x = 0;
182     char* temporary = new char[100];
183     char** found = new char* [8];
184     while (firstcase[i] != '\0') {
```

1:12 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Downlo

jplag.github.io/JPlag/comparison/22L7916.cpp/22l7980assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L7916.cpp

Submission 2
22l7980assignment1.cpp

Match %
45.13

Submission 1 File 1	Submission 2 File 2	Tokens
22L7916.cpp\22L7916.cpp (216 - 258)	22l7980assignment1.cpp\22l7980assignment1.cpp (172 - 215)	79
22L7916.cpp\22L7916.cpp (262 - 298)	22l7980assignment1.cpp\22l7980assignment1.cpp (216 - 250)	50
22L7916.cpp\22L7916.cpp (59 - 84)	22l7980assignment1.cpp\22l7980assignment1.cpp (118 - 143)	46
22L7916.cpp\22L7916.cpp (96 - 111)	22l7980assignment1.cpp\22l7980assignment1.cpp (151 - 166)	29
22L7916.cpp\22L7916.cpp (7 - 13)	22l7980assignment1.cpp\22l7980assignment1.cpp (83 - 89)	18
22L7916.cpp\22L7916.cpp (48 - 55)	22l7980assignment1.cpp\22l7980assignment1.cpp (109 - 117)	14
22L7916.cpp\22L7916.cpp (27 - 32)	22l7980assignment1.cpp\22l7980assignment1.cpp (102 - 107)	12

```
96                      for (int k = 0; k < num; k++) {
97
98                              cout << "Enter Synonym: ";
99                              cin.getline(temp, 100);
100                             count = 0;
101                             for (int l = 0; temp[l] != '\0'; l++) {
102                                     count++;
103                             }
104                             syn[i][k + 1] = new char[count + 1];
105                             for (int l = 0; temp[l] != '\0'; l++) {
106                                     syn[i][k + 1][l] = temp[l];
107                             }
108                             syn[i][k + 1][count] = '\0';
109                     }
110             }
111             else if (choice == 'n' || choice == 'N') {
112                     syn[i][0][count + 1] = '0';
113                     continue;
114             }
115             else {
116                     cout << "Invalid! Try again\n";
117                     goto choice;
118             }
119     }
120 }
121 void replaceWords(char**& syn, char*& useCase1, char**& matched, int&
122     int index = 0;
123     int j = 0;
124     int l;
125     bool flag = true;
126     int a, p, n, b, k, m, syn_choice;
127     char arr[1000];
128     char* temp = new char[100];
129     for (int i = 0; useCase1[i] != '\0'; i++) {
130             if (useCase1[i] == ' ' || useCase1[i] == '.') {
131                     temp[j] = '\0';
132                     j = 0;
133                     for (k = 0; k < r; k++) {
134                             flag = true;
135                             for (l = 0; temp[l] != '\0' || matched[k][
136                                     if (temp[l] != matched[k][l]) {
137                                             flag = false;
138                                             break;
139                                     }
140                             }
141                             if (flag) {
142                                     l = 0;
143                                     for (l = 0; matched[k][l] != '\0';
144                                     }
145                                     l++;
146                                     n = matched[k][l] - '0';
147                                     for (p = 0; syn[n][0][p] != '\0';
148                                     }
149                                     p++;
150                                     if (syn[n][0][p] == '0') {
151                                             cout << "\nNo Synonyms Fou
152                                             for (int g = 0; syn[n][0][
153                                                     cout << syn[n][0][
154                                             }
155                                             cout << "!\n";
156                                             if (useCase1[i + 1] == ' '
157                                                     index = i + 2;
158                                                     i++;
159                                             }
160                                             else {
161                                                     index = i + 1;
162                                             }
163                                     }
164                                     else {
```

```
151                     for (int y = 0; y < num; y++) {
152                             cin.ignore();
153                             cout << "Enter Synonym: ";
154                             cin.getline(temp, 100);
155                             count = 0;
156                             for (int l = 0; temp[l] != '\0'; l++) {
157                                     count++;
158                             }
159                             synonym[i][y + 1] = new char[count + 1];
160                             for (int l = 0; temp[l] != '\0'; l++) {
161                                     synonym[i][y + 1][l] = temp[l];
162                             }
163                             synonym[i][y + 1][count] = '\0';
164                     }
165             }
166             else if (option == 'n' || option == 'N') {
167                     continue;
168             }
169             else {
170                     cout << "Invalid! Try again\n";
171                     goto option;
172             }
173     }
174 }
175 void wordsFound(char*& firstcase, char*& dict, char**& synonym, int& r
176     int i = 0;
177     int j = 0;
178     int count = 0;
179     bool flag;
180     int count2;
181     int x = 0;
182     char* temporary = new char[100];
183     char** found = new char* [0];
184     while (firstcase[i] != '\0') {
185             if (firstcase[i] == ' ' || firstcase[i] == '.') {
186                     temporary[j] = '.';
187                     for (int k = 0; k < rows; k++) {
188                             flag = true;
189                             for (int l = 0; temporary[l] != '.' && dic
190                                     if (toup(temporary[l]) != toup(dic
191                                             flag = false;
192                                             break;
193                                     }
194                             }
195                             if (flag) {
196                                     count2 = 0;
197                                     growSize(found, x);
198                                     for (int l = 0; temporary[l] != '.
199                                             count2++;
200                                     }
201                                     found[x - 1] = new char[count2 + 2
202                                     for (int l = 0; temporary[l] != '.
203                                             found[x - 1][l] = temporar
204                                     }
205                                     found[x - 1][count2] = '\0';
206                                     found[x - 1][count2 + 1] = k;
207                                     count++;
208                                     break;
209                             }
210                             else {
211                                     //dictionary(temp, dic, rows);
212                             }
213                     }
214                     temporary[0] = '\0';
215                     j = 0;
216             }
217             else {
```

1:12 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Downlo

jplag.github.io/JPlag/comparison/22L7916.cpp/22l7980assignment1.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L7916.cpp

Submission 2
22l7980assignment1.cpp

Match %
45.13

Submission 1 File 1	Submission 2 File 2	Tokens
22L7916.cpp\22L7916.cpp (216 - 258)	22l7980assignment1.cpp\22l7980assignment1.cpp (172 - 215)	79
22L7916.cpp\22L7916.cpp (262 - 298)	22l7980assignment1.cpp\22l7980assignment1.cpp (216 - 250)	50
22L7916.cpp\22L7916.cpp (59 - 84)	22l7980assignment1.cpp\22l7980assignment1.cpp (118 - 143)	46
22L7916.cpp\22L7916.cpp (96 - 111)	22l7980assignment1.cpp\22l7980assignment1.cpp (151 - 166)	29
22L7916.cpp\22L7916.cpp (7 - 13)	22l7980assignment1.cpp\22l7980assignment1.cpp (83 - 89)	18
22L7916.cpp\22L7916.cpp (48 - 55)	22l7980assignment1.cpp\22l7980assignment1.cpp (109 - 117)	14
22L7916.cpp\22L7916.cpp (27 - 32)	22l7980assignment1.cpp\22l7980assignment1.cpp (102 - 107)	12

```
7       char** newDic = new char* [rows + 1];
8       int count = 0;
9       for (int i = 0; i < rows; i++) {
10              count = 0;
11              for (int j = 0; dic[i][j] != '\0'; j++) {
12                      count++;
13              }
14              newDic[i] = new char[count + 2];
15              for (int j = 0; dic[i][j] != '\0'; j++) {
16                      newDic[i][j] = dic[i][j];
17              }
18              newDic[i][count] = '\0';
19              newDic[i][count + 1] = dic[i][count + 1];
20      }
21      newDic[rows] = NULL;
22      for (int i = 0; i < rows; i++) {
23              delete[]dic[i];
24      }
25      delete[]dic;
26      dic = newDic;
27      rows++;
28 }
29 void dictionary(char*& sen, char**& dic, int& rows) {
30      char temp[100];
31      int row = 0;
32      int counter = 0;
33      bool flag = false;
34      for (int i = 0; sen[i] != '\0'; i++) {
35              if (sen[i] == ' ' || sen[i] == '.') {
36                      temp[counter] = '\0';
37                      for (int j = 0; j < rows; j++) {
38                              flag = true;
39                              for (int k = 0; temp[k] != '\0' && dic[j][
40                                      if (toupper(temp[k]) != toupper(di
41                                              flag = false;
42                              }
43                      }
44                      if (flag) {
45                              break;
46                      }
47                      }
48                      if (!flag) {
49                              increaseSize(dic, rows);
50                              dic[row] = new char[counter + 1];
51                              for (int j = 0; j < counter; j++) {
52                                      dic[row][j] = temp[j];
53                              }
54                              dic[row][counter] = '\0';
55                              row++;
56                      }
57
58
59                      counter = 0;
60                      if (sen[i + 1] == ' ') {
61                              i++;
62                      }
63              }
64              else {
65                      temp[counter++] = sen[i];
66              }
67      }
68 }
69 void synonyms(char***& syn, char**& dic, int rows) {
70      char choice;
71      char temp[100];
72      int count = 0;
```

```
83      char** New = new char* [row + 1];
84      int count = 0;
85      for (int i = 0; i < row; i++) {
86              count = 0;
87              for (int j = 0; dictionary[i][j] != '\0'; j++) {
88                      count++;
89              }
90              New[i] = new char[count + 1];
91              for (int j = 0; dictionary[i][j] != '\0'; j++) {
92                      New[i][j] = dictionary[i][j];
93              }
94              New[i][count] = '\0';
95      }
96      New[row] = NULL;
97      for (int i = 0; i < row; i++) {
98              delete[]dictionary[i];
99      }
100     delete[]dictionary;
101     dictionary = New;
102     row++;
103 }
104 void dictionary(char*& s, char**& dict, int& rows) {
105     char temporary[100];
106     int row = 0;
107     int x = 0;
108     for (int i = 0; s[i] != '\0'; i++) {
109             if (s[i] == ' ' || s[i] == '.') {
110
111                     growSize(dict, rows);
112                     dict[row] = new char[x + 1];
113                     for (int j = 0; j < x; j++) {
114                             dict[row][j] = temporary[j];
115                     }
116                     dict[row][x] = '\0';
117                     row++;
118                     x = 0;
119                     if (s[i + 1] == ' ') {
120                             i++;
121                     }
122             }
123             else {
124                     temporary[x++] = s[i];
125             }
126     }
127 }
128 void synonyms(char*& synonym, char& dict, int rows) {
129     char option;
130     char temp[100];
131     int count = 0;
132     for (int i = 0; i < rows; i++) {
133             count = 0;
134             cout << "\nDo you want to write synonyms for \"";
135             for (int j = 0; dict[i][j] != '\0'; j++) {
136                     cout << dict[i][j];
137                     count++;
138             }
139             synonym[i][0] = new char[count + 1];
140             for (int j = 0; dict[i][j] != '\0'; j++) {
141                     synonym[i][0][j] = dict[i][j];
142             }
143             synonym[i][0][count] = '\0';
144             cout << "\"? (y/n)";
145     option:
146             cin >> option;
147             int num = 0;
```

1:12 PM
4/14/2023