(1) WhatsA | report-view | Lab Manua | State Life I | The Cl | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

Files of 22L-7921.cpp

22L-7921.cpp\22L-7921.cpp

```cpp
//Ayesha Rafique
//22L_7921
//BS(SE)2C
//OOP Assognment 1
//Task 1,2,3,4


#include <iostream>
#include <cstring>

using namespace std;

void get_input(char* input)
{
    cout << "Please enter the data: ";
    cin.getline(input, 3000);
}

int find_word_index(char** dictionary, int num_words, char* word)
{
    for (int i = 0; i < num_words; i++)
    {
        if (dictionary[i] == word)
        {
            return i;
        }
        /* if (strcmp(dictionary[i], word) == 0)
         {
            return i;
         }*/
    }
    return -1;
}

void tokenize(char* input, char** dictionary, int& num_words)
{
    char word[3000];
    int word_length = 0;
    for (int i = 0; input[i] != '\0'; i++)
    {
        if (input[i] == ' ' || input[i] == ',')
        {
            if (word_length > 0)
            {
                word[word_length] = '\0';
                int index = find_word_index(dictionary, num_words, word);
                if (index == -1)
                {
                    dictionary[num_words] = new char[word_length + 1];
                    for (int j = 0; j < word_length; j++)
                    {
                        dictionary[num_words][j] = word[j];
```

Files of fatima_22L7999.cpp

fatima_22L7999.cpp\fatima_22L7999.cpp

```cpp
#include <iostream>
#include <cstring>

using namespace std;

void get_input(char *input)
{
    cout << "Please enter the data: ";
    ifstream infile("input.txt");
    string input;
    getline(infile, input);
    infile.close();

}

int find_word_index(char**& dictionary, int num_words, char* word)
{
    for (int i = 0; i < num_words; i++)
    {
        bool match = true;
        for (int j = 0; dictionary[i][j] != '\0' || word[j] != '\0'; j++)
        {
            if (dictionary[i][j] != word[j])
            {
                match = false;
                break;
            }
        }
        if (match && dictionary[i][0] != '\0' && word[0] != '\0')
        {
            return i;
        }
    }
    return -1;
}

void tokenize(char *input, char **dictionary, int &num_words)
{
    const int m_word = 100;
    char word[m_word];
    int word_length = 0;
    for (int i = 0; input[i] != '\0'; i++)
    {
        if (input[i] == ' ' || input[i] == ',')
        {
            if (word_length > 0)
            {
                word[word_length] = '\0';
                int index = find_word_index(dictionary, num_words, word);
                if (index == -1)
                {
                    dictionary[num_words] = new char[word_length + 1];
                    int len = strlen(word);
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```
225 }
226
227
228 void replaceWithSynonyms(char*& useCase1, int useCase1Len, char**& dataDict, in
229 {
230     const char* delim = " .";
231     char* token = nullptr;
232     int tokenLen = 0;
233     char* synonym = nullptr;
234     int synonymLen = 0;
235     bool found = false;
236     for (int i = 0; i < useCase1Len; i++)
237     {
238         if (useCase1[i] == ' ' || useCase1[i] == '.')
239         {
240             if (found)
241             {
242                 int numSynonyms = 0;
243                 int randIndex = rand() % numSynonyms;
244                 synonym = synonyms[i][randIndex];
245                 synonymLen = 0;
246                 while (synonym[synonymLen] != '\0')
247                 {
248                     synonymLen++;
249                 }
250                 for (int k = 0; k < synonymLen; k++)
251                 {
252                     useCase1[i - tokenLen + k] = synonym[k];
253                 }
254                 tokenLen = 0;
255                 found = false;
256             }
257             else
258             {
259                 tokenLen = 0;
260             }
261         }
262         else
263         {
264             if (!found)
265             {
266                 token = &useCase1[i];
267                 found = true;
268             }
269             tokenLen++;
270             for (int j = 0; j < numWords; j++)
271             {
272                 if (isEqual(token, tokenLen, dataDict[j]))
273                 {
274                     int numSynonyms = 0;
275                     while (synonyms[j][numSynonyms] != nullptr)
276                     {
277                         numSynonyms++;
278                     }
279                     if (numSynonyms > 0)
280                     {
281                         found = false;
282                     }
283                     break;
284                 }
285             }
286         }
287     }
288 }
289 bool isEqual(char* str1, int len1, char* str2)
290 {
291     int len2 = 0;
292     while (str2[len2] != '\0')
293     {
```

```
233 }
234
235 void replaceWithSynonyms(char *&useCase1, int useCase1Len, char **&dataDict, i
236 {
237     const char *delim = " .";
238     char *token = nullptr;
239     int tokenLen = 0;
240     char *synonym = nullptr;
241     int synonymLen = 0;
242     bool found = false;
243     for (int i = 0; i < useCase1Len; i++)
244     {
245         if (useCase1[i] == ' ' || useCase1[i] == '.')
246         {
247             if (found)
248             {
249                 int numSynonyms = 0;
250                 int randIndex = rand() % numSynonyms;
251                 synonym = synonyms[i][randIndex];
252                 synonymLen = 0;
253                 while (synonym[synonymLen] != '\0')
254                 {
255                     synonymLen++;
256                 }
257                 for (int k = 0; k < synonymLen; k++)
258                 {
259                     useCase1[i - tokenLen + k] = synonym[k];
260                 }
261                 tokenLen = 0;
262                 found = false;
263             }
264             else
265             {
266                 tokenLen = 0;
267             }
268         }
269         else
270         {
271             if (!found)
272             {
273                 token = &useCase1[i];
274                 found = true;
275             }
276             tokenLen++;
277             for (int j = 0; j < numWords; j++)
278             {
279                 if (isEqual(token, tokenLen, dataDict[j]))
280                 {
281                     int numSynonyms = 0;
282                     while (synonyms[j][numSynonyms] != nullptr)
283                     {
284                         numSynonyms++;
285                     }
286                     if (numSynonyms > 0)
287                     {
288                         found = false;
289                     }
290                     break;
291                 }
292             }
293         }
294     }
295 }
296 bool isEqual(char *str1, int len1, char *str2)
297 {
298     int len2 = 0;
299     while (str2[len2] != '\0')
300     {
301         len2++;
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```
49                  dictionary[num_words] = new char[word_length + 1];
50                  for (int j = 0; j < word_length; j++)
51                  {
52                      dictionary[num_words][j] = word[j];
53                  }
54                  dictionary[num_words][word_length] = '\0';
55                  num_words++;
56              }
57              word_length = 0;
58          }
59      }
60      else {
61          if (word_length < 3000 - 1)
62          {
63              word[word_length] = input[i];
64              word_length++;
65          }
66      }
67  }
68  if (word_length > 0)
69  {
70      word[word_length] = '\0';
71      int index = find_word_index(dictionary, num_words, word);
72      if (index == -1)
73      {
74          dictionary[num_words] = new char[word_length + 1];
75          for (int j = 0; j < word_length; j++)
76          {
77              dictionary[num_words][j] = word[j];
78          }
79          dictionary[num_words][word_length] = '\0';
80          num_words++;
81      }
82  }
83 }
84
85 void print_dictionary(char** dictionary, int num_words)
86 {
87     cout << "Data dictionary:\n";
88     for (int i = 0; i < num_words; i++)
89     {
90         cout << dictionary[i] << endl;
91     }
92 }
93
94 void delete_dictionary(char** dictionary, int num_words)
95 {
96     for (int i = 0; i < num_words; i++)
97     {
98         delete[] dictionary[i];
99     }
100     delete[] dictionary;
101 }
102
103 void get_synonym(char***& synonyms, char** dictionary, int num_words, int& num_
104 {
105     // create synonyms array and initialize with null pointers
106     synonyms = new char** [num_words];
107     for (int i = 0; i < num_words; i++)
108     {
109         synonyms[i] = nullptr;
110     }
111
112     // ask for synonyms for each word
113     for (int i = 0; i < num_words; i++)
114     {
115         char response;
116         cout << "Would you like to store synonyms for \"" << dictionary[i] << "
117         cin >> response;
```

```
54                  dictionary[num_words] = new char[len + 1];
55                  for (int i = 0; i < len; i++)
56                  {
57                      dictionary[num_words][i] = word[i];
58                  }
59                  dictionary[num_words][len] = '\0';
60                  num_words++;
61              }
62              word_length = 0;
63          }
64      }
65      else
66      {
67          if (word_length < m_word - 1)
68          {
69              word[word_length] = input[i];
70              word_length++;
71          }
72      }
73  }
74  if (word_length > 0)
75  {
76      word[word_length] = '\0';
77      int index = find_word_index(dictionary, num_words, word);
78      if (index == -1)
79      {
80          dictionary[num_words] = new char[word_length + 1];
81            for (int i = 0; i < word_length; i++)
82          {
83              dictionary[num_words][i] = word[i];
84          }
85          dictionary[num_words][word_length] = '\0';
86          num_words++;
87      }
88  }
89 }
90
91 void print_dictionary(char **dictionary, int num_words)
92 {
93     cout << "Data dictionary:\n";
94     for (int i = 0; i < num_words; i++)
95     {
96         cout << dictionary[i] << endl;
97     }
98 }
99
100 void delete_dictionary(char **dictionary, int num_words)
101 {
102     for (int i = 0; i < num_words; i++)
103     {
104         delete[] dictionary[i];
105     }
106     delete[] dictionary;
107 }
108
109 void initialize(int m_word, char ***&synonyms, int *num_synonyms, char **&dicti
110 {
111     for (int i = 0; i < m_word; i++)
112     {
113         synonyms[i] = new char *[10];
114         for (int j = 0; j < 10; j++)
115         {
116             synonyms[i][j] = NULL;
117         }
118         num_synonyms[i] = 0;
119     }
120
121     for (int i = 0; i < num_words; i++)
122     {
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```cpp
    delete[] num_synonyms;
}
void data_dictionary(char*& usecase1, char** dictionary, int num_words, int& co
{
    char* array = new char[3000];
    cout << "enter the data (at-least 3-4 sentences)\n";
    cin.getline(array, 3000);
    cin.ignore();
    char* n_array = new char[10];
    int k = 0;
    int len = strlen(array);
    while (k < len)
    {
        int s = 0;

        while (array[k] != ' ' && k < len)
        {
            n_array[s] = array[k];
            k++;
            s++;
        }
        n_array[s] = '\0';

        for (int i = 0; i < num_words; i++)
        {
            int a = 0;
            for (int j = 0; j < s; j++)
            {
                if (n_array[j] == dictionary[i][j])
                {
                    a++;
                }
            }
            if (a == s)
            {
                count++;
                int b;
                for (b = 0; b < s; b++)
                {
                    usecase1[b] = n_array[b];
                }
                usecase1[b] = ' ';
                usecase1 += b + 1; // move the pointer to the next position
                break;

            }
        }
        k++;
    }
    usecase1--; // move the pointer back to the last space
    *usecase1 = '\0'; // add null terminator to the end of the string
    delete[] n_array;
}


void replaceWithSynonyms(char*& useCase1, int useCase1Len, char**& dataDict, in
{
    const char* delim = " .";
    char* token = nullptr;
    int tokenLen = 0;
    char* synonym = nullptr;
    int synonymLen = 0;
    bool found = false;
    for (int i = 0; i < useCase1Len; i++)
    {
        if (useCase1[i] == ' ' || useCase1[i] == '.')
        {
            if (found)
```

```cpp
    delete[] synonyms;
}
void data_dictionary(char *&usecase1, char **dictionary, int num_words, int &co
{
    char *array = new char[3000];
    cout << "enter the data (at-least 3-4 sentences)\n";
    cin.getline(array, 3000);
    cin.ignore();
    char *n_array = new char[10];
    int k = 0;
    int len = strlen(array);
    while (k < len)
    {   int s = 0;

            while (array[k] != ' '&& k < len)
            {
                n_array[s] = array[k];
                k++;
                s++;
            }
        n_array[s] = '\0';

        for (int i = 0; i < num_words; i++)
        {   int a = 0;
            for (int j = 0; j < s; j++)
            {
                if (n_array[j] == dictionary[i][j])
                {
                    a++;
                }
            }
            if (a == s)
            {
                count++;
                int b;
                for (b = 0; b < s; b++)
                {
                    usecase1[b] = n_array[b];
                }
                usecase1[b] = ' ';
                usecase1 += b + 1; // move the pointer to the next position
                 break;

            }
        }
        k++;
    }
    usecase1--; // move the pointer back to the last space
    *usecase1 = '\0'; // add null terminator to the end of the string
    delete[] n_array;
}


void print( char *usecase1, int count)
{
    cout << "There are " << count << " matched words.\n";
    cout << "The matched words are: ";
    for (int i = 0; usecase1[i] != '\0'; i++)
    {
        if (usecase1[i] == ' ')
        {
            cout << endl; // print each matched word on a new line
        }
        else
        {
            cout << usecase1[i];
        }
    }
    cout << endl;
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```
37      char word[3000];
38      int word_length = 0;
39      for (int i = 0; input[i] != '\0'; i++)
40      {
41          if (input[i] == ' ' || input[i] == '.')
42          {
43              if (word_length > 0)
44              {
45                  word[word_length] = '\0';
46                  int index = find_word_index(dictionary, num_words, word);
47                  if (index == -1)
48                  {
49                      dictionary[num_words] = new char[word_length + 1];
50                      for (int j = 0; j < word_length; j++)
51                      {
52                          dictionary[num_words][j] = word[j];
53                      }
54                      dictionary[num_words][word_length] = '\0';
55                      num_words++;
56                  }
57                  word_length = 0;
58              }
59          }
60          else {
61              if (word_length < 3000 - 1)
62              {
63                  word[word_length] = input[i];
64                  word_length++;
65              }
66          }
67      }
68      if (word_length > 0)
69      {
70          word[word_length] = '\0';
71          int index = find_word_index(dictionary, num_words, word);
72          if (index == -1)
73          {
74              dictionary[num_words] = new char[word_length + 1];
75              for (int j = 0; j < word_length; j++)
76              {
77                  dictionary[num_words][j] = word[j];
78              }
79              dictionary[num_words][word_length] = '\0';
80              num_words++;
81          }
82      }
83 }
84
85 void print_dictionary(char** dictionary, int num_words)
86 {
87     cout << "Data dictionary:\n";
88     for (int i = 0; i < num_words; i++)
89     {
90         cout << dictionary[i] << endl;
91     }
92 }
93
94 void delete_dictionary(char** dictionary, int num_words)
95 {
96     for (int i = 0; i < num_words; i++)
97     {
98         delete[] dictionary[i];
99     }
100     delete[] dictionary;
101 }
102
103 void get_synonym(char***& synonyms, char** dictionary, int num_words, int& num_
```

```
40      char word[m_word];
41      int word_length = 0;
42      for (int i = 0; input[i] != '\0'; i++)
43      {
44          if (input[i] == ' ' || input[i] == '.')
45          {
46              if (word_length > 0)
47              {
48                  word[word_length] = '\0';
49                  int index = find_word_index(dictionary, num_words, word);
50                  if (index == -1)
51                  {
52                      dictionary[num_words] = new char[word_length + 1];
53                      int len = strlen(word);
54                      dictionary[num_words] = new char[len + 1];
55                      for (int i = 0; i < len; i++)
56                      {
57                          dictionary[num_words][i] = word[i];
58                      }
59                      dictionary[num_words][len] = '\0';
60                      num_words++;
61                  }
62                  word_length = 0;
63              }
64          }
65          else
66          {
67              if (word_length < m_word - 1)
68              {
69                  word[word_length] = input[i];
70                  word_length++;
71              }
72          }
73      }
74      if (word_length > 0)
75      {
76          word[word_length] = '\0';
77          int index = find_word_index(dictionary, num_words, word);
78          if (index == -1)
79          {
80              dictionary[num_words] = new char[word_length + 1];
81              for (int i = 0; i < word_length; i++)
82              {
83                  dictionary[num_words][i] = word[i];
84              }
85              dictionary[num_words][word_length] = '\0';
86              num_words++;
87          }
88      }
89 }
90
91 void print_dictionary(char **dictionary, int num_words)
92 {
93     cout << "Data dictionary:\n";
94     for (int i = 0; i < num_words; i++)
95     {
96         cout << dictionary[i] << endl;
97     }
98 }
99
100 void delete_dictionary(char **dictionary, int num_words)
101 {
102     for (int i = 0; i < num_words; i++)
103     {
104         delete[] dictionary[i];
105     }
106     delete[] dictionary;
107 }
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```
13 void get_input(char* input)
14 {
15     cout << "Please enter the data: ";
16     cin.getline(input, 3000);
17 }
18
19 int find_word_index(char** dictionary, int num_words, char* word)
20 {
21     for (int i = 0; i < num_words; i++)
22     {
23         if (dictionary[i] == word)
24         {
25             return i;
26         }
27         /* if (strcmp(dictionary[i], word) == 0)
28          {
29             return i;
30          }*/
31     }
32     return -1;
33 }
34
35 void tokenize(char* input, char** dictionary, int& num_words)
36 {
37     char word[3000];
38     int word_length = 0;
39     for (int i = 0; input[i] != '\0'; i++)
40     {
41         if (input[i] == ' ' || input[i] == '.')
42         {
43             if (word_length > 0)
44             {
45                 word[word_length] = '\0';
46                 int index = find_word_index(dictionary, num_words, word);
47                 if (index == -1)
48                 {
49                     dictionary[num_words] = new char[word_length + 1];
50                     for (int j = 0; j < word_length; j++)
51                     {
52                         dictionary[num_words][j] = word[j];
53                     }
54                     dictionary[num_words][word_length] = '\0';
55                     num_words++;
56                 }
57                 word_length = 0;
58             }
59         }
60         else {
61             if (word_length < 3000 - 1)
62             {
63                 word[word_length] = input[i];
64                 word_length++;
65             }
66         }
67     }
68     if (word_length > 0)
69     {
70         word[word_length] = '\0';
71         int index = find_word_index(dictionary, num_words, word);
72         if (index == -1)
73         {
74             dictionary[num_words] = new char[word_length + 1];
75             for (int j = 0; j < word_length; j++)
76             {
77                 dictionary[num_words][j] = word[j];
```

```
6 void get_input(char *input)
7 {
8     cout << "Please enter the data: ";
9     ifstream infile("input.txt");
10     string input;
11     getline(infile, input);
12     infile.close();
13
14 }
15
16 int find_word_index(char**& dictionary, int num_words, char* word)
17 {
18     for (int i = 0; i < num_words; i++)
19     {
20         bool match = true;
21         for (int j = 0; dictionary[i][j] != '\0' || word[j] != '\0'; j++)
22         {
23             if (dictionary[i][j] != word[j])
24             {
25                 match = false;
26                 break;
27             }
28         }
29         if (match && dictionary[i][0] != '\0' && word[0] != '\0')
30         {
31             return i;
32         }
33     }
34     return -1;
35 }
36
37 void tokenize(char *input, char **dictionary, int &num_words)
38 {
39     const int m_word = 100;
40     char word[m_word];
41     int word_length = 0;
42     for (int i = 0; input[i] != '\0'; i++)
43     {
44         if (input[i] == ' ' || input[i] == '.')
45         {
46             if (word_length > 0)
47             {
48                 word[word_length] = '\0';
49                 int index = find_word_index(dictionary, num_words, word);
50                 if (index == -1)
51                 {
52                     dictionary[num_words] = new char[word_length + 1];
53                     int len = strlen(word);
54                     dictionary[num_words] = new char[len + 1];
55                     for (int i = 0; i < len; i++)
56                     {
57                         dictionary[num_words][i] = word[i];
58                     }
59                     dictionary[num_words][len] = '\0';
60                     num_words++;
61                 }
62                 word_length = 0;
63             }
64         }
65         else
66         {
67             if (word_length < m_word - 1)
68             {
69                 word[word_length] = input[i];
70                 word_length++;
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```
145 {
146     cout << "Synonyms:\n";
147     for (int i = 0; i < num_words; i++)
148     {
149         cout << dictionary[i] << ": ";
150         for (int j = 0; j < num_synonyms; j++)
151         {
152             if (synonyms[i][j] != nullptr)
153             {
154                 cout << synonyms[i][j] << " ";
155             }
156
157         }
158         cout << endl;
159     }
160 }
161
162 void delete_synonyms(char*** synonyms, int* num_synonyms, int num_words)
163 {
164     for (int i = 0; i < num_words; i++)
165     {
166         for (int j = 0; j < num_synonyms[i]; j++)
167         {
168             delete[] synonyms[i][j];
169         }
170         delete[] synonyms[i];
171     }
172     delete[] synonyms;
173     delete[] num_synonyms;
174 }
175 void data_dictionary(char*& usecase1, char** dictionary, int num_words, int& co
176 {
177     char* array = new char[3000];
178     cout << "enter the data (at-least 3-4 sentences)\n";
179     cin.getline(array, 3000);
180     cin.ignore();
181     char* n_array = new char[10];
182     int k = 0;
183     int len = strlen(array);
184     while (k < len)
185     {
186         int s = 0;
187
188         while (array[k] != ' ' && k < len)
189         {
190             n_array[s] = array[k];
191             k++;
192             s++;
193         }
194         n_array[s] = '\0';
195
196         for (int i = 0; i < num_words; i++)
197         {
198             int a = 0;
199             for (int j = 0; j < s; j++)
200             {
201                 if (n_array[j] == dictionary[i][j])
202                 {
203                     a++;
204                 }
205             }
206             if (a == s)
207             {
208                 count++;
209                 int b;
210                 for (b = 0; b < s; b++)
211                 {
212                     usecase1[b] = n_array[b];
```

```
152 {
153     for (int i = 0; i < num_words; i++)
154     {
155         for (int j = 0; j < 10; j++)
156         {
157             if (synonyms[i][j] != nullptr)
158             {
159                 delete[] synonyms[i][j];
160             }
161         }
162         delete[] synonyms[i];
163     }
164     delete[] synonyms;
165 }
166 void data_dictionary(char *&usecase1, char **dictionary, int num_words, int &co
167 {
168     char *array = new char[3000];
169     cout << "enter the data (at-least 3-4 sentences)\n";
170     cin.getline(array, 3000);
171     cin.ignore();
172     char *n_array = new char[10];
173     int k = 0;
174     int len = strlen(array);
175     while (k < len)
176     {   int s = 0;
177
178         while (array[k] != ' '&& k < len)
179         {
180             n_array[s] = array[k];
181             k++;
182             s++;
183         }
184     n_array[s] = '\0';
185
186     for (int i = 0; i < num_words; i++)
187     {   int a = 0;
188         for (int j = 0; j < s; j++)
189         {
190             if (n_array[j] == dictionary[i][j])
191             {
192                 a++;
193             }
194         }
195             if (a == s)
196         {
197             count++;
198             int b;
199             for (b = 0; b < s; b++)
200             {
201                 usecase1[b] = n_array[b];
202             }
203             usecase1[b] = ' ';
204             usecase1 += b + 1; // move the pointer to the next position
205              break;
206
207         }
208     }
209     k++;
210     }
211     usecase1--; // move the pointer back to the last space
212     *usecase1 = '\0'; // add null terminator to the end of the string
213     delete[] n_array;
214 }
215
216
217 void print( char *usecase1, int count)
218 {
```

12:03 AM
4/14/2023

(1) WhatsA | report-view | Lab Manua | State Life I | The Clo | New Tab

jplag.github.io/JPlag/comparison/22L-7921.cpp/fatima_22L7999.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7921.cpp

Submission 2
fatima_22L7999.cpp

Match %
73.48

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7921.cpp\22L-7921.cpp (225 - 310)	fatima_22L7999.cpp\fatima_22L7999.cpp (233 - 316)	113
22L-7921.cpp\22L-7921.cpp (49 - 103)	fatima_22L7999.cpp\fatima_22L7999.cpp (54 - 109)	72
22L-7921.cpp\22L-7921.cpp (173 - 224)	fatima_22L7999.cpp\fatima_22L7999.cpp (164 - 213)	68
22L-7921.cpp\22L-7921.cpp (37 - 48)	fatima_22L7999.cpp\fatima_22L7999.cpp (40 - 51)	17
22L-7921.cpp\22L-7921.cpp (13 - 22)	fatima_22L7999.cpp\fatima_22L7999.cpp (6 - 19)	14
22L-7921.cpp\22L-7921.cpp (145 - 153)	fatima_22L7999.cpp\fatima_22L7999.cpp (152 - 158)	13
22L-7921.cpp\22L-	fatima_22L7999.cpp\fatima_22L7999.cpp	

```
23          if (dictionary[i] == word)
24          {
25              return i;
26          }
27          /* if (strcmp(dictionary[i], word) == 0)
28           {
29               return i;
30           }*/
31      }
32      return -1;
33 }
34
35 void tokenize(char* input, char** dictionary, int& num_words)
36 {
37     char word[3000];
38     int word_length = 0;
39     for (int i = 0; input[i] != '\0'; i++)
40     {
41         if (input[i] == ' ' || input[i] == '.')
42         {
43             if (word_length > 0)
44             {
45                 word[word_length] = '\0';
46                 int index = find_word_index(dictionary, num_words, word);
47                 if (index == -1)
48                 {
49                     dictionary[num_words] = new char[word_length + 1];
50                     for (int j = 0; j < word_length; j++)
51                     {
52                         dictionary[num_words][j] = word[j];
53                     }
54                     dictionary[num_words][word_length] = '\0';
55                     num_words++;
56                 }
57                 word_length = 0;
58             }
59         }
60         else {
61             if (word_length < 3000 - 1)
62             {
63                 word[word_length] = input[i];
64                 word_length++;
65             }
66         }
67     }
68     if (word_length > 0)
69     {
70         word[word_length] = '\0';
71         int index = find_word_index(dictionary, num_words, word);
72         if (index == -1)
73         {
74             dictionary[num_words] = new char[word_length + 1];
75             for (int j = 0; j < word_length; j++)
76             {
77                 dictionary[num_words][j] = word[j];
78             }
79             dictionary[num_words][word_length] = '\0';
80             num_words++;
81         }
82     }
83 }
84
85 void print_dictionary(char** dictionary, int num_words)
86 {
87     cout << "Data dictionary:\n";
88     for (int i = 0; i < num_words; i++)
```

```
29          if (match && dictionary[i][0] != '\0' && word[0] != '\0')
30          {
31              return i;
32          }
33      }
34      return -1;
35 }
36
37 void tokenize(char *input, char **dictionary, int &num_words)
38 {
39     const int m_word = 100;
40     char word[m_word];
41     int word_length = 0;
42     for (int i = 0; input[i] != '\0'; i++)
43     {
44         if (input[i] == ' ' || input[i] == '.')
45         {
46             if (word_length > 0)
47             {
48                 word[word_length] = '\0';
49                 int index = find_word_index(dictionary, num_words, word);
50                 if (index == -1)
51                 {
52                     dictionary[num_words] = new char[word_length + 1];
53                     int len = strlen(word);
54                     dictionary[num_words] = new char[len + 1];
55                     for (int i = 0; i < len; i++)
56                     {
57                         dictionary[num_words][i] = word[i];
58                     }
59                     dictionary[num_words][len] = '\0';
60                     num_words++;
61                 }
62                 word_length = 0;
63             }
64         }
65         else
66         {
67             if (word_length < m_word - 1)
68             {
69                 word[word_length] = input[i];
70                 word_length++;
71             }
72         }
73     }
74     if (word_length > 0)
75     {
76         word[word_length] = '\0';
77         int index = find_word_index(dictionary, num_words, word);
78         if (index == -1)
79         {
80             dictionary[num_words] = new char[word_length + 1];
81               for (int i = 0; i < word_length; i++)
82             {
83                 dictionary[num_words][i] = word[i];
84             }
85             dictionary[num_words][word_length] = '\0';
86             num_words++;
87         }
88     }
89 }
90
91 void print_dictionary(char **dictionary, int num_words)
92 {
93     cout << "Data dictionary:\n";
94     for (int i = 0; i < num_words; i++)
```

12:03 AM
4/14/2023

WhatsApp | report-view | Lab Manua | State Life I | The Cl | New Tab

jplag.github.io/JPlag/comparison/22L-7859_oopAss1.cpp/22L-6194.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7859_oopAss1.cpp

Submission 2
22L-6194.cpp

Match %
55.49

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (3 - 37)	22L-6194.cpp\22L-6194.cpp (5 - 44)	67
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (41 - 62)	22L-6194.cpp\22L-6194.cpp (47 - 84)	35
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (81 - 105)	22L-6194.cpp\22L-6194.cpp (115 - 139)	28
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (69 - 75)	22L-6194.cpp\22L-6194.cpp (98 - 105)	14

Files of 22L-7859_oopAss1.cpp

..2L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp

```cpp
1 #include <iostream>
2 using namespace std;

3 void tokenize(char data[], char**& DataDictionary, int& num_words) {
4     int s_index = 0;
5     bool flag;
6     for (int i = 0; i < strlen(data); i++) {
7         if (data[i] == ' ' || data[i] == '.') {
8             int length = i - s_index;
9             if (length > 0) {
10                char* word = new char[length + 1];
11                for (int j = 0; j < length; j++) {
12                    word[j] = data[s_index + j];
13                }
14                flag = false;
15                word[length] = '\0';
16                for (int j = 0; j < num_words; j++) {
17                    if (strcmp(word, DataDictionary[j]) == 0) {
18                        flag = true;
19                        break;
20                    }
21                }
22                if (!flag) {
23                    DataDictionary[num_words] = word;
24                    num_words++;
25                }
26                else {
27                    delete[] word;
28                }
29            }
30            s_index = i + 1;
31        }
32    }
33    for (int i = 0; i < num_words; i++) {
34        cout << DataDictionary[i] << endl;
35    }
36 }
37 void getSynonyms(char***& synonyms, char** DataDictionary, int num_words) {
```

```cpp
38    synonyms = new char** [num_words];
39    for (int i = 0; i < num_words; i++) {
40        synonyms[i] = NULL;
```

```cpp
41    }
42    for (int x = 0; x < num_words; x++) {
43        char* word = DataDictionary[x];
44        cout << "Do you want to store synonyms for " << word << "? (enter 'y' for yes
45        char choice;
46        cin >> choice;
47        if (choice == 'y') {
48            int count;
49            cout << "How many synonyms do you want to store? ";
50            cin >> count;
51            synonyms[x] = new char* [count];
52            for (int y = 1; y < count; y++) {
53                static char input[200];
54                cout << "Enter synonym " << y << " for " << word << ": ";
55                cin >> input;
```

Files of 22L-6194.cpp

22L-6194.cpp\22L-6194.cpp

```cpp
1 #include <iostream>
2 #include <cstring>
3 using namespace std;
4

5 void Tokenization(char input[], char** dataDictionary,int&numWords) {
6
7     int startIndex = 0;
8     for (int i = 0; i < strlen(input); i++) {
9         if (input[i] == ' ' || input[i] == '.') {
10            int length = i - startIndex;
11            if (length > 0) {
12                char* word = new char[length + 1];
13                for (int j = 0; j < length; j++) {
14                    word[j] = input[startIndex + j];
15                }
16                word[length] = '\0';
17                // Check for duplicates
18                bool found = false;
19                for (int j = 0; j < numWords; j++) {
20                    if (strcmp(word, dataDictionary[j]) == 0) {
21                        found = true;
22                        break;
23                    }
24                }
25
26                if (!found) {
27                    dataDictionary[numWords] = word;
28                    numWords++;
29                }
30                else {
31                    delete[] word;
32                }
33            }
34            startIndex = i + 1;
35        }
36    }
37
38
39    cout << "Data Dictionary:" << endl;
40    for (int i = 0; i < numWords; i++) {
41        cout << dataDictionary[i] << endl;
42    }
43 }
44 void getsynonyms(char***synonyms,char**dataDictionary,int&numWords) {
```

```cpp
45    for (int i = 0; i < numWords; i++) {
46        synonyms[i] = nullptr;
```

```cpp
47    }
48
49
50    for (int i = 0; i < numWords; i++) {
51        char* word = dataDictionary[i];
52
53
54        cout << "Do you want to store synonyms for " << word << "? (y/n): ";
55        char choice;
```

12:05 AM
4/14/2023

WhatsApp | report-view | Lab Manua | State Life I | The Cl | New Tab

jplag.github.io/JPlag/comparison/22L-7859_oopAss1.cpp/22L-6194.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7859_oopAss1.cpp

Submission 2
22L-6194.cpp

Match %
55.49

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (3 - 37)	22L-6194.cpp\22L-6194.cpp (5 - 44)	67
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (41 - 62)	22L-6194.cpp\22L-6194.cpp (47 - 84)	35
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (81 - 105)	22L-6194.cpp\22L-6194.cpp (115 - 139)	28
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (69 - 75)	22L-6194.cpp\22L-6194.cpp (98 - 105)	14

```
41      }
42      for (int x = 0; x < num_words; x++) {
43          char* word = DataDictionary[x];
44          cout << "Do you want to store synonyms for " << word << "? (enter 'y' for yes)
45          char choice;
46          cin >> choice;
47          if (choice == 'y') {
48              int count;
49              cout << "How many synonyms do you want to store? ";
50              cin >> count;
51              synonyms[x] = new char* [count];
52              for (int y = 1; y < count; y++) {
53                  static char input[200];
54                  cout << "Enter synonym " << y << " for " << word << ": ";
55                  cin >> input;
56                  synonyms[x][y] = new char[strlen(input) + 1];
57                  for (int z = 0; z < strlen(input); z++) {
58                      synonyms[x][y][z] = input[z];
59                  }
60                  synonyms[x][y][strlen(input)] = '\0';
61              }
62          }
63      }
64  }
65  void SearchSynonyms(char* UseCase1, char** dataDictionary, char*** synonyms, int num_w
66      const int w_len = 3000;
67      bool flag = false;
68      char word[w_len];
69      int s_index = 0, x = 0;
70      cout << "Matching words found:\n";
71      for (int i = 0; i <= strlen(UseCase1); i++) {
72          if (UseCase1[i] == ' ' || UseCase1[i] == '.') {
73              int length = i - s_index;
74               if (length > 0) {
75                  if (length >= w_len) {
76                      cout << "Error! maximum length exceeded\n";
77                  }
78                  for (int j = 0; j < length; j++) {
79                      word[j] = UseCase1[s_index + j];
80                  }
81                  word[length] = '\0';
82                  for (int j = 0; j < num_words; j++) {
83                      if (strcmp(word, dataDictionary[j]) == 0) {
84                          flag = true;
85                          break;
86                      }
87                  }
88                  if (flag) {
89                      cout << word << endl;
90                      x++;
91                  }
92
93              }
94              s_index = i + 1;
95          }
96      }
97
98      if (x == 0) {
99          cout << "No Matching words found\n";
100     }
101     else {
102         cout << "Matching words found: " << x << endl;
103     }
104 }
105 void main() {
```

```
47      }
48
49
50      for (int i = 0; i < numWords; i++) {
51          char* word = dataDictionary[i];
52
53
54          cout << "Do you want to store synonyms for " << word << "? (y/n): ";
55          char choice;
56          cin >> choice;
57
58          if (choice == 'y' || choice == 'Y') {
59
60              int count;
61              cout << "How many synonyms do you want to store? ";
62              cin >> count;
63
64              // Allocate memory for the synonyms at this index
65              synonyms[i] = new char* [count];
66
67
68              for (int j = 0; j < count; j++) {
69
70                  static char temp[100];
71
72                  cout << "Enter synonym #" << j + 1 << " for " << word << ": ";
73                  cin >> temp;
74
75                  // Allocate memory for the synonym at this index
76                  synonyms[i][j] = new char[strlen(temp) + 1];
77
78                  // Copy the data character by character
79                  for (int k = 0; k < strlen(temp); k++) {
80                      synonyms[i][j][k] = temp[k];
81                  }
82                  synonyms[i][j][strlen(temp)] = '\0';
83              }
84          }
85          else if (choice == 'n' || choice == 'N')
86          {
87              synonyms[i] = new char* [1];
88              synonyms[i][0] = new char[10];
89              synonyms[i][0][0] = '\0';
90          }
91      }
92  }
93  void SearchWord(char* UseCase1, char** dataDictionary, int numWords) {
94      const int WORD_LEN = 1000;
95      char word[WORD_LEN];
96
97      int startIndex = 0;
98      int count = 0;
99
100      cout << "Matched words:" << endl;
101
102      for (int i = 0; i <= strlen(UseCase1); i++) {
103          if (UseCase1[i] == ' ' || UseCase1[i] == '.') {
104              int length = i - startIndex;
105              if (length > 0) {
106                  if (length >=WORD_LEN) {
107                      cout << "Error: word length exceeds maximum length." << endl;
108                      return;
109                  }
110                  for (int j = 0; j < length; j++) {
111                      word[j] = UseCase1[startIndex + j];
112                  }
113                  word[length] = '\0';
```

12:05 AM
4/14/2023

WhatsApp | report-view | Lab Manua | State Life I | The Clo | New Tab
jplag.github.io/JPlag/comparison/22L-7859_oopAss1.cpp/22L-6194.cpp
Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7859_oopAss1.cpp

Submission 2
22L-6194.cpp

Match %
55.49

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (3 - 37)	22L-6194.cpp\22L-6194.cpp (5 - 44)	67
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (41 - 62)	22L-6194.cpp\22L-6194.cpp (47 - 84)	35
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (81 - 105)	22L-6194.cpp\22L-6194.cpp (115 - 139)	28
22L-7859_oopAss1.cpp\22L-7859_oopAss1.cpp (69 - 75)	22L-6194.cpp\22L-6194.cpp (98 - 105)	14

```cpp
                synonyms[x][y][2] = input[z];
            }
            synonyms[x][y][strlen(input)] = '\0';
        }
    }
}
void SearchSynonyms(char* UseCase1, char** dataDictionary, char*** synonyms, int num_w
    const int w_len = 3000;
    bool flag = false;
    char word[w_len];

    int s_index = 0, x = 0;
    cout << "Matching words found:\n";
    for (int i = 0; i <= strlen(UseCase1); i++) {
        if (UseCase1[i] == ' ' || UseCase1[i] == '.') {
            int length = i - s_index;
             if (length > 0) {
                if (length >= w_len) {
                    cout << "Error! maximum length exceeded\n";
                }
                for (int j = 0; j < length; j++) {
                    word[j] = UseCase1[s_index + j];
                }

                word[length] = '\0';
                for (int j = 0; j < num_words; j++) {
                    if (strcmp(word, dataDictionary[j]) == 0) {
                        flag = true;
                        break;
                    }
                }
                if (flag) {
                    cout << word << endl;
                    x++;
                }

            }
            s_index = i + 1;
        }
    }

    if (x == 0) {
        cout << "No Matching words found\n";
    }
    else {
        cout << "Matching words found: " << x << endl;
    }
}
void main() {
    char data[3000];
    int num_words = 0;
    char** DataDictionary = new char* [1000];
    char*** synonyms = new char** [num_words];
    cout << "Enter text (3-4 sentences) End each sentence with a fullstop: ";
    cin.getline(data, 3000);
    tokenize(data, DataDictionary, num_words);
    getSynonyms(synonyms, DataDictionary, num_words);
    char* UseCase1 = new char[3000];
    cout << "Enter text (end with fullstop): ";
    cin.ignore();
    cin.getline(UseCase1, 3000);
    SearchSynonyms(UseCase1, DataDictionary,synonyms, num_words);
}
```

```cpp
            bool found = false;
            for (int j = 0; j < numWords; j++) {
                if (strcmp(word, dataDictionary[j]) == 0) {
                    found = true;
                    break;
                }
            }
            if (found) {
                cout << word << endl;
                count++;
            }

        }
        startIndex = i + 1;
    }
}

if (count == 0) {
    cout << "No words found in data dictionary." << endl;
}
else {
    cout << "Total matched words: " << count << endl;
}
}
void replaceSynonyms(char*** synonyms, char** dataDictionary, int wordCount)
{
    bool isPresent = true;
    char* useCase1 = new char[2500];
    char* temp = new char[2500];
    int i = 0,j=0,forTemp=0;
    cout << "enter sentence(s) to replace synonyms: ";
    cin.getline(useCase1, 2500);
    while (useCase1[i] != '\0')
    {
        if (i == 0 || useCase1[i] == ' ' || useCase1[i] == '.')
        {
            if (i != 0)
                i++;
            int temp1 = i;
            j = 0;
            while (j < wordCount)
            {
                int characters = 0;
                temp1 = i;
                while (useCase1[temp1] != ' ' && useCase1[temp1] != '.' &
                {

                    if (useCase1[temp1++] == dataDictionary[j][charac
                    {
                        isPresent = true;
                    }
                    else
                    {
                        isPresent = false;
                        break;
                    }
                }
                if (isPresent)
                {
                    if (synonyms[j][0][0] == '\0')
                        isPresent = false;
                    break;
                }
                j++;
            }

            if (isPresent)
            {
                int h = 0;
```

12:05 AM
4/14/2023