WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

Files of 22L-7941.cpp

22L-7941.cpp\22L-7941.cpp

```cpp
#include <iostream>
#include <fstream>
#include <cstring>
using namespace std;

//Task-1
void tokenize(char * input_data, char ** &data_dictionary, int &num_tokens) {
    int x = 0;
    bool flag = false;
     data_dictionary = new char * [20];
     for (int i = 0; i < 20; i++) {
         data_dictionary[i] = new char[20];
     }
     for (int i = 0; i <= 3000; i++) {
         if (input_data[i] == ' ' || input_data[i] == '\0') {
             if (flag) {
                 data_dictionary[num_tokens][x] = '\0';
                 num_tokens++;
                 x = 0;
                 flag = false;
             }
         }
         else {
             if (!flag) {
                 flag = true;
                 char **temp = new char*[num_tokens + 1];
                 for (int j = 0; j < num_tokens; j++) {
                     temp[j] = data_dictionary[j];
                 }
                 temp[num_tokens] = new char[20];
                 data_dictionary = temp;
             }
             data_dictionary[num_tokens][x] = input_data[i];
             x++;
         }
     }
}

//1
void print_data_dictionary(char ** data_dictionary, int numTokens) {
for (int i = 0; i < numTokens; i++) {
        cout << data_dictionary[i] << endl;
    }
}

//1
void deallocate_data_dictionary(char ** tokens, char *input, int numTokens) {
    for (int i = 0; i < numTokens; i++) {
        delete[] tokens[i];
    }
    delete[] tokens;
    delete[] input;
}

//2
void get_synonyms(char ** data_dictionary, int num_tokens, char ***&synonyms) {
```

Files of 22L_7852.cpp

22L_7852.cpp\22L_7852.cpp

```cpp
#include <iostream>
#include <fstream>
#include <string>
using namespace std;

void input(char* &arr1)
{
    cout << "-------------------------------------------------" << endl;

    cout << "\t>>>>> WELCOME TO WORDS WORLD <<<<<\n\n";

    ifstream read;
    read.open("Text.txt");
    arr1 = new char[3000];

    read.getline(arr1, 3000);

    cout << "Enter the Data (Atleast 3-4 sentences) :" << endl;
    cout << arr1 << endl;

    read.close();
}
bool checkunique(char *arr,char **data_dic,const int &row)
{
    bool flag = false;
    for (int i = 0; i < row; i++)
    {
        if (arr[0] == data_dic[i][0])
        {
            flag = true;

            for (int j = 1; data_dic[i][j] != '\0'; j++)
            {
                if (arr[j] != data_dic[i][j])
                {
                    flag = false;
                    break;
                }
            }
        }
        if (flag)
        {
            return false;
        }
    }

    return true;
}
void tokenization(char* const& input_arr, char**& data_dic)
{
    int lenght = strlen(input_arr);

    data_dic = new char* [lenght];

    int row = 0;
    data_dic[row] = new char[lenght];          // memory allocation
```

1:20 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

```cpp
87 void deallocate_synonms(char *** synonyms, int num_tokens) {
88     for (int i = 0; i < num_tokens; i++) {
89         for (int j = 0; j < 10; j++) {
90             if (synonyms[i][j] != nullptr) {
91                 delete[] synonyms[i][j];
92             }
93         }
94         delete[] synonyms[i];
95     }
96     delete[] synonyms;
97 }
98
99 //3
100 void search_data(const char* use_case1, char ** data_dictionary) {
101     char* token = strtok(use_case1, " ");
102     int count = 0;
103     while (token != NULL) {
104         for (int i = 0; i < 20; i++) {
105             if (strcmp(data_dictionary[i], token) == 0) {
106                 cout << data_dictionary[i] << " ";
107                 count++;
108                 break;
109             }
110         }
111         token = strtok(NULL, " ");
112     }
113     cout << endl;
114     cout << count << " words matched." << endl;
115 }
116
117 int main() {
118     //Task-1
119     char * input_data;
120     char ** data_dictionary;
121     int num_tokens = 0;
122     int n = 3000;
123     input_data = new char[n];
124     ifstream inputFile("data.txt");
125     inputFile.getline(input_data, 3000);
126     tokenize(input_data, data_dictionary, num_tokens);
127     print_data_dictionary(data_dictionary, num_tokens);
128     //deallocate_data_dictionary(data_dictionary, input_data, num_tokens);
129
130     //Task-2
131     char *** synonyms;
132     synonyms = new char ** [num_tokens];
133     for (int i = 0; i < num_tokens; i++) {
134         synonyms[i] = new char * [10];
135         for (int j = 0; j < 10; j++) {
136             synonyms[i][j] = nullptr;
137         }
138     }
139     get_synonyms(data_dictionary, num_tokens, synonyms);
140     print_synonyms(synonyms, data_dictionary, num_tokens);
141     //deallocate_synonms(synonyms, num_tokens);
142
143     //Task-3
144     char * use_case1 = new char[3000];
145     cout << "Enter some sentences to search data in the data dictionary: ";
146     cin.getline(use_case1, 3000);
147     search_data(use_case1, data_dictionary);
148
149     //Task-4
150 }
151
```

```cpp
367     delete[] arr2;
368     arr2 = NULL;
369 }
370 void releasesynonyms(char***& synonym, const int& unique_words)
371 {
372     for (int i = 0; i < unique_words; i++)
373     {
374             for (int j = 0; j < unique_words; j++)
375             {
376                     if (synonym[i][j] != nullptr)
377                     {
378                             delete[] synonym[i][j];
379                     }
380             }
381             delete[] synonym[i];
382     }
383     delete[] synonym;
384     synonym = NULL;
385 }
386 void releaseusecase(char* &usecase1)
387 {
388     delete[] usecase1;
389     usecase1 = NULL;
390 }
391
392
393 int main()
394 {
395     char* input_arr = NULL;
396     char** data_dic = NULL;
397
398
399     //1. Tokenization
400     input(input_arr);
401     tokenization(input_arr, data_dic);
402     output(data_dic);
403
404     int unique_words=sizeofuniquewords(data_dic);
405
406
407     //2. Synonyms
408     char*** synonym = NULL;
409     synonymsinsert(data_dic, synonym,unique_words);
410
411
412     //3. Similar Words in data dictionary
413     char* usecase1 = NULL;
414     searchsimilarwords(data_dic, usecase1);
415
416
417     //4. Replace words with synonyms
418     replacewords(usecase1, data_dic, synonym, unique_words);
419     cout << usecase1 << endl;
420
421     cout << "-----------------------------------------------" << endl;
422
423     // 5. Release all the resources
424     releasedatadictionary(input_arr, data_dic);
425     releasesynonyms(synonym, unique_words);
426     releaseusecase(usecase1);
427
428
429     return 0;
430 }
```

1:20 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

```
90              if (synonyms[i][j] != nullptr) {
91                  delete[] synonyms[i][j];
92              }
93          }
94          delete[] synonyms[i];
95      }
96      delete[] synonyms;
97 }
98
99 //3
100 void search_data(const char* use_case1, char ** data_dictionary) {
101     char* token = strtok(use_case1, " ");
102     int count = 0;
103     while (token != NULL) {
104         for (int i = 0; i < 20; i++) {
105             if (strcmp(data_dictionary[i], token) == 0) {
106                 cout << data_dictionary[i] << " ";
107                 count++;
108                 break;
109             }
110         }
111         token = strtok(NULL, " ");
112     }
113     cout << endl;
114     cout << count << " words matched." << endl;
115 }
116
117 int main() {
118     //Task-1
119     char * input_data;
120     char ** data_dictionary;
121     int num_tokens = 0;
122     int n = 3000;
123     input_data = new char[n];
124     ifstream inputFile("data.txt");
125     inputFile.getline(input_data, 3000);
126     tokenize(input_data, data_dictionary, num_tokens);
127     print_data_dictionary(data_dictionary, num_tokens);
128     //deallocate_data_dictionary(data_dictionary, input_data, num_tokens);
129
130     //Task-2
131     char *** synonyms;
132     synonyms = new char ** [num_tokens];
133     for (int i = 0; i < num_tokens; i++) {
134         synonyms[i] = new char * [10];
135         for (int j = 0; j < 10; j++) {
136             synonyms[i][j] = nullptr;
137         }
138     }
139     get_synonyms(data_dictionary, num_tokens, synonyms);
140     print_synonyms(synonyms, data_dictionary, num_tokens);
141     //deallocate_synonms(synonyms, num_tokens);
142
143     //Task-3
144     char * use_case1 = new char[3000];
145     cout << "Enter some sentences to search data in the data dictionary: ";
146     cin.getline(use_case1, 3000);
147     search_data(use_case1, data_dictionary);
148
149     //Task-4
150 }
151
```

```
115     synonym = new char** [unique_words];
116
117     for (int i = 0; i < unique_words; ++i)
118     {
119             synonym[i] = new char* [unique_words];
120             for (int j = 0; j < unique_words; ++j)
121             {
122                     synonym[i][j] = nullptr;
123             }
124     }
125
126     cout << "\t>>>>> 2. INSERT SYNONYMS <<<<<" << endl << endl;
127
128     for (int i = 0; i < unique_words; i++)
129     {
130             char choice;
131             cout << "Synonyms for [" << arr2[i] << "] ? ( Yes or No )";
132             cin >> choice;
133
134             if (choice == 'y')
135             {
136                     int count;
137                     cout << "No. of synonyms to store" << " for [" << arr2[i] << "] "
138                     cin >> count;
139
140                     for (int j = 0; j < count; j++)
141                     {
142                             char temp[100];                 // temporary static array
143                             cout << "Enter synonym #" << j + 1 << ": ";
144                             cin >> temp;
145
146                             int length = strlen(temp);
147                             synonym[i][j] = new char[length + 1];
148                             for (int k = 0; k < length; k++)
149                             {
150                                     synonym[i][j][k] = temp[k];
151                             }
152                             synonym[i][j][length] = '\0';
153                     }
154             }
155     }
156     cout << "\n-----------------------------------------------------" << endl;
157
158     cout << "\t>>>>> SYNONYMS <<<<<" << endl << endl;
159
160     for (int i = 0; i < unique_words; i++)
161     {
162             int no = 1;
163             if (synonym[i][0] != nullptr)
164             {
165                     cout <<"->"<< arr2[i] << endl;
166             }
167             for (int j = 0; j < unique_words; j++)
168             {
169                     if (synonym[i][j] != nullptr)
170                     {
171                             cout <<"    "<< no++ << ". " << synonym[i][j] << endl;
172                     }
173             }
174     }
175 }
176 void searchsimilarwords(char* const* const& arr2, char*& usecase)
177 {
178     usecase = new char[3000];
179
180     cout << "-----------------------------------------------------" << endl;
181     cout << "\t>>>>> INPUT <<<<<" << endl << endl;
```

1:20 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

```cpp
    for (int i = 0; i < num_tokens; i++) {
        cout << "Do you want to store synonyms for " << data_dictionary[i] << "? (y/n)
        char option;
        cin >> option;
        if (option == 'y') {
            cout << "Enter number of synonyms you want to store? ";
            int num_synonyms;
            cin >> num_synonyms;
            for (int j = 0; j < num_synonyms; j++) {
                cout << "Enter synonym-" << (j + 1) << ": ";
                char temp[100];

                cin >> temp;
                synonyms[i][j] = new char[strlen(temp) + 1];
                strcpy(synonyms[i][j], temp);
            }
        }
    }
}

//2
void print_synonyms(char *** synonyms, char ** data_dictionary, int num_tokens) {
 for (int i = 0; i < num_tokens; i++) {
        cout << data_dictionary[i] << endl;
        for (int j = 0; j < 10 && synonyms[i][j] != nullptr; j++) {
            cout << "  Synonym " << (j + 1) << ": " << synonyms[i][j] << endl;
        }
    }
}

//2
void deallocate_synonms(char *** synonyms, int num_tokens) {
    for (int i = 0; i < num_tokens; i++) {
        for (int j = 0; j < 10; j++) {
            if (synonyms[i][j] != nullptr) {
                delete[] synonyms[i][j];
            }
        }
        delete[] synonyms[i];
    }
    delete[] synonyms;
}

//3
void search_data(const char* use_case1, char ** data_dictionary) {
    char* token = strtok(use_case1, " ");
    int count = 0;

    while (token != NULL) {
        for (int i = 0; i < 20; i++) {
            if (strcmp(data_dictionary[i], token) == 0) {
                cout << data_dictionary[i] << " ";
                count++;
                break;
            }
        }

        token = strtok(NULL, " ");
    }
    cout << endl;
    cout << count << " words matched." << endl;
}

int main() {
    //Task-1
    char * input_data;
    char ** data_dictionary;
```

```cpp
    for (int i = 0; i < unique_words; i++)
    {
        char choice;
        cout << "Synonyms for [" << arr2[i] << "] ? ( Yes or No )";
        cin >> choice;

        if (choice == 'y')
        {
            int count;
            cout << "No. of synonyms to store" << " for [" << arr2[i] << "] ?
            cin >> count;

            for (int j = 0; j < count; j++)
            {
                char temp[100];             // temporary static array

                cout << "Enter synonym #" << j + 1 << ": ";
                cin >> temp;

                int length = strlen(temp);
                synonym[i][j] = new char[length + 1];
                for (int k = 0; k < length; k++)
                {
                    synonym[i][j][k] = temp[k];
                }
                synonym[i][j][length] = '\0';
            }
        }
    }
    cout << "\n-----------------------------------------------------" << endl;

    cout << "\t>>>>> SYNONYMS <<<<<" << endl << endl;

    for (int i = 0; i < unique_words; i++)
    {
        int no = 1;
        if (synonym[i][0] != nullptr)
        {
            cout <<"->"<< arr2[i] << endl;
        }
        for (int j = 0; j < unique_words; j++)
        {
            if (synonym[i][j] != nullptr)
            {
                cout <<"    "<< no++ << ". " << synonym[i][j] << endl;
            }
        }
    }
}
void searchsimilarwords(char* const* const& arr2, char*& usecase)
{
    usecase = new char[3000];

    cout << "-----------------------------------------------------" << endl;
    cout << "\t>>>>> INPUT <<<<<" << endl << endl;
    cin.ignore();
    cout << "Enter the Data to check similar words :" << endl;
    cin.getline(usecase, 3000);


    bool flag;
    int l = 1;

    cout << "-----------------------------------------------------" << endl;
    cout << "\t>>>>> 3. SIMILAR WORDS <<<<<" << endl << endl;

    for (int k = 0; k < strlen(usecase); ++k)
    {
        for (int i = 0; arr2[i] != nullptr; i++)
        {
```

1:20 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

```cpp
void print_synonyms(char *** synonyms, char ** data_dictionary, int num_tokens) {
 for (int i = 0; i < num_tokens; i++) {
        cout << data_dictionary[i] << endl;
        for (int j = 0; j < 10 && synonyms[i][j] != nullptr; j++) {
            cout << "  Synonym " << (j + 1) << ": " << synonyms[i][j] << endl;
        }
    }
}

//2
void deallocate_synonms(char *** synonyms, int num_tokens) {
    for (int i = 0; i < num_tokens; i++) {
        for (int j = 0; j < 10; j++) {
            if (synonyms[i][j] != nullptr) {
                delete[] synonyms[i][j];
            }
        }
        delete[] synonyms[i];
    }
    delete[] synonyms;
}

//3
void search_data(const char* use_case1, char ** data_dictionary) {
    char* token = strtok(use_case1, " ");
    int count = 0;

    while (token != NULL) {
        for (int i = 0; i < 20; i++) {
            if (strcmp(data_dictionary[i], token) == 0) {
                cout << data_dictionary[i] << " ";
                count++;
                break;
            }
        }

        token = strtok(NULL, " ");
    }
    cout << endl;
    cout << count << " words matched." << endl;
}

int main() {
    //Task-1
    char * input_data;
    char ** data_dictionary;
    int num_tokens = 0;
    int n = 3000;
    input_data = new char[n];
    ifstream inputFile("data.txt");
    inputFile.getline(input_data, 3000);
    tokenize(input_data, data_dictionary, num_tokens);
    print_data_dictionary(data_dictionary, num_tokens);
    //deallocate_data_dictionary(data_dictionary, input_data, num_tokens);

    //Task-2
    char *** synonyms;

    synonyms = new char ** [num_tokens];
    for (int i = 0; i < num_tokens; i++) {
        synonyms[i] = new char * [10];
        for (int j = 0; j < 10; j++) {
            synonyms[i][j] = nullptr;
        }
    }

    get_synonyms(data_dictionary, num_tokens, synonyms);
    print_synonyms(synonyms, data_dictionary, num_tokens);
```

```cpp
{
    cout << "-----------------------------------------------------" << endl;

    cout << "\t>>>>> 1. DATA DICTIONARY <<<<<" << endl << endl;

    for (int i = 0; arr2[i] != nullptr; i++)
    {
            for (int j = 0; arr2[i][j] != '\0'; j++)
            {
                    cout << arr2[i][j];
            }
            cout << endl;
    }
    cout << endl;

    cout << "-----------------------------------------------------" << endl;
}
int sizeofuniquewords(char* const* const& arr2)
{
    int counter = 0;
    for (int i = 0; arr2[i] != nullptr; i++)
    {
            counter++;
    }
    return counter;
}
void synonymsinsert(char* const* const& arr2, char***& synonym, const int& unique_wor
{

    synonym = new char** [unique_words];

    for (int i = 0; i < unique_words; ++i)
    {
            synonym[i] = new char* [unique_words];
            for (int j = 0; j < unique_words; ++j)
            {
                    synonym[i][j] = nullptr;
            }
    }

    cout << "\t>>>>> 2. INSERT SYNONYMS <<<<<" << endl << endl;

    for (int i = 0; i < unique_words; i++)
    {
            char choice;
            cout << "Synonyms for [" << arr2[i] << "] ? ( Yes or No )";
            cin >> choice;

            if (choice == 'y')
            {
                    int count;
                    cout << "No. of synonyms to store" << " for [" << arr2[i] << "] ?
                    cin >> count;

                    for (int j = 0; j < count; j++)
                    {
                            char temp[100];                // temporary static array

                            cout << "Enter synonym #" << j + 1 << ": ";
                            cin >> temp;

                            int length = strlen(temp);
                            synonym[i][j] = new char[length + 1];
                            for (int k = 0; k < length; k++)
                            {
                                    synonym[i][j][k] = temp[k];
                            }
```

1:20 PM
4/14/2023

WhatsA report-v Lab Mar Downlo BDS - 4 New Tal Convert
jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

```
            if (synonyms[i][j] != nullptr) {
                delete[] synonyms[i][j];
            }
        }
        delete[] synonyms[i];
    }
    delete[] synonyms;
}

//3
void search_data(const char* use_case1, char ** data_dictionary) {
    char* token = strtok(use_case1, " ");
    int count = 0;

    while (token != NULL) {
        for (int i = 0; i < 20; i++) {
            if (strcmp(data_dictionary[i], token) == 0) {
                cout << data_dictionary[i] << " ";
                count++;
                break;
            }
        }

        token = strtok(NULL, " ");
    }
    cout << endl;
    cout << count << " words matched." << endl;
}

int main() {
    //Task-1
    char * input_data;
    char ** data_dictionary;
    int num_tokens = 0;
    int n = 3000;
    input_data = new char[n];
    ifstream inputFile("data.txt");
    inputFile.getline(input_data, 3000);
    tokenize(input_data, data_dictionary, num_tokens);
    print_data_dictionary(data_dictionary, num_tokens);
    //deallocate_data_dictionary(data_dictionary, input_data, num_tokens);

    //Task-2
    char *** synonyms;

    synonyms = new char ** [num_tokens];
    for (int i = 0; i < num_tokens; i++) {
        synonyms[i] = new char * [10];
        for (int j = 0; j < 10; j++) {
            synonyms[i][j] = nullptr;
        }
    }

    get_synonyms(data_dictionary, num_tokens, synonyms);
    print_synonyms(synonyms, data_dictionary, num_tokens);
    //deallocate_synonms(synonyms, num_tokens);

    //Task-3
    char * use_case1 = new char[3000];
    cout << "Enter some sentences to search data in the data dictionary: ";
    cin.getline(use_case1, 3000);
    search_data(use_case1, data_dictionary);

    //Task-4
}
```

```
                                {
                                        for (int q = 0; q < unique_count; q++)
                                        {
                                                if (synonym[p][q] != nullptr && i
                                                {
                                                        cout <<l++<< ". WORD :" <
                                                        cout << "   SYNONYM :" <<

                                                        replacesynonym(usecase, n

                                                        break;
                                                }
                                        }
                                }
                        }
                }
        }
        while (usecase[k] != ' ')
        {
                k++;
                if (k == strlen(usecase))
                {
                        break;
                }
        }
    }
}
void releasedatadictionary(char*& arr1, char**& arr2)
{
    delete[] arr1;
    arr1 = NULL;

    for (int i = 0; arr2[i] != nullptr; i++)
    {
            delete[] arr2[i];
    }
    delete[] arr2;
    arr2 = NULL;
}
void releasesynonyms(char***& synonym, const int& unique_words)
{
    for (int i = 0; i < unique_words; i++)
    {
            for (int j = 0; j < unique_words; j++)
            {
                    if (synonym[i][j] != nullptr)
                    {
                            delete[] synonym[i][j];
                    }
            }
            delete[] synonym[i];
    }
    delete[] synonym;

    synonym = NULL;
}
void releaseusecase(char* &usecase1)
{
    delete[] usecase1;
    usecase1 = NULL;
}


int main()
{
    char* input_arr = NULL;
    char** data_dic = NULL;
```

1:20 PM
4/14/2023

WhatsA | report- | Lab Ma | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/22L-7941.cpp/22L_7852.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22L-7941.cpp

Submission 2
22L_7852.cpp

Match %
22.86

Submission 1 File 1	Submission 2 File 2	Tokens
22L-7941.cpp\22L-7941.cpp (87 - 96)	22L_7852.cpp\22L_7852.cpp (370 - 383)	20
22L-7941.cpp\22L-7941.cpp (132 - 138)	22L_7852.cpp\22L_7852.cpp (115 - 124)	19
22L-7941.cpp\22L-7941.cpp (57 - 67)	22L_7852.cpp\22L_7852.cpp (128 - 142)	15
22L-7941.cpp\22L-7941.cpp (77 - 84)	22L_7852.cpp\22L_7852.cpp (87 - 103)	14
22L-7941.cpp\22L-7941.cpp (103 - 110)	22L_7852.cpp\22L_7852.cpp (331 - 343)	12

```
            if (synonyms[i][j] != nullptr) {
                delete[] synonyms[i][j];
            }
        }
        delete[] synonyms[i];
    }
    delete[] synonyms;
}

//3
void search_data(const char* use_case1, char ** data_dictionary) {
    char* token = strtok(use_case1, " ");
    int count = 0;

    while (token != NULL) {
        for (int i = 0; i < 20; i++) {
            if (strcmp(data_dictionary[i], token) == 0) {
                cout << data_dictionary[i] << " ";
                count++;
                break;
            }
        }

        token = strtok(NULL, " ");
    }
    cout << endl;
    cout << count << " words matched." << endl;
}

int main() {
    //Task-1
    char * input_data;
    char ** data_dictionary;
    int num_tokens = 0;
    int n = 3000;
    input_data = new char[n];
    ifstream inputFile("data.txt");
    inputFile.getline(input_data, 3000);
    tokenize(input_data, data_dictionary, num_tokens);
    print_data_dictionary(data_dictionary, num_tokens);
    //deallocate_data_dictionary(data_dictionary, input_data, num_tokens);

    //Task-2
    char *** synonyms;

    synonyms = new char ** [num_tokens];
    for (int i = 0; i < num_tokens; i++) {
        synonyms[i] = new char * [10];
        for (int j = 0; j < 10; j++) {
            synonyms[i][j] = nullptr;
        }
    }

    get_synonyms(data_dictionary, num_tokens, synonyms);
    print_synonyms(synonyms, data_dictionary, num_tokens);
    //deallocate_synonms(synonyms, num_tokens);

    //Task-3
    char * use_case1 = new char[3000];
    cout << "Enter some sentences to search data in the data dictionary: ";
    cin.getline(use_case1, 3000);
    search_data(use_case1, data_dictionary);

    //Task-4
}
```

```
if (arr2[a][j] != usecase[c])
{
        flag = false;
        break;
}
c++;

g == true)

for (int p = a; p < unique_count; p++)

{
        for (int q = 0; q < unique_count; q++)
        {
                if (synonym[p][q] != nullptr && i==p)
                {
                        cout <<l++<< ". WORD :" << arr2[i] << endl;
                        cout << "   SYNONYM :" << synonym[p][q] << endl << endl;

                        replacesynonym(usecase, arr2[i], synonym[p][q]);

                        break;
                }
        }

}


')

(usecase))


rr1, char++& arr2)


ptr; i++)


ym, const int& unique_words)

s; i++)

que_words; j++)

j] != nullptr)

] synonym[i][j];


)
```

1:20 PM
4/14/2023