jplag.github.io/JPlag/comparison/22I%207963.cpp/assignment%201%2022I-7906.cpp

JPlag Comparison

back

Submission 1
22I 7963.cpp

Submission 2
assignment 1 22I-7906.cpp

Match %
31.29

Submission 1 File 1	Submission 2 File 2	Tokens
22I 7963.cpp\22I 7963.cpp (145 - 169)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (49 - 73)	41
22I 7963.cpp\22I 7963.cpp (117 - 130)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (12 - 25)	18
22I 7963.cpp\22I 7963.cpp (55 - 81)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (89 - 96)	15
22I 7963.cpp\22I 7963.cpp (131 - 145)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (38 - 49)	13

Files of 22I 7963.cpp

22I 7963.cpp\22I 7963.cpp

```cpp
#include <iostream>
#include<string.h>
using namespace std;

void replace(char***sym,char**data_dict,char useCase1)
{
}
void token(char**& datadic, char*& data, int words)
{
    int k = 0;

    for (int i = 0; i < words; i++)
    {
        int count = 0;

            while (data[k] != ' ' && data[k] != '\0')
            {

                count++;

                k++;
            }
            datadic[i] = new char[count];

            datadic[i][count] = '\0';
            k++;

    }

    k = 0;
    for (int i = 0; i < words; i++)
    {
            int j = 0;
            while (  data[k] != '\0')
            {
                if (data[k] == ' ')
                {
                    k++; break;
                }

                datadic[i][j] = data[k];

                j++;
                k++;

            }
    }

}


void synonym(char*** &syn, char **data_dict, int data_count)
{

    syn = new char** [data_count];     //words
    for (int i = 0; i < data_count; i++)
```

Files of assignment 1 22I-7906.cpp

..1 22I-7906.cpp\assignment 1 22I-7906.cpp

```cpp
#include <iostream>
#include<fstream>
using namespace std;
char choice;
int synonym_count;
char temp[1000];
int ft = 0;
int t = 0;


bool SearchUnique(char** data_dict, int data_count, char* word,int &f_index )
{
    for (int i = 0; i < data_count; i++)
    {
        int j = 0;
        while (data_dict[i][j] != '\0' && word[j] != '\0')
        {
            if (data_dict[i][j] != word[j])
            {
                break;
            }
            j++;
        }
        if (data_dict[i][j] == '\0' && word[j] == '\0')
        {
            f_index = i;
            return true;
        }
    }
    return false;
}
bool checkSynonym(char*** synonym, char* word, int data_count,int f_index)
{
    for (int i = 0; i < data_count && f_index!=-1; i++)
    {
        if (synonym[f_index] != nullptr)
        {
            return true;
        }
    }
    return false;
}
int main()
{
    char text[3000];
    cout << "Enter data\n ";
    cin.getline(text, 3000);
    char** data_dict = new char* [3000];

    int data_count = 0, start = 0,f_index=-1;

    for (int i = 0; text[i] != '\0'; i++)
    {
        if (text[i] == ' ' || text[i] == '.')
        {
```

1:18 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Convert

jplag.github.io/JPlag/comparison/22I%207963.cpp/assignment%201%2022I-7906.cpp

Photos - Google Ph... | YouTube | Facebook | WhatsApp | Classes | Temp Mail - Dispos... | LESCO - Customer... | Bill Payment

JPlag Comparison

back

Submission 1
22I 7963.cpp

Submission 2
assignment 1 22I-7906.cpp

Match %
31.29

Submission 1 File 1	Submission 2 File 2	Tokens
22I 7963.cpp\22I 7963.cpp (145 - 169)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (49 - 73)	41
22I 7963.cpp\22I 7963.cpp (117 - 130)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (12 - 25)	18
22I 7963.cpp\22I 7963.cpp (55 - 61)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (89 - 96)	15
22I 7963.cpp\22I 7963.cpp (131 - 145)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (38 - 49)	13

```cpp
145     int words = 0, tracker = 0;

146     for (int i = 0; input[i] != '\0'; i++)
147     {
148             if (input[i] == ' ' || input[i] == '.')
149             {
150                     char* data = new char[(i - tracker) + 1];
151                     int j = 0;
152                     for (int k = tracker; k < i; k++)
153                     {
154                             data[j] = input[k];
155                             j++;
156                     }
157                     data[j] = '\0';
158
159                     if (!SearchUnique(datadic, words, data))
160                     {
161                             int len = strlen(data);
162                             datadic[words] = new char[len + 1];
163                             for (int k = 0; k < len; k++)
164                             {
165                                     datadic[words][k] = data[k];
166                             }
167                             datadic[words][len] = '\0';
168                             words++;
169                     }
170             delete[] data;
171                     tracker = i + 1;
172
173             }
174     }
175     for (int i = 0 ; i <words; i++)
176     {
177             cout << datadic[i] << "\n";
178     }
179
180     bool flag=false;
181     int track = 0;
182     int     lenght = 0;
183     int     y = 0;
184     int x = 0;
185     int samewords = 0;
186
187     char* useCase1 = new char[3000];
188
189     cout << "ENTER SENTENCE FOR USECASE !\n ";
190     cin.getline(useCase1, 3000);
191
192     while (useCase1[track] != '\0')
193     {   y = track;
194             x = 0;
195             lenght = 0;
196
197             while (useCase1[track] != ' ' && useCase1[track] != '\0' )
198             {
199                     lenght++;    track++;
200             }
201             for (int j = 0; j < words; j++) //check in datadic
202             {
203
204                     if (lenght == strlen(datadic[j]))
205                     {
206                             track = y;
207                             while (datadic[j][x] != '\0')
208                             {
209                                     if (datadic[j][x] == useCase1[track])
210                                     {
211                                             flag = true;
212
```

```cpp
49      int data_count = 0, start = 0,f_index=-1;

50      for (int i = 0; text[i] != '\0'; i++)
51      {
52          if (text[i] == ' ' || text[i] == '.')
53          {
54              char* word = new char[(i - start) + 1];
55              int j = 0;
56              for (int k = start; k < i; k++)
57              {
58                  word[j] = text[k];
59                  j++;
60              }
61              word[j] = '\0';
62
63              if (!SearchUnique(data_dict, data_count, word,f_index))
64              {
65                  int word_length = strlen(word);
66                  data_dict[data_count] = new char[word_length + 1];
67                  for (int k = 0; k < word_length; k++)
68                  {
69                      data_dict[data_count][k] = word[k];
70                  }
71                  data_dict[data_count][word_length] = '\0';
72                  data_count++;
73              }
74
75              start = i + 1;
76              delete[] word;
77          }
78      }
79
80
81                      ///+++Task 2+++///
82
83      int counter = 0;
84      for (int i = 0; i < data_count; i++)
85      {
86          cout << data_dict[i] << endl;
87          counter++;
88      }
89      char** synonym = new char* [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
99          cin >> choice;
100          if (choice == 'Y' || choice == 'y')
101          {
102              cout << "How many synonyms do you want to store for " << data_dict[i] <<
103
104              cin >> synonym_count;
105              cin.ignore();
106              synonym[i] = new char* [synonym_count];
107              for (int j = 0; j < synonym_count; j++)
108              {
109                  cout << "Enter synonym for " << data_dict[i] << endl;
110                  char user_synonym[30];
111                  cin.getline(user_synonym, 30);
112                  for (int i = 0; user_synonym[i] != '\0'; i++)
113                  {
114                      temp[ft++] = user_synonym[i];
```

1:18 PM
4/14/2023

WhatsA | report-v | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/22I%207963.cpp/assignment%201%2022I-7906.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
22I 7963.cpp

Submission 2
assignment 1 22I-7906.cpp

Match %
31.29

Submission 1 File 1	Submission 2 File 2	Tokens
22I 7963.cpp\22I 7963.cpp (145 - 169)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (49 - 73)	41
22I 7963.cpp\22I 7963.cpp (117 - 130)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (12 - 25)	18
22I 7963.cpp\22I 7963.cpp (55 - 61)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (89 - 96)	15
22I 7963.cpp\22I 7963.cpp (131 - 145)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (38 - 49)	13

```
117 {
118     for (int i = 0; i < words; i++)
119     {
120             int j = 0;
121             while (datadic[i][j] != '\0' && data[j] != '\0')
122             {
123                     if (datadic[i][j] != data[j])
124                     {
125                             break;
126                     }
127                     j++;
128             }
129             if (datadic[i][j] == '\0' && data[j] == '\0')
130             {
131                     return true;
132             }
133     }
134     return false;
135 }
136
137
138
139 int main()
140 {
141     char input[3000];
142     cout << "Enter data \n ";
143     cin.getline(input, 3000);
144     char** datadic = new char* [3000];
145     int words = 0, tracker = 0;
146     for (int i = 0; input[i] != '\0'; i++)
147     {
148             if (input[i] == ' ' || input[i] == '.')
149             {
150                     char* data = new char[(i - tracker) + 1];
151                     int j = 0;
152                     for (int k = tracker; k < i; k++)
153                     {
154                             data[j] = input[k];
155                             j++;
156                     }
157                     data[j] = '\0';
158
159                     if (!SearchUnique(datadic, words, data))
160                     {
161                             int len = strlen(data);
162                             datadic[words] = new char[len + 1];
163                             for (int k = 0; k < len; k++)
164                             {
165                                     datadic[words][k] = data[k];
166                             }
167                             datadic[words][len] = '\0';
168                             words++;
169                     }
170             delete[] data;
171                     tracker = i + 1;
172
173             }
174     }
175     for (int i = 0 ; i <words; i++)
176     {
177             cout << datadic[i] << "\n";
178     }
179
180     bool flag=false;
181     int track = 0;
```

```
12 {
13     for (int i = 0; i < data_count; i++)
14     {
15         int j = 0;
16         while (data_dict[i][j] != '\0' && word[j] != '\0')
17         {
18             if (data_dict[i][j] != word[j])
19             {
20                 break;
21             }
22             j++;
23         }
24         if (data_dict[i][j] == '\0' && word[j] == '\0')
25         {
26             f_index = i;
27             return true;
28         }
29     }
30     return false;
31 }
32 bool checkSynonun(char*** synonym, char* word, int data_count,int f_index)
33 {
34     for (int i = 0; i < data_count && f_index!=-1; i++)
35     {
36         if (synonym[f_index] != nullptr)
37         {
38             return true;
39         }
40     }
41     return false;
42 }
43 int main()
44 {
45     char text[3000];
46     cout << "Enter data\n ";
47     cin.getline(text, 3000);
48     char** data_dict = new char* [3000];
49     int data_count = 0, start = 0,f_index=-1;
50     for (int i = 0; text[i] != '\0'; i++)
51     {
52         if (text[i] == ' ' || text[i] == '.')
53         {
54             char* word = new char[(i - start) + 1];
55             int j = 0;
56             for (int k = start; k < i; k++)
57             {
58                 word[j] = text[k];
59                 j++;
60             }
61             word[j] = '\0';
62
63             if (!SearchUnique(data_dict, data_count, word,f_index))
64             {
65                 int word_length = strlen(word);
66                 data_dict[data_count] = new char[word_length + 1];
67                 for (int k = 0; k < word_length; k++)
68                 {
69                     data_dict[data_count][k] = word[k];
70                 }
71                 data_dict[data_count][word_length] = '\0';
72                 data_count++;
73             }
74
75             start = i + 1;
76             delete[] word;
```

1:18 PM
4/14/2023

WhatsA | report- | Lab Mar | Downlo | BDS - 4 | New Tal | Convert
jplag.github.io/JPlag/comparison/22I%207963.cpp/assignment%201%2022I-7906.cpp
Photos - Google Ph... YouTube Facebook WhatsApp Classes Temp Mail - Dispos... LESCO - Customer... Bill Payment

JPlag Comparison

back

Submission 1
22I 7963.cpp

Submission 2
assignment 1 22I-7906.cpp

Match %
31.29

Submission 1 File 1	Submission 2 File 2	Tokens
22I 7963.cpp\22I 7963.cpp (145 - 169)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (49 - 73)	41
22I 7963.cpp\22I 7963.cpp (117 - 130)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (12 - 25)	18
22I 7963.cpp\22I 7963.cpp (55 - 81)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (89 - 96)	15
22I 7963.cpp\22I 7963.cpp (131 - 145)	assignment 1 22I-7906.cpp\assignment 1 22I-7906.cpp (38 - 49)	13

```
55      syn = new char** [data_count];      //words
56      for (int i = 0; i < data_count; i++)
57      {
58              syn[i] = nullptr;
59      }
60      for (int i = 0; i < data_count; i++)
61      {
62              cout << " ENTER NUMBER OF SYNONYMS YOU WANT TO ENTER FOR " << data_dict[i
63              int num = 0;
64              cin >> num;
65              syn[i] = new char* [num];   //synonyms num
66
67              for (int j = 0; j < num;j++)
68              {
69                      cout << "ENTER SYNONYMS FOR " << data_dict[i] << ": ";
70                      char* temp = new char[100];
71                      cin.clear();
72                      cin.ignore();
73                      cin.getline(temp, 100);
74                      int l = 0;
75                      while (temp[l] != '\0')
76                      {
77                              l++;  //lenght
78                      }
79                      syn[i][j] = new char[l];    // for storing syns chars (lenght)
80
81                      for (int k = 0; k < l ; k++)
82                      {
83                              syn[i][j][k] = temp[k];
84                      }
85              }
86
87
88
89
90      }
91 }
92
93
94
95
96 //void copy(char**& datadic, char*& data, int words)
97 //{
98 //   int k = 0;
99 //
100 //  for (int i = 0; i < words; i++)
101 //  {
102 //
103 //          int j = 0;
104 //          while (data[k] != ' ' && data[k] != '\0')
105 //          {
106 //                  datadic[i][j] = data[k];
107 //                  j++;
108 //                  k++;
109 //          }
110 //          datadic[i][j] = '\0';
111 //          k++;
112 //
113 //  }
114 //
115 //}
116 bool SearchUnique(char** datadic, int words, char* data)
117 {
118     for (int i = 0; i < words; i++)
119     {
120             int j = 0;
121             while (datadic[i][j] != '\0' && data[j] != '\0')
122             {
```

```
89      char*** synonym = new char** [counter];
90      for (int i = 0; i < counter; i++)
91      {
92          synonym[i] = nullptr;
93      }
94
95      for (int i = 0; i < counter; i++)
96      {
97          again:
98          cout << "Do you want to enter Synonym of " << data_dict[i] << " ? (Y/N)\n";
99          cin >> choice;
100         if (choice == 'Y' || choice == 'y')
101         {
102             cout << "How many synonyms do you want to store for " << data_dict[i] <<
103
104             cin >> synonym_count;
105             cin.ignore();
106             synonym[i] = new char* [synonym_count];
107             for (int j = 0; j < synonym_count; j++)
108             {
109                 cout << "Enter synonym for " << data_dict[i] << endl;
110                 char user_synonym[30];
111                 cin.getline(user_synonym, 30);
112                 for (int i = 0; user_synonym[i] != '\0'; i++)
113                 {
114                     temp[ft++] = user_synonym[i];
115                 }
116                 temp[ft++]='#';
117
118
119
120                 synonym[i][j] = new char[strlen(user_synonym) + 1];
121                 for (int k = 0; k < strlen(user_synonym); k++)
122                 {
123                     synonym[i][j][k] = user_synonym[k];
124                 }
125                 synonym[i][j][strlen(user_synonym)] = '\0';
126             }
127         }
128         else
129             synonym[i] = nullptr;
130         if (choice != 'n' && choice != 'N' && choice != 'Y' && choice != 'y')
131         {
132             cout << "Enter correct choice:\n";
133                 goto again;
134         }
135
136
137     }
138
139     for (int i = 0; i < counter; i++)
140     {
141         cout << "Input word : " << data_dict[i] << endl;
142         if (synonym[i] != nullptr)
143         {
144             for (int j = 0; j < synonym_count; j++)
145             {
146                 cout << "Synonym: ";
147                 for (int k = 0; synonym[i][j][k] != '\0'; k++)
148                 {
149                     cout << synonym[i][j][k];
150                 }
151                 cout << endl;
152             }
153         }
154         cout << endl;
155     }
156
157             //extack Ter//
```

1:18 PM
4/14/2023