

Population Kinetics of a Repetitively-Pulsed Nanosecond Discharge

by

Benjamin T. Yee

A dissertation submitted in partial fulfillment
of the requirements for the degree of
Doctor of Philosophy
(Nuclear Engineering & Radiological Sciences)
in the University of Michigan
2013

Doctoral Committee:

Associate Professor John E. Foster, Chair
Doctor Edward V. Barnat, Sandia National Laboratories
Doctor Isaiah M. Blankson, National Aeronautics and Space Administration
Professor Augustus Evrard
Professor Mark J. Kushner

©Benjamin T. Yee

2013

I would like to dedicate this dissertation to someone else.

A C K N O W L E D G M E N T S

Who is this?

Preface

This is a dissertation about something; I really hope it's good.

TABLE OF CONTENTS

Dedication	ii
Acknowledgments	iii
Preface	iv
List of Figures	vii
List of Tables	viii
List of Appendices	ix
List of Abbreviations	x
Chapter	
1 Introduction	1
1.1 Overview	1
1.1.1 Motivation	1
1.1.2 History	3
1.1.3 Questions	5
1.1.4 Approach	6
1.2 Literature Review	7
1.2.1 Early History of Pulsed Discharges	7
1.2.2 The Streamer Model	9
1.2.3 Ionizing Waves of Potential Gradient	11
1.2.4 Repetitively-Pulsed Nanosecond Discharges	12
2 Theory	16
2.1 Plasmas	16
2.2 Atomic Spectroscopy	18
2.2.1 Spectral Lineshapes	20
2.2.2 Radiation Trapping	21
3 Experiment	22
3.1 Discharge Apparatus	22
3.2 Measurement Conditions	23
3.3 Energy Coupling	24
3.4 Absorption Setup	24

3.4.1 Acquisition Process	25
3.5 Emissions Setup	26
4 Metastable Measurements	27
5 Emission Measurements	28
6 Modeling	29
7 Conclusions	30
Appendices	31
Bibliography	33

LIST OF FIGURES

1.1	A sketch of J.J. Thomson's early experiments on fast ionization waves in long vacuum tubes.	8
-----	---	---

LIST OF TABLES

LIST OF APPENDICES

A Millimeter-Wave Interferometry	31
B Rotational Spectroscopy	32

LIST OF ABBREVIATIONS

RPND repetitively-pulsed nanosecond discharge

APP atmospheric-pressure plasma

VFP Vlasov-Fokker-Planck

EEDF electron energy distribution function

FIW fast ionization wave

LAS laser-absorption spectroscopy

LCIF laser collision-induced fluorescence

CHAPTER 1

Introduction

1.1 Overview

1.1.1 Motivation

Plasmas, commonly called the fourth state of matter, are a gas where a significant fraction of the neutral atoms or molecules have been split into pairs of electrons and positive ions. Initially, a curiosity of the laboratory, they have become a critical part of every day life. The electrically charged nature of plasmas makes them a practical means by which to convert electrical energy into light, chemical reactions, kinetic energy, or even nuclear reactions. From an applications perspective, they are indispensable in lighting, semiconductor manufacturing, plastic processing, and space propulsion. On a more broad scale, virtually all observable light in the universe is the result of a plasma in some form or another.

Some exceptions aside, only three things are required to create a plasma: a gas, an energy source, and a means of transferring the energy to the gas. In man-made applications, the energy source is typically electricity, and the simplest transfer mechanism are two electrodes placed on either side of the gas. When a sufficient voltage is applied across the gap, residual electrons in the gas (often created by background cosmic radiation) are accelerated until they collide with a gas particle. The electron, having acquired a fair amount of energy, knocks a second electron loose from the particle, leaving behind a relatively heavy and immobile ion. Subsequently, both the first and second electron are now accelerated by the electric field,

until they again create new electrons. Electrons continue to be created in this exponentially growing process, referred to as an avalanche, until they cross the gap between the electrodes, leaving behind a plasma.

Despite this relatively simple recipe, the physical characteristics can vary greatly depending on what gas is used, what pressure it is at, what voltage is used, whether the electricity is applied constantly or varied over time, what kind of electrodes are used, etc. As a result, plasmas are generally produced under tightly controlled conditions. For example, a plasma etcher used in semiconductor manufacturing may operate at pressures that are one-thousandth of atmospheric pressure with 99.999% pure gases. In these plasmas, the ions and neutral gas particles often have temperatures that are below 1,000 K. Though this is may be above room temperature, it is well below the electrons which often possess temperatures closer to 20,000 K. This disparity in temperatures is characteristic of plasmas which are not in thermal equilibrium, more colloquially known as “low-temperature” plasmas.

By comparison, plasmas in thermal equilibrium possess electrons, ions, and neutral particles which are all at the same, highly elevated, temperature. For reasons which will later be explained, such plasmas tend to occur at gas pressures which are closer to atmosphere. High-temperature plasmas have their own set of applications, such as arc welders which use a plasma for metal joining. Additional examples include the xenon arc lamps used to simulate the sun, metal-halide lamps used in cars, plasma torches for cutting metals,

Unfortunately, there are a number of applications which would benefit from operation at higher pressures, but with low-temperatures ions and neutral particles. This has spurred a substantial amount of research on atmospheric-pressure plasmas (APPS) in recent years. One product of these efforts has been the use of plasmas to treat polymers so that ink can adhere to the surface. Another, uses low-temperature APPS to generate ozone to kill bacterial contaminants in water.

That said, research on high-pressure, low-temperature plasmas is ongoing. The number of potential applications has continued to grow, and the outcomes include things like better

access to clean water, wound sterilization, improved fuel efficiency, faster airplanes, new materials, nanoparticle production, and much more. However, these plasmas are much more difficult to create as they are subject to a number of instabilities which either snuff out the plasma, or cause it to transition to thermal equilibrium.

Of the few techniques available to create atmospheric plasmas, the repetitively-pulsed nanosecond discharge (RPND) is unique in its ability to create plasmas up to several liters in volume, but with relatively uniform properties throughout. The potential of this plasma to result in even one of the above outcomes more than warrants its close study. This is sentiment is echoed by the National Academies, when, in their recent review of plasma science stated that “[high-pressure nonequilibrium plasmas] have great promise both for practical application, and also as a unifying platform for future low-temperature plasma science research.”

1.1.2 History

Historically, the study of low-temperature APPS has been almost indistinguishable from the study of plasmas as a whole. However, this was not necessarily a matter of reasoned choice. Operation at atmospheric-pressure obviates the need for an effective vacuum pump. Additionally, prior to the creation of large battery banks, early sources of electrical energy had relatively small capacities. This precluded the generation of thermal plasmas which required large amounts of energy.

Indeed, these requirements were sufficiently rudimentary that the first man-made low-temperature APP, and plasma in general, was probably a spark generated by rubbing fur against amber. This is commonly attributed to Thales of Milêtus from around 600 B.C. Electrical sparks came to intrigue many scientists including Gottfried Liebnez, Benjamin Franklin, and Charles Wheatstone. By the mid-1800s, Plücker, Geißler, and Hittorf began some of the first work on low-pressure plasmas though it was Crookes who later identified plasma as a separate state of matter. Eventually, it was J.J. Thomson’s discovery of the

electron and discretized charge that marked the beginning of modern plasma research.

By this time, the necessary tools and techniques existed to create continuous plasmas in pure, rarified gases. Their behavior was dominated by the motion and interaction of the charged electrons and ions, and the presence of neutral gas particles was undesirable. These carefully controlled systems were ideal for basic studies of plasma behavior and were used to great effect by individuals such as Irving Langmuir and Lewi Tonks. In fact, many modern concepts in plasma physics can be traced back to their work.

In contrast, the pulsed APPS, characteristic of the earliest man-made plasmas, while easy to create, were notoriously difficult to work with. Because they did not operate in a steady state, one needed to measure how they changed over time. This demanded a time resolution of billionths of a second. Furthermore, such plasmas possessed large numbers of neutral particles could confound or obscure the important behavior of the charged particles. Despite such problems, these plasmas, including lightning, sparks, and a type that Thomson referred to as a “luminous front,” retained a great deal of interest.

The culmination of these efforts was research into the so-called “fast ionization waves” beginning in the 1970s and continuing to this day. These plasmas were similar to the luminous front described by Thomson; they occurred as an impulse of light which developed from the high voltage to the low voltage electrode and traveled at a reasonable fraction of the speed of light. They were generated by voltage pulses that lasted anywhere from 1-100 billionths of a second and could reach 300 kilovolts. They could be produced in almost any gas, and almost any pressure, provided the voltage was high enough. Furthermore, regardless of pressure, they could uniformly fill large volumes with plasma and highly excited neutral particles, all with little heating.

The properties of the fast ionization wave plasmas were attractive for a number of uses, but their implementation had a number of problems. With the best available equipment, a fast ionization wave could only be generated a few times a second. Since the plasma quickly died away within approximately a thousandth of a second after each pulse, this

meant that a fast ionization wave plasma was only effectively on for a percentage of the time it was operated. This had important repercussions for plasma-processing applications where material had to be treated as quickly as possible. Also problematic were the extremely high voltages necessary to create these plasmas. Such voltages required complex banks of capacitors submerged in baths of oil and careful design of the electronic circuits and pathways to ensure reliable operation.

Recently, the invention of fast solid-state switches with low recovery times has solved both issues. Modern switches can operate almost one-hundred thousand times a second. This results in a plasma that is almost continually on. Furthermore, because the plasma does not completely die away between successive pulses, it requires much lower voltages to reignite with each pulse. Where before the fast ionization wave may have been prohibitively large and expensive for a number of situations, the repetitively-pulsed nanosecond discharge is able to serve as a more capable substitute.

1.1.3 Questions

The large pedigree of pulsed plasma research belies the fact that they are not well-understood. The short time scales, electrical noise, high pressures, and complex chemistries continue to stymie the best experimental equipment and most well-developed simulations. This is particularly true of *RPNDs* which have recently emerged as an area of interest. These discharges present a number of questions with a range of implications in their use and development.

Most fundamentally, the majority of *RPND* research has concentrated on quantities which do not change over time, or change slowly compared to the formation time. The most common of these are chemical composition, gas temperature, total energy deposited. While undoubtedly important, such measurements provide little insight on what is happening while the plasma is forming. Thus the question arises, what are the plasma properties during its formation?

Additionally, the most of the contemporary studies have focused on system in mixtures

of molecular gases such as oxygen, nitrogen, air, and occasionally hydrogen. The choice of these gases reflect a limited number of specific applications. However, several others involve the use of rare gases, such as helium. Notably, rare gas atoms feature unique internal structures which can significantly influence the properties of a plasma. So we naturally would like to address how a rare gas RPND compares one in a molecular gas.

Finally, the persistence of the plasma between pulses can alter the development of the discharge. For example, a large background population of electrons can quickly shield out the applied voltage pulse. This would have the counterintuitive effect of decreasing the final electron density despite a large number of seed electrons. As a result, it is important to study how the trends of various parameters and how they're optimized for different conditions. This is particularly important for application purposes where some excited states are more desirable than others.

1.1.4 Approach

In order to answer these questions, I present a series of experiments, measurements, and simulations of a helium RPND.

Here, I present a series of experiments, measurements, and simulations used to study the dynamics of a helium RPND. Helium was chosen because it is commonly used in gas mixtures to stabilize the plasma between pulses, in addition, it provides a relatively simple atomic system for which a wealth of the necessary electronic, optical, and atomic data are available.

Here, I present the results of a study into the dynamics of a RPND. The primary experimental measurements are laser-absorption spectroscopy of the helium metastable level, supported by calibrated optical emission measurements. The measurements are interpreted with the aid of a helium global model and particle-in-cell simulations.

1.2 Literature Review

RPNDS are only a recent invention which resulted from advances in fast-switching semiconductors. However, the physics of their formation is related to a much larger category of plasmas which includes lightning, sparks, and even some transient phenomena in DC glows. These plasmas are unique in that their formation occurs on timescales much faster than the traditional Townsend mechanism allows for. The means by which these plasmas form has acquired several names in the literature; here we will adopt the term, fast ionization wave (FIW).¹.

1.2.1 Early History of Pulsed Discharges

The first FIW was likely generated by Wheatstone in 1835 [1]. As reported by Thomson [2], Wheatstone built a vacuum tube six feet in length, and applied a high voltage across the gas. As a plasma formed in the tube, Wheatstone observed its formation with a rotating mirror. The use of this apparatus allowed Wheatstone to place a lower limit on the speed with which the plasma travelled from one electrode to the other. Though the discharge crossed the tube with a speed of at least 8×10^7 cm/s, spectral observations indicated that the particles emitting the light were not travelling at that speed [3].

Later, Thomson revisited this work with an improved apparatus [2]. This included a tube that was now 15 m in length and five mm in diameter, as seen in figure 1.1. Also using the rotating mirror apparatus, Thomson was able to greatly improve on the estimates of Wheatstone. He estimated that the so-called “luminous front” had a speed that was more than 1.5×10^{10} , or in excess of half of the speed of light. Furthermore, Thomson determined that the front always appeared to travel from the positively pulsed electrode (anode) to the ground electrode (cathode).

¹It should be noted that the phrase wave does not indicate any kind of periodic motion or spatial arrangement. Simply put, it describes a boundary which separates ionized and unionized gas which travels from one electrode to another.




Figure 1.1: A sketch of J.J. Thomson’s early experiments on fast ionization waves in long vacuum tubes.

The study of these luminous fronts was revisited by several researchers in the wake of Thomson [4–6] with varied success. By his own admission, Beams’s work in 1926 was done “hurriedly,” using a rudimentary Kerr cell. In 1930, Beams returned to the propagation of light pulses in vacuum tubes with a rotating mirror apparatus [7]. In addition to confirming his previous measurements, and those of Thomson, Beams discovered that the FIW always traveled from the electrode with the highest absolute potential, to the lowest one. In other words, the wave could be anode or cathode directed, depending on the magnitude of their potentials relative to ground. Benefiting from an improved understanding of electricity, namely the existence of electrons and ions, Beams was able to provide the first hypothesis on the nature of the FIW:

In the neighborhood of the electrode . . . the field is very high and intense ionization should take place. This ionization due to the large difference in mobilities of positive ions, negative ions and electrons respectively should result in the establishment of a space charge. This space charge, once formed near the high potential electrode Q must move down the tube regardless of the polarity of the applied potential because of the changes it produces in the field near its edges.

At about the same time, Schonland and Collens reported on their observations of lightning [8]. Though the general structure and length scale of lightning is substantially different from the luminous fronts observed by Beams and Thomson, the two phenomena would later prove to be very similar. In their work Schonland and Collens noted that lightning would usually occur in a two-step process. Based on the images they obtained, they suggested that the leader was generated by a relatively small “dart” with a mean vertical velocity of 7.2×10^8 cm/s. The dart moved in a random manner, changing directions at random intervals, but always moving downward.

The second step began when this dart reached the ground. Once there, a bright return stroke would occur along the same path that the leader had traced out. In contrast to the leader stroke, the return stroke had a velocity of 5×10^9 cm/s. Schonland and Collens hesitantly attributed the leader stroke to an extended electron avalanche, and the return stroke to thermal ionization along the conductive path generated by the dart. However, calculations by Cravath and Loeb showed that the speeds of the proposed avalanche would have to be inconsistent with the fields at the head of a lightning stroke [9]. Instead, they suggested that the dart was actually a moving region of space charge which locally accelerated electrons to ionizing energies. This was fundamentally similar to the mechanism proposed by Beams in 1930.

1.2.2 The Streamer Model

It was long known that sparks in air were similar to lightning. Advances in technology during the 1930’s led to experiments which reinforced this similarity. In response to the measurements of Schonland and Collens; Snoddy, Beams, and Dietrich studied the breakdown of gas in a long tube with an oscillograph [10]. The results from the oscillograph showed a very clear return wave for which they measured several parameters the characterized as a function of pressure and applied potential. They observed that at low voltages, the system behaved like a large resistor in series with a capacitor, and below a critical voltage,

no return stroke would form. Finally, in order to explain the propagation of the FIW generated by the positive pulse, they suggested that photoionization was occurring in the space ahead of the wave.

Around the same time, Flegler and Raether had come to a similar conclusion, leading to the first attempt at a theory describing streamers [11]. This same theory was proposed independently by Loeb and Meek in a series of papers [12–14]. The streamer theory divided the initial breakdown of a spark into two steps. In the first step, an electron avalanche is initiated between two electrodes. The avalanche travels toward the anode and leaves behind a region of high positive space charge. In the second step, the return stroke begins at the cathode and travels toward the cathode. It was suggested that the head of the return stroke ionizes the gas ahead of it by pulling in background electrons or via photoionization.²

The streamer model proved relatively successful in describing the development of sparks and lightning. Theoretical estimates of the speed matched the velocity measurements that were acquired through photographs and oscillographs. Additionally, the theory is able to account for the halting manner in which lightning is formed, though it is only tentatively able to describe the branching and stepped appearance. Finally, the streamer mechanism provides an adequate explanation of why streamer discharges are not affected by the shape or material of the cathode, namely, they do not depend on secondary electron emission.

The study of the formation of streamers and lightning continues to be active to this day. Following the initial work of Flegler, Raether, Loeb, and Meek, a number of researchers began to explore the boundary between the Townsend mechanism and the streamer mechanism. Most notable was Fisher and Bederson’s work in 1951 [16], which was later extended to nitrogen [17] and argon [?]. However, there were still a number of phenomena that were poorly explained by the streamer model. In particular, Kunhardt provided a useful overview of the problems in 1980 [18]. However, even before that, it was apparent that the transients

²These early works emphasized the importance of photoionization. It is now known that it is only required for cathode-directed streamers in systems with no background ionization. In addition, Mesyats later showed that the lifetime of the excited states responsible for photoionization were often longer than the lifetime of the streamers [15]

of sparks and lightning was more complicated than thought.

1.2.3 Ionizing Waves of Potential Gradient

Per Chalmers [19], Rogowski and Buss [20, 21] observed a fast, diffuse, glow discharge immediately prior to the filaments which often accompany a streamer discharge. Allibone and Meek, noted similar diffuse discharges in air based on oscillographs and photographs [22–24]. However, the Boys apparatus which was employed in these studies (an ancestor to the modern streak camera) was unable to capture the evolution of the diffuse glow, given its large spatial extent.

This was first noted by Allibone who attempted to use Lichtenberg figures³ to definitively capture this diffuse glow [25]. Later, Saxe and Meek used the recently invented photomultiplier tube to record the evolution of the light emissions in the brief, diffuse glow [26] as a function of space. Both studies agreed in the existence of the diffuse glow, despite some disagreement on the nature of its geometry and propagation.

The similarity of fast, transient, ionization waves in certain glow discharges [27] to the development of lightning and streamers led Loeb to the conclusion that they were all the same phenomena [28]. He referred to them as “ionizing waves of potential gradient.” Loeb stated that such waves required the generation of a steep potential gradient in a sufficiently short period of time.

As reported by Babich, Loika, and Tarasova [29], the detection of x-ray emissions from pulsed, high-pressure, helium discharges created a new avenue of interest for these transient plasmas [30, 31]. Unlike the streamers, which were often filamentary, these new discharges exhibited surprising uniformity. The primary difference being the duration of the pulse (on the order of nanoseconds) and the applied potentials (in excess of 200 kV).

The x-rays suggested that electrons in these discharges were accelerated to unusually

³Such figures directly exposed photographic emulsions to the electrical discharge. The developed image was a time-integrated representation of the discharge.

high energies (on the order of 10 keV) despite the high collisionality implied by the high gas pressures. This prompted Babich and Stankevich to suggest that the x-rays resulted from continually accelerated electrons impinging on the metal electrodes [32]. Briefly, the electric fields in the fronts of the ionizing waves were so large that they managed to accelerate electrons well past the peak in their collisional cross sections.

The presence of runaway electrons was sufficient to explain the production of x-rays, however it did not sufficiently address the uniformity of these discharges. After several experiments, Mesyats, Bychov, and Kremnev came to the conclusion that these transient plasmas were the result of many simultaneous avalanches occurring throughout the gas volume. This contrasts with the classical view of the streamer which involves only a single avalanche. Kunhardt and Byszewski later expanded on this work by developing a kinetic model to explain the behavior of all pulsed discharges above the Townsend threshold [18].

It was based on the studies of the fast electrons in these discharges that Mesyats, Bychov, and Kremnev proposed the use of a fast electron beam for pumping high-pressure gas lasers. Similar work was conducted simultaneously by Fenstermacher et al. [33]. Later, Hunter [34], and Koval'chuk and Mesyats [35] proposed that such discharges be used for fast-closing switches. The need for a homogeneous plasmas in these applications prompted Palmer [36], and Levatter and Lin [37] to investigate the necessary conditions for uniformity. They concluded that the primary requirement for uniformity was a threshold value of fractional ionization.

1.2.4 Repetitively-Pulsed Nanosecond Discharges

The type of discharge originally studied by Babich, Loika, and Tarasova came to be known as the fast ionization wave (FIW). In the years following its discovery, a substantial effort was made to document the properties of the FIW over a wide range of conditions. In these studies, the wave velocity, current, and attenuation were the most frequently measured quantities. Much of this work is summarized in a review by Vasilyak [38]. Also reviewed are Slavin and

Sopin's work which was the first to attempt a computation of the electron energy distribution function $EEDF$ in FIWS [39].

The experimental measurements and computational work reported by Vasilyak were expanded on by studies conducted at the Moscow Institute of Physics. These are reviewed by Starikovskaia et al. [40] and included measurements of the electron density, electric field, and energy coupling for FIWS in air, nitrogen, and hydrogen. The work by Starikovskaia and Starikovskii still represent the most detailed study of the $EEDF$ in FIWS, however its focus was limited to negative discharges in nitrogen.

However, Starikovskaia et al. noted that the usefulness of FIWS was limited by their repetition rates. The power supplies for FIWS were capacitor banks, charged in parallel, and discharged in series (also referred to as the Marx bank). Unfortunately, the spark gaps used to trigger these capacitor banks would not operate above a few hundred Hz. This changed in the late 1990's with the development and commercialization of fast, solid-state switches. Specifically, the fast ionization dynistor allowed repetition rates of 100 kHz.

This led to a new class of repetitively-pulsed discharges, or the RPND. These discharges were operated at sufficiently high rates such that charged particles would persist between pulses. Not only did this increase the effective on-time of the plasma, but this residual ionization made it much easier to obtain a stable discharge with lower voltages. This reflects the preionization threshold that was earlier identified by Levatter and Lin.

The improved qualities of the RPND over the FIW inspired a number of application-driven studies. This included:

- Plasma-assisted combustion [41–43]
- Magnetohydrodynamic energy bypass engines [43–45]
- Plasma actuators [46, 47]
- High-pressure xenon lamps [48]
- Plasma medicine [?, 49]

- Water treatment [50]

Though not specific to the RPND, Becker et al. [51] provide an extensive discussion of the potential uses for non-equilibrium air plasmas.

As a result, contemporary researchers have produced a wealth of literature on the operation of RPNDs. More recently, there have been detailed measurements of the gas temperatures [41, 52–58], chemical composition [54–56], electric fields [59–61], and energy coupling [41, 62]. Notably, these studies have been generally restricted to molecular gases; air, nitrogen, and occasionally, hydrogen.

The first such study was the work of Laroussi and Lu who examined a RPND excited in a stream of helium flowing from a tube into air [63, 64]. The resulting plasma had the appearance of a jet, emitted from the open end of the tube. Using fast photography they observed that the jet was actually a series of plasma “bullets” formed with each pulse. Measurements of the bullet velocities showed that their speed greatly exceed what would be expected purely from electrons drifting under the applied electric field. They concluded that the bullets were essentially cathode-directed streamers which propagated with the aid of photoionization.

The work of Laroussi and Lu spawned a great deal of interest in RPND helium plasma jets⁴ For example, Walsh et al. studied the atomic oxygen production for helium-oxygen mixtures with the use of emission spectroscopy and a global plasma chemistry model [66]. Urabe et al. employed a variety of laser diagnostics to measure the radial density profiles of helium metastable atoms and molecular nitrogen ions in a similar jet. This work was supported by a number of two-dimensional plasma simulations such as those by Naidis [67] and Breden, Miki, and Raja [68].

Simultaneously, study of large-volume RPNDs has received little attention even as the study of single fast ionization waves has declined. The recent work by Takashima et al. represents one of the most complete studies of a FIW, featuring two-dimensional fluid simu-

⁴A distinction should be made between plasma jets, excited by sinusoidal power supplies, similar to the well-known dielectric-barrier discharge [?], and those produced by nanosecond pulses. Differences between the two were reported by Walsh, Shi, and Kong [65].

lations, an analytic model, and capacitive probe measurements in helium and nitrogen [69]. For the measured parameters, the experimental and numerical results showed good agreement.

However, there is reason to believe that a RPND in a similar geometry would exhibit different characteristics. The authors note that changes in the initial electron density can cause significant changes in the peak electric field, final electron density, and wave velocity. Furthermore, little effort has been made to study the excited state dynamics of rare gas FIWS or RPNDs. However, some of these excited states can play an important role as long-lived electron sources [70], and as a source of anomalous electron heating [?]. Finally, measurements of excited state densities can provide important benchmarks for computational simulations.

CHAPTER 2

Theory

2.1 Plasmas

A volume containing some number of charged particles can be considered a plasma if it meets three conditions. The first requires that the motion of charged particles is primarily determined by the electric and magnetic fields of the volume rather than through collisions with neutral particles. This is classically expressed by the inequality

$$\sqrt{n_e e^2 / (\epsilon_0 m_e)} < \nu, \quad (2.1)$$

where n_e is the electron density, e is the fundamental charge, ϵ_0 is the permittivity of free space, m_e is the mass of an electron, and ν is the electron-neutral collision frequency. The left-hand side term is called the electron plasma frequency, it the characteristic frequency at which a plasma oscillates in response to a perturbation.

For a sufficiently large number of particles, the behavior of the each species of the plasma can be described by a continuous probability distribution function. This function, $f_\alpha(\vec{r}, \vec{v}, t)$, describes the probability of finding a particle of species α , at position \vec{r} , The distribution function for a particle can be determined by the Vlasov-Fokker-Planck v_{FP} equation,

$$\frac{\partial f_\alpha}{\partial t} + \vec{v}_\alpha \cdot \nabla f_\alpha + q_\alpha \left(\vec{E} + \vec{v}_\alpha \times \vec{B} \right) \cdot \nabla_{\vec{v}} f_\alpha = \left(\frac{\partial f_\alpha}{\partial t} \right)_{\text{coll}}. \quad (2.2)$$

Here, \vec{E} is the electric field, \vec{B} is the magnetic field, and $\partial f_\alpha / (\partial t)_{\text{coll}}$ is a term representing all collisions. The vfp equation is coupled to Maxwell's equations in order to obtain a self-consistent description of the particle distribution and the resulting fields. In essence, this is the Boltzmann equation from statistical mechanics, however it now includes several changes. Vlasov replaced the original force term with the Lorentz equation, and Fokker and Planck introduced the collision operator on the right-hand side. This is coupled with Maxwell's equations for a solution of the electric and magnetic fields in the plasma.

In the absence of external fields and with only elastic collisions, the equation admits the famous Maxwell-Boltzmann equilibrium distribution,

$$f_\alpha(v) = n \left(\frac{m_\alpha}{2\pi k_B T} \right)^{3/2} \exp \left(-\frac{m_\alpha v_\alpha^2}{2k_B T} \right), \quad (2.3)$$

where n is the number of degrees of freedom, k_B is Boltzmann's constant, and T is the temperature. A species of particles which possesses a Boltzmann distribution is said to be in equilibrium. Likewise, two species with the same distribution are in equilibrium.

Aside from this, the vfp equation is notoriously difficult to solve. As a result, most plasma models use various moments of equation 2.2 where the velocity dependence has been integrated out. These moments are the basis for the two-fluid equations, the MHD formulation, and global models. We will show the first three moments following the notation of Lieberman and Lichtenberg [71]. For example, the first moment is the continuity equation,

$$\frac{\partial n_\alpha}{\partial t} + \nabla \cdot (n_\alpha \vec{u}_\alpha) = G_\alpha - L_\alpha, \quad (2.4)$$

where \vec{u}_α is the mean velocity of species α , G_α is its rate of gain, and L_α is the rate of loss. This equation can be interpreted as the rate of change in particle density for a particular volume of space.

Though the continuity equation is much simpler than the original vfp equation, it cannot be solved alone. The mean velocity, \vec{u} , is undefined. Typically, this leads to the second

moment,

$$mn_\alpha \left[\frac{\partial \vec{u}_\alpha}{\partial t} (\vec{u}_\alpha \cdot \nabla) \right] = q_\alpha n_\alpha (\vec{E} + \vec{u}_\alpha \times \vec{B}) - \nabla \cdot \vec{\Pi}_\alpha + \vec{f}_{\alpha, \text{coll}} \quad (2.5)$$

where $\vec{\Pi}_\alpha$ is the pressure tensor, and $\vec{f}_{\alpha, c}$ is the rate of momentum transfer into species α . Again, any solution is stymied by the presence of a new term, in this case, $\vec{\Pi}_\alpha$. At this point, an equation of state can be used to close the set of equations, in this case relating the pressure to the density. However, later work will benefit from one more moment.

Following the conservation of momentum, the energy conservation equation can be derived from the VFP equation,

$$\frac{\partial}{\partial t} \left(\frac{3}{2} p_\alpha \right) + \nabla \cdot \frac{3}{2} (p_\alpha \vec{u}_\alpha) + p_\alpha \nabla \cdot \vec{u}_\alpha + \nabla \cdot \vec{q}_\alpha = \frac{\partial}{\partial t} \left(\frac{3}{2} p_\alpha \right) \Big|_{\text{coll}} \quad (2.6)$$

where p_α is the species pressure, q_α is the heat flow vector, and the right-hand side is the time rate of change in energy as a result of collisions. In our case, we only consider the flux into the volume (from the electric field) and the distribution of this field via rate constants. This is the basis for the global model.

2.2 Atomic Spectroscopy

Spectroscopy spans a large body of theory which cannot be adequately covered here. Given that the measurements are all for helium, we will limit ourselves to a simple description of atomic spectroscopy. An atom is made of positively charged nucleus and a number of negatively charged electrons which orbit this nucleus. In the unperturbed, or ground state, the electrons occupy orbitals determined by a full solution of the Schrodinger equation.

However, interactions with other particles or photons can excite one or more of the electrons into orbitals with higher potential energy. In most cases relevant to low temperature plasmas, only a single electron will be excited at any given time. Depending on which orbital the electron is excited to, it can transition to orbitals with lower potential energy by

emitting a photon. These are typically called allowed transitions.

Each orbital in an atom can be described by four quantum numbers.

- n - The principal quantum number.
- l - Orbital angular momentum number.
- j - Total angular momentum.
- m_j - Total angular magnetic moment.

The Pauli exclusion principle restricts more than a single electron from occupying any given state defined by this series of numbers. Additionally, each set of numbers determines the potential energy possessed by an electron in that particular level.

Allowed transitions are determined by a series of selection rules. These selection rules can be summed up as the following:

- $\Delta S = 0$
- $\Delta L = \pm 1$

Though other transitions are possible (spin and dipole forbidden respectively), they tend to require an external perturbation in order to induce transition.

Figure shows the what is commonly called a Grotrian diagram for helium. In this diagram, the vertical axis represents the energy above the ground state, and the levels are arranged horizontally based on increasing L . Levels which are radiatively linked are connected by solid lines. As can be seen in this figure, only the levels having $S = 1$ are radiatively connected to the ground state. As a result, any helium atoms that are excited into the triplet manifold tend to stay there, accumulating in the metastable state, 2^3S .

Approaching 24 eV, the excited electron enters what is known as the continuum. The energy separation between states goes as n^{-2} , thus at large n the spacing becomes quite close and the states are almost indistinguishable. The levels are often referred to as Ryberg

states. Above 24.69 eV, the electron becomes totally detached from the helium nucleus, and all that remains is a singly ionized helium atom.

Though the emissions of ions can be quite useful in some plasmas, we do not concern ourselves with them in either the measurements or models. 24.69 eV is the largest known ionization potential, and as a result, the number of ions and the emissions associated with them remain relatively small.

2.2.1 Spectral Lineshapes

It is tempting to think that the energy spacing can be calculated exactly, however there is always some variance about a central energy. This is called the spectral lineshape, and it affects both the energy of the emitted photon in radiative transitions, and the photons that an atom can absorb. Though these variations can be attributed to quantum mechanical effects, the actual result can be derived from the so-called dipole approximation.

In this case, we envision a single electron oscillating about a large, heavy, positive charge. The full details of this derivation are covered in Siegman [72], however we'll address some of the most pertinent portions here. The response of a collection of atoms to an applied electric field can be expressed as a quantity known as the susceptibility. This is generally defined as

$$\tilde{\chi}(\omega) \equiv \frac{\tilde{P}(\omega)}{\epsilon_0 \tilde{E}(\omega)} \quad (2.7)$$

where $\tilde{\chi}$ is the electric susceptibility, \tilde{P} is the macroscopic polarization, \tilde{E} is the applied electric field, and ω is the frequency of the applied field.

Natural Linewidth The electric susceptibility often possesses both a real and imaginary component. Physically, these respectively represent the reactive and absorptive component of the medium. Accounting for level-dependent effects, the standard susceptibility for an

atomic transition can be written as

$$\tilde{\chi}_{\text{at}}(\omega) = -j \frac{3}{4\pi^2} \frac{\Delta N \lambda^3 \gamma_{\text{rad}}}{\Delta \omega_{\text{a}}} \frac{1}{1 + 2j(\omega - \omega_{\text{a}})/\Delta \omega} \quad (2.8)$$

where ΔN represents the population difference between the upper and lower levels of the oscillator, λ is the transition wavelength, γ_{rad} is the natural radiative lifetime of the oscillator, $\Delta \omega_{\text{a}}$ is the linewidth of the transition (for an unperturbed atom, this is simply γ_{rad}), and ω_{a} is the angular frequency of the transition or oscillator.

This equation is generally known as the complex lorentzian. Separated into its components it expresses both the absorptive and reactive properties of the atomic medium. It also clearly susceptible to fields that are displaced from ω_{a} . This is the finite linewidth associated with atomic emissions and absorption.

This linewidth affects each atom within the medium. Each atom will emit or absorb radiation with a probability described by this susceptibility. Consequently, this natural linewidth falls under the homogeneous category of line broadening.

Pressure Broadening Also included in this category is pressure broadening, or more fundamentally, dephasing.

2.2.2 Radiation Trapping

CHAPTER 3

Experiment

3.1 Discharge Apparatus

The discharge apparatus geometry was consistent with the design of a coaxial transmission line. This is similar to the design guidelines provided by Vasilyak [38]. The inner conductor is the plasma generated by the fast ionization wave. Surrounding that is a coaxial dielectric, in this case a quartz tube with 2.75” Conflat flanges on either side. Finally, surrounding the dielectric is the outer conductor or shield. In this case, the shield was an aluminum cylinder with slits of approximately 1.5” by 12” milled lengthwise. Figure ?? is a photograph of this discharge apparatus.

One flange of the quartz tube was held at ground potential, while the other flange was pulsed to approximately 7 kV. Given that the plasma undergoes significant decay between pulses, it is assumed that the impedance is almost infinite when the pulse is first applied, thus the actual voltage on the powered electrode is likely closer to 14 kV. The aluminum shield provides the ground connection for the ground electrode. The two were connected using a copper shim and a compressive shaft collar. The aluminum tube was connected to a second ground shield with a one inch copper braid. This second shield was made of copper and was separated by a teflon cylinder, with walls approximately 1” in thickness, from the powered electrode. Figure ?? is a schematic of the discharge apparatus.

Connected to the powered electrode was a Conflat nipple and an angled quartz window

used in the LCIF experiments. A short, silicone-coated, high voltage wire connected the window flange to the central conductor of an HN connector. The HN connector was seated on a square copper plate, which was pressed against the shield using four 10-32 screws.

The HN connector was used to attach the transmission line from the high voltage pulser. Initial experiments attempted to use N connectors, however these were susceptible to breakdown in the air gap which separated the center conductor from the outer shield. The transmission line was approximately 15 m in length. Observations, consistent with calculations, indicated that this provided a window of approximately 140 ns in which to make measurements before the reflected pulse returned to the system and re-energized the plasma.

Attached grounded flange was a second quartz envelope that isolated the ground electrode from the pumping section of the apparatus. Connected to the second quartz envelope was a stainless steel tee, one side of which was connected to an angled quartz window used for the LCIF experiments. The other side of the tee was isolated with an alumina break from a series of Conflat fittings connected to a roughing pump. The roughing pump was connected with a shutoff valve, as well as two bypass lines with inline needle valves for flow regulation.

3.2 Measurement Conditions

LAS, emission, and coupling energy measurements were made at three different operating pressures. The operating pressures were: 0.3, 0.5, 1.0, 2.0, 3.0, 4.0, 8.0, and 16.0 Torr. Pressures below 10.0 Torr were measured with a capacitance manometer with a full scale range of 10.0 Torr, above this a capacitance manometer with a full scale range of 100.0 Torr was used.

Optical measurements were made at three locations along the axis of the discharge. The measurement location closest to the anode was separated from it by a distance of approximately six inches. Each other optical measurement location was moved further from the

anode by an additional three inches.

For each operating condition, measurements were made of the voltage and current. The voltage measurement was made via an internal divider from the power supply. Current measurements were made using an back-current shunt located at a break in the outer shield of the transmission line. The back-current shunt can be seen in Figure ???. It is composed of nine, low impedance, one ohm resistors, connected in parallel. Each side of the resistors were soldered to a piece of copper foil which was then soldered to the outer shield. A calibrated DC power supply was used to measure the resistance of the current shunt.

All measurements were made using a LeCroy Waverider oscilloscope with a bandwidth of 1 GHz. Connections were made using minimal lengths of RG 50/U cable. When necessary for timing purposes, the cable lengths were matched. Connections were made using minimal lengths of RG 50/U cable. When necessary for timing purposes, the cable lengths were matched. All measurements which required maximum bandwidth were made with a using external 50 ohm terminators.

3.3 Energy Coupling

For comparison to other discharges, estimates of the energy coupling were made using the current and voltage characteristics at each operating pressure.

3.4 Absorption Setup

The LAS setup was based upon the used of a distributed-feedback laser diode. Temperature and current control of the diode provided coarse and fine tuning, respectively, for the output frequency. It was found that it was unnecessary to adjust the temperature for the diode once the correct transition was found, therefore all tuning was accomplished using current tuning.

The laser diode was produced by Toptica Photonics (model #LD-1083-0070-DFB-1), and had a nominal operating power of 70 mW at a center wavelength of 1083 nm. The diode

was held inside a Toptica DL-100 diode housing which contained an integral thermoelectric cooler and collimating optics. The operation of the diode was controlled by a Toptica DC 110 monitor, DCC 110 current control, DTC 110 temperature control, and SC 110 scan control.

A schematic of the optical layout for the absorption experiment can be seen in Figure ?? . Immediately after exiting the housing, the beam was passed through an optical isolator in order to prevent instabilities from back reflections. Next the beam was attenuated using a neutral density filter in order to keep its intensity below the saturation level for the transition. Following that, the beam passed through two apertures for alignment. Here, the beam was split by a partially reflecting mirror. Approximately 98% of the beam was allowed to pass through to a reference photodiode (Thorlabs DET300). After passing through the plasma, entered another aperture to limit near-coincident plasma emissions. The background emissions were further reduced using a long pass filter with a cutoff of 1000 nm. Finally, the beam was coupled into an optical fiber which connected to the detection electronics.

The transmitted laser light was detected with an InGaAs photodiode (Thorlabs DET410). The signal from the diode was often too small to detect, so the output of the signal photodiode was sent through a voltage amplifier (Femto HVA-200M-40-B). The light response of this system is limited by the photodiode which has a nominal rise time of five nanoseconds. The signal from the amplifier was terminated by a 50 ohm terminator and sensed by the aforementioned oscilloscope.

3.4.1 Acquisition Process

The actual acquisition process required a specific series of steps in order to properly account for all noise sources. In order to accommodate this process, a custom LabView script was used to automate the acquisition of the laser transmission spectra. Generally speaking, the

signal can be described as

$$V_{\text{total}} = V_{\text{signal}} + V_{\text{background}} + V_{\text{plasma}}. \quad (3.1)$$

In order to remove the background signal, the acquisition scr

3.5 Emissions Setup

CHAPTER 4

Metastable Measurements

CHAPTER 5

Emission Measurements

CHAPTER 6

Modeling

CHAPTER 7

Conclusions

APPENDIX A

Millimeter-Wave Interferometry

$$e = mc^2 \tag{A.1}$$

APPENDIX B

Rotational Spectroscopy

BIBLIOGRAPHY

- [1] C. Wheatstone. Versuche, die Geschwindigkeit der Elektrizität und die Dauer des elektrischen Lichts zu messen. *Annalen der Physik und Chemie*, 110(3):464–480, 1835.
- [2] J J Thomson. *Notes on Recent Researches in Electricity and Magnetism*. Clarendon Press, Oxford, UK, 1893.
- [3] W. v. Zahn. Spectralröhren mit longitudinaler Durchsicht. *Annalen der Physik und Chemie*, 244(12):675–675, 1879.
- [4] John James. Die Abraham-Lemoinesche Methode zur Messung sehr kleiner Zeitintervalle und ihre Anwendung zur Bestimmung der Richtung und Geschwindigkeit der Entladung in Entladungsröhren. *Annalen der Physik*, 320(15):954–987, 1904.
- [5] R. Whiddington. The Discharge of Electricity through Vacuum Tubes. *Nature*, 116(2918):506–509, October 1925.
- [6] J. Beams. The Time Interval Between the Appearance of Spectrum Lines in Spark and in Condensed Discharges. *Physical Review*, 28(3):475–480, September 1926.
- [7] J. Beams. The Propagation of Luminosity in Discharge Tubes. *Physical Review*, 36(5):997–1001, September 1930.
- [8] B. F. J. Schonland and H. Collens. Development of the Lightning Discharge. *Nature*, 132(3332):407–408, September 1933.
- [9] a. M. Cravath and L. B. Loeb. The Mechanism of the High Velocity of Propagation of Lightning Discharges. *Physics*, 6(4):125, 1935.
- [10] L. Snoddy, J. Beams, and J. Dietrich. The Propagation of Potential in Discharge Tubes. *Physical Review*, 50(5):469–471, September 1936.
- [11] E. Flegler and H. Raether. Der elektrische Durchschlag in Gasen nach Untersuchungen mit der Nebelkammer. *Zeitschrift f r Physik*, 99(9-10):635–642, September 1936.
- [12] Leonard B. Loeb and John M. Meek. The Mechanism of Spark Discharge in Air at Atmospheric Pressure. I. *Journal of Applied Physics*, 11(6):438, June 1940.
- [13] Leonard B. Loeb and J. M. Meek. The Mechanism of Spark Discharge in Air at Atmospheric Pressure. II. *Journal of Applied Physics*, 11(7):459, 1940.

- [14] J. Meek. A Theory of Spark Discharge. *Physical Review*, 57(8):722–728, April 1940.
- [15] Gennadii A Mesyats, Yu I Bychkov, and V V Kremnev. Pulsed nanosecond electric discharges in gases. *Soviet Physics Uspekhi*, 15(3):282–297, March 1972.
- [16] L. Fisher and B. Bedderson. Formative Time Lags of Spark Breakdown in Air in Uniform Fields at Low Overvoltages. *Physical Review*, 81(1):109–114, January 1951.
- [17] G. Kachickas and L. Fisher. Formative Time Lags of Uniform Field Breakdown in N₂. *Physical Review*, 88(4):878–883, November 1952.
- [18] E Kunhardt and W Byszewski. Development of overvoltage breakdown at high gas pressure. *Physical Review A*, 21(6):2069–2077, June 1980.
- [19] I D Chalmers. The transient glow discharge in nitrogen and dry air. *Journal of Physics D: Applied Physics*, 4(8):1147–1151, August 1971.
- [20] W Rogowski, E. Flegler, and R. Tamm. Über Wanderwelle und Durchschlag. *Archiv für Elektrotechnik*, 18(5):479–512, September 1927.
- [21] K. Buss. Der Stufendurchschlag. *Archiv für Elektrotechnik*, 26(4):266–272, April 1932.
- [22] T E Allibone and J M Meek. The Development of the Spark Discharge. II. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 169(937):246–268, December 1938.
- [23] T. E. Allibone and J. M. Meek. The Development of the Spark Discharge. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 166(924):97–126, May 1938.
- [24] T E Allibone. The Mechanism of a Long Spark. *Journal of the Institute of Electrical Engineers*, 82(497):513–521, 1938.
- [25] T E Allibone. Development of the Spark Discharge. *Nature*, 161(4103):970–971, June 1948.
- [26] R F Saxe and J M Meek. Development of Spark Discharges. *Nature*, 162(4111):263–264, August 1948.
- [27] Russell Westberg. Nature and Role of Ionizing Potential Space Waves in Glow-to-Arc Transitions. *Physical Review*, 114(1):1–17, April 1959.
- [28] L B Loeb. Ionizing Waves of Potential Gradient: Luminous pulses in electrical breakdown, with velocities a third that of light, have a common basis. *Science (New York, N.Y.)*, 148(3676):1417–26, June 1965.
- [29] L P Babich, T. V. Loiko, and L. V. Tarasova. The physics of high-voltage nanosecond discharges in dense gases. *Radiophysics and Quantum Electronics*, 20(4):436–442, April 1977.

- [30] Yu L Stankevich and V G Kalinin. Fast electrons and X-radiation in the initial stage of pulse spark discharge development in air. *Doklady Akademii Nauk*, 177:72–73, 1967.
- [31] R. C. Noggle. A Search for X Rays from Helium and Air Discharges at Atmospheric Pressure. *Journal of Applied Physics*, 39(10):4746, 1968.
- [32] L P Babich and Yu L Stankevich. Transitions from streamers to continuous electron acceleration. *Soviet Physics Technical Physics*, 17:1333, 1973.
- [33] C. a. Fenstermacher. Electron-Beam-Controlled Electrical Discharge as a Method of Pumping Large Volumes of CO₂ Laser Media at High Pressure. *Applied Physics Letters*, 20(2):56, 1972.
- [34] R O Hunter. Electron beam controlled switching. In *International Pulsed Power Conference*, pages IC8–1 –IC8–6, New York, NY, 1976. Institute of Electrical Engineers, Inc.
- [35] B M Koval’chuk and G A Mesyats. Rapid cutoff of a high current in an electron-beam-excited discharge. *Soviet Technical Physics Letters*, 2(252), 1976.
- [36] a. Jay Palmer. A physical model on the initiation of atmospheric-pressure glow discharges. *Applied Physics Letters*, 25(3):138, 1974.
- [37] Jeffrey I. Levatter and Shao-Chi Lin. Necessary conditions for the homogeneous formation of pulsed avalanche discharges at high gas pressures. *Journal of Applied Physics*, 51(1):210, 1980.
- [38] L M Vasilyak, S V Kostyuchenko, N N Kudryavtsev, and I V Filyugin. Fast ionisation waves under electrical breakdown conditions. *Physics-Uspekhi*, 37(3):247–268, March 1994.
- [39] B B Slavin and P I Sopin. Breakdown of a neutral gas by ionizing waves of the gradient of a negative potential. *High Temperature I*, 30(1):1–9, 1992.
- [40] S M Starikovskaia, N B Anikin, S V Pancheshnyi, D V Zatsepin, and A Yu Starikovskii. Pulsed breakdown at high overvoltage: development, propagation and energy branching. *Plasma Sources Science and Technology*, 10(2):344–355, May 2001.
- [41] Sergey V. Pancheshnyi, Deanna A. Lacoste, Anne Bourdon, and Christophe O. Laux. Ignition of Propane–Air Mixtures by a Repetitively Pulsed Nanosecond Discharge. *IEEE Transactions on Plasma Science*, 34(6):2478–2487, December 2006.
- [42] S M Starikovskaia. Plasma assisted ignition and combustion. *Journal of Physics D: Applied Physics*, 39(16):R265–R299, August 2006.
- [43] Igor V. Adamovich, Walter R. Lempert, Munetake Nishihara, J. William Rich, and Yurii G. Utkin. Repetitively Pulsed Nonequilibrium Plasmas for Magnetohydrodynamic Flow Control and Plasma-Assisted Combustion. *Journal of Propulsion and Power*, 24(6):1198–1215, November 2008.

- [44] S.O. Macheret, M.N. Shneider, and R.B. Miles. Modeling of air plasma generation by repetitive high-voltage nanosecond pulses. *IEEE Transactions on Plasma Science*, 30(3):1301–1314, June 2002.
- [45] Steven J Schneider, Hani Kamhawi, and Isaiah M Blankson. Efficient Ionization Investigation for Flow Control and Energy Extraction. *AIAA 47th Aerospace Sciences Meeting*, 2009.
- [46] A Yu Starikovskii, A A Nikipelov, M M Nudnova, and D V Roupasov. SDBD plasma actuator with nanosecond pulse-periodic discharge. *Plasma Sources Science and Technology*, 18(3):034015, August 2009.
- [47] Igor V Adamovich, Munetake Nishihara, Inchul Choi, Mruthunjaya Uddi, and Walter R Lempert. Energy coupling to the plasma in repetitive nanosecond pulse discharges. *Physics of Plasmas*, 16(11):113505, 2009.
- [48] Dmitry S. Nikandrov, Lev D. Tsendin, Vladimir I. Kolobov, and Robert R. Arslanbekov. Theory of Pulsed Breakdown of Dense Gases and Optimization of the Voltage Waveform. *IEEE Transactions on Plasma Science*, 36(1):131–139, 2008.
- [49] H Ayan, D Staack, G Fridman, A Gutsol, Y Mukhin, A Starikovskii, A Fridman, and G Friedman. Application of nanosecond-pulsed dielectric barrier discharge for biomedical treatment of topographically non-uniform surfaces. *Journal of Physics D: Applied Physics*, 42(12):125202, June 2009.
- [50] John E. Foster, Grigory Adamovsky, Sarah Nowak Gucker, and Isaiah M. Blankson. A Comparative Study of the Time-Resolved Decomposition of Methylene Blue Dye Under the Action of a Nanosecond Repetitively Pulsed DBD Plasma Jet Using Liquid Chromatography and Spectrophotometry. *IEEE Transactions on Plasma Science*, 41(3):503–512, March 2013.
- [51] K H Becker, U Kogelschatz, K H Schoenbach, and R J Barker. *Non-Equilibrium Air Plasmas at Atmospheric Pressure*. Institute of Physics Publishing, Bristol, UK, 2005.
- [52] Guillaume Pilla, David Galley, Deanna a. Lacoste, Franois Lacas, Denis Veynante, and Christophe O. Laux. Stabilization of a Turbulent Premixed Flame Using a Nanosecond Repetitively Pulsed Plasma. *IEEE Transactions on Plasma Science*, 34(6):2471–2477, December 2006.
- [53] Munetake Nishihara, J. William Rich, Walter R Lempert, Igor V Adamovich, and Sivaram Gogineni. Low-temperature M=3 flow deceleration by Lorentz force. *Physics of Fluids*, 18(8):086101, 2006.
- [54] Ainan Bao, Yurii G. Utkin, Saurabh Keshav, Guofeng Lou, and Igor V. Adamovich. Ignition of Ethylene–Air and Methane–Air Flows by Low-Temperature Repetitively Pulsed Nanosecond Discharge Plasma. *IEEE Transactions on Plasma Science*, 35(6):1628–1638, December 2007.

- [55] Guofeng Lou, Ainan Bao, Munetake Nishihara, Saurabh Keshav, Yurii G Utkin, J William Rich, Walter R Lempert, and Igor V Adamovich. Ignition of premixed hydrocarbon–air flows by repetitively pulsed, nanosecond pulse duration plasma. *Proceedings of the Combustion Institute*, 31(2):3327–3334, January 2007.
- [56] David Z Pai, Gabi D Stancu, Deanna a Lacoste, and Christophe O Laux. Nanosecond repetitively pulsed discharges in air at atmospheric pressure—the glow regime. *Plasma Sources Science and Technology*, 18(4):045030, November 2009.
- [57] Yvette Zuzeek, Inchul Choi, Mruthunjaya Uddi, Igor V Adamovich, and Walter R Lempert. Pure rotational CARS thermometry studies of low-temperature oxidation kinetics in air and ethene–air nanosecond pulse discharge plasmas. *Journal of Physics D: Applied Physics*, 43(12):124001, March 2010.
- [58] Munetake Nishihara, Keisuke Udagawa Takashima, John R. Bruzzese, Igor V. Adamovich, and Datta Gaitonde. Experimental and Computational Studies of Low-Temperature Mach 4 Flow Control by Lorentz Force. *Journal of Propulsion and Power*, 27(2):467–476, March 2011.
- [59] Tsuyohito Ito, Dirk Luggenhölscher, Kazunobu Kobayashi, Sarah Müller, Uwe Czarnetzki, and Satoshi Hamaguchi. Electric field measurement in an atmospheric or higher pressure gas by coherent Raman scattering of nitrogen. *Journal of Physics D: Applied Physics*, 42(9):092003, May 2009.
- [60] Osaka University) Ito, Tsuyohito (Frontier Research Base For Global Young Researchers, Osaka University) Kobayashi, Kazunobu (Center For Atomic And Molecular Technologies, Ruhr-University Bochum) Czarnetzki, Uwe (Institute For Plasma And Atomic Physics, and Osaka University) Hamaguchi, Satoshi (Center For Atomic And Molecular Technologies. Rapid formation of electric field profiles in repetitively pulsed high-voltage high-pressure nanosecond discharges. *Journal of Physics D: Applied Physics*, 43(6):062001, February 2010.
- [61] Sarah Müller, Dirk Luggenhölscher, and Uwe Czarnetzki. Ignition of a nanosecond-pulsed near atmospheric pressure discharge in a narrow gap. *Journal of Physics D: Applied Physics*, 44(16):165202, April 2011.
- [62] S. O. Macheret, M. N. Shneider, and R. C. Murray. Ionization in strong electric fields and dynamics of nanosecond-pulse plasmas. *Physics of Plasmas*, 13(2):023502, 2006.
- [63] M. Laroussi and X. Lu. Room-temperature atmospheric pressure plasma plume for biomedical applications. *Applied Physics Letters*, 87(11):113902, 2005.
- [64] XinPei Lu and Mounir Laroussi. Dynamics of an atmospheric pressure plasma plume generated by submicrosecond voltage pulses. *Journal of Applied Physics*, 100(6):063302, 2006.
- [65] J. L. Walsh, J. J. Shi, and M. G. Kong. Submicrosecond pulsed atmospheric glow discharges sustained without dielectric barriers at kilohertz frequencies. *Applied Physics Letters*, 89(16):161505, 2006.

- [66] J L Walsh, D X Liu, F Iza, M Z Rong, and M G Kong. Contrasting characteristics of sub-microsecond pulsed atmospheric air and atmospheric pressure helium–oxygen glow discharges. *Journal of Physics D: Applied Physics*, 43(3):032001, January 2010.
- [67] G V Naidis. Modelling of streamer propagation in atmospheric-pressure helium plasma jets. *Journal of Physics D: Applied Physics*, 43(40):402001, October 2010.
- [68] Doug Breden, Kenji Miki, and Laxminarayan L. Raja. Computational study of cold atmospheric nanosecond pulsed helium plasma jet in air. *Applied Physics Letters*, 99(11):111501, 2011.
- [69] Keisuke Takashima, Igor V. Adamovich, Zhongmin Xiong, Mark J. Kushner, Svetlana Starikovskaia, Uwe Czarnetzki, and Dirk Luggenhölscher. Experimental and modeling analysis of fast ionization wave discharge propagation in a rectangular geometry. *Physics of Plasmas*, 18(8):083505, 2011.
- [70] G. Nersisyan, T. Morrow, and W. G. Graham. Measurements of helium metastable density in an atmospheric pressure glow discharge. *Applied Physics Letters*, 85(9):1487, August 2004.
- [71] Michael A. Lieberman and Allan J. Lichtenberg. *Principles of Plasma Discharges and Materials Processing*. John Wiley & Sons, Inc., Hoboken, NJ, USA, 2nd edition, April 2005.
- [72] A. E. Siegman. *Lasers*. University Science Books, Sausalito, CA, 1986.