

DAILY DRILLING REPORT (DDR)

WELL IDENTIFICATION & METADATA

Well Name: A-21 / Tipam North	Report Date: 2026-08-28
API / UWI: OIL-A21-2026-007	Report No: Day 10
Latitude: 26.201445 N	Spud Date: 2026-08-15
Longitude: 93.784112 E	Operator: Oil India Limited

Lease/Block: Tipam North / Block 14 Rig Name: BoreMax
Rig 3

OPERATIONS SUMMARY & DEPTH TRACKING

Current MD (m): 2,418	Midnight MD (m): 2,375
-----------------------	------------------------

<i>Current TVD (m): 2,102</i>	<i>Progress (m): 43</i>
<i>Avg ROP (m/hr): 9.2</i>	<i>Rotating Hours: 12.8</i>

Formation: Tipam - Upper sand Hole section: 12.25 in

CHRONOLOGICAL TIME LOG (24-HOUR PROFILE)

From To Hrs Code Operational Description

<i>06:00 10:00 4.0 P</i>	<i>Run BHA for Tipam; circulate.</i>
--------------------------	---

10:00 16:00 6.0 D Drill 12.25 in Tipam sand 2,375-2,400 m; no losses.

16:00 20:00 4.0 D Stuck pipe warning at 2,418 m; overpull 12 klb, torque 8 kNm.

20:00 04:00 8.0 NPT Work string, backream; 4 h NPT stuck.

<i>04:00 06:00 2.0 P</i>	<i>Circulate; hole cleaning.</i>
--------------------------	----------------------------------

DRILLING FLUID PROPERTIES

Mud Type: Water-Based Mud (WBM) Mud Weight (SG):
1.18

Viscosity (s/qt): 44	PV / YP: 15 / 10
Oil/Water Ratio: —	Chlorides (mg/L): 12,000

NWIS DEMO DATASET - SYNTHETIC OPERATIONAL RECORD Page 1

DDR CONTINUATION - RISK & OFFSET WELL INTELLIGENCE

FORMATION / HYDROCARBON INDICATORS

Interval (m) Formation Observed condition Risk
interpretation

2,320 - 2,400 Tipam Upper sand Unconsolidated sand,

cavings Stuck pipe watch

2,400 - 2,418 Tipam Pack-off tendency Monitor
torque/drag

2,418 - 2,500 Tipam Lower Shale stringer	Mud lubricity
---	---------------

OPERATIONAL EVENTS EXTRACTED FOR NWIS

Time Event Depth (m) Severity Mitigation / lesson learned
18:30 Stuck pipe tendency 2,418 High Backream, reduce
WOB; stuck at 2,418 m.

19:10 High torque 2,410 Medium Torque 8 → 12 kNm; add
lubricant.

20:15 NPT - stuck 2,418 Low Work pipe 4 h, free.

DIRECTIONAL SURVEY & NEARBY WELL CONTEXT

Survey MD (m) Inclination Azimuth TVD (m) Offset well /
separation

2,350 18.2 deg 132.4 deg 2,080 A-17 / 2.6 km

2,400 19.1 deg 133.0 deg 2,095 A-08 / 2.9 km

2,418 19.8 deg 133.8 deg 2,102 A-12 / 2.2 km

NWIS DECISION NOTE

Recommendation: Different formation (Tipam) – no loss, dominant stuck pipe mechanism. Not an analogue for Barail loss;

use for negative control.

CASING / CEMENTING PREVIEW

Planned casing Setting depth Cement objective Watch item

9 5/8 in 2,500 m Isolate Tipam Cavings risk

TOC target 1,900 m Surface –

NWIS DEMO DATASET - SYNTHETIC

OPERATIONAL RECORD Page 2