



## BREAK-UP® Professional Oven & Grill Cleaner

Version Number: 3

Preparation date: 2018-08-24

### 1. IDENTIFICATION

**Product name:** BREAK-UP® Professional Oven & Grill Cleaner

**Product Code:** CBD991206

**SDS #:** MS0801099

**Recommended use:**

- Industrial/Institutional
- Oven and Grill Cleaner
- This product is intended to be used neat.

**Uses advised against:** Uses other than those identified are not recommended

**Manufacturer, importer, supplier:**

US Headquarters  
Diversey, Inc.  
2415 Cascade Pointe Blvd.  
Charlotte, NC 28208  
Phone: 1-888-352-2249  
SDS Internet Address: <https://sds.diversey.com>

Canadian Headquarters  
Diversey Canada, Inc.  
3755 Laird Road Units 8-11  
Mississauga, Ontario L5L 0B3  
Phone: 1-800-668-7171

**Emergency telephone number:** 1-800-851-7145; 1-651-917-6133 (Int'l)

### 2. HAZARDS IDENTIFICATION

**Classification for the undiluted product**

|                                   |                                         |
|-----------------------------------|-----------------------------------------|
| Skin corrosion/irritation         | Category 1B                             |
| Serious eye damage/eye irritation | Category 1                              |
| Flammability                      | Extremely flammable aerosol, Category 1 |
| Metal Corrosion:                  | Category 1                              |



**Signal Word:**

**Danger.**

**Hazard and Precautionary Statements**

**EXTREMELY FLAMMABLE AEROSOL. CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY BE CORROSIVE TO METALS.**

Causes burns/ serious damage to mouth, throat and stomach. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Keep only in original container. Do not pierce or burn, even after use. Do not incinerate. Do not breathe vapor or spray. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. Wear chemical-splash goggles, long chemical-resistant gloves, protective clothing and protective footwear when spraying and wiping. Do not spray towards face. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Absorb spillage to prevent material damage. Store in corrosive-resistant container with a resistant inner liner. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION: DO NOT MIX WITH AMMONIA, BLEACH OR OTHER CHLORINATED COMPOUNDS. Mix only with water. Can react to release hazardous gases. May vigorously react with strong alkaline products resulting in spattering and excessive heat.

**Health hazards not otherwise classified (HHNOC)** - Not applicable  
**Physical hazards not otherwise classified (PHNOC)** - Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Classified Ingredients

| Ingredient(s)                 | CAS #     | Weight % |
|-------------------------------|-----------|----------|
| Diethylene glycol butyl ether | 112-34-5  | 10 - 20% |
| Sodium hydroxide              | 1310-73-2 | 3 - < 5% |
| Butane                        | 106-97-8  | 1 - < 3% |
| Isobutane                     | 75-28-5   | 1 - < 3% |
| Monoethanolamine              | 141-43-5  | 1 - < 3% |

\*Exact percentages are being withheld as trade secret information

### 4. FIRST AID MEASURES

#### Undiluted Product:

**Eyes:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

**Skin:** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

**Inhalation:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**Ingestion:** IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

**Most Important Symptoms/Effects:** Burning. Coughing and/ or wheezing.

**Immediate medical attention and special treatment needed** Not applicable.

### 5. FIRE-FIGHTING MEASURES

**Specific methods:** No special methods required  
**Suitable extinguishing media:** Dry chemical, water spray, foam, carbon dioxide.  
**Specific hazards:** Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol. Corrosive material (See sections 8 and 10).

**Special protective equipment for firefighters:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Extinguishing media which must not be used for safety reasons:** No information available.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Remove all sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Use personal protective equipment. Do not get in eyes, on skin, or on clothing.  
**Environmental precautions and clean-up methods:** Eliminate all ignition sources. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. ALWAYS WEAR LONG CHEMICAL-RESISTANT GLOVES, CHEMICAL-SPLASH GOGGLES AND PROTECTIVE FOOTWEAR WHEN SPRAYING AND WIPING. Do not spray toward face. Wash hands and arms after use. Do not spray on or let spray contact pilot light, electrical connections, switches, light bulbs, heating elements, receptacles, or thermostats. Spray may cause electric short. Do not let product contact floor coverings, linoleum, aluminum, copper, chrome, painted surfaces or plastics. Do not use on continuous or self-cleaning ovens. Do not taste or swallow. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Can react to release hazardous gases. EXTREMELY FLAMMABLE AEROSOL. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. PRESSURIZED CONTAINER: Do not pierce or burn, even after use. Do not incinerate. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Mix only with water. Do not mix with any other product or chemical. May vigorously react with acids resulting in spattering and excessive heat. Absorb spillage to prevent material damage. FOR COMMERCIAL AND

INDUSTRIAL USE ONLY.

**Storage:** NFPA 30B Level 1 Aerosol. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Store in corrosive-resistant container with a resistant inner liner.

**Aerosol Level (if applicable) :** Level 1

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines:

| Ingredient(s)                 | CAS #     | ACGIH                         | OSHA                                     |
|-------------------------------|-----------|-------------------------------|------------------------------------------|
| Diethylene glycol butyl ether | 112-34-5  | 10 ppm (TWA)                  | -                                        |
| Sodium hydroxide              | 1310-73-2 | 2 mg/m <sup>3</sup> (Ceiling) | 2 mg/m <sup>3</sup> (TWA)                |
| Butane                        | 106-97-8  | 1000 ppm (STEL)               | -                                        |
| Isobutane                     | 75-28-5   | 1000 ppm (STEL)               | -                                        |
| Monoethanolamine              | 141-43-5  | 6 ppm (STEL)<br>3 ppm (TWA)   | 3 ppm (TWA)<br>6 mg/m <sup>3</sup> (TWA) |

### Undiluted Product:

#### Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

#### Personal Protective Equipment

**Eye protection:** Chemical-splash goggles.

**Hand protection:** Chemical-resistant gloves.

**Skin and body protection:** If major exposure is possible, wear suitable protective clothing and footwear.

**Respiratory protection:** In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Aerosol

**Evaporation Rate:** No information available

**Odor threshold:** No information available.

**Melting point/range:** Not determined

**Autoignition temperature:** No information available

**Solubility in other solvents:** No information available

**Density:** 8.75 lbs/gal 1.049 Kg/L

**Bulk density:** No information available

**Flash point (°F):** 19.4 °F -7 °C

**Viscosity:** No information available

**VOC:** 8.1 % \*

**Flammability (Solid or Gas):** Not applicable

**Sustained combustion:** Not applicable

**Explosion limits:** - upper: Not determined - lower: Not determined

**Color:** Opaque Tan

**Odor:** Citrus Slightly perfumed

**Boiling point/range:** Not determined

**Decomposition temperature:** Not determined

**Solubility:** Dispersible

**Relative Density (relative to water):** 1.049

**Vapor density:** No information available

**Vapor pressure:** No information available.

**Partition coefficient (n-octanol/water):** No information available

**Elemental Phosphorus:** 0.00 % by wt.

**pH:** 13

**Corrosion to metals:** Corrosive

\* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

## 10. STABILITY AND REACTIVITY

**Reactivity:** Not Applicable

**Stability:** The product is stable

**Possibility of hazardous reactions:** May vigorously react with acids resulting in spattering and excessive heat.

**Hazardous decomposition products:** None reasonably foreseeable.

**Materials to avoid:** Strong bases. Ammonia. Do not mix with chlorinated products (such as bleach). Do not mix with any other product or chemical unless specified in the use directions. Strong acids.

**Conditions to avoid:** Extremes of temperature and direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure:

Skin contact, Inhalation, Ingestion, Eye contact

**Delayed, immediate, or chronic effects and symptoms from short and long-term exposure**

**Skin contact:** Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed).

**Eye contact:** Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

**Ingestion:** Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea.

**Inhalation:** May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

**Sensitization:** No known effects.

**Target Organs (SE):** None known

**Target Organs (RE):** None known

**Numerical measures of toxicity**

ATE - Oral (mg/kg): >5000

ATE - Dermal (mg/kg): >5000

ATE - Inhalatory, mists (mg/l): >20

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity:** No information available.

**Persistence and Degradability:** No information available.

**Bioaccumulation:** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste from residues / unused products (undiluted product):** This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

**RCRA Hazard Class (undiluted product):** D001 Ignitable Waste D002 Corrosive Waste

**Contaminated Packaging:** Do not re-use empty containers.

**14. TRANSPORT INFORMATION**

**DOT (Ground) Bill of Lading Description:** LTD. QTY.

**IMDG (Ocean) Bill of Lading Description:** UN1950, AEROSOLS, 2.1, LTD. QTY.

**15. REGULATORY INFORMATION****International Inventories at CAS# Level**

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).



**WARNING:** This product can expose you to chemicals including diethanolamine, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**RIGHT TO KNOW (RTK)**

| Ingredient(s)                 | CAS #     | MARTK: | NJRTK: | PARTK: | RIRTK: |
|-------------------------------|-----------|--------|--------|--------|--------|
| Water                         | 7732-18-5 | -      | -      | -      | -      |
| Diethylene glycol butyl ether | 112-34-5  | -      | X      | -      | -      |
| Sodium hydroxide              | 1310-73-2 | X      | X      | X      | X      |
| Butane                        | 106-97-8  | X      | X      | X      | -      |
| Isobutane                     | 75-28-5   | X      | X      | X      | -      |

|                  |          |   |   |   |   |
|------------------|----------|---|---|---|---|
| Monoethanolamine | 141-43-5 | X | X | X | - |
|------------------|----------|---|---|---|---|

#### **CERCLA/ SARA**

| Ingredient(s)                 | CAS #     | Weight % | CERCLA/SARA RQ (lbs) | Section 302 TPQ (lbs) | Section 313 |
|-------------------------------|-----------|----------|----------------------|-----------------------|-------------|
| Diethylene glycol butyl ether | 112-34-5  | 10 - 20% |                      |                       | X           |
| Sodium hydroxide              | 1310-73-2 | 3 - < 5% | 1000                 |                       |             |

| Ingredient(s)                 | CAA HAP | CAA ODS | CWA Priority Pollutants |
|-------------------------------|---------|---------|-------------------------|
| Diethylene glycol butyl ether | X       |         |                         |

#### **Canadian Regulations**

| Ingredient(s)                 | CAS #    | NPRI |
|-------------------------------|----------|------|
| Diethylene glycol butyl ether | 112-34-5 | X    |

### **16. OTHER INFORMATION**

#### **NFPA (National Fire Protection Association)**

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

**Health** 3

**Flammability** 4

**Instability** 0

**Version Number:** 3

**Preparation date:** 2018-08-24

**Reason for revision:**

Not applicable

**Prepared by:**

NAPRAC

**Additional advice:**

• Contains an added fragrance, see "Odor" heading in section 9 for specific description

*Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.*