

Safety Data Sheet
acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915,
1926

1 Identification

- **Product identifier**
 - Trade name: ***EP75 Graffiti Remover***
 - **Article number:** 2087210001, 2087278001
 - **Recommended use** Graffiti remover
 - **Restrictions on use**
All other uses than those indicated on the product label and technical data sheet.
- **Details of the supplier of the safety data sheet**
 - **Manufacturer:**
Avmor LTD
950, Michelin
Laval, QC,
Canada
H7L 5C1
1-800-387-8074
www.avmor.com
 - **Client Identification Number** 119100
 - **Emergency telephone number:** CANUTEC 1-613-996-6666

2 Hazard(s) identification

- **Classification of the product:**



Eye Irrit. 2A H319 CAUSES SERIOUS EYE IRRITATION.

- **Label elements**

- **Hazard pictograms:**



GHS07

- **Signal word:** Warning
- **Hazard statements:**
H319 CAUSES SERIOUS EYE IRRITATION.
- **Precautionary statements**
 - P280 Wear protective gloves and eye or face protection.
 - P264 Wash thoroughly after handling.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P337+P313 IF EYE IRRITATION PERSISTS: Get medical attention.

(Contd. on page 2)

Safety Data Sheet
acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915,
1926

Trade name: **EP75 Graffiti Remover**

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 0
Reactivity = 0

- **Hazard not otherwise classified** None
- **Notes:** For the wording of the listed abbreviations refer to section 16.

3 Composition/information on ingredients

- **Dangerous components:**

C A S
(% w/w)

C o m p o n e n t

627-93-0	dimethyl adipate	10-<25%
577-11-7	docusate sodium	3-<10%
1569-01-3	1-propoxypropan-2-ol	3-<10%
1119-40-0	dimethyl glutarate	3-<10%

4 First-aid measures

- **General information:**
- **After inhalation:**
Rarely cause discomfort; supply fresh air and consult doctor in case of complaints.
- **After skin contact:** May induce a skin irritation.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After ingestion:** If symptoms persist consult a doctor.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.

5 Fire-fighting measures

- **Suitable extinguishing media**
- **Suitable extinguishing media** Use fire fighting measures that suit the environment.
- **Specific hazards arising from the product**
In case of accidental fire and extreme heat conditions, the following gaseous products can be released after water evaporation: hydrocarbons, carbon monoxides and dioxides (COx) and nitrogen dioxide (NOx).
- **Advice for firefighters**
 - **Special protective equipment and precautions for fire-fighters** No special measures required.
- **Additional information** This product is not flammable.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear recommended protective equipment(s). Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety Data Sheet
acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915,
1926

Trade name: **EP75 Graffiti Remover**

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
Surround and absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation at the workplace.
Prevent formation of aerosols.
- **Conditions for safe storage, including any incompatibilities**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Conditions for safe storage, including any incompatibilities**
Keep in the original receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Appropriate engineering controls** Ensure appropriate aeration and ventilation.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
 - **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
 - **Personal protective equipment:**



Tightly sealed goggles

- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes.
- **Breathing equipment:** Not required.
- **Protection of hands:** Not required.
- **Eye protection:** Tightly sealed goggles
- **Body protection:** No special measures required.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
 - **General Information**
 - **Appearance:**
 - **Form:** Liquid
 - **Colour:** Colorless.
 - **Odour:** Characteristic

(Contd. on page 4)

Safety Data Sheet

acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915, 1926

Trade name: **EP75 Graffiti Remover**

(Contd. of page 3)

· Odour threshold:	Not determined.
· pH-value at 25 °C:	5.0-7.0
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C
· Flash point:	53 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	252 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure at 20 °C:	23 hPa
· Density at 25 °C:	1.020-1.040 g/cm ³
· Relative density	Not determined.
· Vapour density (air=1)	<1 (aqueous solution)
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Solvent content:	
· Organic solvents:	0.0 %

10 Stability and reactivity

- **Reactivity** Not determined.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid freezing and extreme heat conditions.
- **Incompatible materials:** This product may react with strong oxidizing agents.
- **Hazardous decomposition products:**
In case of decomposition: carbon monoxide and carbon dioxide and traces of volatile halogenated compounds.

11 Toxicological information

- **Information on the likely routes of exposure** Skin and eyes contact

(Contd. on page 5)

Safety Data Sheet

acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915, 1926

Trade name: **EP75 Graffiti Remover**

(Contd. of page 4)

- Acute toxicity:
- Numerical measures of toxicity

Components Mean of exposure	Type	Value (Species)
ATE (Acute Toxicity Estimates)		
Oral	LD50	14067 mg/kg (rat)
Dermal	LD50	8568 mg/kg
Inhalative	LC50 (4 h)	55 mg/L (rat)

627-93-0 dimethyl adipate		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 (4 h)	>11 mg/L (rat)
Irritation of eyes	OECD, guideline 405	cat. 2B (rabbit)
Sensitization	OECD, guideline 406	cat. 2 (guinea pig)

- **Symptoms related to the physical, chemical and toxicological characteristics**
- **by inhalation:**
Vapours may cause irritation to the airways. Inhalation of larger amounts may induce discomfort, nausea, dizziness, headache, narcosis, and unconsciousness.
- **If on the skin:** May cause irritation by prolonged contact with skin.
- **If on the eye:** Irritating effect.
- **after ingestion:**
May cause irritation of the gastrointestinal tract, nausea, vomiting and headache.
- **Sensitization:** No sensitizing effects known.
- **Delayed and immediate effects, and chronic effects from short-term and long-term exposure**
Prolonged or frequent contact can cause eczema and inflammation of the skins as a result of degreasing.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.

12 Ecological information

- **Toxicity**

· Aquatic toxicity:	
627-93-0 dimethyl adipate	
EC50 (48 h, OECD guideline 202)	72 mg/L (daphnia magna [water flea])
EC50 (72 h, OECD guideline 201)	>100 mg/L (algae)
LC50 (96 h, OECD guideline 203)	18-24 mg/L (pimephales promelas [fathead minnow])

(Contd. on page 6)

Safety Data Sheet
acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915,
1926

Trade name: **EP75 Graffiti Remover**

(Contd. of page 5)

- **Persistence and degradability**
Organic compounds of this product are readily biodegradable according to the OECD Guideline 301.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** Does not accumulate in organisms
 - **Mobility in soil** No further relevant information available.
- **Ecotoxicity** No relevant information available
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system unless significantly diluted or neutralized.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.
 - **Recommended cleansing agent:** Water.

14 Transport information

· DOT, ADN, IMDG, IATA	Not regulated.
· UN proper shipping name · DOT	Not regulated.
· Transport hazard class(es) · Class	Not regulated.
· Packing group · DOT	Not regulated.
· Environmental hazards: · Marine pollutant:	No
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet
acc. to SOR/2015-17 and OSHA 29 CFR Parts 1910, 1915,
1926

Trade name: **EP75 Graffiti Remover**

(Contd. of page 6)

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of creation/last revision:** 04/28/2015

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

CA