



## Safety Data Sheet

Copyright, 2017, 3M Canada Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |            |                         |            |
|------------------------|------------|-------------------------|------------|
| <b>Document group:</b> | 11-4257-9  | <b>Version number:</b>  | 31.01      |
| <b>Issue Date:</b>     | 2017/05/16 | <b>Supersedes Date:</b> | 2016/11/17 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Super 77 Spray Adhesive

##### Product Identification Numbers

|                |                |                |                |                |
|----------------|----------------|----------------|----------------|----------------|
| 62-4437-0921-7 | 62-4437-0922-5 | 62-4437-0925-8 | 62-4437-0926-6 | 62-4437-0927-4 |
| 62-4437-0928-2 | 62-4437-0929-0 | 62-4437-0930-8 | 62-4437-0931-6 | 62-4437-0933-2 |
| 62-4437-0934-0 | 62-4437-4026-1 | 62-4437-4030-3 | 62-4437-4830-6 | 62-4437-4835-5 |
| 62-4437-4840-5 | 62-4437-4920-5 | 62-4437-4921-3 | 62-4437-4925-4 | 62-4437-4926-2 |
| 62-4437-4930-4 | 62-4437-4931-2 | 62-4437-4933-8 | 62-4437-4935-3 | 62-4437-4936-1 |
| 62-4437-4937-9 | 62-4437-4938-7 | 62-4437-4939-5 | 62-4437-4950-2 | 62-4437-4955-1 |
| 62-4437-9999-4 | AS-0192-9224-7 | CS-0406-2131-3 | CS-0406-6984-1 | CS-0406-7003-9 |
| H0-0015-4394-3 | H0-0016-4533-4 | LT-0000-8922-8 | UU-0040-2681-9 | XT-0615-9197-7 |

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Aerosol Adhesive, Industrial use

##### Restrictions on use

Not Applicable

#### 1.3. Supplier's details

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| <b>Company:</b>   | 3M Canada Company                                                      |
| <b>Division:</b>  | Industrial Adhesives and Tapes Division                                |
| <b>Address:</b>   | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| <b>Telephone:</b> | (800) 364-3577                                                         |
| <b>Website:</b>   | www.3M.ca                                                              |

#### 1.4. Emergency telephone number

Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place:

CS-0406-7294-4, CS-0406-7057-5

## 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.

Gas Under Pressure: Liquefied gas.

Reproductive Toxicity: Category 2.

Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

### Pictograms



### Hazard statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.

Causes damage to organs: cardiovascular system |

### Precautionary statements

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

#### Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

None known.

18% of the mixture consists of ingredients of unknown acute dermal toxicity.

18% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

This material is a mixture.

| <b>Ingredient</b>                     | <b>C.A.S. No.</b> | <b>% by Wt</b> |
|---------------------------------------|-------------------|----------------|
| Non-Hazardous Components              | Trade Secret      | 15 - 40        |
| Cyclohexane                           | 110-82-7          | 10 - 30        |
| Hydrotreated light naptha (petroleum) | 64742-49-0        | 10 - 30        |
| Dimethyl Ether                        | 115-10-6          | 7 - 13         |
| Isobutane                             | 75-28-5           | 7 - 13         |
| Propane                               | 74-98-6           | 7 - 13         |
| Hexane                                | 110-54-3          | < 1            |

Non-Hazardous Components is a non-hazardous Trade Secret material according to WHMIS criteria.

Hydrotreated light naptha (petroleum) is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Cyclohexane is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Dimethyl Ether is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### **Inhalation:**

Remove person to fresh air. Get medical attention.

##### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

##### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

##### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

Substance

Condition

## 3M™ Super 77 Spray Adhesive

Aldehydes  
Carbon monoxide  
Carbon dioxide  
Toxic Vapor, Gas, Particulate

During Combustion  
During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Collect as much of the spilled material as possible using non-sparking tools. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Protect from sunlight. Store in a well-ventilated place. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient     | C.A.S. No. | Agency | Limit type               | Additional Comments |
|----------------|------------|--------|--------------------------|---------------------|
| Hexane         | 110-54-3   | ACGIH  | TWA:50 ppm               | SKIN                |
| Cyclohexane    | 110-82-7   | ACGIH  | TWA:100 ppm              |                     |
| Dimethyl Ether | 115-10-6   | AIHA   | TWA:1880 mg/m3(1000 ppm) |                     |

## 3M™ Super 77 Spray Adhesive

|             |         |       |                              |  |
|-------------|---------|-------|------------------------------|--|
| Propane     | 74-98-6 | ACGIH | Limit value not established: |  |
| Natural gas | 75-28-5 | ACGIH | Limit value not established: |  |
| Isobutane   | 75-28-5 | ACGIH | STEL:1000 ppm                |  |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                              |                                              |
|------------------------------|----------------------------------------------|
| Physical state               | Gas                                          |
| Appearance/Odour             | light cream coloured, sweet/fruity odour.    |
| Odour threshold              | No Data Available                            |
| pH                           | Not Applicable                               |
| Melting point/Freezing point | No Data Available                            |
| Flash Point                  | -41.1 °C [Test Method: Tagliabue Closed Cup] |
| Evaporation rate             | 1.9 [Ref Std: ETHER=1]                       |
| Flammability (solid, gas)    | Flammable Aerosol: Category 1.               |
| Flammable Limits(LEL)        | Approximately 1.5 % volumen                  |
| Flammable Limits(UEL)        | Approximately 8.6 % volumen                  |
| Vapour Density               | 2.97 [Ref Std: AIR=1]                        |
| Density                      | 0.697 g/ml                                   |

|                                                |                                                |
|------------------------------------------------|------------------------------------------------|
| <b>Relative density</b>                        | 0.697 [Ref Std: WATER=1]                       |
| <b>Water solubility</b>                        | Nil                                            |
| <b>Solubility- non-water</b>                   | No Data Available                              |
| <b>Partition coefficient: n-octanol/ water</b> | No Data Available                              |
| <b>Autoignition temperature</b>                | No Data Available                              |
| <b>Decomposition temperature</b>               | Not Applicable                                 |
| <b>Viscosity</b>                               | Not Applicable                                 |
| <b>Molecular weight</b>                        | No Data Available                              |
| <b>Volatile Organic Compounds</b>              | 75 % [Test Method:calculated per CARB title 2] |
| <b>Heat of Combustion</b>                      | <=43.5 kJ/g                                    |
| <b>Solids Content</b>                          | 15 - 40 %                                      |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Intentional concentration and inhalation may be harmful or fatal. Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal

## 3M™ Super 77 Spray Adhesive

discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

### Skin Contact:

Prolonged or repeated exposure may cause:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

### Additional Health Effects:

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name                                  | Route                      | Species | Value                                          |
|---------------------------------------|----------------------------|---------|------------------------------------------------|
| Overall product                       | Dermal                     |         | No data available; calculated ATE >5,000 mg/kg |
| Overall product                       | Inhalation-Vapor(4 hr)     |         | No data available; calculated ATE >50 mg/l     |
| Overall product                       | Ingestion                  |         | No data available; calculated ATE >5,000 mg/kg |
| Hydrotreated light naptha (petroleum) | Dermal                     | Rabbit  | LD50 > 3,160 mg/kg                             |
| Hydrotreated light naptha (petroleum) | Inhalation-Vapor (4 hours) | Rat     | LC50 > 14.7 mg/l                               |
| Hydrotreated light naptha (petroleum) | Ingestion                  | Rat     | LD50 > 5,000 mg/kg                             |
| Isobutane                             | Inhalation-Gas (4 hours)   | Rat     | LC50 276,000 ppm                               |
| Propane                               | Inhalation-Gas (4 hours)   | Rat     | LC50 > 200,000 ppm                             |
| Cyclohexane                           | Dermal                     | Rat     | LD50 > 2,000 mg/kg                             |
| Cyclohexane                           | Inhalation-Vapor (4 hours) | Rat     | LC50 > 32.9 mg/l                               |
| Cyclohexane                           | Ingestion                  | Rat     | LD50 6,200 mg/kg                               |
| Non-Hazardous Components              | Dermal                     |         | LD50 estimated to be > 5,000 mg/kg             |
| Non-Hazardous Components              | Ingestion                  |         | LD50 estimated to be 2,000 - 5,000 mg/kg       |
| Dimethyl Ether                        | Inhalation-Gas (4 hours)   | Rat     | LC50 164,000 ppm                               |
| Hexane                                | Dermal                     | Rabbit  | LD50 > 2,000 mg/kg                             |
| Hexane                                | Inhalation-Vapor (4 hours) | Rat     | LC50 170 mg/l                                  |

**3M™ Super 77 Spray Adhesive**

|        |           |     |                     |
|--------|-----------|-----|---------------------|
| Hexane | Ingestion | Rat | LD50 > 28,700 mg/kg |
|--------|-----------|-----|---------------------|

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name                                  | Species                | Value                     |
|---------------------------------------|------------------------|---------------------------|
| Overall product                       |                        | Minimal irritation        |
| Hydrotreated light naptha (petroleum) | Rabbit                 | Irritant                  |
| Isobutane                             | Professional judgement | No significant irritation |
| Propane                               | Rabbit                 | Minimal irritation        |
| Cyclohexane                           | Rabbit                 | Mild irritant             |
| Non-Hazardous Components              | Professional judgement | Minimal irritation        |
| Hexane                                | Human and animal       | Mild irritant             |

**Serious Eye Damage/Irritation**

| Name                                  | Species                | Value                     |
|---------------------------------------|------------------------|---------------------------|
| Hydrotreated light naptha (petroleum) | Rabbit                 | Mild irritant             |
| Isobutane                             | Professional judgement | No significant irritation |
| Propane                               | Rabbit                 | Mild irritant             |
| Cyclohexane                           | Rabbit                 | Mild irritant             |
| Hexane                                | Rabbit                 | Mild irritant             |

**Skin Sensitization**

| Name                                  | Species    | Value          |
|---------------------------------------|------------|----------------|
| Hydrotreated light naptha (petroleum) | Guinea pig | Not classified |
| Hexane                                | Human      | Not classified |

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name                                  | Route    | Value                                                                        |
|---------------------------------------|----------|------------------------------------------------------------------------------|
| Hydrotreated light naptha (petroleum) | In Vitro | Not mutagenic                                                                |
| Isobutane                             | In Vitro | Not mutagenic                                                                |
| Propane                               | In Vitro | Not mutagenic                                                                |
| Cyclohexane                           | In Vitro | Not mutagenic                                                                |
| Cyclohexane                           | In vivo  | Some positive data exist, but the data are not sufficient for classification |
| Dimethyl Ether                        | In Vitro | Not mutagenic                                                                |
| Dimethyl Ether                        | In vivo  | Not mutagenic                                                                |
| Hexane                                | In Vitro | Not mutagenic                                                                |
| Hexane                                | In vivo  | Not mutagenic                                                                |

**Carcinogenicity**

| Name                                  | Route      | Species | Value                                                                        |
|---------------------------------------|------------|---------|------------------------------------------------------------------------------|
| Hydrotreated light naptha (petroleum) | Inhalation | Mouse   | Some positive data exist, but the data are not sufficient for classification |
| Dimethyl Ether                        | Inhalation | Rat     | Not carcinogenic                                                             |



**3M™ Super 77 Spray Adhesive**

|        |            |       |                                                                              |
|--------|------------|-------|------------------------------------------------------------------------------|
| Hexane | Dermal     | Mouse | Not carcinogenic                                                             |
| Hexane | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

| Name           | Route      | Value                                  | Species | Test result           | Exposure Duration    |
|----------------|------------|----------------------------------------|---------|-----------------------|----------------------|
| Cyclohexane    | Inhalation | Not classified for female reproduction | Rat     | NOAEL 24 mg/l         | 2 generation         |
| Cyclohexane    | Inhalation | Not classified for male reproduction   | Rat     | NOAEL 24 mg/l         | 2 generation         |
| Cyclohexane    | Inhalation | Not classified for development         | Rat     | NOAEL 6.9 mg/l        | 2 generation         |
| Dimethyl Ether | Inhalation | Not classified for development         | Rat     | NOAEL 40,000 ppm      | during organogenesis |
| Hexane         | Ingestion  | Not classified for development         | Mouse   | NOAEL 2,200 mg/kg/day | during organogenesis |
| Hexane         | Inhalation | Not classified for development         | Rat     | NOAEL 0.7 mg/l        | during gestation     |
| Hexane         | Ingestion  | Toxic to male reproduction             | Rat     | NOAEL 1,140 mg/kg/day | 90 days              |
| Hexane         | Inhalation | Toxic to male reproduction             | Rat     | LOAEL 3.52 mg/l       | 28 days              |

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

| Name                                  | Route      | Target Organ(s)                   | Value                                                                        | Species                 | Test result         | Exposure Duration |
|---------------------------------------|------------|-----------------------------------|------------------------------------------------------------------------------|-------------------------|---------------------|-------------------|
| Hydrotreated light naptha (petroleum) | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human and animal        | NOAEL Not available |                   |
| Hydrotreated light naptha (petroleum) | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification |                         | NOAEL Not available |                   |
| Hydrotreated light naptha (petroleum) | Ingestion  | central nervous system depression | May cause drowsiness or dizziness                                            | Professional judgement  | NOAEL Not available |                   |
| Isobutane                             | Inhalation | cardiac sensitization             | Causes damage to organs                                                      | Multiple animal species | NOAEL Not available |                   |
| Isobutane                             | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human and animal        | NOAEL Not available |                   |
| Isobutane                             | Inhalation | respiratory irritation            | Not classified                                                               | Mouse                   | NOAEL Not available |                   |
| Propane                               | Inhalation | cardiac sensitization             | Causes damage to organs                                                      | Human                   | NOAEL Not available |                   |
| Propane                               | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human                   | NOAEL Not available |                   |
| Propane                               | Inhalation | respiratory irritation            | Not classified                                                               | Human                   | NOAEL Not available |                   |
| Cyclohexane                           | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human and animal        | NOAEL Not available |                   |
| Cyclohexane                           | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human and animal        | NOAEL Not available |                   |
| Cyclohexane                           | Ingestion  | central nervous system depression | May cause drowsiness or dizziness                                            | Professional judgement  | NOAEL Not available |                   |

**3M™ Super 77 Spray Adhesive**

|                |            |                                   |                                                                              |        |                     |               |
|----------------|------------|-----------------------------------|------------------------------------------------------------------------------|--------|---------------------|---------------|
|                |            |                                   |                                                                              | nt     |                     |               |
| Dimethyl Ether | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Rat    | LOAEL 10,000 ppm    | 30 minutes    |
| Dimethyl Ether | Inhalation | cardiac sensitization             | Some positive data exist, but the data are not sufficient for classification | Dog    | NOAEL 100,000 ppm   | 5 minutes     |
| Hexane         | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human  | NOAEL Not available | not available |
| Hexane         | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Rabbit | NOAEL Not available | 8 hours       |
| Hexane         | Inhalation | respiratory system                | Not classified                                                               | Rat    | NOAEL 24.6 mg/l     | 8 hours       |

**Specific Target Organ Toxicity - repeated exposure**

| Name           | Route      | Target Organ(s)                                                                         | Value                                                                        | Species | Test result           | Exposure Duration     |
|----------------|------------|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------|-----------------------|-----------------------|
| Isobutane      | Inhalation | kidney and/or bladder                                                                   | Not classified                                                               | Rat     | NOAEL 4,500 ppm       | 13 weeks              |
| Cyclohexane    | Inhalation | liver                                                                                   | Not classified                                                               | Rat     | NOAEL 24 mg/l         | 90 days               |
| Cyclohexane    | Inhalation | auditory system                                                                         | Not classified                                                               | Rat     | NOAEL 1.7 mg/l        | 90 days               |
| Cyclohexane    | Inhalation | kidney and/or bladder                                                                   | Not classified                                                               | Rabbit  | NOAEL 2.7 mg/l        | 10 weeks              |
| Cyclohexane    | Inhalation | hematopoietic system                                                                    | Not classified                                                               | Mouse   | NOAEL 24 mg/l         | 14 weeks              |
| Cyclohexane    | Inhalation | peripheral nervous system                                                               | Not classified                                                               | Rat     | NOAEL 8.6 mg/l        | 30 weeks              |
| Dimethyl Ether | Inhalation | hematopoietic system                                                                    | Not classified                                                               | Rat     | NOAEL 25,000 ppm      | 2 years               |
| Dimethyl Ether | Inhalation | liver                                                                                   | Not classified                                                               | Rat     | NOAEL 20,000 ppm      | 30 weeks              |
| Hexane         | Inhalation | peripheral nervous system                                                               | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available   | occupational exposure |
| Hexane         | Inhalation | respiratory system                                                                      | Some positive data exist, but the data are not sufficient for classification | Mouse   | LOAEL 1.76 mg/l       | 13 weeks              |
| Hexane         | Inhalation | liver                                                                                   | Not classified                                                               | Rat     | NOAEL Not available   | 6 months              |
| Hexane         | Inhalation | kidney and/or bladder                                                                   | Not classified                                                               | Rat     | LOAEL 1.76 mg/l       | 6 months              |
| Hexane         | Inhalation | hematopoietic system                                                                    | Not classified                                                               | Mouse   | NOAEL 35.2 mg/l       | 13 weeks              |
| Hexane         | Inhalation | auditory system   immune system   eyes                                                  | Not classified                                                               | Human   | NOAEL Not available   | occupational exposure |
| Hexane         | Inhalation | heart   skin   endocrine system                                                         | Not classified                                                               | Rat     | NOAEL 1.76 mg/l       | 6 months              |
| Hexane         | Ingestion  | peripheral nervous system                                                               | Some positive data exist, but the data are not sufficient for classification | Rat     | NOAEL 1,140 mg/kg/day | 90 days               |
| Hexane         | Ingestion  | endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder | Not classified                                                               | Rat     | NOAEL Not available   | 13 weeks              |

**Aspiration Hazard**

| Name                                  | Value             |
|---------------------------------------|-------------------|
| Hydrotreated light naptha (petroleum) | Aspiration hazard |
| Cyclohexane                           | Aspiration hazard |
| Hexane                                | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

#### Trade Secret Information:

**HMIRA Registry Number:** 9906  
**Filing date:** 11-04-2016

**Claim status:** Claim for exemption has been filed.

**Date of decision:**

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health:** 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### HMIS Hazard Classification

**3M™ Super 77 Spray Adhesive**

**Health: 2    Flammability: 4    Physical Hazard: 0    Personal Protection: X** - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

|                        |            |                         |            |
|------------------------|------------|-------------------------|------------|
| <b>Document group:</b> | 11-4257-9  | <b>Version number:</b>  | 31.01      |
| <b>Issue Date:</b>     | 2017/05/16 | <b>Supersedes Date:</b> | 2016/11/17 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**