

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND OF THE COMPANY

Identification of Preparation: OX LIME
Date of Safety Data Sheet: January 16, 2017
Use of Preparation: Cleaner.
Company Identification: Action Industrial
Flamborough Ontario L9H 5E1

Company Emergency Telephone Number: Emergency Phone: 866-731-4329

Transportation Emergency Telephone Number: CANUTEC 613-996-6666 or * 666 for cell phone

2. HAZARD IDENTIFICATION

Acute Tox. 4 (Oral) H302
Eye Dam. 1 H318
STOT Not established

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS) :



Signal Word (GHS) : Danger

Hazard Statements (GHS) :

H302 - Harmful if swallowed

H318- Causes serious eye damage

Non Corrosive to Skin: (as defined and tested in accordance with the U.S. OSHA's Hazard Communication Standard, DOT Hazardous Material Regulations, Canada's WHMIS regulations and TDG Regulations. Classified as a mild skin irritant as per the 1992 OECD Guideline for Testing of Chemicals, Number 404 "Acute Dermal Irritation/Corrosion.")

Precautionary Statements (GHS) :

P260 - Do not breathe mist, spray, vapors.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection.

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

P301+P312 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTRE or doctor/ physician.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Description:

Chemical blend

Ingredient	CAS #	% by Wt	Classification
Urea, monohydrochloride	506-89-8	7.5-15	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 STOT Information not currently available.
Alcohol Ethoxylate	68991-48-0	1-5	Eye Irritation Category 2A – H319

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If symptoms persist consult physician.
Eye Contact:	Remove contacts. Flush with water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin Contact:	Thoroughly wash exposed skin with soap and water. Remove any contaminated clothing and wash before reuse.
Ingestion:	Wash out mouth with water. Drink plenty of water. Do not induce vomiting unless directed by medical personal. Never give anything to an unconscious person. Get medical aid.
Notes to Physician:	Treatment based on judgment of attending physician.

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Any standard extinguishing media (alcohol foam, water spray or fog, CO2 dry chemical, etc.).
Unsuitable extinguishing media:	None known.
Special exposure hazards	
Special safety equipment:	Self-contained positive pressure breathing apparatus and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

7. HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Information about fire - and explosion protection:

Keep respiratory protective device available.

No special measures required.

Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Protect from humidity and water.

Unsuitable material for receptacle: steel.

Unsuitable material for receptacle: aluminium.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Do not store together with alkaline products or strong acids.

Store away from oxidizing agents.

Store away from foodstuffs.

· Further information about storage conditions:

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Keep container tightly sealed.

·**Specific end use(s)** No further relevant information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection:	Use local exhaust or dilution ventilation.
Hand protection:	Chemical resistant gloves.
Eye protection:	Safety goggles or full face shield.
Skin protection:	Use body-covering impervious clothing.
Working hygiene:	Take usual precautions when handling. Workers should wash hands before eating, drinking or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid	Odour	Typical
Appearance	Clear liquid.	Odour Threshold	No data available.
Colour	Amber.	Remarks/Method	
Property	Values		
pH	1.00	None known	
Melting/Freezing Point	No data available	None known	
Boiling Point/Range	No data available	None known	
Flash Point	Not applicable.	None known	
Evaporation Rate	Similar	None known	
Flammability (solid, gas)	Not flammable.	None known	
Flammability Limit in Air:			
Upper Limit	No data available	None known	
Lower Limit	No data available	None known	
Vapour Pressure	No data available	None known	
Vapour density	No data available	None known	
Specific Gravity	1.00-1.01 g/cm3		
Water Solubility	Soluble in water.	None known	
Solubility Other Solvents	No data available	None known	
Partition Coefficient:			
n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition	No data available	None known	
Temperature			
Kinematic Viscosity	No data available	None known	

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

Dynamic Viscosity	No data available	None known
Explosive Properties	No data available	None known
Oxidizing Properties	No data available	None known

Other Properties:

Softening Point	No data available
VOC Content %	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity

Chemical stability

Stable up to 110 C/230F

Thermal decomposition / conditions to be avoided:

Heating above 110C/230F results in an exothermic decomposition with rapid release of CO₂ gas

Reacts with alkali and metals.

Reacts with amines.

Reacts with oxidizing agents.

Corrodes aluminium.

Conditions to avoid Store away from oxidizing agents.

Incompatible materials:

Warning! Do not use together with other products. May release dangerous gases (chlorine). Avoid contact with oxidizers. This material may be extremely hazardous in contact with chlorates or nitrates. This material is acidic. Contact with hypochlorites (e.g. chlorine bleach, sulfides, or cyanides will liberate toxic gases. Contact with alkaline materials (e.g. aqua ammonia) will generate heat.

Hazardous decomposition products:

Thermal decomposition may yield oxides of carbon, nitrogen, and chlorine. Hydrogen gas may be released upon contact with certain metals.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

506-89-8 Urea Hydrochloride

Oral LD50 1100 mg/kg (rat)

Primary irritant effect:

on the skin: Caustic effect on mucous membranes.

Non Corrosive to Skin: (as defined and tested in accordance with the U.S. OSHA's Hazard Communication Standard, DOT Hazardous Material Regulations, Canada's WHMIS regulations and TDG Regulations. Classified as a mild skin irritant as per the 1992 OECD Guideline for Testing of Chemicals, Number 404 "Acute Dermal Irritation/Corrosion.")

on the eye: Strong caustic effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method:

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12. ECOLOGICAL INFORMATION

Toxicity:

Not classified

Persistence and Degradability Not available

Bioaccumulative Potential

Not available

Mobility in Soil

Not available

Other Adverse Effects

Other Information:

Avoid release to the environment.

13. DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

14. TRANSPORTATION INFORMATION

Canadian T.D.G.: Regulated Material (quantity under 5 litres can be shipped Limited Quantity)

Proper Shipping Name: Corrosive liquid, N.O.S.

Contains (urea monohydrochloride)

Hazard Class: 8

ID Number: UN 1760

Packing Group: III



***Note: This material is corrosive to Aluminum only. Non-Corrosive to Skin & Mild Steel**

Water Transportation (IMDG): Regulated Material

Proper Shipping Name: Corrosive liquid, N.O.S.

Contains (urea monohydrochloride)

Hazard Class: 8

ID Number: UN 1760

Packing Group: III

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME



***Note: This material is corrosive to Aluminum only. Non-Corrosive to Skin & Mild Steel**

Air Transportation (IATA): Regulated Material

Proper Shipping Name: Corrosive liquid, N.O.S.

Contains (urea monohydrochloride)

Hazard Class: 8

ID Number: UN 1760

Packing Group: III



***Note: This material is corrosive to Aluminum only. Non-Corrosive to Skin**

US DOT Material is exempt from regulation as a hazardous material when transported by rail or road per 49CFR173.154(d)(1).

15. REGULATION

Occupational Health & Safety Regulations:

WHMIS 1988 Classification: Class D - Division 2B, Class E



OSHA & WHMIS: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) and Canadian WHMIS regulations (Controlled Products Regulations under the Hazardous Products Act).

California Prop. 65

The following components of this product are substances, or belong to classes of substances, known to the state of California to cause cancer and/or reproductive toxicity: **Chemical Name: none**

SAFETY DATA SHEET

ACTION INDUSTRIAL - OX LIME

16. OTHER INFORMATION

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.