

Fabric Shield

SECTION 1. IDENTIFICATION

Product Identifier	Fabric Shield
Other Means of Identification	Code No. 214
Recommended Use	Fabric Protectant.
Restrictions on Use	Use only as directed according to label instructions.
Manufacturer	Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832
Emergency Phone No.	CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods
SDS No.	0240

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquid - Category 3; Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 2A; Aspiration hazard - Category 1



SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Naphtha (petroleum), heavy alkylate	64741-65-7	60-95	
Stoddard solvent	8052-41-3	1-5	
Trimethylated silica	68988-56-7	1-5	
Tetraisopropyl Titanate	546-68-9	1-5	
Xylene (mixed isomers)	1330-20-7	0.5-1.5	
1,2,4-Trimethylbenzene	95-63-6	0.1-1.0	
Ethylbenzene	100-41-4	0.1-1.0	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.
 Seek medical attention if person feels unwell.
 If not breathing, give artificial respiration.
 Should breathing be difficult, give oxygen.

Skin Contact

Avoid skin contact.

In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Wash clothing before reuse.
Call a physician if irritation develops or persists.

Eye Contact

In case of eye contact, immediately flush eyes with plenty of lukewarm water with eyelids open for at least 20 minutes.
Remove contact lenses if worn.
Seek immediate medical attention.

Ingestion

If swallowed, do NOT induce vomiting unless directed to do so by medical personnel.
Never give anything by mouth to an unconscious person.
Seek immediate medical attention.

Most Important Symptoms and Effects, Acute and Delayed

May cause irritation of the respiratory system.
May cause irritation or defatting of skin on prolonged exposure.
Harmful if swallowed.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system, digestive system, nervous system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Specific Hazards Arising from the Chemical

If involved in a fire, it may generate oxides of carbon, nitrogen or ammonia if heated above its boiling point.

Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and respiratory protection.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.
Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.
If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.
Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Eliminate all sources of ignition, flames or sources of electrical discharge.
No smoking.
Use ventilation adequate to keep exposures (airborne levels of fumes / vapours) below recommended exposure limits.
Use non-sparking tools and explosion proof equipment in the case of large spills.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes.

Product Identifier: Fabric Shield
SDS No.: 0240
Date of Preparation: November 25, 2015

Do NOT ingest.
Do not breath gas/fumes/vapour/spray.
Keep containers tightly sealed when not in use.

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.
Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Naphtha (petroleum), heavy alkylate	192 mg/m3					
Stoddard solvent	100 ppm		100 ppm			
Trimethylated silica			5 mg/m3			
Xylene (mixed isomers)	100 ppm	150 ppm				
Ethylbenzene	20 ppm		100 ppm			

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

Individual Protection Measures

Eye/Face Protection

Wear eye / face protection.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear colourless.
Odour	Petroleum distillate
pH	Not applicable
Melting Point/Freezing Point	Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	~ 30.5 °C (86.9 °F)
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Solubility	Insoluble in water
Other Information	
Physical State	Liquid
Bulk Density	~ 0.77 kg/L

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Product Identifier: Fabric Shield
SDS No.: 0240
Date of Preparation: November 25, 2015

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Prevent mixing with incompatible materials.

Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides), strong bases (e.g. sodium hydroxide).

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Naphtha (petroleum), heavy alkylate	> 5900 mg/L (rat) (4-hour exposure)	> 7600 mg/kg (rat)	> 3040 mg/kg (rat)
Stoddard solvent	> 5500 mg/m3 (4-hour exposure)	> 5000 mg/kg (rat)	> 3000 mg/kg (rabbit)
Trimethylated silica		> 5000 mg/kg (rat)	
Tetraisopropyl Titanate		7460 mg/kg (rat)	15500 mg/kg (rabbit)
Xylene (mixed isomers)		4300 mg/kg (rat)	
1,2,4-Trimethylbenzene	> 2000 ppm (rat) (4-hour exposure)	3400 mg/kg (rat)	> 3160 mg/kg (rabbit)
Ethylbenzene	17.2 mg/L (rat) (4-hour exposure)	3500 mg/kg (rat)	15354 mg/kg (rabbit)

Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Serious Eye Damage/Irritation

May cause severe irritation or burns.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory system.

Skin Absorption

May cause irritation on prolonged contact.

Ingestion

May cause burns or irritation of the digestive system including nausea or vomiting.

May be harmful if swallowed.

Product Identifier: Fabric Shield

SDS No.: 0240

Date of Preparation: November 25, 2015

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited. Harmful if aspirated into the lungs.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No chronic effects are expected provided adequate person protection is taken during usage.

Respiratory and/or Skin Sensitization

Not expected to produce any respiratory system problems when used in a well ventilated area.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity**Development of Offspring**

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

None known.

SECTION 12. ECOLOGICAL INFORMATION**Toxicity**

May cause long-term adverse effects in the aquatic environment.

Persistence and Degradability

Not available.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal Methods**

This material and its container must be disposed of in a safe way.

Do not allow product to enter waterways.

Dispose of in accordance with local and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Special Precautions Please note: Special shipping instructions- Not regulated if less than 450 liters volume.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION**Safety, Health and Environmental Regulations****Canada**

Product Identifier: Fabric Shield
SDS No.: 0240
Date of Preparation: November 25, 2015

WHMIS Classification



Class B3



Class D2B

B3 - Combustible Liquid; D2B - Toxic (Skin irritant; Eye irritant)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

SECTION 16. OTHER INFORMATION

SDS Prepared By	Mark Bryans
Phone No.	(905) 648-7832 ext 351
Date of Preparation	November 25, 2015

Product Identifier:	Fabric Shield
SDS No.:	0240
Date of Preparation:	November 25, 2015

Page 06 of 06