

## Royal Glaze

### SECTION 1. IDENTIFICATION

|                                      |                                                                                                                       |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>Product Identifier</b>            | Royal Glaze                                                                                                           |
| <b>Other Means of Identification</b> | Code No. 821                                                                                                          |
| <b>Recommended Use</b>               | Polishing Wax.                                                                                                        |
| <b>Restrictions on Use</b>           | Use only as directed according to label instructions.                                                                 |
| <b>Manufacturer</b>                  | Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832 |
| <b>Emergency Phone No.</b>           | CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods                                               |
| <b>SDS No.</b>                       | 0250                                                                                                                  |

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquid - Category 3; Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 2B; Aspiration hazard - Category 1



### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                                                                                  | CAS No.    | %       | Other Identifiers |
|------------------------------------------------------------------------------------------------|------------|---------|-------------------|
| Stoddard solvent                                                                               | 8052-41-3  | 10-30   |                   |
| Alkanes, C12-14-iso-                                                                           | 68551-19-9 | 1-5     |                   |
| Siloxanes and Silicones, di-Me, [[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxy]-terminated | 71750-80-6 | 0.5-1.5 |                   |
| Solvent naphtha                                                                                | 64742-94-5 | 1-5     |                   |
| Ethanol                                                                                        | 64-17-5    | 0.1-1.0 |                   |

### SECTION 4. FIRST-AID MEASURES

#### First-aid Measures

##### Inhalation

If irritation is experienced, remove person to fresh air.  
 Seek medical attention if person feels unwell.  
 If not breathing, give artificial respiration.  
 Should breathing be difficult, give oxygen.

##### Skin Contact

Avoid skin contact.  
 In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.  
Wash clothing before reuse.  
Call a physician if irritation develops or persists.

#### **Eye Contact**

In case of eye contact, immediately flush eyes with plenty of lukewarm water with eyelids open for at least 20 minutes.  
Remove contact lenses if worn.  
Seek immediate medical attention.

#### **Ingestion**

If swallowed, do NOT induce vomiting unless directed to do so by medical personnel.  
Never give anything by mouth to an unconscious person.  
Seek immediate medical attention.

#### **Most Important Symptoms and Effects, Acute and Delayed**

May cause irritation of the respiratory system.  
May cause irritation or defatting of skin on prolonged exposure.  
Harmful if swallowed.

#### **Immediate Medical Attention and Special Treatment**

##### **Target Organs**

Eyes, skin, respiratory system, digestive system, nervous system.

##### **Medical Conditions Aggravated by Exposure**

Asthma, skin allergies.

## **SECTION 5. FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

#### **Suitable Extinguishing Media**

Carbon dioxide, dry chemical powder or appropriate foam.

### **Specific Hazards Arising from the Chemical**

If involved in a fire, it may generate oxides of carbon, nitrogen or ammonia if heated above its boiling point.

### **Special Protective Equipment and Precautions for Fire-fighters**

Wear full fire fighting equipment and respiratory protection.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment, and Emergency Procedures**

Use the personal protective equipment recommended in Section 8 of this safety data sheet.  
Increase ventilation to area or move leaking container to a well-ventilated and secure area.

### **Environmental Precautions**

Do not allow into any sewer, on the ground or into any waterway.  
If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.  
Minimize the use of water to prevent environmental contamination.

### **Methods and Materials for Containment and Cleaning Up**

Eliminate all sources of ignition, flames or sources of electrical discharge.  
No smoking.  
Use ventilation adequate to keep exposures (airborne levels of fumes / vapours) below recommended exposure limits.  
Use non-sparking tools and explosion proof equipment in the case of large spills.

## **SECTION 7. HANDLING AND STORAGE**

### **Precautions for Safe Handling**

Avoid contact with skin and eyes.  
Do NOT ingest.

---

Product Identifier: Royal Glaze  
SDS No.: 0250  
Date of Preparation: November 26, 2015

Do not breath gas/fumes/vapour/spray.  
Keep containers tightly sealed when not in use.

#### Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.  
Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Chemical Name        | ACGIH TLV® |          | OSHA PEL   |         | AIHA WEEL |     |
|----------------------|------------|----------|------------|---------|-----------|-----|
|                      | TWA        | STEL     | TWA        | Ceiling | 8-hr TWA  | TWA |
| Stoddard solvent     | 100 ppm    |          | 100 ppm    |         |           |     |
| Alkanes, C12-14-iso- |            |          | 200 ppm    |         |           |     |
| Solvent naphtha      |            |          | 100 mg/m3  |         |           |     |
| Ethanol              |            | 1000 ppm | 1900 mg/m3 |         |           |     |

### Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

### Individual Protection Measures

#### Eye/Face Protection

Wear eye / face protection.

#### Skin Protection

Wear protective gloves and clothing to prevent skin contact.

#### Respiratory Protection

Use in well ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

|                                             |                                              |
|---------------------------------------------|----------------------------------------------|
| Appearance                                  | Opaque - purple liquid.                      |
| Odour                                       | cherry almond                                |
| pH                                          | Not applicable                               |
| Melting Point/Freezing Point                | Not available (freezing)                     |
| Initial Boiling Point/Range                 | Not available                                |
| Flash Point                                 | ~ 43.0 °C (109.4 °F)                         |
| Flammability (solid, gas)                   | Not available                                |
| Upper/Lower Flammability or Explosive Limit | Not available (upper); Not available (lower) |
| Vapour Pressure                             | Not available                                |
| Solubility                                  | Insoluble in water                           |
| Other Information                           |                                              |
| Physical State                              | Liquid                                       |
| Bulk Density                                | ~ 0.98 kg/L                                  |

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

**Chemical Stability**

Normally stable.

**Possibility of Hazardous Reactions**

Prevent mixing with incompatible materials.

**Conditions to Avoid**

High temperatures.

Freezing.

Incompatible materials.

**Incompatible Materials**

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides), strong bases (e.g. sodium hydroxide).

**Hazardous Decomposition Products**

May include but are not limited to oxides of carbon, nitrogen and ammonia.

**SECTION 11. TOXICOLOGICAL INFORMATION****Likely Routes of Exposure**

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

**Acute Toxicity**

| Chemical Name        | LC50                                       | LD50 (oral)        | LD50 (dermal)          |
|----------------------|--------------------------------------------|--------------------|------------------------|
| Stoddard solvent     | > 5500 mg/m <sup>3</sup> (4-hour exposure) | > 5000 mg/kg (rat) | > 3000 mg/kg (rabbit)  |
| Alkanes, C12-14-iso- |                                            | > 5000 mg/kg (rat) |                        |
| Solvent naphtha      | > 3.8 mg/L (rat) (4-hour exposure)         | > 4460 mg/kg (rat) |                        |
| Ethanol              | > 61 mg/L (rat) (4-hour exposure)          | 7060 mg/kg (rat)   | > 15800 mg/kg (rabbit) |

**Skin Corrosion/Irritation**

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

**Serious Eye Damage/Irritation**

May cause severe irritation or burns.

**STOT (Specific Target Organ Toxicity) - Single Exposure****Inhalation**

May cause irritation of the respiratory system.

**Skin Absorption**

May cause irritation on prolonged contact.

**Ingestion**

May cause burns or irritation of the digestive system including nausea or vomiting.

May be harmful if swallowed.

**Aspiration Hazard**

May be drawn into the lungs (aspirated) if swallowed or vomited. Harmful if aspirated into the lungs.

**STOT (Specific Target Organ Toxicity) - Repeated Exposure**

No chronic effects are expected provided adequate person protection is taken during usage.

**Respiratory and/or Skin Sensitization**

Product Identifier: Royal Glaze  
SDS No.: 0250  
Date of Preparation: November 26, 2015

Not expected to produce any respiratory system problems when used in a well ventilated area.

#### **Carcinogenicity**

Not known to cause cancer.

#### **Reproductive Toxicity**

##### **Development of Offspring**

Not known to harm the unborn child.

##### **Sexual Function and Fertility**

Not known to cause effects on sexual function or fertility.

##### **Effects on or via Lactation**

Not known to cause effects on or via lactation.

#### **Germ Cell Mutagenicity**

Not known to be a mutagen.

#### **Interactive Effects**

None known.

## **SECTION 12. ECOLOGICAL INFORMATION**

#### **Toxicity**

May cause long-term adverse effects in the aquatic environment.

#### **Persistence and Degradability**

Not available.

#### **Bioaccumulative Potential**

No information was located.

#### **Mobility in Soil**

No information was located.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

This material and its container must be disposed of in a safe way.

Do not allow product to enter waterways.

Dispose of in accordance with local and federal regulations.

## **SECTION 14. TRANSPORT INFORMATION**

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

**Special Precautions for User** Please note: Limited Quantity Exemption  
Less than 450 liters not regulated.

#### **Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

## **SECTION 15. REGULATORY INFORMATION**

#### **Safety, Health and Environmental Regulations**

##### **Canada**

##### **WHMIS Classification**



Class B3      Class D2B

B3 - Combustible Liquid; D2B - Toxic (Skin irritant; Eye irritant)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

## SECTION 16. OTHER INFORMATION

**SDS Prepared By**      Mark Bryans  
**Phone No.**              (905) 648-7832 ext 351  
**Date of Preparation**    November 26, 2015

---

Product Identifier:      Royal Glaze  
SDS No.:                0250  
Date of Preparation:    November 26, 2015

---

Page 06 of 06