

Speed Bead

SECTION 1. IDENTIFICATION

Product Identifier	Speed Bead
Other Means of Identification	Code No. 825
Recommended Use	Vehicle Drying Agent.
Restrictions on Use	Use only as directed according to label instructions.
Manufacturer	Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832
Emergency Phone No.	CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods
SDS No.	0252

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 2B



SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Isopropyl Alcohol	67-63-0	3-7	
2-Butoxyethanol	111-76-2	1-5	
Alcohols, C9-11, ethoxylated, liquids	68439-46-3	1-5	
Quaternary compounds	not available	1-5	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.

Seek medical attention if person feels unwell.

Skin Contact

Avoid skin contact.

In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Wash clothing before reuse.

Call a physician if irritation develops or persists.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the

eyelid(s) open.

Remove contact lenses, if present and easy to do.

If eye irritation persists, get medical advice/attention.

Ingestion

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting.

If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again.

Immediately call a Poison Centre or doctor.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Chemical

This product presents no unusual hazards in a fire situation.

If involved in a fire, it may generate oxides of carbon, nitrogen or ammonia if heated above its boiling point.

Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and respiratory protection.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Contain and/or absorb spill with commercial absorbents and then place into a suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes.

Do NOT ingest.

Do not breathe gas/fumes/vapour/spray.

Keep containers tightly sealed when not in use.

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.

Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product Identifier: Speed Bead

SDS No.: 0252

Date of Preparation: November 26, 2015

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
2-Butoxyethanol	20 ppm		25 ppm			
Alcohols, C9-11, ethoxylated, liquids	Not established		Not established			
Isopropyl Alcohol	200 ppm	400 ppm				
Quaternary compounds			400 ppm			

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

Individual Protection Measures**Eye/Face Protection**

Wear eye / face protection.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**Basic Physical and Chemical Properties**

Appearance	Clear yellow liquid.
Odour	Faint
pH	~ 7.0
Melting Point/Freezing Point	~ 0 °C (32 °F) (freezing)
Flash Point	Not applicable
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Solubility	Soluble in water
Other Information	
Physical State	Liquid
Bulk Density	~ 0.97 kg/L

SECTION 10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Prevent mixing with incompatible materials.

Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g.

Product Identifier: Speed Bead

SDS No.: 0252

Date of Preparation: November 26, 2015

hydrides).

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
2-Butoxyethanol	450 ppm (rat) (4-hour exposure)	530 mg/kg (rat)	400-500 mg/kg (rabbit)
Alcohols, C9-11, ethoxylated, liquids		1378 mg/kg (rat)	> 2000 mg/kg (rabbit)
Isopropyl Alcohol	16000 ppm (rat) (4-hour exposure)	5045 mg/kg (rat)	5030-7900 mg/kg (rabbit)
Quaternary compounds		2490 mg/kg (rat)	

Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Serious Eye Damage/Irritation

May cause severe irritation or burns.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory system.

Skin Absorption

May cause irritation on prolonged contact.

Ingestion

May cause burns or irritation of the digestive system including nausea or vomiting.

May be harmful if swallowed.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No chronic effects are expected provided adequate person protection is taken during usage.

Respiratory and/or Skin Sensitization

Not expected to produce any respiratory system problems when used in a well ventilated area.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Product Identifier: Speed Bead

SDS No.: 0252

Date of Preparation: November 26, 2015

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

May cause long-term adverse effects in the aquatic environment.

Persistence and Degradability

May cause long-term adverse effects in the aquatic environment.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

This material and its container must be disposed of in a safe way.

Do not allow product to enter waterways.

Dispose of in accordance with local and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

WHMIS Classification



Class D2B

D2B - Toxic (Skin irritant; Eye irritant)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

SECTION 16. OTHER INFORMATION

SDS Prepared By Mark Bryans
Phone No. (905) 648-7832 ext 351
Date of Preparation November 26, 2015

Product Identifier: Speed Bead
SDS No.: 0252
Date of Preparation: November 26, 2015

Page 05 of 05