

MATERIAL SAFETY DATA SHEET

SECTION I - MATERIAL IDENTIFICATION AND USE	
Material Name	VINYL, PLASTIC & CARPET DYES Code No. 250-285
Manufacturer's Name	Supplier's Name Auto Valet Detalling Products a div. of 597401 ontario limited 1366 Sandhill Dr., Ancaster, Ontario L9G 4V5
Emergency Telephone Number:	(905) 648-7682

Chemical Name NA	Chemical Family Solvent dye	Chemical Formula Proprietary
Molecular Weight NA	Trade Name and Synonyms Carpet Dyes	Material Use Automotive dye

SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL				
Hazardous Ingredients	Approximate Concentration %	C.A.S. N.A. or U.N. Numbers	Exposure Limits OSHA/ACGIH	LD ₅₀ /LC ₅₀ Specify Species and Route
Xylene	7.0 - 13.0	1330-20-7	TLV 100 ppm	LD ₅₀ 4.3 g/kg rat, oral LD ₅₀ 3.35 g/kg rabbit, skin
Toluene	7.0 - 13.0	108-88-3	TLV 100 ppm	ND
Acetone	30.0 - 60.0	67-64-1	TLV 750 ppm	LD ₅₀ 9750 mg/kg rat, oral LD ₅₀ 20 g/kg rabbit, skin
Diacetone Alcohol	3.0 - 7.0	123-42-2	TLV 50 ppm	ND
2-Butanone	7.0 - 13.0	78-93-3	TLV 200 ppm	ND
Propane/Isobutane	15.0 - 40.0	68476-86-8	TLV 800 ppm	ND

SECTION III - PHYSICAL DATA FOR MATERIAL				
Physical State GAS ☐ LIQUID ☒ SOLID ☐	Odour and Appearance Solvent odor / various colors		Odour Threshold (p.p.m.) NE	Specific Gravity 0.900
Vapour Pressure (mm) NE	Vapour Density (Air-1) > air	Evaporation Rate > water	Boiling Point (°C) NE	Freezing Point (°C) NE
Solubility in Water (20°C) NIL	% Volatile (by volume)	pH NA	Coefficient of water/oil distribution NA	

SECTION IV - FIRE AND EXPLOSION HAZARD OF MATERIAL			
Flammability Yes ☒ No ☐ If yes, under which conditions: Vapours may form explosive mixture with air; excessive heat			
Means of Extinction Water fog, dry chemical, carbon dioxide, alcohol foam, foam			
Special Procedures Containers may build up pressure if exposed to heat/fire, firefighters should wear NIOSH approved positive pressure self-contained breathing apparatus and full protective gear.			
Flashpoint (°C) and Method -18°C	Upper explosion limit (% by volume) NE	Lower explosion limit (% by volume) NE	
Auto Ignition Temperature (°C) NE	Hazardous Combustion Products Oxides of carbon		
Explosion Data NE	Rate of Burning NE	Explosive Power NE	Sensitivity to Static Discharge

SECTION V - REACTIVITY DATA	
Chemical Stability	If no, under which conditions:
Yes ☒ No ☐	
Incompatibility to other substances	If yes, under which conditions: Strong acids, alkalis, oxidizers
Yes ☒ No ☐	
Reactivity and under what conditions Direct contact	
Hazardous Decomposition Products Oxides of carbon	

Fire (red)

Health (blue)

Reactivity (Yellow)

HAZARD INDEX

4. Severe Hazard
3. Serious Hazard
2. Moderate Hazard
1. Slight Hazard
0. Minimal Hazard

Personal Protection

MATERIAL SAFETY DATA SHEET

Material Name / Identifier VINYL, PLASTIC & CARPET DYES Code No. 250-285		
SECTION VI - TOXICOLOGICAL PROPERTIES OF PRODUCT		
Route of Entry ☒ SKIN CONTACT ☒ SKIN ABSORPTION ☒ EYE CONTACT ☒ INHALATION ACUTE ☒ INHALATION CHRONIC ☒ INGESTION		
Effects of Acute Exposure to Product Skin contact - can cause irritation and possible allergic reaction Eyes - severe eye irritant Inhalation - headaches, dizziness, nausea, change in heart rate Ingestion - harmful or fatal. Irritating to mouth, throat and stomach		
Effects of Chronic Exposure to Product Long term exposure (years) to vapour may cause lung, liver, or kidney damage. Toluene and Xylene and VM & P have been reported to affect the central nervous system.		
LD ₅₀ of Product (Specify Species and Route) NE	Irritancy of Product NE	Exposure limits of Product NE
LD ₅₀ of Product (Specify Species) NE	Sensitization to Product NE	Synergistic materials NE
Carcinogenicity ☐ Reproductive Effects ☒ Teratogenicity ☐ Mutagenicity ☐ Xylene and Toluene are known to the state of California to cause birth defects and other reproductive harm.		
SECTION VII - PREVENTATIVE MEASURES		
Personal Protective Equipment		
Gloves (Specify) Nitrile gloves #10781 or #10790	Respiratory (Specify) Self-contained breathing apparatus if TLV limits exceeded.	Eyes (Specify) Chemical splash goggles #10790
Footwear (Specify) NA	Clothing (Specify) NA	Other (Specify)
Engineering Controls (e.g. ventilation, enclosed process, specify) Mechanical local exhaust to keep air contaminants within TLV limits.		
Leak and Spill Procedure Use absorbent material to soak up spill and collect into containers.		
Waste Disposal Dispose according to federal, provincial and local regulations		
Handling Procedures and Equipment Store at temperatures below 50°C. Keep away from heat, sparks, or open flame. Do not smoke while using.		
Storage Requirements Store at temperatures below 50°C. Keep away from heat, sparks, or open flame. Do not smoke while using. Keep out of reach of children.		
Special Shipping Information Consumer commodity.		
SECTION VIII - FIRST AID MEASURES		
Skin Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.		
Eye Flush eyes immediately with plenty of water. Get medical attention if irritation persists.		
Inhalation Rescuers should wear protective gear. Remove victim from area of exposure. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.		
Ingestion Do not induce vomiting. Give victim a glass of water or milk. Call physician or poison control centre immediately. Never give anything by mouth to an unconscious person.		
General Advice Give victim comfort, warmth and rest.		
SECTION IX - PREPARATION DATA OF M.S.D.S.		
Additional Information		
Sources Used Supplier's MSDS		
Prepared by: N. Copley	Phone number 905-648-7832	Date January 1, 2015
NA = NOT APPLICABLE ND = NO DATA AVAILABLE NE = NONE ESTABLISHED NR = NOT REGULATED		