



Safety Data Sheet

Fabric Shield

SECTION 1. IDENTIFICATION

Product Identifier Fabric Shield
Other Means of Identification Code No. 214
Recommended Use Fabric Protectant.
Restrictions on Use Use only as directed according to label instructions.
Manufacturer Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832
Emergency Phone No. CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods
SDS No. 0240

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable liquid - Category 4; Skin irritation - Category 2; Eye irritation - Category 2A; Aspiration hazard - Category 1

Label Elements



Danger
Combustible liquid.
May be fatal if swallowed and enters airways.
Causes skin and eye irritation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Naphtha (petroleum), heavy alkylate	64741-65-7	60-95	
Stoddard solvent	8052-41-3	1-5	
Trimethylated silica	68988-56-7	1-5	
Tetraisopropyl Titanate	546-68-9	1-5	
Xylene (mixed isomers)	1330-20-7	0.5-1.5	
1,2,4-Trimethylbenzene	95-63-6	0.1-1.0	
Ethylbenzene	100-41-4	0.1-1.0	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.

Product Identifier: Fabric Shield
SDS No.: 0240
Date of Preparation: August 04, 2016

Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

In case of contact, immediately flush skin with plenty of water.

Call a physician if irritation develops or persists.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

If eye irritation persists, get medical advice or attention.

Ingestion

In case of ingestion, call a doctor or anti-poison Centre.

Most Important Symptoms and Effects, Acute and Delayed

Harmful if swallowed.

May cause severe eye irritation or burns.

May cause skin irritation on prolonged contact.

May irritate the respiratory system.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system, digestive system, nervous system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Specific Hazards Arising from the Product

If involved in a fire, it may generate oxides of carbon, nitrogen or ammonia if heated above its boiling point.

Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and respirator.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Contain and/or absorb spill with commercial absorbents and then place into a suitable container for disposal.

Use ventilation adequate to keep exposures (airborne levels of fumes / vapours) below recommended exposure limits.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.

Do NOT ingest.

Keep containers tightly sealed when not in use.

Do not breathe gas/fumes/vapour/spray.

Product Identifier: Fabric Shield

SDS No.: 0240

Date of Preparation: August 04, 2016

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.

Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Naphtha (petroleum), heavy alkylate	192 mg/m3					
Stoddard solvent	100 ppm		100 ppm			
Trimethylated silica			5 mg/m3			
Xylene (mixed isomers)	100 ppm	150 ppm				
Ethylbenzene	20 ppm		100 ppm			

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Wear eye protection if contact is not preventable.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear colourless.
Odour	Petroleum distillate
pH	Not applicable
Melting Point/Freezing Point	Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	~ 30.5 °C (86.9 °F)
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Solubility	Insoluble in water
Other Information	
Physical State	Liquid
Bulk Density	~ 0.77 kg/L

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Product Identifier: Fabric Shield
SDS No.: 0240
Date of Preparation: August 04, 2016

None expected under normal conditions of storage and use.

Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides), strong bases (e.g. sodium hydroxide).

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Naphtha (petroleum), heavy alkylate	> 5900 mg/L (rat) (4-hour exposure)	> 7600 mg/kg (rat)	> 3040 mg/kg (rat)
Stoddard solvent	> 5500 mg/m3 (4-hour exposure)	> 5000 mg/kg (rat)	> 3000 mg/kg (rabbit)
Trimethylated silica		> 5000 mg/kg (rat)	
Tetraisopropyl Titanate		7460 mg/kg (rat)	15500 mg/kg (rabbit)
Xylene (mixed isomers)		4300 mg/kg (rat)	
1,2,4-Trimethylbenzene	> 2000 ppm (rat) (4-hour exposure)	3400 mg/kg (rat)	> 3160 mg/kg (rabbit)
Ethylbenzene	17.2 mg/L (rat) (4-hour exposure)	3500 mg/kg (rat)	15354 mg/kg (rabbit)

Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Serious Eye Damage/Irritation

May cause severe irritation or burns.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory system.

Skin Absorption

May cause irritation on prolonged contact.

Ingestion

Harmful if swallowed.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No chronic effects are expected provided adequate person protection is taken during usage.

Respiratory and/or Skin Sensitization

Product Identifier: Fabric Shield

SDS No.: 0240

Date of Preparation: August 04, 2016

May irritate the respiratory system.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

May cause long-term adverse effects in the aquatic environment.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

WHMIS 1988 Classification



Class B3



Class D2B

B3 - Combustible Liquid; D2B - Toxic (Skin irritant; Eye irritant)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

SECTION 16. OTHER INFORMATION

SDS Prepared By Mark Bryans

Product Identifier: Fabric Shield

SDS No.: 0240

Date of Preparation: August 04, 2016

Phone No. (905) 648-7832 ext 351

Date of Preparation August 04, 2016

Disclaimer The user of this product assumes all risks incident to the use of this product.
To the best of our knowledge, the information contained herein is accurate.
However, the supplier assumes no liability whatsoever for the accuracy or completeness of the information contained herein.
No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers.
The data contained on this sheet apply to the products supplied to the user.

Product Identifier: Fabric Shield

SDS No.: 0240

Page 06 of 06

Date of Preparation: August 04, 2016