



Safety Data Sheet

Flame

SECTION 1. IDENTIFICATION

Product Identifier Flame

Other Means of Identification Code No. 302

Recommended Use Acidic vehicle rim cleaner.

Restrictions on Use Use only as directed according to label instructions.

Manufacturer Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832

Emergency Phone No. CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods

SDS No. 0206

SECTION 2. HAZARD IDENTIFICATION

Classification

Acute toxicity (Oral) - Category 4; Skin corrosion - Category 1B; Serious eye damage - Category 1

Label Elements



Danger
Corrosive
Causes severe eye damage and skin irritation or burns.
Harmful if swallowed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Sulfuric acid	7664-93-9	10-15	
Ammonium bifluoride	1341-49-7	5-10	
2-Butoxyethanol	111-76-2	1-5	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.
Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Wash clothing before reuse.

Product Identifier: Flame

SDS No.: 0206

Date of Preparation: August 04, 2016

Call a physician if irritation develops or persists.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

If eye irritation persists, get medical advice or attention.

Ingestion

In case of ingestion, call a doctor or anti-poison Centre.

Most Important Symptoms and Effects, Acute and Delayed

Can cause severe eye and skin irritation and burns.

Harmful if swallowed.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system, digestive system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

This product presents no unusual hazards in a fire situation.

If involved in a fire, it may generate oxides of carbon, nitrogen or ammonia if heated above its boiling point.

Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and respirator.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Contain and/or absorb spill with commercial absorbents and then place into a suitable container for disposal.

Large spills can be neutralized with sodium carbonate.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.

Do NOT ingest.

Wear personal protective equipment to avoid direct contact with this chemical.

Keep containers tightly sealed when not in use.

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.

Product Identifier: Flame

SDS No.: 0206

Date of Preparation: August 04, 2016

Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
2-Butoxyethanol	20 ppm		25 ppm			
Sulfuric acid	0.2 mg/m3					
Ammonium bifluoride	2.5 mg/m3					

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear red liquid.
Odour	Acidic (Sulfuric acid)
Melting Point/Freezing Point	~ 0 °C (32 °F) (freezing)
Flash Point	Not applicable
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Solubility	Soluble in water
Other Information	
Physical State	Liquid
Bulk Density	~ 1.10 kg/L

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Avoid contact with alkaline (basic) chemicals.

Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

Incompatible Materials

Strong bases (e.g. sodium hydroxide), strong oxidizing agents (e.g. perchloric acid).

Product Identifier: Flame
SDS No.: 0206
Date of Preparation: August 04, 2016

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation.
Skin contact.
Skin absorption.
Eye contact.
Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
2-Butoxyethanol	450 ppm (rat) (4-hour exposure)	530 mg/kg (rat)	400-500 mg/kg (rabbit)
Sulfuric acid	255 mg/m3 (rat) (4-hour exposure)	2140 mg/kg (rat)	
Ammonium bifluoride		130 mg/kg (rat)	

Skin Corrosion/Irritation

Corrosive, can cause severe irritation and burns.

Serious Eye Damage/Irritation

Contact causes severe burns with redness, swelling, pain and blurred vision. Permanent damage including blindness can result.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory system.

Skin Absorption

May cause severe irritation or burns on prolonged contact.

Ingestion

May cause burns or irritation of the digestive system including nausea or vomiting.
Harmful if swallowed.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No chronic effects are expected provided adequate person protection is taken during usage.

Respiratory and/or Skin Sensitization

May irritate the respiratory system.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Product Identifier: Flame
SDS No.: 0206
Date of Preparation: August 04, 2016

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

May cause adverse effects in the aquatic environment.

Persistence and Degradability

May cause long-term adverse effects in the aquatic environment.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	3264	Corrosive Liquid, Acid, N.O.S. (Sulphuric Acid Mixture)	8	II

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

WHMIS 1988 Classification



Class D2A; D2B



Class E

D2A - Very Toxic (Chronic toxicity); D2B - Toxic (Skin irritant; Eye irritant); E - Corrosive

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

SECTION 16. OTHER INFORMATION

SDS Prepared By Mark Bryans

Phone No. (905) 648-7832 ext 351

Date of Preparation August 04, 2016

Disclaimer The user of this product assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, the supplier assumes no liability whatsoever for the accuracy or completeness of the

Product Identifier: Flame

SDS No.: 0206

Date of Preparation: August 04, 2016

information contained herein.

No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers.

The data contained on this sheet apply to the products supplied to the user.

Product Identifier: Flame
SDS No.: 0206
Date of Preparation: August 04, 2016

Page 06 of 06