

Stik Strip

SECTION 1. IDENTIFICATION

Product Identifier	Stik Strip
Other Means of Identification	Code No. 563
Recommended Use	Viscous Floor Finish Stripper.
Restrictions on Use	Use only as directed according to label instructions.
Manufacturer	Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832
Emergency Phone No.	CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods
SDS No.	0545

SECTION 2. HAZARD IDENTIFICATION

Classification

Skin irritation - Category 2; Serious eye damage - Category 1

Label Elements



Danger

Corrosive

Causes severe eye damage and skin irritation or burns.

May be harmful if swallowed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Ethanolamine	141-43-5	1-5		
2-Butoxyethanol	111-76-2	10-15		
Tetrapotassium pyrophosphate	7320-34-5	1-5		
Tetrasodium ethylenediaminetetraacetate	64-02-8	0.5-1.0		
Alcohols, C9-11, ethoxylated, liquids	68439-46-3	0.1-0.5		

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.

Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

In case of contact, immediately flush skin with plenty of water.

Call a physician if irritation develops or persists.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

Remove contact lenses, if present and easy to do.

If eye irritation persists, get medical advice or attention.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting.

If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again.

Immediately call a Poison Centre or doctor.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system, digestive system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

This product presents no unusual hazards in a fire situation.

Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and respirator.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Contain and/or absorb spill with commercial absorbents and then place into a suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.

Do not breathe gas/fumes/vapour/spray.

Do NOT ingest.

Keep containers tightly sealed when not in use.

Product Identifier: Stik Strip - Ver. 1

Date of Preparation: April 06, 2017

Date of Last Revision:

SDS No.: 0545

Page 02 of 06

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.

Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Ethanolamine	3 ppm	6 ppm				
2-Butoxyethanol	20 ppm		25 ppm			
Alcohols, C9-11, ethoxylated, liquids	Not established		Not established			
Tetrapotassium pyrophosphate	Not established					
Tetrasodium ethylenediaminetetraacetate	Not established					

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

Provide eyewash and safety shower if contact or splash hazard exists.

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear yellow liquid.
Odour	Sassafrass
pH	~ 11.4
Melting Point/Freezing Point	~ 0 °C (32 °F) (freezing)
Flash Point	Not applicable
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Solubility	Soluble in water
Viscosity	2000 - 3000 centistokes (kinematic)
Other Information	
Physical State	Liquid
Bulk Density	~ 1.03 kg/L

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Product Identifier: Stik Strip - Ver. 1

Date of Preparation: April 06, 2017

Date of Last Revision:

SDS No.: 0545

Page 03 of 06

Chemical Stability

Normally stable.

Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides).

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION**Likely Routes of Exposure**

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethanolamine	> 1.21 mg/L (rat) (4-hour exposure)	1720 mg/kg (rat)	1000 mg/kg (rabbit)
2-Butoxyethanol	450 ppm (rat) (4-hour exposure)	530 mg/kg (rat)	400-500 mg/kg (rabbit)
Alcohols, C9-11, ethoxylated, liquids		1378 mg/kg (rat)	> 2000 mg/kg (rabbit)
Tetrapotassium pyrophosphate		2444 mg/kg (rat)	4640 mg/kg (rabbit)
Tetrasodium ethylenediaminetetraacetate	> 1000 mg/m3 (rat)	> 4140 mg/kg (rat)	> 12800 mg/kg (rabbit)

Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Serious Eye Damage/Irritation

May cause severe irritation or burns.

STOT (Specific Target Organ Toxicity) - Single Exposure**Inhalation**

May cause irritation of the respiratory system.

Skin Absorption

May cause irritation on prolonged contact.

Ingestion

Harmful if swallowed.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No chronic effects are expected provided adequate person protection is taken during usage.

Respiratory and/or Skin Sensitization

Product Identifier: Stik Strip - Ver. 1

Date of Preparation: April 06, 2017

Date of Last Revision:

SDS No.: 0545

Page 04 of 06

Not expected to produce any respiratory system problems when used in a well ventilated area.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

May cause long-term adverse effects in the aquatic environment.

Persistence and Degradability

Readily biodegradable (test method #301D, OECD).

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
	1760	Corrosive Liquid N.O.S. (alkaline)	Class 8	III

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

WHMIS 1988 Classification



Product Identifier: Stik Strip - Ver. 1

Date of Preparation: April 06, 2017

Date of Last Revision:

SDS No.: 0545

Page 05 of 06

Class D2B Class E

D2B - Toxic (Skin irritant; Eye irritant); E - Corrosive

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

SECTION 16. OTHER INFORMATION

SDS Prepared By Mark Bryans
Phone No. (905) 648-7832 ext 351
Date of Preparation April 06, 2017
Disclaimer The user of this product assumes all risks incident to the use of this product.
 To the best of our knowledge, the information contained herein is accurate.
 However, the supplier assumes no liability whatsoever for the accuracy or completeness of the
 information contained herein.
 No representation of warranties, either expressed or implied, of merchantability, fitness for a
 particular purpose or of any other nature are made hereunder with respect to the information or
 the product to which the information refers.
 The data contained on this sheet apply to the products supplied to the user.

Product Identifier: Stik Strip - Ver. 1
Date of Preparation: April 06, 2017
Date of Last Revision:

SDS No.: 0545

Page 06 of 06