



Material Safety Data Sheet

WHMIS	Protective Clothing	TDG Road / Rail

Section 1. Product Identification and Uses

Product Name	Bebee (Vision)	CI#	Not applicable.
Synonyms	Not available.	DSL	CEPA DSL: Product(s): Ethanol
Chemical Name	Not applicable.	CAS #	Not applicable.
Chemical Formula	Not applicable.	Code	8094
Chemical Family	Aliphatic hydrocarbon (heavy). (Solvent.)	Molecular Weight	Not applicable.
Supplier	ROOT INDUSTRIES INC. 3700 WESTON ROAD NORTH YORK, ONTARIO M9L 2Z4 (416) 746-3700	Manufacturer	ROOT INDUSTRIES INC. 3700 WESTON ROAD NORTH YORK, ONT. M9L 2Z4 (416) 746-3700
Material Uses	Consumer products: Odour counteractant & air freshener.		

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀
Ethanol	64-17-5	15-25	ORAL (LD ₅₀) mg/kg: Acute: 7060 (Rat.). VAPOR (LC ₅₀)ppm : Acute: 8000 (Rat.) (4 hour(s)).
Naphtha, hydrotreated heavy	64742-48-9	35-45	Not available.
Dimethyl methane	000074986	10-30	Not available.
Trimethyl methane	000075285	10-30	GAS (LC ₅₀) ppm : Acute: 142500 (Rat) (4 hour(s)).
Propylene glycol	000057556	1-5	ORAL (LD ₅₀) mg/kg: Acute: 10000 (Dog).

Section 3. Physical Data

Physical State and Appearance	Liquid.	Odor	Slight.
pH (1% Soln/Water)	Neutral.	Taste	Not available.
Odor Threshold	The highest known value is 10 ppm (Ethanol)	Color	Clear
Volatility	99.46% (v/v).		
Evaporation Rate	55 [Butyl acetate.]		
Melting Point	May start to solidify at -59°C (-74.2°F) based on data for: Propylene glycol. Weighted average: -106.91°C (-160.4°F)		
Boiling Point	78.5°C (173.3°F)		
Density	0.7755 (Water = 1)		
Vapor Density	Greater than air.		
Vapor Pressure	The highest known value is 43 mm of Hg (@ 20°C) (Ethanol). Weighted average: 16.52 mm of Hg (@ 20°C)		
LogK _{ow}	The product is much more soluble in oil.		
Ionicity (Surface Active Agent)	Not available.		
Critical Temperature	The lowest known value is 243.1°C (469.6°F) (Ethanol).		
Instability Temperature	Not available.		
Conditions of Instability	No additional remark.		

Continued on Next Page

WHMIS

Protective Clothing

TDG Road / Rail



A B-5 D-2B



CONSUMER COMMODITY.

Dispersion Properties	Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol.
Solubility	Easily soluble in methanol, diethyl ether, n-octanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Data

The Product is:	Flammable.
Auto-ignition Temperature	The lowest known value is 410°C (770°F) (Propylene glycol).
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Flash Points	CLOSED CUP: 12.78°C (55°F) (Ethanol). Flame extension: >45 cm. NFC Cdn. Stage 1.
Flammable Limits	The greatest known range is LOWER: 3.3% UPPER: 19% (Ethanol)
Extinguishing Media	Flammable liquid, insoluble in water. SMALL FIRE: Use DRY chemicals, CO ₂ , alcohol foam or water spray. LARGE FIRE: Use water spray or fog.
Flammability	Highly flammable in presence of open flames and sparks. Flammable in presence of heat, of oxidizing materials, of reducing materials, of combustible materials. The flammability of an aerosol by WHMIS definition is determined by its flame-extension or its flashback. The flame extension of this product is greater than 45cm. Canadian NFC, Level 3
Risks of Explosion	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. Slightly explosive to explosive in presence of oxidizing materials.

Section 5. Reactivity

Stability	The product is stable.
Hazardous Decomposition Products	Not available.
Degradability	Not available.
Products of Degradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. The products of degradation are less toxic than the product itself.
Corrosivity	Not available.
Reactivity	Highly reactive with oxidizing agents, alkalis. Reactive with reducing agents, organic materials, acids. Slightly reactive to reactive with metals.
Instability Temperature	Not available.
Conditions of Instability	No additional remark.

WHMIS

Protective Clothing

TDG Road / Rail



A B-5 D-2B



CONSUMER COMMODITY.

Section 6. Toxicological Properties

Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
TLV	Ethanol TWA: 1000 (ppm) from ACGIH (TLV) Naphtha, hydrotreated heavy TWA: 300 (ppm) Dimethyl methane Simple asphyxiant. Consult local authorities for acceptable exposure limits.
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 3450 mg/kg [Mouse]. (Ethanol). Acute dermal toxicity (LD50): 20800 mg/kg [Rabbit]. (Propylene glycol). Acute toxicity of the gas (LC50): 142500 ppm 4 hour(s) [Rat]. (Trimethyl methane). Acute toxicity of the vapor (LC50): 8000 ppm 4 hour(s) [Rat]. (Ethanol).
Chronic Effects on Humans	The substance is toxic to the reproductive system, blood, kidneys, liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to an highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.
Acute Effects on Humans	Very dangerous in case of eye contact (irritant), of ingestion, of inhalation. Slightly dangerous to dangerous in case of skin contact (irritant, permeator). Very slightly to slightly dangerous in case of skin contact (sensitizer). This product is an eye irritant. This product may irritate eyes and skin upon contact. Inflammation of the eye is characterized by redness, watering, and itching. Aspiration of material into the lungs can cause chemical pneumonitis, which can be fatal.
Synergetic Products (Toxicologically)	Not available.
Irritation/Corrosivity	Very hazardous in case of eye contact (irritant). Hazardous in case of skin contact (irritant).
Sensitization	Slightly hazardous in case of skin contact (sensitizer).
Carcinogenic Effects	CARCINOGENIC EFFECTS: Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol].
Toxic Effects on Reproduction	DEVELOPMENTAL TOXICITY: PROVEN [Ethanol]
Teratogenic Effects	TERATOGENIC EFFECTS: Not available.
Mutagenic Effects	MUTAGENIC EFFECTS: Not available.

Section 7. Preventive Measures

Small Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.	
Personal Protective Equipment	Not normally required when used as directed.	
Large Spill and Leak	Not applicable for aerosol containers.	
Protective Clothing	Not applicable for aerosol containers.	
Engineering Controls	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.	

Continued on Next Page

WHMIS

Protective Clothing

TDG Road / Rail



A B-5 D-2B



CONSUMER COMMODITY.

Precautions	If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, acids, alkalis.
Storage	CONTENTS UNDER PRESSURE. Do not puncture, incinerate, store the container at temperatures above 49°C (120°F) or in direct sunlight. Store and use away from heat, sparks, open flame, or any other ignition source. Store in a dry, cool and well ventilated area.
Handling	Not available.
Waste Disposal	Consult your local or regional authorities.
Special Shipping Information	Not available.

Section 8. First Aid

Eye Contact	Flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Call a physician immediately.
Skin Contact	Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Completely decontaminate clothing, shoes and leather goods before reuse or discard. Call a doctor if irritation develops.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Slight Inhalation	Allow the victim to rest in a well ventilated area. Oxygen may be administered if breathing is difficult. If the victim is not breathing, perform mouth-to-mouth resuscitation. Provide general supportive measures (comfort, warmth, rest). Seek immediate medical attention.
Hazardous Inhalation	No additional information.
Slight Ingestion	DO NOT induce vomiting. Seek immediate medical attention.
Hazardous Ingestion	No additional information.

Section 9. MSDS Preparation

References Not available.

No additional remark.

Validated by Root Industries Inc. on 5/26/09

Verified by Root Industries Inc..

Printed 5/26/09

Emergency phone: CANUTEC (613) 996-6666

Responsible
Name/
Telephone No.

Classification

TDG Road / CONSUMER COMMODITY.
Rail



Not applicable.

Continued on Next Page

WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-2B		CONSUMER COMMODITY.

WHMIS WHMIS CLASS A: Compressed gas. WHMIS CLASS B-5: Flammable aerosol. WHMIS CLASS D-2B: Material causing other toxic effects (TOXIC).	
--	---

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.