Executive Summary

To: Mr. Timothy Ryan, University Fire Marshal and Director of Fire Protection and Emergency Services

Addressee specified by the supplied contest brief. Desk review dated 9 November 2026.

We studied the evacuation of all 1,329 modelled audience members, including three wheelchair users, using reconstructed circulation, individual response and route choice, finite queues, six Crowd Managers and optional LED guidance/open belts. The main questions are the effects of concert-emergency guidance and interventions; lecture familiarity is represented explicitly but its demographic and response assumptions are not measured at Bailey.

A new manager-message comparison evaluated 100 paired fresh audiences for each of four policies, with the same six posts and final-forty commitment rule. Nearest-time instructions from all six managers averaged 162.4 s (nominal 95% interval 159.7–165.0 s), with 92/100 clearances by 180 s. Lower-floor-only nearest-time instructions averaged 178.7 s; fixed coordinated destinations averaged 177.2 s. All 400 runs cleared the complete audience. No walking, response, compliance or capacity parameter was retuned. No added LEDs or barriers were used in this comparison.

The tested corridor belts and full partitions should not be installed on the basis of this study. In the earlier 500-run intervention study, partial belts had no clear additional benefit over LEDs (paired change +0.54 s; 95% interval −0.42 to +1.50 s). They narrow circulation near auditorium-door junctions. Sightline preservation and a graph bypass do not address door swings, post bases, cane detection or crowd contact. Current Cornell EHS guidance requires unobstructed egress circulation. The experimental drawings are not installation plans.

Prioritize a venue walkthrough of clear, coordinated staff instructions and supplementary directional signs, keeping circulation unobstructed. Every proposed LED needs an intelligible local arrow and continuity to a verified exterior route, with particular scrutiny of stage-side access and balcony stairs. The simulation's exit-name messages and staff-priority rule do not validate arrow comprehension, consistency between devices, emergency power or failure behavior. Any physical pilot must be integrated with the venue's existing approved guidance.

The 180 s mean is conditional, not an operational guarantee. The earlier intervention study's slower-response sensitivity averaged 258.8 s with its combined policy, and finer integration changed individual clearances by up to 19.1 s in three checks. Geometry, response, correlated attention, external landing congestion and assistance logistics remain uncertain. No measured Bailey evacuation was available for calibration.

The accompanying manuscript documents these limitations, literature, layout review, tests and preserved experiment evidence. The software review fixes installation-validation and interface defects while retaining the historical results and reproducibility. The next decision requires real measurements and a supervised comprehension/route walkthrough, not further parameter changes to force a faster simulation.

Bailey(ing) Out

Revised 9 November 2026: intervention study and practical/code review

Abstract

The evacuation of Bailey Hall depends on the available exits, the flow permitted by aisles and doors, and the decisions occupants make as congestion develops. The model represents 1,329 people moving through a network of walkways with finite capacity and storage. Individual walking speeds, response times, familiarity, and companions affect movement, while Crowd Managers and signs provide guidance and removable barriers alter circulation. The formulation distinguishes physical delays from the delays people can observe and describes the assumptions used where Bailey-specific measurements are unavailable.

The revised computational study compares five fixed policies on 100 fresh audiences each. Original staff instructions yield a mean of 195.2 s; coordinated staff alone yield 175.9 s. The preselected dynamic-LED and partial-belt combination yields 172.5 s, with 77/100 replications clearing by 180 s. These are fixed-model results, not Bailey measurements. Slower response and material time-step sensitivity limit their operational interpretation.

A subsequent 400-run comparison of manager messages, with no added LEDs or barriers, selects nearest-time instructions from all six managers. The mean is 162.4 s, with 92/100 clearances by 180 s. The user-requested final-forty rule is held fixed across those four policies; these results remain conditional on the model.

1 Introduction

Bailey Hall is a semicircular auditorium at Cornell University, with the orchestra and mezzanine on the first floor and the balcony above. The full audience consists of 1,329 people: 527 in the orchestra, 486 in the mezzanine, and 316 in the balcony, including three wheelchair users. Six access points connect the orchestra to the mezzanine. Nine doors lead from the auditorium to the curved outer corridor, which in turn connects to the foyer and side porticoes. The balcony is served by stairways near the foyer and emergency routes beside the stage. Most visitors ordinarily leave through the foyer and its exterior staircase, although the porticoes provide additional routes to street level. The elevator at the west side of the foyer is excluded from emergency evacuation. The geometry and these restrictions come from the Bailey Hall problem description and accompanying plans [1].

The seating plan is approximately symmetric about the centre of the auditorium. Interior photographs show the wide common space, visible auditorium doors and exit signs, and clear views across much of the lower seating area. The raised mezzanine and the walls beyond its doors still separate the auditorium from the outer corridors. Occupants are therefore assumed to know the signed exit routes serving their level, without seeing the queues or obstructions beyond those doors. This distinction is consistent with Fu, Liu, and Liu's findings that visibility and familiarity influence attention to emergency exits and subsequent route choice [1, 29, 30].

The reference case is a full concert. Under the staffing rule in the problem statement, at least one Crowd Manager is required for every 250 attendees, so a full audience of 1,329 requires at least six. Six is the baseline, not a maximum: additional managers can be considered at separate posts without changing the audience or physical capacities. During regular lectures, the problem assumes no Crowd Managers and greater student familiarity with the building [1].

A short path is not necessarily a fast one. Many visitors may head toward the foyer because it is familiar, even if a side exit has a shorter queue. Others may hesitate at the alarm, wait for companions, or

discover only partway through their route that a door is blocked. The model therefore combines movement through a network with individual exit decisions. Spearpoint and Xiang compared a network model with evacuations from university lecture theatres and found that accounting for restrictions at aisles and doors was important for reasonable clearance-time predictions [6]. The representation retains aisle and door bottlenecks without simulating individual body contacts.

The principal outcome is the time between the evacuation announcement and the last occupant crossing the building's exterior boundary. Arrival at street level is recorded separately, particularly for people requiring assisted descent. The problem sets a benchmark of 180 seconds for building clearance [1]. It is not used to calibrate movement parameters.

2 Key Assumptions

The following assumptions define the scope of the model.

1. **Geometry.** Routes follow the seating rows, longitudinal aisles, transverse cross-aisles, corridors and stairs shown in the plans. The short stepped passage joining the outer transverse cross-aisle to the inner seating-block circulation is treated as a public connector, not a restricted seating row. It does not provide wheelchair access. People cannot cut through seats or walls [1].

2. **Audience.** Walking speeds and response times vary among individuals. The reference audience includes 20% adults aged at least 65. This approximates a mixed-age university concert, but is not a demographic estimate for Bailey Hall: the national share of older adults is about 18%, whereas particular music audiences may be much older [21, 22]. The audience mix is therefore varied separately rather than treated as known.

3. **Response.** Recognition and movement preparation are represented by separate delays. The main hall is treated as one alarmed space, without assigning separate alarm-arrival times to seating sections. There is no additional, explicitly sampled belongings-collection delay; brief individual actions are encompassed by the response-time distribution. Hopkin, Galea, and Deere observed substantially longer pre-movement times and frequent coat-related actions in a real theatre evacuation, so the reference represents prompt, clearly directed departure rather than their measured audience [7].

4. **Movement.** Links have finite flow and storage. Congestion develops when a downstream link or doorway cannot admit people as quickly as they arrive. Spacing and time-headway observations motivate this network approximation; contacts, pushing, and falls are not resolved [4, 5].

5. **Information.** Occupants initially know the signed auditorium exits serving their level but not the conditions along the corresponding exterior routes. This relatively favourable starting knowledge reflects the open room and visible signs without implying a view through the surrounding walls. Familiarity and visual attention can still bias choices among known doors [29, 30].

6. **Social behaviour.** Nearby people can accelerate initial recognition, while companions may wait for one another and coordinate their routes. General crowd imitation does not continue to alter route preferences after departure; later social coordination is restricted to identified companions. This distinction follows evidence that groups affect early response and approach more clearly than discharge through a door [9].

7. **Interventions.** Managers and signs change information, not passage capacity. Only low or visually transparent barriers are considered, so installations do not obscure the stage, exit openings, or neighbouring circulation. They can still reduce usable width or lengthen a route [16, 15].

8. **Accessibility.** Three wheelchair users remain in the population, and the elevator is excluded as instructed in the problem. Backstage and ground-level spaces are outside its scope. Assistance is represented separately from walking on stairs [1, 27].

Numerical choices without venue measurements are stated where they enter the model. Published studies motivate the mechanisms but do not provide a fitted parameter set for Bailey Hall.

3 Model Formulation

3.1 Navigation Network and Occupant State

Let V denote junctions at aisle intersections, doors, stair connections, and changes in direction, and let E denote the walkway links. The navigation network is the directed graph

$$G = (V, E). \tag{1}$$

A link e has walking length L_e, horizontal length $L_{e,\text{plan}}$, usable width w_e, lane count m_e, floor, and permitted direction. Its path follows the reconstructed walkway. A person may leave a seating row through its ends but cannot use a different row as a shortcut. Closed and inaccessible links are excluded from the set of feasible routes [6].

The orchestra seating plan shows transverse cross-aisles dividing the outer seating blocks. At the middle break, the outer cross-aisle meets the curved longitudinal aisle and continues through a short stepped opening into the inner seating-block circulation. The stair-like treads and bounded opening in the enlarged plan, together with the open internal circulation visible in photographs, identify this as a passage rather than a row of seats. The same arrangement is represented on the opposite side where the plan shows its corresponding opening. In the network, this connection joins the neighbouring aisles, allowing movement between seating blocks without passing through occupied rows. Its stepped section uses stair travel and service rules and is unavailable to wheelchair users; the accessible route remains elsewhere in the network [1]. The topology follows the drawn passage rather than an adjacent seat row. The implemented 1.2 m horizontal run and width and 0.54 m rise (three assumed 0.18 m steps) are explicit reconstruction assumptions, not surveyed measurements.




Figure 1: Orchestra cross-aisle connection. It is part of the circulation network, with a stepped transition and no through-route across seating rows. Schematic, not to scale.

The model distinguishes seven exterior exit groups: the foyer; the west and east porticoes; the west and east stage routes; and the northwest and northeast balcony exits. The seven groups follow the building plans [1] and retain distinct queues and familiarity levels.

Each occupant begins at a seat with a walking speed, response delay, social group, and exit preference. The principal states are recognition, response, waiting for companions or row access, movement, queuing, and departure. The separate belongings-preparation state is omitted; the model accounts for leaving a seat through travel along its row, but does not add time for collecting possessions. An assisted occupant may reach the exterior before reaching street level.

Metric and inventory assumptions. The traced network preserves topology and section totals, not a chair-by-chair surveyed inventory. The orchestra is allocated 323 central and 102 seats on each side; the mezzanine has 483 ordinary chairs and three separate wheelchair positions; the balcony has 316 chairs. Wheelchair origins are assumed at rear raised-level stations 4, 6 and 8. The local footprint is approximately 32 m wide and 25 m deep relative to the stage reference. These dimensions and the following clear widths remain editable reconstruction assumptions, held fixed during the intervention comparison.




Figure 2: Occupant states. Building departure and arrival at street level are recorded separately.

Element	Implemented metric assumption
Ordinary aisle / stepped connector	1.2 m clear width
Outer corridor	2.4 m clear width
Auditorium / portico doorway	1.4 m clear width
Rear balcony stair	1.8 m, two divided lanes; two 2.1 m drops
Foyer inlet / exterior doorway	1.8 m / 1.5 m clear width
Stage / direct balcony escape doorway	1.2 m clear width

The existing-sign arrows are an inferred mapping from signed auditorium openings to exterior routes, not a verified sign inventory. Wall and column coordinates constrain visibility but do not resolve crowd occlusion. Ordinary street-level arrivals add assumed external free stair travel (12 m from the foyer, 8 m from porticoes, 3 m from other exits); external queues and landing spillback are omitted. Only the building-exterior endpoint is used for the primary 180 s comparison.

3.2 Audience Characteristics

Each ambulatory occupant i receives a free walking speed v_{0i}. Let Z_i be a standard normal draw, $\mu = 1.40$ m/s the reference mean for non-older adults, $\sigma = 0.18$ m/s its standard deviation, and $f_i = 0.85$ for occupants aged at least 65 and 1 otherwise. The operator $\mathrm{clip}_{[a,b]}(x)$ restricts a value to $[a, b]$. Then

$$v_{0i} = \mathrm{clip}_{[0.5,2.0]}[f_i(\mu + \sigma Z_i)], \qquad Z_i \sim \mathcal{N}(0,1). \tag{2}$$

The reference older share is 20%, and the three wheelchair users have a separate free speed of 0.8 m/s. Murtagh and colleagues report mean outdoor speeds of 1.31 m/s at a usual pace and 1.47 m/s at a medium pace, placing the 1.40 m/s assumption between them [18]. Indoor walking experiments by Daamen and Hoogendoorn report observed and estimated free-speed spreads ranging from roughly 0.15 to 0.25 m/s in several flow arrangements, making 0.18 m/s a reasonable single-group spread [19]. In the Rotterdam Study, the mean gait speed of community-dwelling older adults was 1.20 m/s; the factor 0.85 gives approximately 1.19 m/s before clipping [23, 20]. These are walking speeds before congestion, not speeds in a crowded aisle or on stairs. The age mix and the transfer from these studies to a concert remain assumptions.

For ambulatory occupants, effective body radius is normally distributed with mean 0.22 m and standard deviation 0.02 m, bounded by 0.17 and 0.30 m. The wheelchair radius is 0.45 m. These are approximate space requirements. Speed on stairs is multiplied by 0.57 for ordinary walkers and 0.51 for older walkers, with any scenario-specific environmental factor. NIST measurements show that stair movement differs substantially from free corridor walking, although they do not establish these multipliers for Bailey Hall [26].

3.3 Recognition, Response, and Group Behaviour

Recognizing an alarm and deciding to move are treated as separate delays. Hopkin, Galea, and Deere found that response times in a theatre were strongly right-skewed and depended in part on seat location

[7]. A delay τ with median m and logarithmic standard deviation s is represented as

$$\tau = \exp(\log m + sZ), \qquad Z \sim \mathcal{N}(0, 1). \tag{3}$$

Recognition has median 6 s and logarithmic standard deviation 0.6. The subsequent response delay has median 14 s and the same logarithmic standard deviation. No additional linear correction for distance from the aisle or a balcony seat is imposed: both factors already affect travel through the reconstructed network. Hopkin, Galea, and Deere found that pre-movement behaviour varies among occupants and may depend on seat location, but their study does not establish a distance coefficient transferable to Bailey Hall [7]. The chosen 6 s and 14 s medians describe a clearly signalled, prompt-response case. They are appreciably shorter than the mean time to movement observed in the unannounced Marlowe Theatre evacuation, where Galea and colleagues reported 55.6 s for non-disabled participants excluding helpers [8]. The study measured the full interval preceding movement rather than these two clocks separately. Faster recognition (3 s) and response (8 s), together with a slower pre-movement scenario, remain comparison cases rather than calibrated alternatives.

There is no separate random draw for retrieving coats or personal belongings. The general response delay covers ordinary hesitation and brief preparation, but not prolonged retrieval. In the Marlowe Theatre study, 39% of the observed population collected or put on coats, so omitting an explicit retrieval phase may shorten predicted times [8]. It cannot be defended by analogy with an aircraft; the reference instead represents a scenario with clear instructions to depart without collecting possessions.

Initial recognition may accelerate as nearby occupants begin reacting. Let $\phi_i \in [0, 1]$ be the fraction of occupant i's original seat neighbours who have begun responding or moving, and let $c_i(t)$ denote progress through the recognition phase. During that phase,

$$\frac{dc_i}{dt} = 1 + \phi_i. \tag{4}$$

Only the initial recognition clock is affected; later route decisions do not depend on the movement of unrelated distant occupants. The local influence is consistent with observed social cues during evacuation, while the unit coefficient is a modest modelling assumption rather than a measured response factor [9, 29].

About half the audience belongs to groups of two to four. Of these groups, 70% are pairs, 20% consist of three people and 10% of four. Members sit near one another, may wait for companions for at most 20 s, and normally adopt the leader's destination unless an accepted safety instruction or an inaccessible route requires a change. Pairs are more common than larger groups because coordination between one or two companions is a plausible concert-going pattern; the shares are not measured for Bailey Hall. The waiting cap is shorter than a prolonged search because the group begins in adjacent seats and encounters the same alarm. Bode and colleagues found that groups mainly influence response and approach rather than the capacity of the final exit [9]. Group members already on the same link may also pace one another locally, as described below.

3.4 Walking Service and Finite Storage

Each link e has walking-service capacity C_e^{walk} (persons/s) and storage limit S_e (persons). Here m_e is its lane count, $\bar{v}_e$ its representative speed, $d_b = 0.44$ m the assumed mean body diameter, $H = 0.7$ s the following headway, and $\rho_{\max} = 4.5$ persons/m^2 the storage density. Define $\gamma_e = L_{e,\text{plan}}/L_e$, which converts walking length to horizontal length. Then

$$C_e^{\text{walk}} = \frac{m_e \bar{v}_e}{d_b + H\bar{v}_e}, \qquad S_e = \max(m_e, \lfloor \rho_{\max} L_e w_e \gamma_e \rfloor), \qquad \rho_{\max} = 4.5 \text{ persons/m}^2. \tag{5}$$

For stairs, drop_e is the vertical drop and $L_e = \sqrt{L_{e,\text{plan}}^2 + \text{drop}_e^2}$. The lower bound $S_e \geq m_e$ allows one person per lane on short links, even where this exceeds the area-based density. Storage does not represent contact pressure.

The flow formula comes from an assumed spacing of $d_b + H\bar{v}_e$ between successive pedestrians: dividing speed by that spacing gives a per-lane passage rate. Seyfried and colleagues studied how pedestrian spacing and density relate to speed, while Johansson identified approximately constant net-time headway as an important feature across several datasets [4, 5]. The 0.7 s headway gives a finite separation between successive pedestrians even when they walk quickly, while 4.5 persons/m^2 is an upper storage assumption used to prevent unbounded accumulation on short passage links. Neither quantity is measured for Bailey Hall, and storage density should not be interpreted as a safe operating density.

Where the plan does not specify lanes, the reconstructed width determines an approximate count:

$$m_e = \max\left(1, \left\lfloor \frac{w_e}{0.6\ \mathrm{m}} \right\rfloor\right) \qquad \text{for a traversable link.} \tag{6}$$

The nominal 0.6 m lane width is a geometric convention, not a measured queue spacing. Each person must still fit through the actual link; in particular, wheelchair accessibility cannot be inferred from m_e alone. Seat rows have their own body-spacing storage and release people through their two ends. They cannot be used to pass between aisles. No additional fixed speed cap is assigned to an occupied row. Spearpoint and Xiang found that a separate row-speed reduction generally overpredicted lecture-theatre clearance times when aisle and doorway restrictions were already represented [6]. The representative speed in Eq. (5) uses the configured free-speed mean and the applicable corridor or stair factor; faster walkers can therefore affect both link travel time and potential service.

The two directions of a passage cannot independently claim its full capacity. Let $m_{e,+}$ and $m_{e,-}$ be the numbers of logical lanes assigned to outgoing and opposing streams. When only one direction is active, it may use all m_e lanes. If both are active on a link with at least two lanes, lanes are divided as evenly as possible, with any extra lane assigned to the direction whose queue has been waiting longer. An occupied lane is not reassigned before its users have cleared it. With $\delta \in \{+, -\}$ denoting direction, the available service is

$$C^{\mathrm{walk}}_{e,\delta} = \frac{m_{e,\delta}\bar{v}_e}{d_b + H\bar{v}_e}, \qquad m_{e,+} + m_{e,-} \le m_e. \tag{7}$$

On a one-lane passage, entry is restricted to one direction at a time until it clears. This is an integer-lane approximation of self-organized counterflow, rather than a calculation of individual avoidance. Feliciani, Murakami, and Nishinari showed that bidirectional capacity depends on both opposing-flow conflicts and lane formation [2]. Their results support accounting for shared capacity, not the precise lane-assignment rule used here. In all cases, the combined directional service cannot exceed the physical passage capacity.

Doors and stair entrances have an additional admission limit. Let q_e be their specific flow in persons/(m s), b_e the boundary width lost at each side of an opening, and f_{env} an environmental factor (one in the reference scenario). Define $[x]_+ = \max(0, x)$. The effective width and maximum gate service are

$$w_{e,\mathrm{eff}} = [w_e - 2b_e]_+, \qquad C^{\mathrm{gate}}_e = q_e w_{e,\mathrm{eff}} f_{\mathrm{env}}. \tag{8}$$

The baseline takes $q_e = 1.3$ persons/(m s) and $b_e = 0.15$ m for doors, and $q_e = 1.0$ persons/(m s) and $b_e = 0.09$ m for stair passages. For stair flights divided into m_e lanes, the aggregate usable width is $m_e[w_e/m_e - 2b_e]_+$. These specific flows lie within commonly used engineering ranges: Gwynne and colleagues report the SFPE doorway value of 1.3 persons/(m s) and stair rates of approximately 0.94–1.16 persons/(m s) [3]. The effective-width correction is a standard simplifying convention, but actual door operation and leaf geometry can alter throughput [3]. In particular, if the effective width is zero, the gate has no service; an arbitrary minimum positive width is not introduced. No separate urgency or luggage multiplier is applied.

Flow through a passage is limited by both its walking-service rate and any gate at the next link. People are admitted in their arrival order, with fractional service carried between short time intervals so that the nominal capacity is not rounded to zero at each interval. Actual congestion is determined by these rates and by downstream storage, not by an additional perceived-density penalty.

Let n^k_e be the number on link e at step k and A^k_e, D^k_e the admissions and departures during that step. Occupancy satisfies

$$n^{k+1}_e = n^k_e + A^k_e - D^k_e, \qquad 0 \le n^k_e \le S_e. \tag{9}$$

A person occupies storage even while travelling along the link. A full downstream link blocks transfers and causes queue spillback. At a junction, entry in either direction is permitted only when the assigned lane and the receiving link have enough space; counterflow never creates additional storage or service.

The two physically divided rear-stair lanes are continuous through the entrance approach, upper flight, intermediate landing connection, lower flight and lower approach. These segments retain separate storage and service but share their logical lane directions. Their effective lane count is two; their physical widths are unchanged. Closing a logical lane to new admissions does not freeze people already using it: they may continue into the next segment of that same lane, subject to unchanged receiving storage and service. A lane reverses only after every occupant in the continuous passage has left it. This distinction is necessary for drainage, and does not permit entry from seat rows or other branches into a lane being cleared. This convention follows the divided-flight topology in the supplied brief and prevents an artificial graph boundary from assigning head-on directions to the same physical lane. The same continuity convention applies to the four collinear parts of each stepped orchestra cross-aisle; the short tread-to-level transition must not generate incompatible lane directions. It is not an added intervention or additional capacity.

Within each lane, waiting people are served in their order of arrival; the ends of a seating row are ordered by their individual readiness times. Someone who has not completed the link's walking time cannot yet enter its discharge queue. Different lanes may advance independently, but a formed doorway queue cannot be overtaken. Opposite faces of a gate have distinct arrival queues: a blocked incoming queue does not suppress the outgoing stream needed to drain it. Both directions debit the same gate-service budget, so separating these queues never doubles capacity. The model thus separates travel along a passage from waiting to leave it.

Companions who remain on the same link, travel in the same direction, and are within 4 m of one another adopt the slowest member's free speed. Farther-separated members do not hold an entire group to that pace. Bode and colleagues' observations suggest that much of the effect of social groups occurs before the final bottleneck, which supports representing this coordination locally [9]; the 4 m threshold is an assumed range. Let ℓ_i^k denote a walker's remaining distance on the current link, v_i^k the current speed, and t_i^{ready} the projected completion time. Then

$$\ell_i^{k+1} = \max(0, \ell_i^k - v_i^k \Delta t), \qquad t_i^{\text{ready}} = t_k + \ell_i^k / v_i^k \quad (v_i^k > 0). \tag{10}$$

A person who has reached the end of a link still waits when downstream storage or service is unavailable.

3.5 Perception and Exit Choice

The approximately symmetric auditorium and the visible exit signs make the auditorium doors relatively easy to locate. The interior photographs show long sightlines across the lower seating, but the raised mezzanine and perimeter walls conceal much of the circulation beyond those doors. The reference case therefore assumes knowledge of the signed exits serving each person's level, not sight of every exterior doorway, queue, or obstruction. Fu, Liu, and Liu found that familiarity and visual attention affect use of available exits [29, 30]. Thus knowing an exit exists does not determine whether it is selected, and sign detection is not used to teach an exit that the occupant already knows.

At each junction, person i estimates the walking time to a candidate exit group g along connected, accessible links. Let $\mathcal{P}_{ig}$ be the set of feasible paths to g, v_{ie} the expected free speed of person i on link e, and $\mathcal{V}_i(t)$ the gates whose queues are directly visible to that person at time t. A gate is visible only on the same floor, within 15 m, and without a wall or column across the sightline. Let $\widehat{Q}_{ie}(t)$ count visible waiting occupants and let C_e^{gate} be the nominal gate capacity. The perceived route time is

$$\widehat{T}_{ig}(t) = \min_{P \in \mathcal{P}_{ig}} \left\{ \sum_{e \in P} \frac{L_e}{v_{ie}} + \sum_{e \in P \cap \mathcal{V}_i(t)} \frac{\widehat{Q}_{ie}(t)}{C_e^{\text{gate}}} \right\}. \tag{11}$$

The first term depends on the occupant's position and physical route lengths. The second adds delay only at a gate whose queue can be seen. There is no separate penalty based on the total number of

people somewhere along an ordinary aisle. They still cause physical queues through the service and storage constraints in Section 3.4. Treating an unseen queue as unknown, rather than supplying its true length, avoids giving people perfect knowledge of the building. The 15 m sight range is an assumed local observation distance; it does not assert that an actual line of sight is clear through a crowd.

Two broad preferences replace the six finely weighted behavioural categories. A proportion $p_T = 0.65$ uses estimated route time as its main criterion, while $p_H = 0.35$ has a preference for the familiar foyer. Let H_i be 0 seconds for a time-oriented occupant and 12 seconds for a familiarity-oriented occupant. Let $F_g = 1$ for the foyer and 0 for other exits. Finally, ε_{ig} is a fixed Gumbel preference draw, with scale 4 seconds, for each occupant–exit pair. The perceived utility is

$$U_{ig}(t) = -\widehat{T}_{ig}(t) - H_i(1 - F_g) + \varepsilon_{ig}, \qquad g_i = \arg\max_g U_{ig}(t). \tag{12}$$

Fixed random utility allows two people with similar routes to make different choices without independently redrawing their tastes at every junction [10]. Experiments support the existence of travel-time and familiarity preferences, not a particular population split [11, 30]. The 65/35 split, 12 s familiarity allowance, and 4 s preference dispersion are therefore illustrative, not values estimated by the cited experiments. A balanced preference split is a useful alternative because no observed Bailey Hall choice frequencies are available. People travelling with companions normally retain the leader's destination, so companionship is represented separately rather than through another arbitrary behavioural type. Accepted guidance takes priority over either preference when it identifies a feasible exit.

Choices may be reconsidered upon reaching a junction, encountering a visible queue, receiving new guidance, or learning that a planned link is closed. To avoid reacting to very small estimates, a person switches from the current destination g to a new destination h only if

$$U_{ih}(t) - U_{ig}(t) \geq 8 \text{ s}. \tag{13}$$

The eight-second margin represents inertia in the presence of uncertain queue estimates, not a measured switching threshold. In Liao and colleagues' experiments, people who changed exits formed only about 0–7.5% of participants within individual runs, despite opportunities for reconsideration [11]. Reviews therefore occur at junctions or after meaningful new information, but they do not force frequent switching. A smaller 5 s margin represents a more adaptive alternative, rather than an established typical response. Any chosen destination becomes effective only at a connected junction; it cannot reverse completed travel or take a shortcut through seating.

3.6 Lecture Students and Unfamiliar Visitors

Student status is not a movement class. The implementation separates initial exit knowledge, entrance preference, age, response and staffing. The brief assumes regular lecture students know emergency exits and have no Crowd Managers [1]; it does not establish a faster walking speed or a precise response distribution.

Let k denote `knowledge`. The foyer is known initially; each other exit eligible for the person's seating level is included in their initial known set independently with probability k, using a fixed person–exit draw. This is route knowledge, not awareness of remote queues or closures. Let p_H denote `familiarityShare`. That legacy field name is the share with the 12 s foyer utility preference described above, not a measure of knowing the building well. A well-informed regular attendee can still prefer their usual entrance; an unfamiliar visitor can know the entrance without knowing alternatives. The two controls are independent.

The legacy lecture preset uses $k = 1$, $p_H = 0$, no managers, 10% older share and recognition and preparation medians of 3/8 s. The concert reference uses $k = 1$, $p_H = 0.35$, six managers, 20% older share and 6/14 s medians. Both initially know all eligible exits. Their difference is a bundled scenario assumption, not a measured student effect or an isolated familiarity comparison. It is retained for reproducibility and labelled accordingly in the interface.

Three controlled information presets now keep demographics, speeds, response, groups and compliance fixed, with no managers: $(k, p_H) = (1, 0.35)$, $(0.5, 0.35)$, and $(1, 0)$. These isolate reduced exit knowledge and removal of foyer bias respectively. The value 0.5 is a sensitivity assumption, not an estimated visitor probability. Tests verify that a common seed preserves the other traits. No new lecture-versus-visitor Monte Carlo result is claimed in this review.

Tong et al.'s observations in a university library show that familiarity and exit choice depend on context, including whether an evacuation is a drill [33]. They do not calibrate these Bailey probabilities. Another limitation remains: knowing an exit name implies graph-route knowledge in the current model. It does not represent incomplete cognitive maps, wandering, or interpretation of successive arrows. This is particularly relevant to unfamiliar visitors and must be resolved before treating the sign results as a real wayfinding prediction.

3.7 Current-State Guidance and Route Commitment

A fresh message is not a fresh random route-choice lottery. Fixed preferences, notice and compliance draws remain fixed. At the time an instruction is considered, the model uses the occupant's current link, direction, remaining distance, destination and known obstructions. Instructions received before movement may establish an initial destination. After movement begins, a different recommendation is accepted only if it is feasible and either the current route is known to be infeasible or the locally estimated improvement is at least eight seconds:

$$\text{accept switch} \iff h \text{ feasible} \wedge \left[g \text{ infeasible} \vee \widehat{T}_{ig}(t) - \widehat{T}_{ih}(t) \geq 8 \text{ s} \right]. \tag{14}$$

Both alternatives are evaluated from the next physically reachable junction, after completing the current link. Its unfinished walking time is common to both alternatives and is not discarded. Only gates visible from the person's current position contribute queue estimates. A proposed return includes the positive distance of the return traversal. Known closures can override commitment; unknown remote conditions cannot. An occupant already traversing the final link to an exterior boundary completes that crossing and cannot accept a diversion. Repeated consistent messages can reinforce a destination without changing it.

This extends the original route-switching inertia to instructions received while moving. It addresses the implausible late changes observed when accepted guidance previously overrode a nearly completed route without considering progress. It is a computational/behavioural convention, not a newly measured Bailey parameter. Liao et al. found comparatively infrequent route revisions, and Galea et al. stress consistent voice and sign information [11, 13]. Those findings motivate persistence and consistency, but do not establish an eight-second threshold. The same rule is applied to the revised reference and every intervention arm; improvements from this correction are not credited to LEDs or belts.

3.8 User-Requested Nearest-Time and Final-Occupant Scenario

Engine 1.4.0 adds a separately configured behavioural scenario. It does not replace the historical 1.3.0 LED/barrier experiment below. In the initial nearest-time candidate, CM1–CM4 retain their posts but broadcast "use the nearest exit by estimated travel time" instead of a fixed portico destination. CM5 and CM6 retain their balcony instructions in that candidate. The subsequent comparison in Section 7 selects nearest-time instructions from all six managers for the current default. Each compliant listener evaluates known, feasible exits from the next reachable junction using Eq. (11), with current visible queues and individual speed. The unfinished link remains mandatory. This common public rule does not supply unknown exits or remote queue information. Ordinary current-state switching inertia still applies.

The optional `tailFallback` rule begins when at most 40 people remain anywhere inside the building. Exterior wheelchair waiting is not included in this count. A person who has completed a link and remained in its discharge queue for strictly more than 10 continuous seconds during this final phase selects

$$g_i^* = \arg \min_{g \in K_i \cap \mathcal{F}_i(t)} \widehat{T}_{ig}(t),$$

where K_i is the known-exit set and $\mathcal{F}_i(t)$ restricts routes by accessibility, width, learned closures and the existing return-lane convention. The snapshot uses current waiting occupants and the original visibility rule. Foyer preference, fixed random taste, companion destinations, prior guidance and the eight-second switching threshold do not enter this final choice. Ties are broken by exit identifier.

The timer starts at the later of entry into the final phase and the current queue arrival. Progress onto a new link resets it. Recognition, preparation and seat/group waiting are not locomotion stalls. A person already traversing an exterior-crossing link continues outside. Each stalled person acts individually; moving members of the final forty are not redirected by someone else's stall.

The selected exit and complete route are then locked. Subsequent guidance, companion choices and changing queue estimates are ignored, while travel length, FIFO, lane direction, gate service and finite storage remain unchanged. A final-commitment event retains the decision state, alternatives and route. If no feasible known exit exists, none is invented. A locked path encountering an obstruction can remain unresolved; the lock cannot authorize crossing a barrier or manufacture capacity.

These thresholds and permanent withdrawal from guidance are user-requested scenario assumptions, not values calibrated to Bailey or established by the literature. The emergency JSON enables them explicitly, and the interface allows them to be enabled for other scenarios. Omission disables the rule, preserving historical configurations. New regression experiments are reported separately; the historical 100-replication-per-policy means below must not be attributed to this revision.

A regression experiment evaluated ten paired audiences (seeds 5001–5010) with the revised manager messages, with and without the final-occupant rule. Both arms cleared all 1,329 people in every run, averaged 182.5 s and met 180 s in 3/10 replications. All paired clearance times were identical despite 90 final commitments in the enabled arm. All 90 retained an exit already minimizing their estimated time. This sample does not demonstrate a clearance benefit. It was not used to retune parameters and does not replace the historical 100-replication study.

3.9 Managers and Announcements

The baseline concert includes six Crowd Managers, the minimum specified for 1,329 attendees [1]. Additional managers can occupy distinct posts. Each becomes active after a lognormal delay with median 10 s and logarithmic standard deviation 0.5. A spoken instruction can reach an occupant on the same floor within 12 m, provided no represented wall blocks the acoustic path. Let $h = 0.35\ \mathrm{s}^{-1}$ be the hearing rate, u_i^{CM} a fixed uniform draw for occupant i, and A_i^{CM} its acceptance indicator. The probability of hearing during an exposure interval Δt and the chance of accepting a heard instruction are

$$p_{\mathrm{hear}}(\Delta t) = 1 - e^{-h\Delta t}, \qquad A_i^{CM} = \mathbf{1}\{u_i^{CM} < 0.85\}, \qquad u_i^{CM} \sim U(0,1). \tag{15}$$

Hearing and acceptance remain distinct. The 12 m range confines each manager's influence to a local part of the open hall, and the persistent draw avoids making compliance inevitable after repeated instructions. The 85% acceptance assumption represents a relatively high but incomplete response to a clear instruction from trained staff. In an analysis of 126 real-emergency videos, van der Wal and colleagues found that staff guidance was associated with less delayed response than alarms alone; their analysis did not measure the probability that a given person complied [24]. Mayr and Köster studied routing with limited compliance, supporting its treatment as an uncertain behavioural parameter rather than perfect obedience [25]. Neither study establishes 85% for Bailey Hall; a 70–90% range represents different levels of trust and instruction clarity.

Hearing an instruction brings an occupant who has not yet recognized the alarm into the response phase. Accepting a feasible destination recommendation takes precedence over an ordinary route preference, subject to the current-state commitment rule in Section 3.7; it cannot overcome a blocked corridor or inaccessible stair. Subsequent consistent instructions reinforce the destination; a newly discovered obstruction may require another choice. A manager is modelled as a source of information, not as an extra body occupying doorway capacity.

An optional pre-announcement reaches 60% of the audience, and 70% of those reached accept its suggested seat-block exit. Reach means successful reception and attention, not that the public-address system is inaudible to others. A recommendation does not cancel the ordinary recognition, response, or companion-waiting delays. These rates are assumptions for an advance-information scenario, not measured effects.

Managers can remain at their posts or walk between connected, level, non-gated corridor locations at an assumed 1 m/s, provided the route is at least 1.8 m wide and not occupied in a way that prevents passage. Liu and colleagues distinguish stationary and moving guide effectiveness and show that placement matters [28]. The chosen patrol speed and width screen keep the range of staff instructions physically limited without resolving detailed staff–audience contacts.

3.10 Exit Signs and Dynamic Guidance

Directional signs make the known exits easier to locate and can recommend a different route. A wall sign occupies a point and has a facing direction; an LED strip follows a polyline along an existing walkway. Each installation has a location, activation time, viewing range, detection probability, acceptance probability, and public exit message. Static installations retain their message, while dynamic signs may update it. The distinction between making a sign visible and making its guidance persuasive follows the signage experiments of Galea and colleagues [12]. Legibility is represented through visibility and detection rather than a detailed model of illumination or eye movement.

A wall sign is visible only when it is active, on the observer's floor, within range, in front of the sign, and not hidden by a represented wall or column. Let $\mathbf{y}_j$ and $\mathbf{f}_j$ be sign j's position and facing unit vector, $\mathbf{x}_i$ the occupant's position, R_j its viewing radius, and α_j its facing half-angle. Let I_{floor}, I_{range}, I_{facing}, I_{clear}, and I_{active} be indicators of, respectively, floor agreement, distance, facing, an unobstructed sightline, and activation. Their product E_{ij} indicates geometric eligibility to see a sign:

$$E_{ij} = I_{\text{floor}} I_{\text{range}} I_{\text{facing}} I_{\text{clear}} I_{\text{active}}, \tag{16}$$

$$I_{\text{range}} = \mathbf{1}\{\|\mathbf{x}_i - \mathbf{y}_j\| \le R_j\}, \tag{17}$$

$$I_{\text{facing}} = \mathbf{1}\left\{\mathbf{f}_j \cdot \frac{\mathbf{x}_i - \mathbf{y}_j}{\|\mathbf{x}_i - \mathbf{y}_j\|} \ge \cos\alpha_j\right\}. \tag{18}$$

If the observer occupies the sign's point, the facing condition is satisfied. For a strip, visibility is checked along its segments at points no more than 0.5 m apart, without a facing cone. Walls and columns can block sight, but head occlusion and gaze direction are not modelled.

Added LEDs activate after 3 s, are visible within 8 m, and, for wall signs, have a 70° half-angle. Their detection probability is 0.77 and their acceptance probability is 0.8. Existing exit signs are assigned detection probability 0.38. Galea, Xie, and Lawrence observed conventional signs being noticed by 38% of participants and tested dynamic signs by 77% in a controlled unfamiliar-building setting [12]. These are transferred detection values, not Bailey Hall measurements. In that study, people who noticed the dynamic sign followed it; the present 0.8 acceptance probability is a more cautious transfer to a crowded concert. The 3 s activation represents rapid illumination after an alarm; the 8 m range and 70° cone limit influence to people with a plausible view of a sign. The 0.8 acceptance value allows a noticed sign to be disregarded. The remaining placement and acceptance values are assumptions. No numerical smoke or darkness multiplier is imposed without optical measurements; reduced-visibility scenarios instead use separately stated detection assumptions. Galea and colleagues' later full-scale trials also suggest that voice messages and changing signs must be mutually consistent; they do not provide a second independent detection probability [13].

For a particular person and sign, noticing and accepting are separate, persistent tendencies. Seeing the same unchanged message again does not automatically create another independent chance to notice it. A new message can be considered, but the underlying individual tendencies remain the same. Noticing a message gives information about the recommended direction; accepting it can commit the person to that

exit if the route is accessible and the current-state switch rule permits it. If the message conflicts with an already accepted Crowd Manager instruction, the manager's instruction takes priority. This rule avoids simultaneously committing the same person to incompatible destinations.

Dynamic signs may change their messages when managers observe congestion or a blocked exit. An observation becomes available locally after 2 s and reaches the sign controller after an additional 3 s. The controller uses the most recent reports from managers with a view of the relevant gate; it does not see the true state of every corridor. Signs compare estimated route times with reported queues and change direction only if the alternative is at least 8 s better and the current message has been displayed for 20 s. This uses the same improvement margin as individual route reconsideration, while the holding time prevents rapid public-message reversals. The observation and reporting delays are modest scenario assumptions, not measured Bailey communication times. López-Carmona and Paricio García's adaptive guidance research supports responding to changing congestion rather than relying on a fixed assignment [14]. An LED strip points along the currently recommended route; its arrow changes when that route changes.

A manager who can see a gate is assumed to know its current queue and nominal service rate. Reports from other managers remain in use until replaced. If no report exists, the controller falls back to nominal route time rather than assuming that a gate is known to be empty. The model gives staff precise counts at gates they can see, but no instantaneous information about the whole building. Unexpected obstructions are learned only through local observation or a report.




Figure 3: Local gate observations reach the sign controller after a delay. Occupants receive guidance by hearing a manager or noticing a sign.

3.11 Temporary Barriers

Temporary barriers are limited to low belts, ropes, and open railings that preserve sightlines toward the stage and nearby exits. Opaque panels are excluded. The model treats a barrier as a physical object that can redirect occupants, change walking distance, or reduce usable width, but never increase a doorway's service rate by itself.

For a barrier of length b placed at angle θ to the corridor direction, let w_e be the original corridor width. The projected obstruction and remaining bypass width are

$$w_{\text{span}} = |b \sin \theta|, \qquad w_{\text{bypass}} = w_e - w_{\text{span}}. \tag{19}$$

The barrier is anchored along one side, leaving a single detour around its free end. The bypass follows the altered walkway rather than crossing the device. A positive bypass uses the same lane-width convention as Eq. (6) and the same walking-service rule as any other passage; an oblique barrier may also increase walking distance. A barrier spanning the entire width closes the link. Devices are confined to identified corridor positions, away from seating rows and door thresholds. A partial bypass must remain at least 1.1 m wide, and all wheelchair origins must retain an accessible path. This width is a modelling screen, not a statement of building-code compliance. Experiments by Wang and colleagues and by Feliciani and colleagues show that obstacle placement can improve or worsen flow depending on geometry and crowd conditions [15, 16, 17]. Consequently, no general percentage improvement is assigned to barriers.

3.12 Evidence-Based Intervention Comparisons

The design objective is to reduce the average of full-house clearance times through arrangements of public guidance and visually open devices, without calibrating walking speed, reaction times, audience composition, door capacity or inferred dimensions to the target. Guidance choreography is coordinated across nearby posts. Static-message LED strips retain a fixed route indication but are assumed to use conspicuous active illumination; dynamic-message strips additionally revise the indicated exit through the existing delayed-report controller. Transferring detection results from active signs to strips remains uncertain. The 66% redirection reported in full-scale station trials is not a time reduction or a second independent detection probability [13].

No generic obstacle benefit is assumed. Wang et al.'s safety barriers increased clearance times by 0.88% and 2.67% at the tested distances, while other devices behaved differently [15]. Feliciani et al. show that obstacles can relocate local congestion [16]. Their opaque cylinders are not proposed here. The admissible devices are low belts, ropes or open rails with no opaque panels and no added sightline obstruction. Candidates include partial side-anchored bypasses and full internal-corridor partitions between exit service areas, as contemplated by the supplied brief. No device occupies an exit threshold. A full partition closes its graph connection rather than creating a hidden capacity bonus. All occupied origins, including the three wheelchair positions, must retain an exterior route. This is a theoretical layout screen, not permission to install a barrier in a real egress path.

Pilot audiences beginning at seed 3001 are used to compare fixed layouts. Every tried layout, including slower and unfinished cases, is retained. The final policies are frozen before an independent block of 100 audiences, seeds 5001–5100. Within this block each policy shares the same audience seed, while different replications resample audience traits, groups and all named stochastic streams. Separate arms isolate LEDs, barriers and their combination with identical staff posts/messages. Comparison with the original-post reference is reported separately. Low-compliance and numerical-refinement experiments are labelled sensitivities. A sanguine interpretation of a small pilot is avoided: a mean below 180 seconds is distinct from meeting the threshold in every replication, and from robustness to unmeasured geometry.

3.13 Evaluated Experimental Layout

This is a preserved simulation layout, not a recommendation to install barriers. The practical review below rejects those belts as an installation proposal. The selected experimental candidate uses the same six posts as the reference. CM2, CM3, CM5 and CM6 recommend the foyer; the end posts retain portico messages. All four factorial policies use these coordinated messages. The original-message baseline is an additional control. Locations below are graph junctions, not surveyed installation coordinates.

Manager	Junction	Public recommendation
CM1	`m1`	west portico
CM2	`m4`	foyer
CM3	`m8`	foyer
CM4	`m11`	east portico
CM5	`b4`	foyer
CM6	`b8`	foyer

Table 1: Fixed six-manager arrangement for the intervention arms.

The two side-anchored open belts occupy `corridor-3` and `corridor-8`. Each is 1 m long at 30° to its corridor direction. Its projected span is 0.5 m, leaving 1.9 m of the assumed 2.4 m width; the lane count falls from four to three. Both travel directions remain allowed. The altered polyline includes a free-end bypass detour. These are low/open devices with no opaque panel or added sightline obstacle. Wheelchair and all-origin connectivity are checked. Neither belt occupies a door threshold.

LED	Junction	Installed walkway	Initial public message
1	`m1`	`mezzanine-1`	west portico
2	`m3`	`mezzanine-3`	foyer
3	`m5`	`mezzanine-5`	foyer
4	`m7`	`mezzanine-7`	foyer
5	`m9`	`mezzanine-9`	foyer
6	`m11`	`mezzanine-11`	east portico
7	`b1`	`balcony-1`	northwest balcony
8	`b4`	`balcony-4`	foyer
9	`b7`	`balcony-7`	foyer
10	`b10`	`balcony-10`	northeast balcony
11	`c1`	`corridor-1`	west portico
12	`c4`	`corridor-4`	foyer
13	`c7`	`corridor-7`	foyer
14	`c10`	`corridor-10`	east portico
15	`oL0`	`inner-L-1`	west stage
16	`oR0`	`inner-R-1`	east stage

Table 2: Sixteen dynamic strip installations. The controller may change messages through the delayed observation and holding rules; messages are not personalized.




Figure 4: Installation schematic generated from the same network as the simulation. Numbers identify the LED strips in the table. Belts preserve views but still consume physical width. Metric reconstruction and installation feasibility require venue verification.

3.14 Practical Placement Review

The tested belts and full corridor partitions are not recommended for installation. The retained layout is an experimental graph configuration. Cornell EHS requires clear egress circulation and unobstructed door operation [31]. The two partial belts share junctions with auditorium discharge doors; reducing a nominal 2.4 m passage to a 1.9 m bypass is not evidence that door swings, turning crowds or device bases fit. An open view is not an unobstructed escape route. Full partitions additionally remove cross-corridor choices and redundancy. The model's 1.1 m screen establishes neither required egress width nor regulatory compliance.

Cane detection and objects between posts are addressed separately in accessibility guidance [32]. No belt height, base footprint or anchorage is supplied here. Keeping a wheelchair path connected is therefore insufficient to establish accessibility for an actual device. Since the experiments show no clear incremental belt benefit, there is no evidence-based reason to introduce these unresolved physical obstructions.

Location	Physical interpretation and disposition
`corridor-3,8` belts	Adjacent to auditorium-door junctions. Reject as installation recommendations; retain only as experimental layouts.
ZLED1–6, mezzanine	Candidate doorway/route-decision areas. Verify floor-strip visibility, raised-level transitions and row discharge; no equipment in usable width.
ZLED7–10, balcony	Verify actual rear-stair and front-escape arrows, landings and column occlusion. No implied level wheelchair route.
ZLED11–14, corridor	Provide intelligible local turn indications and continuity at foyer/portico doors; survey both approach directions and door swings.
ZLED15–16, stage side	The brief shows stage escape routes, but the graph abbreviates the side passage. Verify public audience access, hardware and stage-use restrictions before proposing an arrow.
Staff decision posts	Points have no body footprint. Actual standing positions must avoid the moving line and doorway sweep; speech and sign messages must agree.

Table 3: Desk review against the supplied drawings and photographs. These are not surveyed installation coordinates or an approved operating plan.

The next defensible step is a venue walkthrough of staff instructions and supplementary directional signs, keeping circulation unobstructed. Existing required signs and emergency illumination are not replaced. A real LED system needs local arrow comprehension, continuity through every turn, suitable mounting, emergency power, maintenance, and an agreed failure response. The simulation does not evaluate those hardware functions.

The distinction is substantive: the model broadcasts an *exit-group name*, and an occupant who learns that name can route through the graph. One luminous strip may not supply a newcomer with that knowledge in reality. The 16 strips are therefore test locations for information exposure, not a validated arrow chain. The updated validator requires each strip's controller node to belong to its walkway; this prevents a software inconsistency but does not validate human comprehension.

Dynamic signs update independently using delayed reports. They can disagree with one another or with a fixed manager. Manager priority in an occupant's decision logic does not remove contradictory information from the real environment. Galea et al.'s trials motivate coordinated signs and voice messages, not independent installation of this controller [13]. Before a field pilot, test a coherent public message plan, downstream arrows, accessible alternatives, stale observations and fallback to the venue's approved guidance. No such integrated physical controller is claimed here.

There is also a transfer limitation in the literature. Wang et al.'s Table 2 gives safety-barrier increases of 2.67% at 1 m and 0.88% at 3 m, whereas its abstract reverses the order. Their measure averages three repetitions after dropping five initial and five final pedestrians [15]. It is not our full-house maximum. Similarly, the assumed 0.77 detection and independent person–installation draws are not calibrated to multiple floor strips, correlated inattention, or occlusion by a standing crowd. Statistical uncertainty in

the Monte Carlo mean does not include these modelling uncertainties.

3.15 Software Review and Preserved Evidence

Engine 1.3.1 corrects input validation, including installation identity and strip/controller consistency, without changing movement, response, routing, guidance or service algorithms for previously valid scenarios. The interface now preserves LED locations when switching static/dynamic mode and separates exit knowledge from foyer preference. Exploratory sweeps require a fresh output directory to protect existing evidence.

The reviewed version passed 66 automated engine and review tests and five browser tests, including equivalence between browser and Node results and preservation of all sixteen LED positions. TypeScript and the production build passed. Complete first-seed results for all five study policies matched their archived 1.3.0 results after normalizing only the reported version field. This is five replay checks, not a new 500-run Monte Carlo study. The historical results below retain their original engine version and archived source. Physical, behavioural and numerical limitations are not removed by these software checks.

3.16 Assisted Evacuation

The three wheelchair users retain access only to feasible routes. The west-foyer elevator is excluded from emergency evacuation under the problem statement [1]. Two assistance teams are assumed to become available after 60 s, and assisted descent takes a lognormal time with median 60 s and log standard deviation 0.4. Research on stair evacuation by people with mobility impairments documents substantial differences among unaided, accompanied, and equipment-assisted movement [27]. This supports representing assistance separately rather than assigning everyone an ordinary stair speed. Two teams represent scarce assistance rather than simultaneous help for every person; availability after 60 s allows time for teams to reach their positions. A median descent of 60 s with a lognormal spread allows assisted movement to be substantially slower and more variable than ordinary walking. These are scenario assumptions, not measurements of Bailey Hall staffing or assisted-descent times. An occupant can leave the building onto an exterior assistance landing before reaching street level, so those two times are recorded separately.

3.17 Time Evolution of the Evacuation

The evacuation evolves through discrete intervals of duration Δt. The reference interval is 0.1 s, with a finer variant of 0.0125 s. The finer interval tests how much discretization of queues and arrival times affects predictions without altering the physical model. Neighbour activity is considered during initial recognition; manager hearing is evaluated over simulated one-second intervals, while route reviews occur at meaningful decision points. These time scales describe the same continuous event at different levels of detail: walking and queue service need short steps, while recognition and communication change less frequently. The step sizes are numerical choices, not observed human reaction times.

Within an interval, visible queues and messages may change a person's intended destination. Recognition, response, and group waiting then progress; those already moving advance along the current walkway. Completing a link does not guarantee entry to the next one: the connection must be open and accessible, and both its storage and any relevant passage or gate service must be available. Otherwise the occupant remains upstream, allowing queues to extend backward through the building. This sequence couples individual decisions to the restrictions created by other people's movements.

If a person's speed changes while already on a link, the remaining distance is preserved and the completion time is recalculated using the new positive speed. A speed change neither resets the distance travelled nor allows someone to cross several positive-length links instantaneously.

For comparisons between interventions, a sampled audience retains the same seats, body sizes, speeds, response delays, groups, and persistent preferences. Only the arrangement of staff, signs, barriers, or

instructions is changed. Common audience draws reduce sampling noise in paired comparisons, but not parameter uncertainty.

4 Evaluation Metrics

4.1 Full-House Clearance

The principal performance measure is the time when the last audience member crosses the building's exterior boundary. It is not the mean time taken by an individual: most people may be outside while a small group remains trapped by a queue or awaiting assistance. Let t_{ir} denote occupant i's first exterior crossing in audience replication r. For $N = 1329$ occupants and R replications,

$$T_r = \max_{1 \le i \le N} t_{ir}, \qquad \overline{T} = \frac{1}{R} \sum_{r=1}^{R} T_r, \qquad \widehat{p}_{180} = \frac{1}{R} \sum_{r=1}^{R} \mathbf{1}\{T_r \le 180\}. \tag{20}$$

The 180-second threshold is specified by the contest problem [1]; it is not used to calibrate the movement rules. If a replication still has people inside at the 900-second observation horizon, its clearance time is known only to exceed 900 seconds. It does not meet the target, and a mean computed only over completed replications must be described as conditional rather than as an unconditional average.

4.2 Exit Use, Queues, and Density

Two arrangements may have similar clearance times while producing different crowding patterns. The model therefore also records which exits are used, how long people wait, whether assistance is complete, and where queues accumulate. Because occupancy is represented on links, density is a link-average quantity:

$$\rho_e(t) = \frac{n_e(t)}{L_e w_e \gamma_e}. \tag{21}$$

The recorded outputs include peak and time-varying link density, queue lengths and waiting times, exit usage, and completion of assisted descent. Time spent above a reference density of 2 persons/m^2 may also be compared between layouts, but that value is an analytical reporting threshold rather than an injury threshold. The network cannot estimate contact forces or injury risk.

5 Interpretation of Parameter Uncertainty

The reference values describe a prompt, well-signalled concert departure, not a calibration to measured Bailey Hall evacuation times. The free-speed mean of 1.40 m/s lies between usual and medium walking paces; 1.30 m/s is a slower alternative [18]. The assumed 20% older share is compared with differently composed audiences, including 10%, 35%, and 50% older attendees, since the programme and attendance records are unspecified. The response medians of 6 and 14 s are shorter than the pre-movement delays observed in the Marlowe Theatre and require a slower-response comparison [8]. Staff acceptance of 0.85 is similarly compared with 0.70 and 0.90; these are assumed probabilities, not findings from staff-guidance experiments. Initial knowledge of signed exits, the two route-preference shares, the counterflow lane rule, sign-reporting delays, and the switching margin also remain assumptions. Such comparisons vary the model's inputs; they are not statistical confidence intervals derived from the literature.

6 Monte Carlo Intervention Results

The confirmatory experiment uses engine 1.3.0 and 5 fixed policies, each with 100 fresh audiences (seeds 5001–5100). The selected combined layout was frozen after pilot experiments and before the confirmatory

runs. Each seed preserves audience attributes across policies. Mean and paired-difference intervals use Student t with 99 degrees of freedom; these nominal intervals have no multiplicity adjustment and exclude model uncertainty. All means below refer to full-house exterior clearance, not individual average exit time.

Policy	Complete	Mean (s)	SD (s)	$T \leq 180$
Original staff assignments	100/100	195.2	7.9	1/100
Coordinated staff only	100/100	175.9	11.9	76/100
Partial open belts	100/100	176.9	11.6	71/100
Dynamic LEDs only	100/100	172.0	13.4	80/100
Dynamic LEDs + partial belts	100/100	172.5	13.4	77/100

Table 4: Independent validation audiences; common seeds pair policies. Means are withheld if any run is censored at 900 s.

For the preselected combination, the mean is 172.5 s, with Monte Carlo 95% confidence interval 169.9–175.2 s. Its 180 s success fraction is 77/100; the Wilson 95% interval is 67.8–84.2%. An average below the target, when attained, is not a guarantee for each audience.




Figure 5: Clearance distributions retain all replications in the denominator. The dashed line marks 180 s. Error bars are 95% confidence intervals for the mean, not prediction intervals.

Paired contrast	Mean difference (s)	95% CI (s)
LED effect without barriers	-3.9	-6.1 to -1.8
Barrier effect without LEDs	0.9	-0.2 to 2.1
Barrier effect with LEDs	0.5	-0.4 to 1.5
Combined effect	-3.4	-5.4 to -1.4

Table 5: Within-seed differences; negative means faster. These isolate interventions from staff coordination and engine corrections.

The selected combination evacuated 300/300 wheelchair-user observations across the exterior boundary and 300/300 to street level. The three observations within each replication share the crowd environment. Mean accumulated queue wait was 33.1 s per person. Full logs, policy JSON, source hashes and per-seed results accompany the repository report.




Figure 6: Exit redistribution and paired combined-policy differences. No additional door capacity is assigned to guidance or barriers.

6.1 Interpretation of the Comparisons

Changing the six managers' messages changes mean clearance by -19.3 s relative to the original messages. Adding dynamic LEDs to coordinated staff changes it by -3.9 s. These comparisons use the same corrected engine and separate staffing information from the device effects.

Adding partial belts to the LED layout changes mean clearance by 0.5 s (paired 95% CI -0.4 to 1.5 s). The interval includes zero: the study does not establish an incremental belt benefit, and this is not proof of equivalence.

The slower-response sensitivity and time-step differences must be considered alongside the main result. The 180-second criterion is conditional on the reference audience and prompt response assumptions, not a demonstrated property of the real hall.

6.2 Numerical Refinement and Sensitivities

The selected combination was rerun for the first three validation audiences with $\Delta t = 0.0125$ s, compared with the prescribed 0.1 s step. Only the integration interval changes. These are numerical checks, not three additional independent validation audiences.

Seed	Coarse clearance (s)	Fine clearance (s)	Fine minus coarse (s)
5001	168.9	164.8	-4.1
5002	168.5	187.6	19.1
5003	187.8	185.0	-2.8

Table 6: Time-step refinement; full-run invariant and replay checks pass at both steps.

The full network exhibits material numerical sensitivity: route decisions and lane-request ordering can change discontinuously. These three pairs do not establish time-step convergence. Isolated saturated-gate tests verify the prescribed throughput at both intervals, but that does not imply a converged full-house clearance estimate. The 0.1 s reference is retained regardless of whether refinement is faster or slower. Monte Carlo confidence intervals exclude this numerical uncertainty.

Two separately labelled parameter sensitivities use 20 audiences per policy, seeds 6001–6020. The low-guidance case changes staff acceptance from 0.85 to 0.70, LED detection from 0.77 to 0.60, and LED acceptance from 0.80 to 0.60. The slow-response cases use recognition and preparation medians of 10 and 30 s instead of 6 and 14 s. These assumptions are stress cases, not fitted literature estimates. Main-study parameters and layouts remain unchanged.

Case	Complete	Mean (s)	$T \leq 180$
Combined, nominal guidance	20/20	175.4	13/20
Combined, weaker guidance	20/20	175.9	12/20
Original staff, slower response	20/20	259.1	0/20
Combined, slower response	20/20	258.8	0/20

Table 7: Separate parameter sensitivities. A censored case has no unconditional mean.

Weaker guidance minus nominal guidance: paired mean difference 0.5 s over 20 complete pairs. Student-t 95% interval: -6.8 to 7.8 s.

Combined minus original staff under slower response: paired mean difference -0.3 s over 20 complete pairs. Student-t 95% interval: -3.4 to 2.8 s.

The slow-response tail is visible in individual records: in seed 6008, the last occupant has a sampled preparation delay of 301.8 s and crosses outside at 352.8 s; in seed 6020 the corresponding delay is 312.9 s and clearance is 349.3 s. These are model draws, not observed people. No response-tail truncation was introduced to force the benchmark, and neither last occupant changes destination after the initial choice in these records.

6.3 Verification and Reproducibility

The original engine 1.3.0 study implementation passed 49 automated engine tests and 4 browser tests, plus TypeScript and production builds. All 500 confirmatory archives and all 86 numerical/sensitivity archives were audited against hashes and reconstructed crossing counts. Each study exactly replayed the complete first-seed result for every policy. Initial audience hashes confirm distinct audiences across replications and identical paired audiences across policies. Every run enforces population conservation, storage, connectivity and accessibility invariants. These checks establish consistency with the declared model, not empirical validation of Bailey Hall.

7 Crowd Manager Message-Policy Selection

A separate engine 1.4.0 experiment compared four message policies on 100 fresh audiences each (seeds 8001–8100). The six posts, activation and compliance draws, audience and physical parameters, and final-forty rule were identical across policies. No added LEDs or barriers were used. Only manager messages differed. Candidate configurations and selection criteria were recorded before completion of the experiment; no parameter was fitted to the results.

Policy	Complete	Mean (s)	95% interval (s)	≤ 180 s
Nearest-time lower floor; original balcony exits	100/100	178.7	176.6–180.9	55/100
Nearest-time from all six managers	100/100	162.4	159.7–165.0	92/100
Fixed coordinated destinations	100/100	177.2	175.1–179.3	68/100
Nearest-time lower floor; foyer from balcony	100/100	163.3	160.7–165.9	91/100

Table 8: Fixed-policy comparison. Mean intervals quantify Monte Carlo sampling uncertainty, not physical or behavioural uncertainty.

The selected candidate is **Nearest-time from all six managers**. Lowest observed unconditional mean among fully completed policies.

The selected mean's simultaneous 95% interval, adjusted over the four candidate means, is 158.98 to 165.74 s. This accounts for inspecting several means, but not physical or parameter uncertainty.




Figure 7: Empirical clearance distributions and nominal mean intervals for four manager policies. Dashed lines mark 180 seconds.

Relative to the requested lower-floor nearest-time policy with the original balcony exits, the selected policy's paired mean change is -16.37 s. Its simultaneous 95% interval is -19.08 to -13.66 s.

Manager	Post	Public instruction
CM1	`m1`	Nearest known feasible exit by estimated travel time
CM2	`m4`	Nearest known feasible exit by estimated travel time
CM3	`m8`	Nearest known feasible exit by estimated travel time
CM4	`m11`	Nearest known feasible exit by estimated travel time
CM5	`b4`	Nearest known feasible exit by estimated travel time
CM6	`b8`	Nearest known feasible exit by estimated travel time

Table 9: Selected simulated messages. Posts are graph junctions, not approved standing positions.

The paired comparisons use Student-t intervals with Bonferroni simultaneous 95% coverage across the six candidate contrasts. Selection uses the same sample, so it is not independent confirmation or a claim of global optimality. Unfinished runs remain in the success denominator and prevent an unconditional mean.

For implementation in the hall, fixed destination messages must map to clear local directions, with balcony foyer guidance using the appropriate rear stairs. Staff must remain clear of door swings and crowd movement, and speech and existing signs must agree. A generic nearest-time instruction assumes listeners can estimate route time from known exits and visible queues; this comprehension is not validated. The physical-placement limits in Section 3.14 remain applicable. These results do not authorize changing the venue emergency plan.

Nearest-time guidance keeps a single public instruction. Listeners evaluate known feasible routes using their current position and visible queues; managers do not periodically switch public destinations in response to congestion. The foyer-directed balcony variant is statistically close to the all-nearest variant; the adjusted interval for their paired difference includes zero. A selected sample minimum is not a proven unique optimum.

All 400 archives passed hash and crossing-count audits, with exact full-result replay of the first seed of each policy. All 741 final commitments were checked for connected routes and absence of later updates. The selected arm had 22 final commitments, including 12 exit changes, and 300/300 wheelchair-user observations reached the exterior and 300/300 reached street level within the horizon. The implementation passed 79 automated tests, 6 browser tests, TypeScript and the production build. The selected default reproduced its first-seed result completely after normalizing only the scenario title.

8 Limitations

The geometry is reconstructed from architectural and seating plans, not from surveyed walkway measurements. The stepped cross-aisle is included as circulation between the outer and inner seating-block aisles; its width and change in elevation are approximated from the plans. It is not treated as a level accessible crossing or as a shortcut across seating rows. The photographs help distinguish open seating circulation from barriers, but cannot provide precise passage dimensions or verify exit hardware. The model consequently retains geometric uncertainty even though the cross-aisle's role as a pedestrian connection is fixed.

The audience is assumed to respond promptly and to walk briskly when unobstructed. Its age composition, route preferences, manager compliance and companion waiting have not been observed at Bailey Hall. Published work supports heterogeneous behaviour without fixing these numerical values. Other audience compositions, slower response, weaker guidance and less complete exit knowledge can change clearance times without changing the building.

Network congestion accounts for gate throughput, finite storage, and queue spillback, but not collisions, pushing, falls, injuries, or detailed interactions among seated neighbours. Low barriers preserve architectural sightlines but may still create local crowding. Sightline checks do not include heads blocking a view, detailed smoke optics, or the movement of staff through a tightly packed crowd. Assisted descent is estimated rather than measured in this building, and the omitted backstage and ground-level occupants remain outside the defined population.

The predicted clearance time is an estimate for the stated audience and scenario, not a certification of compliance with building or fire-safety regulations.

References

[1] Cornell Mathematical Contest in Modeling (2026). *Bail(ey)ing Out*. Bailey Hall problem statement, building description, and supplied floor and seating plans.

[2] C. Feliciani, H. Murakami, and K. Nishinari (2018). *A universal function for capacity of bidirectional pedestrian streams: Filling the gaps in the literature*. PLOS ONE 13(12), e0208496. https://doi.org/10.1371/journal.pone.0208496.

[3] S. M. V. Gwynne, E. D. Kuligowski, J. Kratchman, and J. A. Milke (2009). *Questioning the linear relationship between doorway width and achievable flow rate*. Fire Safety Journal 44, 80–87. https://doi.org/10.1016/j.firesaf.2008.03.010.

[4] A. Seyfried et al. (2005). *The fundamental diagram of pedestrian movement revisited*. https://arxiv.org/abs/physics/0506170.

[5] A. Johansson (2009). *Constant-net-time headway as a key mechanism behind pedestrian flow dynamics*. Physical Review E 80, 026120. https://doi.org/10.1103/PhysRevE.80.026120.

[6] M. Spearpoint and X. Xiang (2011). *Calculating evacuation times from lecture theatre type rooms using a network model*. Fire Safety Science 10, 599–612. https://doi.org/10.3801/IAFSS.FSS.10-599.

[7] C. G. Hopkin, E. R. Galea and S. J. Deere (2015). *A study of response behaviour in a theatre during a live performance*. Human Behaviour in Fire, 385–398. https://gala.gre.ac.uk/id/eprint/14359/.

[8] E. R. Galea, S. J. Deere, C. G. Hopkin, and H. Xie (2017). *Evacuation response behaviour of occupants in a large theatre during a live performance*. Fire and Materials 41, 467–492. https://doi.org/10.1002/fam.2424.

[9] N. W. F. Bode et al. (2015). *Disentangling the impact of social groups on response times and movement dynamics in evacuations*. PLOS ONE 10, e0121227. https://doi.org/10.1371/journal.pone.0121227.

[10] K. Train (2009). *Discrete Choice Methods with Simulation*, 2nd ed., Chapter 3. https://eml.berkeley.edu/books/choice2nd/Ch03_p34-75.pdf.

[11] W. Liao, A. U. Kemloh Wagoum and N. W. F. Bode (2017). *Route choice in pedestrians: determinants for initial choices and revising decisions*. Journal of the Royal Society Interface. https://doi.org/10.1098/rsif.2016.0684.

[12] E. R. Galea, H. Xie and P. J. Lawrence (2014). *Experimental and survey studies on the effectiveness of dynamic signage systems*. Fire Safety Science 11, 1129–1143. https://doi.org/10.3801/IAFSS.FSS.11-1129.

[13] E. R. Galea et al. (2017). *Evaluating the effectiveness of an improved active dynamic signage system using full scale evacuation trials*. Fire Safety Journal 91, 908–917. https://doi.org/10.1016/j.firesaf.2017.03.022.

[14] M. A. López-Carmona and Á. Paricio García (2021). *CellEVAC: an adaptive guidance system for crowd evacuation through behavioral optimization*. Safety Science 139, 105215. https://doi.org/10.1016/j.ssci.2021.105215.

[15] L. Wang et al. (2023). *Influence of pre-bottleneck diversion devices on pedestrian flow*. Journal of Statistical Mechanics. https://arxiv.org/abs/2212.01296.

[16] C. Feliciani et al. (2020). *Systematic experimental investigation of the obstacle effect during non-competitive and extremely competitive evacuations*. Scientific Reports 10, 15947. https://pmc.ncbi.nlm.nih.gov/articles/PMC7525554/.

[17] H. Chen et al. (2023). *Effect of S-shaped guardrails on pedestrian crowd flows in bottleneck areas*. Safety Science 159, 106020. https://doi.org/10.1016/j.ssci.2022.106020.

[18] E. M. Murtagh, J. L. Mair, E. Aguiar, C. Tudor-Locke, and M. H. Murphy (2021). *Outdoor walking speeds of apparently healthy adults: A systematic review and meta-analysis*. Sports Medicine 51, 125–141. https://doi.org/10.1007/s40279-020-01351-3.

[19] W. Daamen and S. P. Hoogendoorn (2006). *Free Speed Distributions for Pedestrian Traffic*. Transportation Research Board Annual Meeting. https://www.pedbikeinfo.org/cms/downloads/Free%20Speed%20Distributions%20for%20Pedestrian%20Traffic.pdf.

[20] R. W. Bohannon (1997). *Comfortable and maximum walking speed of adults aged 20–79 years: Reference values and determinants*. Age and Ageing 26, 15–19. https://doi.org/10.1093/ageing/26.1.15.

[21] U.S. Census Bureau (2025). *Older Adults Outnumber Children in 11 States and Nearly Half of U.S. Counties*. https://www.census.gov/newsroom/press-releases/2025/older-adults-outnumber-children.html.

[22] M. Kalmijn and K. Henkens (2026). *Do classical concert halls need to worry about ageing audiences?* NIDI Demos 40(5), 3. https://nidi.nl/demos/do-classical-concert-halls-need-to-worry-about-ageing-audiences/.

[23] L. J. Dommershuijsen et al. (2022). *Gait speed reference values in community-dwelling older adults: Cross-sectional analysis from the Rotterdam Study*. Experimental Gerontology 158, 111646. https://doi.org/10.1016/j.exger.2021.111646.

[24] C. N. van der Wal, M. A. Robinson, W. Bruine de Bruin, and S. Gwynne (2021). *Evacuation behaviors and emergency communications: An analysis of real-world incident videos*. Safety Science 136, 105121. https://doi.org/10.1016/j.ssci.2020.105121.

[25] C. M. Mayr and G. Köster (2022). *Guiding crowds when facing limited compliance: Simulating strategies*. PLOS ONE 17, e0276229. https://doi.org/10.1371/journal.pone.0276229.

[26] E. D. Kuligowski et al. (2015). *Movement on Stairs During Building Evacuations*. NIST Technical Note 1839. https://doi.org/10.6028/NIST.TN.1839.

[27] E. D. Kuligowski et al. (2014). *Stair Evacuation of People with Mobility Impairments*. National Institute of Standards and Technology. https://www.nist.gov/publications/stair-evacuation-people-mobility-impairments.

[28] W. Liu et al. (2026). *Mode-dependent optimal positioning of evacuation guides: An experimental–modeling study on static and dynamic guidance effect*. Tunnelling and Underground Space Technology 171, 107458. https://doi.org/10.1016/j.tust.2026.107458.

[29] M. Fu, R. Liu and Q. Liu (2023). *How individuals sense environments during indoor emergency wayfinding: An eye-tracking investigation*. Journal of Building Engineering 79, 107854. https://doi.org/10.1016/j.jobe.2023.107854.

[30] M. Fu, R. Liu and Q. Liu (2024). *Why individuals do not use emergency exit doors during evacuations: A virtual reality and eye-tracking experimental study*. Advanced Engineering Informatics 60, 102396. https://doi.org/10.1016/j.aei.2024.102396.

[31] Cornell Environment, Health and Safety. *Event Setup*. Reviewed 9 November 2026. https://ehs.cornell.edu/campus-health-safety/event-management/event-setup.

[32] U.S. Access Board. *ADA Accessibility Standards, Section 307: Protruding Objects*. Reviewed 9 November 2026. https://www.access-board.gov/ada/.

[33] Y. Tong, N. W. F. Bode, M. Haghani and R. Lovreglio (2025). *Exploring occupant exit choices during fire drills and false alarm evacuations in a library*. Safety Science 182, 106708. https://doi.org/10.1016/j.ssci.2024.106708.