

A Primer on Sheaf Theory for Computer Scientists and Mathematicians

Bjørn Remseth
Email: la3lma@gmail.com
With AI assistance

Abstract—Sheaf theory is a mathematical language for describing how local data can be restricted, compared, and glued into global data. Although it originated in algebraic topology, complex analysis, and algebraic geometry, its central idea is broadly useful: local consistency should determine global structure when the local pieces are compatible. This report gives a first-principles introduction to sheaves for readers with a background in computer science and mathematics. It introduces presheaves, sheaves, sections, stalks, germs, sheafification, and the local-to-global principle. It also relates the theory to functions, manifolds, databases, constraint satisfaction, distributed systems, and cohomological obstruction theory. *Note: This document was created with AI assistance; see “About This Document” and “Note on References and Verification” sections for details on methodology and verification processes.*

Index Terms—sheaf theory, presheaves, local-to-global principles, algebraic topology, computational topology, distributed systems, constraint satisfaction

version:2026-04-26-22:03:02-CEST-57ee6c0-u/la3lma/
codex/eml-ga-risky-sequence-sweep

Note on document creation: This document was created with AI assistance. See the “About This Document” section for details on the methodology and verification processes used.

I. INTRODUCTION

The core intuition of sheaf theory is simple:

We understand a thing locally, on small pieces, and we want to know when those local pieces glue together into a coherent global thing.

A sheaf is a systematic way of assigning data to regions of a space, together with rules for restricting data to smaller regions and gluing compatible local data into global data. The slogan is:

A sheaf is local data plus restriction plus gluing.

This makes sheaf theory relevant in several settings that are familiar from computer science and applied mathematics: distributed databases, sensor networks, constraint satisfaction, type inference, program semantics, local coordinate systems, and local solutions of differential equations.

At the same time, sheaf theory is central in modern geometry. Smooth manifolds, schemes in algebraic geometry, vector bundles, differential forms, and solution spaces of equations are all naturally described using sheaves. The same formalism can therefore connect computational ideas about consistency with geometric ideas about locality.

Readers who mainly want intuition can read straight through the first seven sections, treat Section X as optional on a first pass, and then return to the geometric and computational applications.

II. THE BASIC IDEA

Suppose that we have a space X . For each region $U \subseteq X$, we want to assign some collection of data available on U . We denote this assignment by

$$U \mapsto F(U). \quad (1)$$

Here $F(U)$ might be a set, a group, a vector space, a ring, or some other algebraic structure.

For example, if X is a topological space, $F(U)$ might be the set of continuous functions

$$f : U \rightarrow \mathbb{R}. \quad (2)$$

If $V \subseteq U$, then any function defined on U can be restricted to V :

$$f \mapsto f|_V. \quad (3)$$

Thus data on a larger region gives data on a smaller region.

This direction is important. The inclusion $V \subseteq U$ points from the small region into the large region, but the induced map on data goes in the opposite direction:

$$F(U) \longrightarrow F(V). \quad (4)$$

This contravariance is one of the first structural features of sheaf theory.

A Running Example

It helps to keep one concrete cover in mind throughout the paper. Let

$$U = (-2, 2), \quad U_1 = (-2, 1), \quad U_2 = (-1, 2). \quad (5)$$

Then $U = U_1 \cup U_2$ and the overlap is $U_1 \cap U_2 = (-1, 1)$. If $F(U)$ is the set of continuous real-valued functions on U , a section $s_1 \in F(U_1)$ and a section $s_2 \in F(U_2)$ should determine one global function on U exactly when they agree on the overlap. Figure 1 is the picture to keep in mind whenever the words “restriction”, “compatibility”, and “gluing” appear.




Fig. 1. The local-to-global pattern behind sheaf theory. Two sections over overlapping open sets can be glued into one unique global section precisely when their restrictions agree on the overlap.

III. PRESHEAVES

A presheaf is the first formal layer. It remembers that data can be restricted from larger regions to smaller regions.

Definition 1 (Presheaf). Let X be a topological space. A presheaf F on X consists of:

- (i) for every open set $U \subseteq X$, an object $F(U)$;
- (ii) for every inclusion $V \subseteq U$, a restriction map

$$\rho_V^U : F(U) \rightarrow F(V), \quad (6)$$

satisfying the identity and composition laws:

$$\rho_U^U = \text{id}_{F(U)}, \quad (7)$$

$$\rho_W^U = \rho_W^V \circ \rho_V^U \quad \text{whenever } W \subseteq V \subseteq U. \quad (8)$$

The elements of $F(U)$ are called sections over U .

The identity law says that restricting data to the same region does nothing. The composition law says that restricting from U to W directly is the same as first restricting from U to V and then from V to W .

From a category-theoretic viewpoint, if $\text{Open}(X)$ is the category whose objects are open subsets of X and whose morphisms are inclusions, then a presheaf is a contravariant functor

$$F : \text{Open}(X)^{op} \rightarrow \mathbf{Set}, \quad (9)$$

or more generally

$$F : \text{Open}(X)^{op} \rightarrow \mathcal{C}, \quad (10)$$

where $\mathcal{C}$ might be $\mathbf{Ab}$, $\mathbf{Ring}$, $\mathbf{Vect}$, or another category.

Takeaway. A presheaf knows how to move data from large regions to small regions. At this stage, nothing yet says that compatible local data must come from a global object.

IV. SHEAVES

A sheaf is a presheaf satisfying a local-to-global consistency condition. It must be possible to glue compatible local sections uniquely.

Suppose U is covered by open subsets:

$$U = \bigcup_{i \in I} U_i. \quad (11)$$

Suppose further that for each i we have a section

$$s_i \in F(U_i). \quad (12)$$

The family $(s_i)_{i \in I}$ is called *compatible* if the sections agree on all pairwise overlaps:

$$\rho_{U_i \cap U_j}^{U_i}(s_i) = \rho_{U_i \cap U_j}^{U_j}(s_j) \quad \text{for all } i, j. \quad (13)$$

Definition 2 (Sheaf). A presheaf F on X is a sheaf if, for every open set $U \subseteq X$, every open cover $U = \bigcup_i U_i$, and every compatible family of sections $s_i \in F(U_i)$, there exists a unique section $s \in F(U)$ such that

$$\rho_{U_i}^U(s) = s_i \quad \text{for every } i. \quad (14)$$

Thus a sheaf satisfies two principles:

- 1) **Local identity:** if two sections agree locally on a cover, then they are equal globally.
- 2) **Gluing:** compatible local sections glue to a unique global section.

Equivalently, for a cover $U = \bigcup_i U_i$, $F(U)$ is the equalizer of the diagram

$$F(U) \longrightarrow \prod_i F(U_i) \rightrightarrows \prod_{i,j} F(U_i \cap U_j). \quad (15)$$

In words, global sections over U are exactly compatible families of local sections over the U_i .

Takeaway. The sheaf axioms turn a presheaf into a true local-to-global machine: global data is exactly the same thing as compatible local data.

V. THE MODEL EXAMPLE: CONTINUOUS FUNCTIONS

Let X be a topological space and define

$$F(U) = \{\text{continuous functions } U \rightarrow \mathbb{R}\}. \quad (16)$$

For $V \subseteq U$, define the restriction map by ordinary function restriction:

$$\rho_V^U(f) = f|_V. \quad (17)$$

Proposition 1. The assignment $U \mapsto F(U)$ is a sheaf.

Proof. Let $U = \bigcup_i U_i$ be an open cover, and suppose we have continuous functions

$$f_i : U_i \rightarrow \mathbb{R} \quad (18)$$

that agree on overlaps. Define $f : U \rightarrow \mathbb{R}$ by

$$f(x) = f_i(x) \quad \text{if } x \in U_i. \quad (19)$$

This is well-defined because if $x \in U_i \cap U_j$, then $f_i(x) = f_j(x)$. The resulting function is continuous because continuity




Fig. 2. Why the presheaf of bounded continuous functions is not a sheaf. The local sections are mutually compatible, but their only natural glue is the unbounded global function x , which is not a section of $B(\mathbb{R})$.

can be checked locally on the open cover. Finally, f is unique because every point of U lies in some U_i . $\square$

This example is the prototype for sheaf theory. The reason it works is that continuity is a local property.

VI. A PRESHEAF THAT IS NOT A SHEAF

Not every presheaf is a sheaf. The failure often reveals that a property is global rather than local.

Example 1 (Bounded continuous functions). Let $X = \mathbb{R}$ and define

$$B(U) = \{\text{bounded continuous functions } U \rightarrow \mathbb{R}\}. \quad (20)$$

Restriction of functions makes B a presheaf.

However, B is not a sheaf. Cover $\mathbb{R}$ by open intervals

$$U_n = (-n, n), \quad n \in \mathbb{N}. \quad (21)$$

On each U_n , define

$$f_n(x) = x. \quad (22)$$

Each f_n is bounded on U_n , and these functions agree on overlaps. They therefore form a compatible family of local sections. If they glued in $B(\mathbb{R})$, the glued function would be $f(x) = x$ on all of $\mathbb{R}$, but this function is not bounded. Thus compatible local bounded functions need not glue to a globally bounded function.

This example illustrates an important lesson:

Some properties are local. Some properties are global. Sheaves naturally encode local properties.

VII. SECTIONS, STALKS, AND GERMS

The elements of $F(U)$ are called sections over U . One can also ask what the sheaf looks like infinitesimally near a point.

Definition 3 (Stalk). Let F be a sheaf on X , and let $x \in X$. The stalk of F at x , denoted F_x , is obtained by taking all sections over all open neighborhoods of x and identifying two sections if they agree on some smaller neighborhood of x .

An element of F_x is called a *germ*. Informally, a germ is the local behavior of a section near a point, with all information away from that point forgotten.




Fig. 3. Two sections can determine the same germ at x_0 even when they differ far away. The shaded neighborhood is all the stalk remembers.

For example, if F is the sheaf of continuous real-valued functions, then a germ at x is an equivalence class of functions defined near x . Two functions represent the same germ if they agree on some neighborhood of x .

This construction is useful because many local questions are naturally questions about stalks. For instance, a property of a function may be checked by asking whether the corresponding germ at each point has that property.

VIII. CONSTANT PRESHEAVES AND CONSTANT SHEAVES

A subtle but important example is the distinction between the constant presheaf and the constant sheaf.

Let A be a set. The naive constant presheaf assigns

$$F(U) = A \quad (23)$$

for every nonempty open set U , with identity restriction maps.

This is often not a sheaf. Suppose U has two disjoint open components U_1 and U_2 . A locally constant choice could assign one value $a \in A$ on U_1 and another value $b \in A$ on U_2 . Since $U_1 \cap U_2 = \emptyset$, there is no compatibility obstruction. But the constant presheaf forces a single value of A over all of U , so it cannot glue arbitrary locally constant choices.

The associated constant sheaf instead assigns to U the set of locally constant functions

$$U \rightarrow A. \quad (24)$$

Thus, on a disconnected region, different connected components may carry different values.

This distinction captures a common theme: sheafification converts a naive global notion of sameness into a local notion of sameness.

IX. SHEAFIFICATION

Every presheaf can be converted into a sheaf by a process called *sheafification*. Sheafification modifies a presheaf just enough to enforce the sheaf axioms while preserving its local behavior.

Informally, sheafification proceeds by:

- 1) looking at germs of local sections;
- 2) allowing compatible germs to glue;
- 3) identifying data that cannot be distinguished locally.

The constant presheaf provides a concrete example of what changes. Before sheafification, a disconnected open set only remembers one value of A . After sheafification, a section over



Fig. 4. On a disconnected open set, the constant presheaf forces the same value on every component, while the constant sheaf allows different values on different connected components.

that same open set becomes a locally constant function $U \rightarrow A$, as shown in Figure 4. In other words, sheafification does not invent new local behavior. It reorganizes the presheaf so that sections are determined by what can really be seen and glued locally.

Sheafification is analogous to turning a loosely specified local data model into one that satisfies a precise locality principle. It preserves what can be observed locally while correcting failures of gluing or locality.

Takeaway. Sheafification is a repair process. It keeps the local behavior encoded by germs, but replaces globally rigid sections with sections that behave correctly under locality and gluing.

X. AN OPTIONAL CATEGORICAL VIEW

Readers new to category theory can safely skip this section on a first reading. For readers with category-theoretic background, the definition can be compressed.

Let $\text{Open}(X)$ be the category of open subsets of X , where there is a unique morphism $V \rightarrow U$ when $V \subseteq U$. A presheaf on X is a contravariant functor

$$F : \text{Open}(X)^{op} \rightarrow \mathbf{Set}. \quad (25)$$

The sheaf condition says that for each open cover $U = \bigcup_i U_i$, the diagram

$$F(U) \longrightarrow \prod_i F(U_i) \rightrightarrows \prod_{i,j} F(U_i \cap U_j) \quad (26)$$

is an equalizer diagram.

The two arrows to the double product are induced by restriction to overlaps. A compatible family is a family of local sections whose two images in the overlap product agree.

This categorical formulation makes clear that sheaves are instances of a more general idea called *descent*: global objects are reconstructed from local objects plus compatibility data.

XI. SHEAVES IN GEOMETRY

Sheaf theory is central in geometry because geometric objects are often locally simple but globally nontrivial.

A. Manifolds

A smooth manifold is locally modeled on $\mathbb{R}^n$. On a manifold M , one naturally considers sheaves such as:

- smooth real-valued functions;
- vector fields;
- differential forms;
- local solutions of differential equations.

For example, smooth functions form a sheaf because smoothness is a local property. If smooth functions are defined on open patches and agree on overlaps, they glue uniquely into a smooth function on the union.

B. Bundles and Twisting

Many geometric structures are locally trivial but globally twisted. A cylinder and a Möbius strip both look locally like a product of an interval with a line, but globally they differ.

Sheaf-theoretically, one can describe such objects using local trivializations and transition functions on overlaps. The transition data records how local descriptions are related. If the transition data can be globally simplified, the object is trivial; if not, the object has a genuine global twist.

C. Schemes

In algebraic geometry, a scheme is not merely a topological space. It is a topological space equipped with a sheaf of rings:

$$(X, \mathcal{O}_X). \quad (27)$$

The sheaf $\mathcal{O}_X$ tells us which functions are available on each open set. This is one of the main reasons sheaf theory is foundational in modern algebraic geometry.

XII. SHEAVES IN COMPUTER SCIENCE

Although sheaf theory began in pure mathematics, its core ideas are computationally natural.

A. Constraint Satisfaction

Consider a system with local variables and consistency constraints. Each region has a set of possible local assignments. Restriction maps project assignments onto smaller variable sets. A global section is a globally consistent assignment.

For example, suppose one local record contains values for variables (A, B) and another contains values for (B, C) . These can be glued if they agree on the shared variable B .




Fig. 5. A simple constraint-satisfaction sheaf. The local records on (A, B) and (B, C) both restrict to information on the shared variable B . A global section exists exactly when those restricted values agree.

The diagram says that both local records restrict to a value of B . Compatibility means that these values agree. A global glued record has values for (A, B, C) .

B. Databases

Database projection is a natural example of restriction. If a relation has attributes (A, B, C) , then projecting onto (A, B) is a restriction of data from a larger context to a smaller one.

Given partial tuples on overlapping attribute sets, gluing asks whether there is a full tuple that realizes the partial data. For example,

$$(A = 1, B = 2), \quad (28)$$

$$(B = 2, C = 3) \quad (29)$$

glue to

$$(A = 1, B = 2, C = 3). \quad (30)$$

But

$$(A = 1, B = 2), \quad (31)$$

$$(B = 5, C = 3) \quad (32)$$

do not glue, because the two local records disagree on B .

Thus sheaves provide a mathematical language for consistency of partial information.

C. Distributed Systems

In a distributed system, each node may have local state, and communication links may impose consistency requirements between states. A sheaf can assign possible states to nodes and possible shared observations to links. Restriction maps describe what each local state implies about the shared interface.

A global section is then a choice of state at every node such that all shared observations agree. Failure to find a global section corresponds to inconsistency.

This perspective is especially useful when a system is not expected to have one central global state, but still has local compatibility requirements.

D. Types and Program Semantics

There are also deep connections between sheaves, logic, and type theory. Very roughly:

- open sets can be understood as contexts;
- sections can be understood as terms or data valid in a context;
- restriction corresponds to moving to a smaller context;
- gluing corresponds to assembling compatible local constructions.

Sheaves and topoi provide models of constructive logic and appear in categorical semantics, homotopy type theory, and related areas.

A *topos* (plural: *topoi*) is a category that behaves like the category of sets but with a richer logical structure. Formally, a topos is a category with finite limits, exponentials, and a subobject classifier. The key insight is that topoi generalize set theory to contexts where the “law of excluded middle” may not hold.

The simplest example is the category of sheaves on a topological space, which forms a topos. In this setting:

- “sets” are replaced by sheaves (which assign sets to open regions);
- “truth values” become sheaves of truth values (which may vary by location);
- logical operations respect the local nature of truth.

This connection makes topoi fundamental in constructive mathematics, intuitionistic logic, and theoretical computer science, where they provide semantic models for type theories and programming languages that respect computational realizability.

XIII. OBSTRUCTIONS AND SHEAF COHOMOLOGY

The sheaf condition says that compatible local data glue uniquely. In many important situations, however, one studies data that is locally available but globally obstructed.

Sheaf cohomology measures the failure of local information to assemble globally.

The rough pattern is as follows. Suppose an object is described locally by sections s_i on open sets U_i . On overlaps, these sections may not agree exactly. Instead, their differences may be encoded by transition data

$$g_{ij} \quad \text{on } U_i \cap U_j. \quad (33)$$

If this transition data can be removed by changing local representatives, then the object is globally trivial. If not, the transition data records a genuine global obstruction.

A good geometric picture is a line bundle on a circle. One can cover the circle by overlapping arcs U_1, U_2, U_3 . On each arc the bundle looks trivial, so one can choose a local frame s_i . The interesting information lives on the overlaps: how should s_i and s_j be compared on $U_i \cap U_j$? If all of those overlap comparisons can be eliminated by changing the local frames, the bundle is globally untwisted. If they cannot, the local data hides a real global twist, as in the Möbius strip.

This idea appears in many mathematical contexts:




Fig. 6. A Čech-style picture of obstruction data. Local sections live on the open sets U_i , while transition data g_{ij} lives on overlaps. Cohomology detects when the edge data cannot be removed by changing the local representatives.

- line bundles and vector bundles;
- differential forms and de Rham cohomology;
- complex geometry;
- algebraic geometry;
- gauge theory and field theory;
- obstructions to solving equations globally.

A useful informal slogan is:

Cohomology measures the gap between local solvability and global solvability.

Takeaway. Ordinary sheaf theory asks whether compatible local sections glue. Cohomology begins when local data almost glues, and measures the leftover obstruction.

XIV. WHY THE DIRECTION OF RESTRICTION IS CONTRAVARIANT

A common initial confusion is that inclusions go one way while restriction maps go the other.

If $V \subseteq U$, then there is an inclusion of regions

$$V \hookrightarrow U. \quad (34)$$

But data usually restricts in the opposite direction:

$$F(U) \rightarrow F(V). \quad (35)$$

A function on a large domain can be restricted to a smaller domain. A function on a small domain generally cannot be extended uniquely to a larger domain.

This is why presheaves are contravariant functors.

XV. A COMPACT COMPUTATIONAL MENTAL MODEL

One may think of a sheaf as an abstract API, as shown in Figure 7.

The invariant is:

$$\text{global data} \cong \text{compatible local data}. \quad (36)$$

For a cover $U = \bigcup_i U_i$, this becomes:

$$F(U) \cong \left\{ (s_i)_i \in \prod_i F(U_i) \mid s_i|_{U_i \cap U_j} = s_j|_{U_i \cap U_j} \right\}. \quad (37)$$

This formula is perhaps the shortest usable summary of the sheaf condition.

XVI. CONCLUSION

Sheaf theory provides a language for local-to-global reasoning. A presheaf assigns data to regions and restriction maps to inclusions of regions. A sheaf is a presheaf in which compatible local data glue uniquely into global data.

The main concepts are:

- **sections:** data over a region;
- **restriction maps:** projections from larger regions to smaller regions;
- **compatibility:** agreement on overlaps;
- **gluing:** construction of global data from compatible local data;
- **stalks and germs:** local behavior near a point;
- **sheafification:** forcing a presheaf to satisfy locality and gluing;
- **cohomology:** measurement of obstructions to globalizing local data.

For a computer scientist, sheaves can be viewed as a disciplined abstraction for distributed consistency, partial information, projection, and reconstruction. For a geometer, they are a natural language for functions, spaces, bundles, and local structure. The unifying idea is that local data is meaningful only when one understands how it restricts, overlaps, and glues.

FURTHER READING

The following references provide useful next steps for readers interested in deeper study of sheaf theory, ranging from introductory to advanced levels.

For a first rigorous sequel, Bredon's text [1] gives the standard mathematical introduction with proofs and a large supply of examples. It is a natural next step after a conceptual primer.

For category theory and logic, Mac Lane and Moerdijk [2] is the bridge from sheaves to topoi and categorical semantics.

For geometry, Hartshorne [3] shows how deeply sheaves permeate algebraic geometry, while Kashiwara and Schapira [4] gives an advanced analytic and microlocal perspective.

For computational and applied directions, Ghrist [5] connects topology to engineering and data science, and Curry [6] is especially useful for readers who want to see sheaves and cosheaves used in networks, sensor fusion, and distributed computation.

ABOUT THIS DOCUMENT

This document represents a technical exploration created through a collaborative process between human and AI. The production process followed these steps:

- 1) **Discovery:** The need for a comprehensive introduction to sheaf theory that bridges the gap between pure mathematics and computational applications was identified through research into topological data analysis and distributed systems consistency models.
- 2) **Initial Exploration:** The document began as an interactive dialogue with AI systems exploring the fundamental

<code>F.get(U)</code>	-> data valid on region U
<code>F.restrict(U,V,s)</code>	-> restriction of s from U to V, where V subset U
<code>F.glue({(U_i,s_i)})</code>	-> global data if the local data agree on overlaps

Fig. 7. *Sheaf API: A computational mental model showing the three fundamental operations on sheaves. The `get` operation retrieves sections over a region, `restrict` projects sections to smaller regions, and `glue` constructs global sections from compatible local data.*

concepts of sheaf theory, starting from basic principles and building up to applications in computer science and mathematics.

- 3) **Synthesis:** The conversational exploration was systematically organized into a structured pedagogical document, following IEEE conference format and emphasizing both mathematical rigor and computational intuition.
- 4) **Implementation:** The document includes conceptual diagrams created using TikZ to illustrate key sheaf-theoretic constructions and their computational analogies.
- 5) **Visualization:** Diagrams were designed to maintain readability when scaled for publication, with attention to font sizes and visual clarity in the final PDF output.
- 6) **Verification:** All references were scrutinized for authenticity. URLs were tested for accessibility, author names were verified, and content relevance was checked against citations. This verification process is documented in the following section.

This document serves as an introductory text for mathematicians and computer scientists seeking to understand sheaf theory’s foundational concepts and their practical applications in distributed systems, constraint satisfaction, and topological data analysis.

NOTE ON REFERENCES AND VERIFICATION

This document contains AI-generated content. All references have been subject to rigorous verification to ensure academic integrity.

Verification Process:

- All URLs were tested for accessibility using automated tools
- Author names were verified against real publications
- DOIs were confirmed where available
- Publication venues (journals, conferences) were validated
- Content relevance was checked against citations

Verification Status in References: Each reference includes a `note` field indicating its verification status:

- “Verified: URL accessible” – URL was tested and works
- “Verified: DOI accessible” – DOI was confirmed
- “Standard reference” – Well-known textbook or established work
- “Requires verification” – Needs manual review

Important Notice: Due to the AI-assisted nature of this document’s creation, readers should independently verify any references used for critical applications.

REFERENCES

- [1] G. E. Bredon, *Sheaf Theory*, 2nd ed., ser. Graduate Texts in Mathematics. New York, NY, USA: Springer, 1997, vol. 170, verified: DOI accessible, Springer Link accessible. [Online]. Available: <https://link.springer.com/book/10.1007/978-1-4612-0647-7>
- [2] S. Mac Lane and I. Moerdijk, *Sheaves in Geometry and Logic: A First Introduction to Topos Theory*, ser. Universitext. New York, NY, USA: Springer, 1992, verified: DOI accessible, Springer Link accessible. [Online]. Available: <https://link.springer.com/book/10.1007/978-1-4612-0927-0>
- [3] R. Hartshorne, *Algebraic Geometry*, ser. Graduate Texts in Mathematics. New York, NY, USA: Springer, 1977, vol. 52, verified: DOI accessible, Springer Link accessible. [Online]. Available: <https://link.springer.com/book/10.1007/978-1-4757-3849-0>
- [4] M. Kashiwara and P. Schapira, *Sheaves on Manifolds*, ser. Grundlehren der mathematischen Wissenschaften. Berlin, Germany: Springer, 1990, vol. 292, verified: DOI accessible, Springer Link accessible. [Online]. Available: <https://link.springer.com/book/10.1007/978-3-662-02661-8>
- [5] R. Ghrist, *Elementary Applied Topology*. Createspace, 2014, verified: Author’s UPenn webpage with free PDF chapters accessible. [Online]. Available: <https://www2.math.upenn.edu/~ghrist/notes.html>
- [6] J. Curry, “Sheaves, cosheaves and applications,” Ph.D. dissertation, University of Pennsylvania, 2014, verified: arXiv accessible - final version (v2) accepted doctoral thesis. [Online]. Available: <https://arxiv.org/abs/1303.3255>