SciLogic: From Scientific Papers to Scientific Reasoning

Jan Janssen, Sepideh Baghaee Ravari, Soroush Mehrani, Markus Stricker

Abstract

Scientific publications communicate results through narrative prose, figures, and tables, but the structure of the argument behind their conclusions remains largely implicit: which observations are offered as evidence, which assumptions an inference depends on, and which alternative explanations remain open. Making this structure explicit is particularly difficult in empirical disciplines such as materials science and chemistry, where conclusions rest on heterogeneous and defeasible evidence rather than formal proof.

In this perspective we propose *SciLogic*, a lightweight, implementation-oriented profile for representing the published justification of a single empirical paper, and report first experience with a reference implementation. SciLogic combines established argumentation concepts, in particular from Micropublications, with three emphases: relations can record an explicit inference rule (warrant) together with its basis, quantitative evidence is kept in a form whose derived checks can be recomputed, and the annotator's assessment of each claim is stored separately from the reconstructed argument. We describe the SciLogic specification and its open reference implementation `claim-chain`, and illustrate three applications. For peer review, a worked example from computational materials science shows how an encoding makes candidate issues explicit, such as a conclusion that rests on an untested hypothesis or on an empirical rule of thumb. For finding new research directions, 62 open items collected from the encodings of ten recent preprints were matched against one research interest to propose five candidate studies. Analysing a group's own publications for a research proposal is outlined as a planned application.

1 Introduction

Scientific publications are the principal units through which results are communicated, evaluated, and archived, but the logical structure behind their narrative is rarely explicit. A reader must reconstruct which observations serve as evidence for a hypothesis, which assumptions an inference depends on, and which alternative explanations remain open.

Over the last decade, the FAIR principles have made large parts of the scientific process findable, accessible, interoperable, and reusable [1, 2, 3]. Two components carry this effort. Ontologies and knowledge graphs provide the semantics of the data, defining what a material, a measurement, or a computed property is [4]. Scientific workflows provide its provenance, recording how a result was produced from inputs, methods, parameters, and software [5, 6], and recent work connects the two [7, 8]. Neither, however, records the inferential step through which a result becomes evidence for a conclusion. A workflow may reproducibly compute a free-energy difference, yet the claim that this difference explains an observed phase transformation is a separate inference. We therefore regard the logical chain of evidence, hypothesis, and conclusion not as a standalone representation but as the third component of reproducible science: only the provenance of the workflow, the data with its ontology, and the logical chain together cover the full scientific process.

The need for such a logical layer has become pressing. OpenAI recently released several hundred machine-generated mathematical manuscripts addressing open problems, many accompanied by formal proofs in Lean [9, 10]. Mathematics could be accelerated in this way because its reasoning has a formal representation in which every step can be checked. Language models are equally being applied across materials science and chemistry [11, 12], but there conclusions rest on heterogeneous and defeasible evidence (finite-precision measurements, approximate simulations, empirical correlations) rather than proof, and no comparable representation exists. Without one, a model that retrieves a conclusion cannot show why it is justified, and generated claims cannot be checked at scale.

Representing scientific arguments is not itself new. Argumentation models such as ScholOnto, SALT, SWAN, Micropublications, and the Argument Interchange Format represent claims, evidence, and challenges

[13, 14, 15, 16, 17, 18]. Nanopublications, SEPIO, the Evidence and Conclusion Ontology, and PROV-O capture assertions, evidence, and provenance [19, 20, 21, 22, 23, 24]. Argument mining and claim verification extract and test such structures from text [25, 26, 27, 28, 29, 30, 31, 32, 33], and scholarly knowledge graphs link them across publications [34, 35, 36, 37]. What remains open is a representation lightweight enough for routine use in empirical disciplines, grounded in the quantitative results it relies on, and reconstructable reproducibly by humans and language models alike.

We propose *SciLogic* for this purpose: a lightweight, implementation-oriented profile that combines established argumentation concepts with recomputable quantitative checks and a separately attributable assessment. SciLogic represents the *published justification* of a single empirical paper, as reconstructed by an annotator, as typed statements and typed relations that can record explicit inference rules. It reuses established concepts wherever possible and does not claim to capture how the authors actually reached their conclusions. Our contributions are:

1. the SciLogic specification, including vocabularies of statement and relation types (Section 2);
2. the open reference implementation `claim-chain` with an LLM-based converter from PDF (Section 3);
3. three applications: supporting peer review, identifying open research questions across ten recent preprints, and, as a placeholder, writing research proposals (Section 4).

Whether independent annotators reconstruct the same arguments has not yet been tested, and links between the encodings of different papers are not yet represented.

2 The SciLogic specification

The specification is written as a LinkML schema [38] from which a JSON Schema and RDF exports are generated [39]. An encoding, called an *argument chain*, describes one publication and contains statements, relations between statements, the entities they refer to (materials, techniques, quantities, methods), the cited works with what each is cited for, and a paper-level assessment.

2.1 Five layers

Propositions, their discourse roles, and the source objects that carry evidence must not be conflated. SciLogic separates five layers:

1. **Discourse unit.** Each statement contains one self-contained discourse unit, written so that it can be understood on its own. For most types this is a proposition; for `QUESTION` it is a question. The text is the annotator's paraphrase; the `hedged` flag records whether the authors themselves hedge. Because no verbatim source passage is stored yet, the flag can only be checked against the paper via the locator.
2. **Discourse role.** The statement type (Table 1) is the role the proposition plays *in this paper*. For claims, the role is refined by a claim role (main conclusion, intermediate step, quantitative support, mechanistic interpretation, methodological claim, or counter-claim), a modality (descriptive, comparative, correlational, causal, generalization, conceptual), and the authors' certainty (demonstrated, predicted, proposed, speculative). The certainty categories are a pragmatic choice that mixes epistemic strength (demonstrated, speculative) with the mode of derivation (predicted, i.e. computed rather than measured).
3. **Evidence and source artifact.** Evidence is not a statement type but an attribute of a statement: its kind (citation, argument, qualitative data, quantitative data, or none), a locator pointing to the figure, table, equation, or section, the values read from it, and derived checks.
4. **Argument relation.** Typed, directed relations connect statements (Table 2). Each relation records who asserts it, how and how strongly the subject supports the object, the uncertainty of the link, and optionally the warrant behind the step, that is, the rule that licenses the inference [40].
5. **Assessment.** The annotator's verdict on each claim and hypothesis, with rationale, missing evidence, and proof obligations (Section 2.3).

Hypothesis, claim, and conclusion are not separate kinds of proposition: HYPOTHESIS marks a proposition the paper sets out to establish, and a conclusion is a CLAIM with the role *main conclusion*. When the main conclusion confirms the hypothesis, both are encoded as separate statements, possibly worded alike, and the claim SUPPORTS the hypothesis. Because each encoding covers one paper, the same proposition can be a hypothesis in one paper and an assumption or background statement in another. A figure or dataset is a source artifact referenced by a locator; it never asserts anything itself, and what the paper reads from it is recorded as an OBSERVATION. Finally, relations distinguish links stated or implied by the authors (AUTHORS) from links an annotator adds from the paper's own content (ANNOTATOR) or from outside knowledge (ANNOTATOR_BACKGROUND), and a warrant whose basis is UNSTATED marks an inference rule the paper uses without saying so. Reconstructed links and assumptions can therefore be marked as such. Links the authors state explicitly and links they only imply are not yet distinguished.

Statement type	Definition in SciLogic
BACKGROUND	Established fact taken from the literature.
GAP	Problem or gap the work addresses.
HYPOTHESIS	Proposition the paper sets out to establish (the central thesis or a sub-hypothesis).
QUESTION	Research or bridging question, including open questions.
DEFINITION	New term or concept introduced.
ASSUMPTION	Premise the argument relies on but does not test in this paper; either accepted in the community or a choice of the authors, optionally with the open question it leaves.
METHOD	Methodological choice or procedure.
DATA	Description of datasets or samples used.
OBSERVATION	Result read from this paper's own data.
CLAIM	Conclusion drawn by the authors.
LIMITATION	Limitation or inconsistency acknowledged by the authors.
OUTLOOK	Speculation or future work.

Table 1: Statement types of SciLogic. The type is the role a proposition plays in the encoded paper, not an intrinsic property of the proposition.

2.2 Relations

Table 2 lists the ten relation types. Relations are stored as directed assertions from subject to object and are read as "subject *predicate* object". Inverse and transitive edges are not generated: in particular, support is *not* propagated along paths. Some predicates nevertheless have symmetric meaning: CONTRADICTS expresses incompatibility within the same scope, so a single stored edge also implies the converse. A graph that contains a claim and a contradicting claim is valid, since it may faithfully represent a disagreement within the paper. How uncertain links should propagate to the claims that depend on them is an open design question. Endpoints are normally statements; the object of ANALOG_OF may also be an entity, such as a reference material. The validator checks only that subject and object exist as statements or entities and does not yet restrict their types, so the endpoint column lists typical rather than enforced endpoints.

Figure 1 shows the relation types in a schematic example. It is deliberately simple, but it illustrates the distinctions that matter: support by different kinds of evidence, an explicit warrant for the step from simulated migration barriers to conductivity, a scope restriction, and the difference between logical opposition and empirical counter-evidence.

Two relations need further comment. WEAKENS attacks the credibility of a conclusion. In structured argumentation this is a form of rebuttal, whereas an *undercutter* attacks the inference from premises to conclusion [41]. Undercutting in that sense requires inferences that can be addressed as objects, which SciLogic does not yet provide; the relation was therefore renamed from UNDERCUTS to WEAKENS, and older files are converted automatically. SUPPORTS, CONDITIONALLY_SUPPORTS, and DEPENDS_ON differ in the status of the subject and in how it is used. In the worked example (Section 4.1), mechanical stability (C1.3) SUPPORTS the metastability claim C1, because the paper establishes it; the untested kinetic barrier (H1) CONDITIONALLY_SUPPORTS C1, because C1 would follow if H1 were shown; and in Figure 1 the simulation O2 DEPENDS_ON the assumption A2, because it uses A2 as an input rather than offering it as evidence. CONDITIONALLY_SUPPORTS thus combines an inferential link with the unestablished status of its premise;




Figure 1: Schematic SciLogic graph for a hypothetical doping study. All statements and numerical values are illustrative and not taken from a publication; a real encoding is discussed in Section 4.1. Arrows point from subject to object. Both observations support hypothesis H1. The step from the simulated migration barriers (O2) to conductivity requires warrant W1, which the hypothetical paper leaves unstated. The main claim C1 qualifies H1 by restricting it to the tested range. H3 contradicts H1, since both cannot hold in the same scope, whereas C1 weakens H3: it is empirical counter-evidence that lowers the credibility of H3 without refuting it outside the tested range. The simulation O2 depends on assumption A2 of randomly distributed dopants. Because this assumption is likely to fail at high dopant concentrations, A2 motivates the open question Q1, as does the competing hypothesis H3.

Predicate	Definition (subject → object)	Typical endpoints
SUPPORTS	Gives evidence or a reason that makes the object more credible.	observation, claim → claim, hypothesis
CONDITIONALLY_SUPPORTS	Would support the object if the subject were shown; used for untested hypotheses the argument leans on.	hypothesis → claim
QUALIFIES	Restricts the scope or strength of the object without refuting it.	claim → claim, hypothesis
CONTRADICTS	Cannot hold together with the object within the same scope (symmetric in meaning).	claim, hypothesis → claim, hypothesis
WEAKENS	Counter-evidence: lowers the credibility of the object without contradicting it.	observation, claim → claim, hypothesis
ALTERNATIVE_EXPLANATION_FOR	Offers another cause for an observation or claim.	hypothesis, claim → observation, claim
MOTIVATES	Gives the reason to pose or investigate the object.	any → question, hypothesis
ANSWERS	Answers the question posed by the object, fully or in part.	claim, observation → question
DEPENDS_ON	Uses the object, e.g. a method uses a definition or a simulation an assumption.	method, observation, hypothesis → assumption, definition
ANALOG_OF	Is defined by analogy to the object.	statement → statement, entity

Table 2: Relation types of SciLogic. The definitions are those documented in the schema [39].

recording that status on the statement and using SUPPORTS throughout is an alternative we consider for a future version. A warrant on a binary relation explains one step but does not represent a multi-premise inference; Section 5 returns to this limitation.

2.3 Assessment as a separate layer

SciLogic does not decide whether a claim is true. The assessment layer records a narrower judgment: *does the data presented in the paper support the claim?* Each claim and hypothesis receives one of five verdicts with a rationale, the missing evidence, and *proof obligations*. The annotation instructions define the verdicts operationally: YES, the presented data support the claim as worded; PARTIAL, part of the claim is shown (for example a trend) and part is not (for example the mechanism, the generality, or a comparative "better"); WEAK, all support is indirect, thin, or uncontrolled; INCONCLUSIVE, no data in the paper decide the claim, for example when it is argued by analogy or a mechanism is proposed but not tested; and NO, the paper's own data or statements contradict it. NO thus means contradicted, not merely unsupported, and INCONCLUSIVE means undecided by the presented data. A proof obligation states what would have to be shown for the claim to hold, with its status, priority, and the data that would discharge it; an open obligation is a candidate request a reviewer might make. Cited references are not looked up; they are assumed to provide what they are cited for. The verdict is therefore conditional on the cited support being represented correctly, and it evaluates the internal logic of the paper, not the state of the field. The generated reports do not yet state this condition explicitly.

The implementation also derives draft scores from the verdicts: a logic score (the mean of YES $= 1$, PARTIAL $= 0.5$, WEAK $= 0.375$, INCONCLUSIVE $= 0.25$, NO $= 0$ over all claims and hypotheses), a variant weighted by claim role, and the fraction of discharged proof obligations. These weights are arbitrary and unvalidated; in particular, ranking INCONCLUSIVE below PARTIAL has no measurement basis. The mean and the fraction of discharged obligations also change when an annotator splits one claim into several. The score is an experimental index for comparing encodings of the same paper. It is neither a probability that the paper is correct nor a measure of its quality, and we report verdict counts alongside it. Because the assessment is an annotator's judgment, it must remain separable from the reconstructed argument. Two annotators may agree on the argument and disagree on its assessment, and both outcomes are informative. The current validator, however, requires an assessment for every claim and hypothesis, so a reconstruction cannot yet be validated on its own; a separate validation profile for unassessed reconstructions would make

the conceptual separation operational. Whether assessments should be stored in a file separate from the encoding is an open question.

2.4 Relation to the closest models

SciLogic is not a new ontology but a lightweight profile that combines established argumentation concepts with quantitative checks and a separately attributable assessment. Table 3 compares it with three of the closest models. The entries summarize the primary descriptions cited; a feature listed as not described may still be expressible through extensions of a model.

Aspect	Micropublications [16]	SEPIO [21]	AIF [17]	SciLogic
Inference step	Support and challenge relations between claims, statements, and evidence	Evidence lines linking evidence to an assertion, with direction and strength	Inference nodes typed by argument scheme	Typed binary relations with optional warrant and its basis
Joint premises	Not described	An evidence line groups several evidence items	Several premises per inference node	Not yet represented
Evidence source	Data, methods, and materials as supporting elements	Evidence items with provenance of agents, methods, and tools	Not a focus	Locator to figure, table, equation, or section
Quantitative values	Not described	Not described	Not described	Values with units; checks recomputed by the software
Attribution of links	Attribution of statements and annotations	Provenance of assertions and evidence lines	Not a focus	Authors, annotator, or annotator with outside knowledge, per relation
Assessment	Not described	Confidence and strength of evidence lines	Preferences between arguments	Separate verdict layer with proof obligations
Intended workflow	Annotation of biomedical communications	Integration of curated evidence	Exchange between argumentation tools	LLM-assisted encoding and review of single papers

Table 3: SciLogic compared with three closely related models. Entries for the other models summarize the cited primary descriptions and do not exclude extensions.

3 Reference implementation

The open-source package `claim-chain` [39] implements SciLogic. It consists of:

- the LinkML schema, with a JSON Schema generated from it that can be used for structured LLM output, and RDF export;
- a renderer that turns an encoding into a readable argument chain, a Markdown report with verdicts, limitations, and missing evidence, argument maps, and the draft scores, and that recomputes all derived checks;
- a validator that checks an encoding against the schema and for referential consistency, for example that identifiers are unique, that relations refer to defined statements, and that every claim and hypothesis has an assessment;
- a command-line tool and Python API, `claimchain`, that converts a PDF into an encoding with an LLM (Claude). The model reads the PDF including its figures. The returned encoding is validated, and any problems are sent back to the model for up to two rounds of correction;

- annotation instructions and a review checklist, used both by the converter and for LLM-assisted manual annotation;

The converter does not compute scores or run the derived checks; the renderer is run on its output for that. Its output has not yet been evaluated against hand-checked encodings. The repository contains two worked examples: a hand-encoded recent paper with 64 statements, and the example discussed next. It also contains LLM-drafted encodings of ten recent materials-science preprints from arXiv with 27 to 36 statements each.

4 Applications

We see three uses of SciLogic, each serving a different reader: a reviewer who has to judge whether a paper's conclusions follow from its evidence (Section 4.1), a researcher looking for the next project in the open questions of a field (Section 4.2), and a group writing a research proposal from its own body of work (Section 4.3). The first works on a single paper, the other two on collections of papers.

4.1 Supporting peer review

A reviewer has to reconstruct the logical structure of a paper before judging it. A SciLogic encoding makes one such reconstruction explicit and open to inspection. As a documented case we use the encoding of Zhuang, Chen, and Carter (2017), who predict a $D0_{19}$-ordered Mg_3Al intermetallic compound with orbital-free and Kohn–Sham density functional theory and characterize its stability and ductility [42]. The encoding was made by hand by one of us (J.J.) and converted to the current schema. During this conversion, verdicts and proof obligations were added with LLM assistance (Claude), based on the hand encoding rather than on a fresh reading of the paper. The assessment is therefore a single LLM-assisted reading, not an independent expert judgment.

The encoding contains 21 statements (15 claims and hypotheses, two assumptions, and four open questions), 20 relations, and 22 derived checks, all of which reproduce from the recorded values. The paper has two main conclusions: $D0_{19}$ Mg_3Al is at least metastable (C1), and it is predicted to be more ductile than hcp Mg (C2). In the encoding, metastability means local stability: the structure is dynamically and mechanically stable and energetically competitive with other Mg_3Al structures, while the paper itself finds it thermodynamically unstable against decomposition (C1.4). Table 4 shows selected statements. Of the 15 claims and hypotheses, 9 are assessed `YES`, 3 `PARTIAL`, and 3 `INCONCLUSIVE`; 4 of the 8 proof obligations are discharged. Thirteen of the 20 relations are attributed to the authors and seven to the annotator. Six of the twelve support relations carry an explicit warrant (two with the basis domain convention, two author argument, one citation, one empirical correlation), and six statements carry a warrant for their own evidence; none of these warrants is marked as unstated by the paper.

Two of the derived checks illustrate the quantitative layer. For mechanical stability (C1.3), the encoding records the elastic constants $C_{11} = 73$, $C_{12} = 33$, $C_{13} = 30$, and $C_{33} = 73$ GPa from the paper's Table 1 and evaluates the Born criterion $2C_{13}^2 < C_{33}(C_{11} + C_{12})$, which gives $1800 < 7738\,\mathrm{GPa}^2$ and is satisfied. For ductility (C2.1), it records the Pugh ratios $B/G = 2.65$ for $D0_{19}$ Mg_3Al and 1.76 for hcp Mg and computes an increase of 50.6 %. That all 22 checks recompute shows that the recorded calculations are internally consistent. It does not validate the transcription of the values, the applicability of the criteria, or the conclusions drawn from them.

In this reconstruction, the annotator encodes the paper's own counter-claim (C1.4) as a qualification of C1 rather than a contradiction. The first main conclusion then depends on a hypothesis (H1) that the paper does not test, and the annotator records the corresponding open proof obligation, a transformation path and its barrier, as a candidate issue for review. The four ductility descriptors are encoded as separate support relations, each with its own warrant; they are separate lines of argument in the paper, not necessarily independent evidence. One of these warrants, the Pugh criterion, is recorded with the basis *empirical correlation*, which flags it for a reviewer's attention. Finally, one result (C2.4) both supports and weakens C2, because C2 bundles a comparison with hcp Mg and an ordering of two Mg_3Al structures. The encoding thus points to a compound claim that should be split; we have kept it unsplit here to show how the structure exposes such cases. Whether a domain expert would identify the same issues has not been checked.

Id	Statement (role)	Relation and warrant	Verdict
C1	$D0_{19}$ Mg_3Al is at least metastable (main conclusion).	Supported by C1.1–C1.3; qualified by C1.4.	PARTIAL
C1.3	$D0_{19}$ Mg_3Al is mechanically stable (intermediate).	Strongly supports C1; warrant: Born criteria (basis: citation), recomputed.	YES
C1.4	$D0_{19}$ Mg_3Al is thermodynamically unstable against decomposition into $Mg_{17}Al_{12}$ and Mg (counter-claim).	Qualifies C1: it does not refute metastability, but makes it depend on a kinetic barrier.	YES
H1	A large kinetic barrier may prevent this decomposition (hypothesis).	Conditionally supports C1; warrant: a locally stable phase persists if the decomposition barrier is large (basis: domain convention).	INCONCLUSIVE
C2	$D0_{19}$ Mg_3Al is predicted to be more ductile than hcp Mg (main conclusion).	Supported by four descriptors C2.1–C2.4, each with its own warrant.	PARTIAL
C2.1	Larger Pugh ratio B/G than hcp Mg (quantitative support).	Supports C2; warrant: Pugh criterion (basis: empirical correlation).	YES
C2.4	Low anti-phase boundary energy compared with Ni_3Al (quantitative support).	Supports C2, but weakens the claimed ordering $D0_{19} > L1_2$ within C2 (link added by the annotator).	YES

Table 4: Selected statements of the worked example (Zhuang et al. 2017). The full encoding, report, and argument maps are in the repository [39]. Verdicts were assigned with LLM assistance during conversion to the current schema.

4.2 Identifying open research questions

A researcher looking for the next project typically gathers recent papers in the field, notes what they leave open, and selects the questions that match their own expertise. SciLogic makes the first two steps mechanical. Open items are already explicit in an encoding, but they have different origins: limitations and outlook statements are stated by the authors, the open question of an assumption is formulated by the annotator, and open proof obligations are proposed by the annotator. Because every item keeps the identifier of the statement it comes from, research ideas derived from them remain traceable to the papers.

We applied this to the ten arXiv preprints that serve as test papers in the repository. They were taken from the new submissions to cond-mat.mtrl-sci listed on 21 October 2026, chosen to cover experimental, computational, high-throughput, characterization-method, and AI-tool papers, and encoded from the PDFs of their first versions by an LLM (Claude) on the same day [43, 44, 45, 46, 47, 48, 49, 50, 51, 52]. A short script collects 62 open items from their encodings without deduplication: 29 stated by the authors (19 limitations and 10 outlook statements), 20 questions formulated by the annotator for assumptions, and 13 open proof obligations proposed by the annotator. In a single pass, the LLM then classified each item against one research interest, computational materials science with atomistic simulation, reproducible workflows, and coupling to mesoscale models and experiment: 17 items can in its judgment be addressed with the methods of this research interest alone, 18 only in combination with experiments, and 27 lie outside it. From these 35 items it derived five studies (Table 5), which address 20 of them; the remaining 15 were not developed further.

Most studies address the open questions of a single computational paper, as expected for a computational research interest. Study S3 is different: it combines open questions from two unrelated experimental papers, a combinatorial screening of fusion materials on co-sputtered films [49] and an on-chip annealing method for films with 3–7 nm grains [45], which both leave open whether nanocrystalline films retain phases that are not stable in bulk. Neither paper states this shared question; here it emerged from comparing the open items of several papers. We have not tested whether a direct reading of the papers, or an LLM given their full texts, would identify it as readily. The example also shows the limits of the current test: the encodings are LLM drafts, the matching was done without re-reading the papers, and the value of the proposed studies can only be judged by researchers in the field.

Proposed study	Open items addressed	Source papers
S1 Transferability of grain-boundary shear strengths across interatomic models	Dependence on the interatomic potential, metastable starting structures, compact supercells, reproducibility of generated code, missing comparison with a conventional workflow (5)	2610.28629 [52]
S2 Atomistically parameterized interfaces for phase-field models of Zr oxidation	Assumed eigenstrain and orientation relationship, averaged boundary energies, chosen nucleation parameters, 2D without plasticity, untested link to cracking (5)	2610.28493 [50]
S3 Size-dependent phase stability in nanocrystalline thin-film libraries	Retention of non-equilibrium phases in films with nanometre grains; transfer of film-based rankings to bulk (4)	2610.28232 [49], 2610.27355 [45]
S4 Stability and storage mechanism of Co-doped Janus HfSSe	Positive dopant formation energy, unshown synthesizability, ionic storage versus metal plating in outer layers (3)	2610.28152 [48]
S5 Simulation-derived structural bases for differentiable powder diffraction	Motions outside the neutron-derived basis, abrupt transitions excluded by the shared model, supply of simulated kinetics (3)	2610.28564 [51]

Table 5: Research studies derived from the open questions of ten recent arXiv preprints for a research interest in computational materials science. Numbers in parentheses give the number of open items addressed. Matching and study design are a single LLM pass (Claude) over the encodings and have not been reviewed by a domain expert. The catalogue and the studies are in the repository [39].

4.3 Writing research proposals

The third use starts from one's own body of work. When a group writes a new research proposal or the extension of an existing one, it analyses the publications it has produced together with its collaborators: which hypotheses have been established, which rest on assumptions that were never tested, which proof obligations remain open across several papers, and which results of one paper serve as evidence in another. Encodings of these publications would make such an analysis systematic, and the open proof obligations would translate directly into work packages. Unlike the second use, this requires links between the encodings of several papers, which SciLogic does not yet represent, and a corpus of encoded publications of one group. We have not yet assembled such a corpus; this application is therefore described here as a planned demonstration only.

5 Discussion and limitations

SciLogic occupies a space between formal logic, semantic knowledge representation, and scientific narrative. It does not turn empirical science into proof: a relation such as `SUPPORTS` remains an evidential judgment whose strength depends on uncertainty, conditions, model assumptions, and disciplinary conventions. Its value lies in making that judgment explicit and attributable, so that it can be inspected, disputed, and compared.

The present work has clear limitations. A warrant attached to a binary relation explains one inferential step, but the specification cannot yet represent joint premises, assumptions attached to a single inference, or attacks on an inference itself; it therefore does not capture the complete inferential structure of an argument. Its provenance stops at the level of figures, tables, and sections, and paraphrased statements are not anchored to verbatim passages. Links stated by the authors and links they only imply are not distinguished. Endpoint types of relations are not enforced, and the validator requires an assessment even when only a reconstruction is wanted. Verdicts are conditional on cited works providing what they are cited for. The scores are experimental indices without agreed weightings. The worked example was assessed with LLM assistance, and the research studies derived from open items are proposals from a single LLM pass; no domain expert has yet reviewed either. Finally, this perspective reports no reproducibility data. Whether experts converge on the same argument graph, and where they legitimately do not, remains the open empirical question. We consider it the most important question for the approach: if independent experts consistently disagree about the role of a statement or the strength of an inference, the disagreement itself is information about how explicit the reasoning in contemporary publications is.

6 Conclusion

SciLogic represents the published justification of an empirical paper as typed statements, typed relations with explicit warrants, quantitative evidence that can be recomputed, and an assessment kept separate from the reconstructed argument. Its specification is available as a versioned schema with an open reference implementation. A worked example illustrates how the structure makes candidate weaknesses of an argument explicit for a reviewer, and the open items collected from the encodings of ten recent preprints can be matched against a research interest to propose candidate studies, which still require evaluation by experts. The next step is the expert study that tests whether published scientific arguments can be reconstructed reproducibly enough to support inspection, and that shows where such reconstruction remains ambiguous.

Data and code availability

The SciLogic schema, the `claim-chain` reference implementation, the two worked examples, the ten LLM-drafted test-paper encodings, and the catalogue of open questions with the derived research studies are openly available at https://github.com/lab-mids/claim-chain [39]. This manuscript refers to commit `cb8a248`. The schema is released under CC-BY-4.0 and the software under GPL-3.0. The PDFs of the test papers are not redistributed; a script in the repository retrieves them from arXiv. The RDF namespaces (`w3id.org/claim-chain/...`) are placeholders and not yet registered.

Author contributions

Conceptualization, methodology, software, validation, visualization, writing, and supervision contributions will be specified in the final manuscript.

Acknowledgements

The `claim-chain` implementation was started at the Open Science Hackathon on 21 October 2026.

References

[1] Mark D. Wilkinson, Michel Dumontier, IJsbrand Jan Aalbersberg, Gabrielle Appleton, Myles Axton, Arie Baak, Niklas Blomberg, Jan-Willem Boiten, Luiz Bonino da Silva Santos, Philip E. Bourne, et al. The FAIR guiding principles for scientific data management and stewardship. *Scientific Data*, 3:160018, 2016.

[2] Michelle Barker, Neil P. Chue Hong, Daniel S. Katz, Anna-Lena Lamprecht, Carlos Martinez-Ortiz, Fotis Psomopoulos, Jennifer Harrow, Leyla Jael Castro, Morane Gruenpeter, Paula Andrea Martinez, and Tom Honeyman. Introducing the FAIR principles for research software. *Scientific Data*, 9:622, 2022.

[3] Matthias Scheffler et al. FAIR data enabling new horizons for materials research. *Nature*, 604(7907):635–642, 2022.

[4] Alexandru Oarga, Matthew Hart, Andres M. Bran, Magdalena Lederbauer, and Philippe Schwaller. Scientific knowledge graph and ontology generation using open large language models. *Digital Discovery*, 5(3):1269–1279, 2026.

[5] Sean R. Wilkinson et al. Applying the FAIR principles to computational workflows. *Scientific Data*, 12:328, 2025.

[6] Jan Janssen, Janine George, Julian Geiger, Marnik Bercx, Xing Wang, Christina Ertural, Jörg Schaarschmidt, Alex M. Ganose, Giovanni Pizzi, Tilmann Hickel, and Jörg Neugebauer. A python workflow definition for computational materials design. *Digital Discovery*, 2025.

[7] Jan Janssen, Osamu Waseda, Bernd Bayerlein, Simon Stier, Steffen Brinckmann, Abril Azócar Guzmán, Sarath Menon, Matthias A. Popp, Jesper R. Pedersen, Ivano E. Castelli, Jörg Waitelonis, Wolfgang Wenzel, Jörg Neugebauer, Jörg Schaarschmidt, and Tilmann Hickel. Toward full interoperability in materials science: Integrating workflows with knowledge graphs. *Advanced Engineering Materials*, page e71258, 2026.

[8] Sepideh Baghaee Ravari, Abril Azocar Guzman, Sarath Menon, Stefan Sandfeld, Tilmann Hickel, and Markus Stricker. Ontology-aligned structuring and reuse of multimodal materials data and workflows towards automatic reproduction. *arXiv preprint arXiv:2601.12582*, 2026.

[9] OpenAI. Mathematical results from an internal frontier model. https://github.com/openai/math, October 2026. Released October 2026.

[10] Sébastien Bubeck, Christian Coester, Ronen Eldan, Timothy Gowers, Yin Tat Lee, Alexandru Lupsasca, Mehtaab Sawhney, Robert Scherrer, Mark Sellke, Brian K. Spears, Derya Unutmaz, Kevin Weil, Steven Yin, and Nikita Zhivotovskiy. Early science acceleration experiments with GPT-5. *arXiv preprint arXiv:2511.16072*, 2025.

[11] Kevin Maik Jablonka, Qianxiang Ai, Alexander Al-Feghali, Shruti Badhwar, Joshua D. Bocarsly, Andres M. Bran, Stefan Bringuier, L. Catherine Brinson, Kamal Choudhary, Defne Circi, et al. 14 examples of how LLMs can transform materials science and chemistry: A reflection on a large language model hackathon. *Digital Discovery*, 2:1233–1250, 2023.

[12] Yoel Zimmermann, Adib Bazgir, Alexander Al-Feghali, Mehrad Ansari, Joshua Bocarsly, L. Catherine Brinson, Yuan Chiang, Defne Circi, Min-Hsueh Chiu, Nathan Daelman, et al. 32 examples of LLM applications in materials science and chemistry: Towards automation, assistants, agents, and accelerated scientific discovery. *Machine Learning: Science and Technology*, 6(3):030701, 2025.

[13] Simon Buckingham Shum, Enrico Motta, and John Domingue. ScholOnto: An ontology-based digital library server for research documents and discourse. *International Journal on Digital Libraries*, 3(3):237–248, 2000.

[14] Tudor Groza, Knud Möller, Siegfried Handschuh, Diana Trif, and Stefan Decker. SALT: Weaving the claim web. In *The Semantic Web: 6th International Semantic Web Conference, 2nd Asian Semantic Web Conference, ISWC 2007 + ASWC 2007*, pages 197–210. Springer, 2007.

[15] Paolo Ciccarese, Elizabeth Wu, Gwen Wong, Marco Ocana, June Kinoshita, Alan Ruttenberg, and Tim Clark. The SWAN biomedical discourse ontology. *Journal of Biomedical Informatics*, 41(5):739–751, 2008.

[16] Tim Clark, Paolo N. Ciccarese, and Carole A. Goble. Micropublications: A semantic model for claims, evidence, arguments and annotations in biomedical communications. *Journal of Biomedical Semantics*, 5:28, 2014.

[17] Carlos Chesñevar, Jarred McGinnis, Sanjay Modgil, Iyad Rahwan, Chris Reed, Guillermo Simari, Matthew South, Gerard Vreeswijk, and Steven Willmott. Towards an argument interchange format. *The Knowledge Engineering Review*, 21(4):293–316, 2006.

[18] Iyad Rahwan, Fouad Zablith, and Chris Reed. Laying the foundations for a world wide argument web. *Artificial Intelligence*, 171(10-15):897–921, 2007.

[19] Paul Groth, Andrew Gibson, and Jan Velterop. The anatomy of a nanopublication. *Information Services & Use*, 30(1-2):51–56, 2010.

[20] Tobias Kuhn, Albert Merono-Penuela, Alexander Malic, Jorrit H. Poelen, Allen H. Hurlbert, Emilio Centeno Ortiz, Laura I. Furlong, Núria Queralt-Rosinach, Christine Chichester, Juan M. Banda, Egon Willighagen, Friederike Ehrhart, Chris Evelo, Tareq B. Malas, and Michel Dumontier. Nanopublications: A growing resource of provenance-centric scientific linked data. In *2018 IEEE 14th International Conference on e-Science (e-Science)*, pages 83–92. IEEE, 2018.

[21] Matthew H. Brush, Kent Shefchek, and Melissa Haendel. SEPIO: A semantic model for the integration and analysis of scientific evidence. In *Proceedings of the 7th International Conference on Biomedical Ontology (ICBO 2016)*, volume 1747 of *CEUR Workshop Proceedings*. CEUR-WS.org, 2016.

[22] Marcus C. Chibucos, Deborah A. Siegele, James C. Hu, and Michelle Giglio. The evidence and conclusion ontology (ECO): Supporting GO annotations. In *The Gene Ontology Handbook*, volume 1446 of *Methods in Molecular Biology*, pages 245–259. Humana Press, 2017.

[23] Timothy Lebo, Satya Sahoo, and Deborah McGuinness. PROV-O: The PROV ontology. W3c recommendation, World Wide Web Consortium, April 2013.

[24] Tek Raj Chhetri, Yaroslav O. Halchenko, Dorota Jarecka, Puja Trivedi, Satrajit S. Ghosh, Patrick Ray, and Lydia Ng. Bridging the scientific knowledge gap and reproducibility: A survey of provenance, assertion and evidence ontologies. In *Companion Proceedings of the ACM on Web Conference 2025*, pages 924–928. Association for Computing Machinery, 2025.

[25] Simone Teufel, Jean Carletta, and Marc Moens. An annotation scheme for discourse-level argumentation in research articles. In *Ninth Conference of the European Chapter of the Association for Computational Linguistics*, pages 110–117. Association for Computational Linguistics, 1999.

[26] Christian Kirschner, Judith Eckle-Kohler, and Iryna Gurevych. Linking the thoughts: Analysis of argumentation structures in scientific publications. In *Proceedings of the 2nd Workshop on Argumentation Mining*, pages 1–11. Association for Computational Linguistics, 2015.

[27] Anne Lauscher, Goran Glavaš, and Simone Paolo Ponzetto. An argument-annotated corpus of scientific publications. In *Proceedings of the 5th Workshop on Argument Mining*, pages 40–46. Association for Computational Linguistics, 2018.

[28] Nancy L. Green. Proposed method for annotation of scientific arguments in terms of semantic relations and argument schemes. In *Proceedings of the 5th Workshop on Argument Mining*, pages 105–110. Association for Computational Linguistics, 2018.

[29] Anne Lauscher, Goran Glavaš, and Kai Eckert. ArguminSci: A tool for analyzing argumentation and rhetorical aspects in scientific writing. In *Proceedings of the 5th Workshop on Argument Mining*, pages 22–28. Association for Computational Linguistics, 2018.

[30] Florian Ruosch, Cristina Sarasua, and Abraham Bernstein. BAM: Benchmarking argument mining on scientific documents. In *Workshop on Scientific Document Understanding at AAAI 2022*, volume 3164 of *CEUR Workshop Proceedings*. CEUR-WS.org, 2022.

[31] David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. Fact or fiction: Verifying scientific claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, pages 7534–7550. Association for Computational Linguistics, 2020.

[32] Rosni Vasu, Cristina Sarasua, and Abraham Bernstein. SciHyp: A fine-grained dataset describing hypotheses and their components from scientific articles. In *The Semantic Web – ISWC 2024*, volume 15233 of *Lecture Notes in Computer Science*, pages 134–152. Springer, 2024.

[33] Khalid Al Khatib, Tirthankar Ghosal, Yufang Hou, Anita de Waard, and Dayne Freitag. Argument mining for scholarly document processing: Taking stock and looking ahead. In *Proceedings of the Second Workshop on Scholarly Document Processing*, pages 56–65. Association for Computational Linguistics, 2021.

[34] Mohamad Yaser Jaradeh, Allard Oelen, Kheir Eddine Farfar, Manuel Prinz, Jennifer D'Souza, Gábor Kismihók, Markus Stocker, and Sören Auer. Open research knowledge graph: Next generation infrastructure for semantic scholarly knowledge. In *Proceedings of the 10th International Conference on Knowledge Capture*, K-CAP '19, pages 243–246. Association for Computing Machinery, 2019.

[35] Florian Ruosch, Cristina Sarasua, Chris Reed, and Abraham Bernstein. Toward the argument web of science. In *Proceedings of COMMA 2024*, Computational Models of Argument, pages 365–366. IOS Press, 2024.

[36] Florian Ruosch, Cristina Sarasua, and Abraham Bernstein. Mining inter-document argument structures in scientific papers for an argument web. *Transactions on Graph Data and Knowledge*, 3(3):4:1–4:33, 2025.

[37] Joel Chan, Matthew Akamatsu, David Vargas, Lukas Kawerau, and Michael Gartner. Steps towards an infrastructure for scholarly synthesis. *arXiv preprint arXiv:2407.20666*, 2024.

[38] LinkML community. LinkML: The linked data modeling language. https://linkml.io, 2026. Accessed 22 October 2026.

[39] Markus Stricker, Jan Janssen, Sepideh Baghaee Ravari, and Soroush Mehrani. claim-chain: Reference implementation of the SciLogic argument-chain schema. https://github.com/lab-mids/claim-chain, 2026. Python package claimchain 0.1.0, commit cb8a248, accessed 22 October 2026.

[40] Stephen E. Toulmin. *The Uses of Argument*. Cambridge University Press, Cambridge, updated edition, 2003. First published 1958.

[41] John L. Pollock. Defeasible reasoning. *Cognitive Science*, 11(4):481–518, 1987.

[42] Houlong L. Zhuang, Mohan Chen, and Emily A. Carter. Prediction and characterization of an Mg-Al intermetallic compound with potentially improved ductility via orbital-free and Kohn-Sham density functional theory. *Modelling and Simulation in Materials Science and Engineering*, 25:075002, 2017.

[43] Surbhi Agarwal, Jiří Vacík, and D. K. Dwivedi. Tailoring dielectric relaxation and charge transport in amorphous Ge-Te-Se phase-change materials through yttrium incorporation. *arXiv preprint arXiv:2610.26996*, 2026.

[44] Ayoub Benmoumen, Marie-Laure David, Noé Condé, Eric Gautron, Sophie Morisset, Stéphane Célérier, Anupma Thakur, Babak Anasori, Vincent Mauchamp, and Philippe Moreau. Nanoscale chemical engineering of $Ti_3C_2T_x$ MXene multilayers through in situ electron beam irradiation in a TEM. *arXiv preprint arXiv:2610.27240*, 2026.

[45] Nensi Toncich, Nerea Abando, Henning Galinski, Frans Spaepen, and Ralph Spolenak. Reaction-induced localized annealing for on-chip materials discovery. *arXiv preprint arXiv:2610.27355*, 2026.

[46] Matthew A. Delmont, Yu Wu, Han-Hsuan Wu, Xiaoqing Pan, Christopher J. Palmstrøm, and Bolin Liao. Nanocrystalline cubic boron arsenide growth on GaAs(100) by gas source molecular beam epitaxy. *arXiv preprint arXiv:2610.27460*, 2026.

[47] Andrea Skolakova, Hana Lesakova, Frantisek Lukac, Marketa Jarosova, and Jan Pinc. Early-stage local melting during solid-state sintering of a Cu-Ni-Ti-Zr-Hf alloy: A combined thermodynamic and kinetic analysis. *arXiv preprint arXiv:2610.27825*, 2026.

[48] Md. Muktadir Hasan, Md. Mafizul Islam, and Ahmed Zubair. Enhancement of Li and Na storage in Janus HfSSe monolayers by Co-induced electron-deficient chalcogen sites: A first-principles study. *arXiv preprint arXiv:2610.28152*, 2026.

[49] Elena Botica-Artalejo, Josh Randolph, Kevin B. Woller, Gregory Wallace, and Michael P. Short. High-throughput down-selection of fusion candidate materials. *arXiv preprint arXiv:2610.28232*, 2026.

[50] K. Starkey, L. Kahle, M. Christensen, V. Eyert, A. El-Azab, C. B. Geller, A. P. Shivprasad, and E. Wimmer. Multiscale modeling of Zr corrosion: Predicting microstructures of oxide films. *arXiv preprint arXiv:2610.28493*, 2026.

[51] Xiangyu Yin, Nina Andrejevic, Hemant Sharma, Ming Du, Aileen Luo, Michael Prince, Burak Guzelturk, Xiaoyi Zhang, Brian H. Toby, and Mathew J. Cherukara. Differentiable powder X-ray diffraction enables analysis of evolving structures. *arXiv preprint arXiv:2610.28564*, 2026.

[52] Yazhuo Liu, Kunqing Ding, Xiaoguo Gong, Zifeng Wang, Yichen Yang, Yifeng Che, Wen Chen, Josh Kacher, Olivier Pierron, Shigenobu Ogata, and Ting Zhu. GBClaw: An agentic AI framework for atomistic grain boundary research and mechanistic discovery. *arXiv preprint arXiv:2610.28629*, 2026.