
Candle Flicker LED Options*

COLOR	-	10 mm Dia	1	5 mm Dia	1	3 mm Dia	
Yellow	T	BL-L101UYW-B-S3	T	BL-L513UYW-B-S3	T	BL-L314UYW-B-S3	ī
Red		not available	Ī	BL-L513URW-B-S3	1	BL-L314URW-B-S3	1
Green		not available	1	not available	\perp	BL-L314UGW-B-S3	1



Bill of Materials

Ref	Description	Mfg	Mfg P/N	+BATT	PWR_FLAG
BAT1	CR2032 Battery Holder	ADAM TECH	BH-125A-1	1	Ŷ
SW1	Switch, SMT 8.7 x 3.0 mm Mini-Slide	Würth Elektronik	450405020524	⇒ PWR FLAG	GND
R1, R2	Resistor, 47 Ohms ± 5%, 0.4W 0805	Rohm Semi	ESR10EZPJ470	T WING LAG	GIVD
D1, D2	LED, of your choosing	BetLux	BL-Lxxxxxx-B-S3		

* Available from EvilMadScientist - https://shop.evilmadscientist.com/productsmenu/partsmenu/189-candled

lab64 / Stanford University Electrical Engineering Department 350 Jane Stanford Way Stanford, CA 94305—9505

blame- steven.clark@stanford.edu

Sheet: /

File: cat_pcb_2a.sch

|--|

	Titte. Cut #2	FZ TWO LEDS					
Size: USLetter		Date:	Rev: 0.1				
KiCad E.D.A. ki		ad (5.1.9-0-10_14)	ld: 1/1				