

The Metric Architecture of Intelligence: A Proposal for Bypassing the Dual No-Go Theorems via Layered Fiber-Bundle Manifolds

Author: Labinot Marku, M.D.

Affiliation: Department of Neurosurgery, KRH Klinikum Nordstadt Hannover, Haltenhoffstr. 41, 30167 Hannover, Germany

Contact: labinot.marku@krh.de

Date: January 2, 2026

Field: Theoretical Information Geometry / Nonlinear Dynamics

⚠ Document Status

This is a theoretical proposal and research direction, NOT a validated result.

-  Mathematical framework is internally consistent
-  Addresses real problem (dual no-go theorems)
-  No experimental validation
-  No proof that proposal works in practice
-  Highly speculative - treat as hypothesis, not established fact

Use case: Vision document to stimulate research, not publication-ready manuscript

Abstract

This document proposes a theoretical framework for addressing the fundamental tension identified in our dual no-go theorems. We establish that pairwise ($p=2$) architectures are "topologically constrained," acting as projection operators that cannot preserve auxiliary degrees of freedom such as phase information. Conversely, higher-order ($p \geq 3$) interactions necessarily violate core dynamical safety properties through mechanisms including exponential growth of critical points and state-dependent stability.

To potentially bypass this dual constraint, we propose a **Layered Fiber-Bundle Architecture** combining:

1. A stable $p=2$ base manifold (ensuring convergence and robustness)
2. Controlled $p \geq 3$ fiber terms (providing expressivity)
3. A "Governor Inequality" constraint (regulating interaction strength)

The central hypothesis is that transient higher-order dynamics can provide computational flexibility while asymptotic collapse to the $p=2$ base ensures long-term stability. This proposal requires substantial experimental validation before any claims about AGI or practical utility can be made.

Keywords: fiber bundles, state-dependent metrics, hybrid architectures, associative memory, stability constraints

1. Motivation: The Dual No-Go Problem

Our previous work established two complementary impossibility results:

1.1 The $p=2$ Projection Theorem

Result: Pairwise gradient systems cannot preserve information encoded in energy-flat directions.

Consequence:

- Phase-coded memories fail (validated: 1,800 trials at chance level)
- Trajectory-based encoding fails
- Any auxiliary coordinate without energy curvature collapses
- Capacity limited to $M = O(N)$

Interpretation: $p=2$ systems are "safe but limited"

1.2 The $p \geq 3$ Instability Theorem

Result: Higher-order interactions violate multiple safety criteria:

- S1 (Basin Stability): State-dependent forces create sensitivity
- S2 (Predictability): Critical point counting is NP-hard
- S3 (Smooth Dependence): Generic bifurcations occur
- S4 (Interpretability): Exponential complexity in interactions

Consequence:

- Modern Hopfield networks exhibit training instabilities
- Transformers require extensive stabilization (LayerNorm, warmup)
- Attention entropy collapse at certain temperatures
- Hallucinations and unpredictable failure modes

Interpretation: $p \geq 3$ systems are "powerful but brittle"

1.3 The Central Challenge

Question: Can we design an architecture that combines:

- The stability and interpretability of $p=2$ systems
- The expressivity and capacity of $p \geq 3$ systems

Standard approaches that fail:

- "Better optimization" → doesn't change universality class
- "Careful tuning" → doesn't remove fundamental instabilities
- "More data" → doesn't alter topological constraints

This proposal: Geometric separation through fiber-bundle structure

2. Background: Why $p=2$ Systems Are Constrained

2.1 Quadratic Energy Landscape

Claim in original: "All pairwise systems have quadratic energy"

Correction: This is too strong. More precisely:

Definition 2.1 (Pairwise System): A system has pairwise interactions if:

$$E(x) = \sum_{i < j} J_{ij} f(x_i, x_j) + \sum_i h_i(x_i)$$

Examples:

- Classical Hopfield: $f(x_i, x_j) = x_i x_j$ (quadratic)
- Continuous Hopfield: f nonlinear but interactions pairwise
- CONN: $f(A_i, A_j, \phi_i, \phi_j) = A_i A_j \cos(\phi_i - \phi_j)$ (pairwise but not quadratic)

The key property for quadratic case:

For $E = -\frac{1}{2}x^T A x$:

- Hessian: $H = -A$ (constant, state-independent)
- Gradient: $\nabla E = -Ax$ (linear in state)
- Metric: Standard Euclidean $g_{ij} = \delta_{ij}$

Consequence: The "distance" between states is fixed, determined by A .

2.2 Information Geometry Perspective

Original claim: "Fisher Information Metric cannot adapt"

Clarification: Need to distinguish two different metrics:

1. Parameter space metric (Fisher Information):

$$g_{ij}^{\text{Fisher}}(\theta) = E_x[\partial \log p(x|\theta) / \partial \theta^i \cdot \partial \log p(x|\theta) / \partial \theta^j]$$

This is on parameter space Θ , not state space X .

2. State space metric (Riemannian):

$g_{ij}(x)$ defines gradient flow: $\dot{x}^i = -g^{ij}(x) \partial E / \partial x^j$

What we actually mean:

For quadratic $p=2$ systems with standard gradient descent:

$g_{ij} = \delta_{ij}$ (Euclidean, state-independent)

Implication: Distance between patterns is "frozen" - cannot be adapted based on context.

Correct statement:

"In quadratic $p=2$ systems with Euclidean metric, the geometry of state space is fixed. State-dependent metric deformation could potentially provide adaptive geometry, but this requires moving beyond simple gradient descent or adding structure."

2.3 The Phase Fiber Collapse

Geometric setup:

State space: $M = B \times F$

- B : Base space (amplitudes, spatial patterns)
- F : Fiber space (phases, auxiliary coordinates)

Energy: $E(b, f) \approx E_0(b) + \epsilon \cdot E_1(b, f)$

Dynamics:

$\dot{b} = -\nabla_b E \approx -\nabla_b E_0$ (strong gradient)
 $\dot{f} = -\nabla_f E \approx -\epsilon \cdot \nabla_f E_1$ (weak gradient)

Timescales:

- $\tau_{\text{base}} \sim 1/\|\nabla_b E_0\| = O(1)$
- $\tau_{\text{fiber}} \sim 1/(\epsilon \cdot \|\nabla_f E_1\|) = O(1/\epsilon) \rightarrow \infty$ as $\epsilon \rightarrow 0$

Result: Fiber equilibrates much slower than base

- For $\epsilon \ll 1$: Fiber effectively "frozen" on base timescale
- Information in fiber coordinates not reliably preserved

The "25% Wall":

This refers to experimental observation:

- $K=4$ phase variants $\rightarrow 25\%$ accuracy (chance = 25%)
- $K=2$ phase variants $\rightarrow 50\%$ accuracy (chance = 50%)

Not a universal constant but rather validation that phase discrimination fails in $p=2$ systems.

3. Background: Why $p \geq 3$ Systems Are Unstable

3.1 Exponential Critical Point Growth

Mathematical basis (Kac-Rice formula):

For random Gaussian energy landscape in N dimensions:

$$E[N_{\text{crit}}] = E[\int |\det(\text{Hess } E)| \cdot \delta(\nabla E = 0) dx]$$

For polynomial degree p :

From spin-glass theory and random matrix theory:

$$\begin{aligned} \text{Total critical points: } N_{\text{crit}} &\sim \exp(c_1 \cdot N) \\ \text{Stable minima: } N_{\text{stable}} &\sim c_2 \cdot N^{((p-1)/2)} \end{aligned}$$

Example for $p=3$:

- Critical points: $\sim \exp(0.7N)$
- Stable minima: $\sim N^{(3/2)}$

Consequence: Most critical points are unstable saddles. The landscape becomes a "fractal" with exponentially many directions to escape any given attractor.

Terminology note: "Fractal Storm" is metaphorical. More precisely: "Exponentially complex critical point structure."

3.2 State-Dependent Stability

For $p \geq 3$, Hessian depends on state:

Example (cubic):

$$E = \sum J_{\{ijk\}} x_i x_j x_k$$

$$H_{\{ab\}}(x) = \partial^2 E / \partial x_a \partial x_b = \sum_k J_{\{abk\}} x_k$$

Consequence: Local curvature changes with state x .

At state $\mathbf{x}_1$: $\lambda_{\min}(H(\mathbf{x}_1)) < 0 \rightarrow$ locally convex $\rightarrow$ attractor **At state $\mathbf{x}_2$:** $\lambda_{\min}(H(\mathbf{x}_2)) > 0 \rightarrow$ locally concave $\rightarrow$ repeller

Implication: Attractor structure is **state-dependent**.

Connection to hallucinations:

In language models:

- System enters region where $H(\mathbf{x})$ has wrong sign
- No nearby stable attractor corresponding to valid output
- System "jumps" to spurious attractor (hallucination)

Terminology: "Manifold Ripping" is dramatic. Better: "State-dependent attractor topology" or "dynamical bifurcations."

4. Proposed Solution: Layered Fiber-Bundle Architecture

4.1 Geometric Structure

Total energy:

$$E_{\text{total}}(\mathbf{y}, \boldsymbol{\phi}) = E_{\text{base}}(\mathbf{y}) + \varepsilon \cdot E_{\text{fiber}}(\mathbf{y}, \boldsymbol{\phi})$$

where:

- $\mathbf{y} \in \mathbb{R}^N$: Base coordinates (spatial patterns, amplitudes)
- $\boldsymbol{\phi} \in \mathbb{T}^k$: Fiber coordinates (phases, auxiliary variables)
- $\varepsilon \ll 1$: Coupling strength (control parameter)

Base energy ($p=2$):

$$E_{\text{base}}(\mathbf{y}) = -\frac{1}{2} \mathbf{y}^T \mathbf{A} \mathbf{y} + h(\mathbf{y})$$

- Convex with stable minimum
- Provides "biological anchor"
- Guarantees asymptotic convergence


Fiber energy ($p \geq 3$):

$$E_{\text{fiber}}(\mathbf{y}, \boldsymbol{\phi}) = \sum_{\{ijk\}} J_{\{ijk\}} f_i(\mathbf{y}) f_j(\mathbf{y}) g_k(\boldsymbol{\phi})$$

- Provides expressive coupling

- Enables state-dependent metric
- Controlled by small ε

Geometric picture:



4.2 The Governor Inequality

Statement:

$$\lambda_{\min}(A) > \varepsilon \cdot \rho(H_{\text{fiber}}(x))$$

where:

- $\lambda_{\min}(A)$: Smallest eigenvalue of base Hessian
- $\rho(H_{\text{fiber}})$: Spectral radius of fiber Hessian
- ε : Coupling strength

Interpretation:

This ensures total Hessian remains positive-definite:

$$H_{\text{total}} = H_{\text{base}} + \varepsilon \cdot H_{\text{fiber}}$$

$$\lambda_{\min}(H_{\text{total}}) \geq \lambda_{\min}(A) - \varepsilon \cdot \|H_{\text{fiber}}\|_2$$

If Governor Inequality holds:

$$\lambda_{\min}(H_{\text{total}}) \geq \lambda_{\min}(A) - \varepsilon \cdot \rho(H_{\text{fiber}}) > 0$$

System remains stable (all eigenvalues positive).

Design implication:

Choose ε small enough:

$$\varepsilon < \lambda_{\min}(A) / \max_x \|H_{\text{fiber}}(x)\|_2$$

Trade-off:

- **Large ϵ :** Strong fiber effects but risk instability
- **Small ϵ :** Guaranteed stability but weak expressivity

Open question: Can ϵ be large enough to provide meaningful computational benefit while satisfying the inequality?

Terminology note: "Restorative Gravity" is metaphorical. Technically: "Spectral dominance of base Hessian ensuring positive-definiteness of total Hessian."

4.3 State-Dependent Metric

Proposal:

$$g_{ij}(x) \approx A_{ij} + \epsilon \sum_k J_{ijk} x_k$$

Effect on gradient flow:

$$\dot{x}^i = -g^{ij}(x) \partial E / \partial x^j$$

Geometric interpretation:

Distance element:

$$ds^2 = g_{ij}(x) dx^i dx^j$$

As state x changes, metric $g(x)$ changes $\rightarrow$ effective "distance" between points varies.

The "folding" metaphor:

Two patterns ξ^1, ξ^2 might be:

- Far in Euclidean space: $\|\xi^1 - \xi^2\|_2 = \text{large}$
- Close in Riemannian distance: $d_g(\xi^1, \xi^2) = \text{small}$

If metric "contracts" space between semantically similar patterns:

- Enables faster transitions between related concepts
- Potentially improves compositional generalization
- Creates effective "shortcuts" through state space

The "insight" claim:

Original: "Mathematical derivation of Insight"

Reality: This is a **hypothesis**, not a derivation. To claim this enables "insight" would require:

1. Empirical demonstration on compositional tasks

- 2. Comparison to attention mechanisms
- 3. Validation that metric adapts appropriately
- 4. Evidence of novel generalization capabilities

Current status: Plausible idea requiring validation

Terminology: "Topological Adjacency" is non-standard. Better: "State-dependent metric contraction" or "Adaptive distance geometry."

5. Asymptotic Fiber Collapse

5.1 The Hypothesis

Claim: For safety, higher-order synthesis must be transient.

Proposed mechanism:

As $t \rightarrow \infty$:
Fiber gradients $\rightarrow 0$
System settles to $p=2$ base
Stability guaranteed

Mathematical requirement:

For asymptotic collapse to $p=2$ base:

$$\lim_{t \rightarrow \infty} \phi(t) = \phi_{\text{base}}$$

where ϕ_{base} are attractors of E_{base} alone.

5.2 When Does This Occur?

Scenario 1: Time-dependent coupling

If $\epsilon = \epsilon(t)$ with $\epsilon(t) \rightarrow 0$ as $t \rightarrow \infty$:

$$E_{\text{total}}(t) = E_{\text{base}} + \epsilon(t) \cdot E_{\text{fiber}}$$

System becomes pure $p=2$ asymptotically.

Problem: Requires non-conservative dynamics (time-dependent Hamiltonian).

Scenario 2: Timescale separation

If fiber equilibration much slower than base:

$$\tau_{\text{fiber}} \gg \tau_{\text{base}}$$

For intermediate times: fiber "frozen", base equilibrates
Eventually ($t \rightarrow \infty$): both equilibrate

Problem: Doesn't guarantee collapse unless fiber is truly flat.

Scenario 3: Fiber is asymptotically flat

If $E_{\text{fiber}}(y^*, \phi) \approx \text{constant}$ at base attractors y^* :

$$\nabla_{\phi} E_{\text{fiber}}(y^*, \phi) \approx 0$$

Then fiber has no restorative force at equilibrium.

Problem: This brings us back to the original no-go theorem!

5.3 The Central Tension

For transient expressivity:

- Need ε large enough to create meaningful state-dependent effects
- Need E_{fiber} to have curvature in ϕ directions

For asymptotic collapse:

- Need $\varepsilon \rightarrow 0$ or $\nabla_{\phi} E \rightarrow 0$ eventually
- Need system to settle on $p=2$ base

Unresolved question: Can we have:

1. Strong enough fiber effects to matter (ε not too small)
2. Asymptotic collapse to stable base (safety)
3. Long enough transient phase to perform computation

This requires:

- Precise characterization of timescales
- Quantification of transient computation capacity
- Proof that collapse actually occurs under specified conditions

Status: Core open problem - not proven in this document

5.4 "Thinks in Riemannian, Remembers in Euclidean"

The metaphor:

- **Thinking (short-term):** State-dependent metric, higher-order active
- **Remembering (long-term):** Collapsed to $n=2$ fixed metric

Analogies:

1. Working memory vs. long-term memory (neuroscience)
2. Fast weights vs. slow weights (neural networks)
3. Attention vs. parameters (transformers)

What would make this work:

Mechanism 1: Multi-timescale dynamics

Fast layer: State-dependent, $p \geq 3$ (thinking)
Slow layer: Fixed, $p=2$ (remembering)
Information transfer: Fast $\rightarrow$ slow consolidation

Mechanism 2: Gating

Thinking mode: Higher-order terms active ($\epsilon = \epsilon_0$)
Storage mode: Higher-order suppressed ($\epsilon \rightarrow 0$)
Controlled switching between modes

Mechanism 3: Energy landscape morphing

During reasoning: E_{fiber} creates adaptive landscape
At convergence: Collapse to E_{base} attractors
Transient computation $\rightarrow$ permanent storage

Current status: Conceptual proposal without implementation

6. Critical Assessment

6.1 What This Proposal Actually Provides

✓ Valid contributions:

1. **Clear problem statement:** Dual no-go theorems create genuine challenge
2. **Geometric framework:** Fiber-bundle structure is mathematically sound
3. **Specific constraint:** Governor Inequality is a real stability condition
4. **Testable hypothesis:** Transient expressivity + asymptotic collapse is concrete
5. **Design guidance:** Suggests how to balance stability vs. expressivity

✗ What is NOT established:

1. **No proof this works:** Governor Inequality may be too restrictive
2. **No experimental validation:** Zero tests of proposed architecture
3. **No comparison to alternatives:** Other hybrid approaches not considered
4. **No AGI connection:** Claims about "path to AGI" are unsupported speculation
5. **No collapse proof:** Asymptotic Fiber Collapse stated but not proven

6.2 Overclaiming in Original

Original claims to remove:

✗ "The only viable path to AGI"

- This is **one possible approach** among many

✗ "Closed Theory of AGI"

- This is an **open hypothesis** requiring validation

✗ "Mathematically incapable of uncontrolled hallucination"

- This is **unproven** without experimental testing

✗ "Mathematical derivation of Insight"

- This is a **metaphor**, not a derivation

Honest reframing:

✓ "A proposed approach to combining $p=2$ stability with $p \geq 3$ expressivity"

✓ "Theoretical framework requiring experimental validation"

✓ "Hypothesis that state-dependent metrics could enable adaptive computation"

✓ "Suggests possible design constraints for hybrid architectures"

6.3 Technical Issues

Issue 1: Undefined terms

- "Topological Torsion" → Should be "lack of energy curvature"
- "Manifold Ripping" → Should be "state-dependent bifurcations"
- "Fractal Storm" → Should be "exponential critical point growth"
- "Restorative Gravity" → Should be "spectral dominance"

Issue 2: Imprecise statements

- "All pairwise systems are quadratic" → False, only some are
- "Fisher metric cannot adapt" → Confuses parameter vs. state space metrics

- "25% Wall" → Refers to specific experimental result, not universal law

Issue 3: Missing proofs

- Theorem I: States known results, not new
- Theorem II: Summarizes literature, not new proof
- Asymptotic Collapse Lemma: No proof provided

Issue 4: Unsupported speculation

- Connection to AGI
- Claims about "insight"
- "Closed theory" framing

6.4 Relation to Existing Work

Similar ideas in literature:

1. **Fast/Slow Weights** [Hinton & Plaut 1987; Ba et al. 2016]
 - Fast: Transient, context-dependent
 - Slow: Permanent, stable
 - **Connection:** Fiber = fast, Base = slow
2. **Hierarchical RL** [Sutton et al. 1999]
 - High-level: Slow, stable policies
 - Low-level: Fast, flexible control
 - **Connection:** Multi-level stability
3. **Neural ODEs** [Chen et al. 2018]
 - Continuous dynamics
 - Learnable vector fields
 - **Connection:** State-dependent flow
4. **Attention Mechanisms** [Vaswani et al. 2017]
 - Context-dependent routing
 - Transient connectivity
 - **Connection:** State-dependent metric

What's potentially novel:

- Explicit fiber-bundle geometric framing
- Governor Inequality as design constraint

- Asymptotic collapse as safety mechanism
- Integration with no-go theorem framework

What needs acknowledgment: These ideas build on existing multi-timescale and adaptive architecture concepts.

7. Research Program

If pursuing this direction, here's what's needed:

Phase 1: Theoretical Development (3-6 months)

Task 1.1: Formalize Collapse Mechanism

- Specify dynamics: $\dot{y} = F_y(y, \phi, t)$, $\dot{\phi} = F_\phi(y, \phi, t)$
- Prove: $\lim_{t \rightarrow \infty} \phi(t) \rightarrow \phi_{\text{base}}$ under stated conditions
- Quantify: $T_{\text{transient}} = f(\epsilon, \lambda_{\text{min}}, \dots)$

Task 1.2: Prove Stability Under Governor Inequality

- Show: H_{total} positive-definite when inequality satisfied
- Compute: Basin of attraction size
- Derive: Robustness bounds to perturbations

Task 1.3: Characterize Trade-off

- Define: Expressivity measure E_{metric}
- Define: Stability measure S_{metric}
- Plot: Trade-off curve E vs S as function of ϵ
- Find: Optimal operating point (if exists)

Deliverable: Technical report with complete proofs

Phase 2: Toy Validation (3-6 months)

Task 2.1: Minimal Implementation

- Network: $N=16$ neurons
- Base: $E_{\text{base}} = -\frac{1}{2} y^T A y$
- Fiber: $E_{\text{fiber}} = \sum J_{\{ijk\}} y_i y_j \phi_k$
- Test: Pattern storage and retrieval

Task 2.2: Parameter Sweep

- Vary ϵ from 10^{-3} to 10^{-1}
- Measure: Convergence, stability, capacity
- Verify: Governor Inequality threshold
- Compare: Pure $p=2$, pure $p \geq 3$, hybrid

Task 2.3: Timescale Analysis

- Measure: τ_{base} , τ_{fiber} at different ϵ
- Track: Transient vs asymptotic behavior
- Verify: Collapse mechanism (does it work?)

Deliverable: Jupyter notebook with results

Phase 3: Proof-of-Concept Task (6-9 months)

Task 3.1: Choose Benchmark Options:

- Compositional generalization (SCAN, COGS)
- Associative memory with structured patterns
- Continual learning without catastrophic forgetting

Task 3.2: Full Implementation

- Scale to $N=64-128$
- Implement learning rule for $J_{\{ijk\}}$
- Add noise, test robustness
- Measure: accuracy, stability, efficiency

Task 3.3: Comparison to Baselines

- Pure $p=2$ (Hopfield, CONN)
- Pure $p \geq 3$ (Modern Hopfield, attention)
- Other hybrids (fast weights, mixture of experts)

Deliverable: Conference paper (if results positive)

Phase 4: Real-World Validation (12+ months)

Task 4.1: Scale Up

- Network sizes $N > 1000$
- Realistic tasks (language, vision)

- Training on GPUs
- Benchmark performance

Task 4.2: Architectural Refinements

- Learned $\varepsilon(x)$ (adaptive coupling)
- Hierarchical fiber bundles
- Integration with modern components

Task 4.3: Theoretical Extensions

- Non-conservative dynamics
- Stochastic fiber terms
- Information-theoretic analysis

Deliverable: Journal paper (if breakthrough results)

8. Honest Conclusion

8.1 What We Have

Established (from previous work):

-  No-go theorem for phase-coding in $p=2$ systems
-  Instability issues in $p \geq 3$ systems
-  Capacity-safety trade-off is real

Proposed (this document):

-  Fiber-bundle architecture as possible solution
-  Governor Inequality as design constraint
-  Asymptotic collapse as safety mechanism

8.2 What We Don't Have

Missing:

-  Proof that proposal works
-  Experimental validation
-  Comparison to alternatives
-  Evidence of practical utility
-  Connection to AGI (speculative)

8.3 How to Position This

For GitHub:

markdown

Status: Theoretical Proposal

⚠️ ****This is a research direction, not an established result.****

- Framework is internally consistent
- Addresses real problem (dual no-go theorems)
- Requires substantial experimental validation
- Claims about AGI are speculative
- Treat as hypothesis to be tested

Contributions and critiques welcome!

For discussions:

"Our no-go theorems suggest hybrid architectures may be necessary. This proposes one possible direction using fiber-bundle geometry, but it requires validation before we know if it works."

For publications: Current document is NOT publication-ready. Would need:

- 6-12 months of theoretical development
- 12-18 months of experimental validation
- Honest limitations section
- Comparison to related work
- Removal of overclaims

8.4 Probability Assessment

Realistic outcomes:

- 15% - Works well, becomes important contribution
- 25% - Works partially, inspires refinements
- 40% - Doesn't work, but framework useful
- 20% - Complete failure, interesting idea only

Base rate: Most speculative architectural proposals don't pan out. This is high-risk research.

8.5 Strategic Recommendation

Do:

-  Upload to GitHub as speculative proposal
-  Pursue as long-term research project
-  Start with theoretical proofs
-  Test in toy systems first
-  Be honest about status

Don't:

-  Claim this is "the path to AGI"
 -  Submit for publication without validation
 -  Stake reputation on this working
 -  Oversell to collaborators/funders
 -  Ignore alternative approaches
-

9. References

- [1] Amari, S. I. (2016). Information Geometry and Its Applications. Springer.
- [2] Fyodorov, Y. V. (2004). Complexity of random energy landscapes, glass transition, and absolute value of the spectral determinant of random matrices. Physical Review Letters, 92(24), 240601.
- [3] Hopfield, J. J. (1982). Neural networks and physical systems with emergent collective computational abilities. PNAS, 79(8), 2554-2558.
- [4] Sompolinsky, H., Crisanti, A., & Sommers, H. J. (1988). Chaos in random neural networks. Physical Review Letters, 61(3), 259.
- [5] Amit, D. J. (1989). Modeling brain function: The world of attractor neural networks. Cambridge University Press.
- [6] Ba, J., Hinton, G. E., Mnih, V., Leibo, J. Z., & Ionescu, C. (2016). Using fast weights to attend to the recent past. NeurIPS.
- [7] Chen, R. T., Rubanova, Y., Bettencourt, J., & Duvenaud, D. K. (2018). Neural ordinary differential equations. NeurIPS.
- [8] Vaswani, A., et al. (2017). Attention is all you need. NeurIPS.
- [9] Marku, L. (2026). No-Go Theorem for Phase-Coded Associative Memory. GitHub repository.
- [10] Marku, L. (2026). Geometry, Topology, and Universality Boundaries in Associative Memory Networks. GitHub repository.
-

Appendix: Mathematical Notation

Appendix: Mathematical Notation

Symbol	Meaning
p	Interaction order (2=pairwise, ≥ 3 =higher-order)
N	Network size (number of neurons)
M	Capacity (number of storable patterns)
y	Base coordinates (amplitudes, spatial patterns)
ϕ	Fiber coordinates (phases, auxiliary variables)
ϵ	Coupling strength (control parameter)
E_{base}	Base energy ($p=2$, stable)
E_{fiber}	Fiber energy ($p\geq 3$, expressive)
A	Base Hessian matrix
$\lambda_{\min}(A)$	Smallest eigenvalue of A
$\rho(H)$	Spectral radius of Hessian H
$g_{\{ij\}}(x)$	Riemannian metric tensor
τ	Characteristic timescale

Last Updated: January 2, 2026
Version: 1.0.0 (Speculative Proposal)
Status: Theoretical Framework - Requires Validation

Author's Note

This document represents my attempt to find a constructive solution to the dual no-go theorems. The mathematical framework is consistent and addresses a real problem, but I want to be completely transparent: **I don't know if this actually works**. It's a hypothesis that needs testing.

The strong language in earlier drafts ("only path to AGI", "closed theory") was aspirational but not justified. This revision aims for intellectual honesty while preserving the core ideas.

If you're interested in pursuing this direction, I welcome collaboration and critique. If the experiments fail, that's also a valuable result - it would help clarify the boundaries of what's possible.