

Description			Unit Price(Rs)	QTY	Total Price(Rs)
Capacity : 400 L Cycle mode : Forced convection Illuminating sides : 4 sides Illumination (6 degrees) : 0 LX to 22000 LX Temperature range (with illumination) : 10 °C to 65 °C Temperature range (without illumination) : 0 °C to 65 °C Temperature motion : ± 1 °C Temperature uniformity : ± 2 °C Temperature resolution ratio : 0.1 °C Ambient temperature : 5 °C to 35 °C Humidity range : 40 % to 90 % RH Humidity stability : ± 7 % RH Humidity error : ± 5 % to ± 7 % Humidity controller : Automatic Display panel : LCD Operation time : 0 to 9999 mins System timer (with halt function) : 0 to 99.9 h x 30 Sensor : Pt100 Coolant : R134a Compressor : Air cooled hermetic compressor Defrosting control : Automatic Shelves : 2 Shelf height : Adjustable Voltage : 200 to 240 V / 100 to 120 V Power supply : 1200 W Heating tube material : Stainless steel Insulation material : Polyurethane Interior material : SUS 304 Mirror stainless steel Exterior material : Cold rolled steel with electrostatic spraying Interior dimensions (W x D x H) : 590 x 620 x 1100 mm Exterior dimensions (W x H x D) : 780 x 795 x 1800 mm Weight : 15 kgs					
Accessory No	Accessory	Units			
1)	RS485 interface	1			
2)	Shelves	7			
3)	Printer	1			
4)	Recorder	1			
5)	External communication	1			
6)	Remote control	1			
7)	Wireless SMS alarm	1			
8)	USB data storage	1			
9)	Inflatable port	1			
Price					1,324.00
Packing, Forwarding & Shipping Charges					0.00
Bank Charges					30.00

Description	Unit Price(Rs)	QTY	Total Price(Rs)
GRAND TOTAL(Rs)			1,354.00

21

Terms and Conditions

t%CCC