





DỰ ÁN MẪU (TKTW)

BÀI 3: THỰC HIỆN DỰ ÁN 1 3.4. XÂY DỰNG DAO CHO BẢNG LOẠI

www.poly.edu.vn





- On lại kiến thức lập trình PDO
- Xây dựng thư viện tiện ích PDO
- Lập trình CSDL theo mô hình DAO
- Xây dựng DAO làm việc với loại
- Xây dựng DAO cho các bảng khác





```
<?php
   require_once 'pdo.php';
   function loai_insert(){...}
   function loai_update(){...}
   function loai_delete(){...}
   function loai_select_all(){...}
   function loai_select_by_id(){...}
   function loai_exist(){...}
```



```
function loai_insert($ten loai){
  $sql = "INSERT INTO loai(ten_loai) VALUES(?)";
  pdo_execute($sql, $ten_loai);
function loai_update($ma_loai, $ten_loai){
  $sql = "UPDATE loai SET ten_loai=? WHERE ma_loai=?";
  pdo_execute($sql, $ten_loai, $ma_loai);
```



```
function loai_delete($ma_loai){
  $sql = "DELETE FROM loai WHERE ma_loai=?";
  if(is_array($ma_loai)){
    foreach ($ma_loai as $ma) {
       pdo_execute($sql, $ma);
  else{
    pdo_execute($sql, $ma_loai);
```



```
function loai select all(){
  $sql = "SELECT * FROM loai";
  return pdo_query($sql);
function loai_select_by_id($ma_loai){
  $sql = "SELECT * FROM loai WHERE ma_loai=?";
  return pdo_query_one($sql, $ma_loai);
function loai_exist($ma_loai){
  $sql = "SELECT count(*) FROM loai WHERE ma_loai=?";
  return pdo_query_value($sql, $ma_loai) > 0;
```





```
require "../../dao/loai.php";
extract($_REQUEST);
if(exist_param("btn_insert")){
   loai_insert($ten_loai);
else if(exist_param("btn_update")){
   loai_update($ma_loai, $ten_loai);
else if(exist_param("btn_delete")){
   loai_delete($ma_loai);
else if(exist_param("btn_edit")){
  $item = loai_select_by_id($ma_loai);
else if(exist_param("btn_list")){
  $items = loai_select_all();
```



Demo 3.4. Xây dựng DAO cho loại