



Title

rdrobustplot — Diagnostic plot for a previous **rdrobust** result.

Syntax

```
rdrobustplot [, nbins(# #) binselect(binmethod) noci shade scale(# #)
title(string) xtitle(string) ytitle(string) col_dots(color) col_lines(color)
graph_options ]
```

Description

rdrobustplot produces a diagnostic RD plot for the results of the most recent **rdrobust** call. It wraps **rdplot** with the main bandwidth and polynomial order that **rdrobust** used, and decorates the subtitle with the estimated RD coefficient and its robust bias-corrected confidence interval.

This mirrors the **plot.rdrobust()** S3 method in the R package and the **plot_rdrobust()** function in the Python package.

Requires Stata 16 or later.

Options

nbins(# #) number of bins per side; default is 20 20.

binselect(*binmethod*) bin selection rule; default is **esmv** (mimicking-variance evenly-spaced bins). See **rdplot**.

noci suppresses the per-bin confidence intervals.

shade draws the pointwise confidence bands as a shaded ribbon instead of error bars.

title(), **xtitle()**, **ytitle()** custom text for the plot elements (defaults follow **rdrobust**'s outcome / running variable).

col_dots(), **col_lines()** colors for the binned means and the polynomial fit line.

Any other option is passed through to **rdplot**'s **graph_options()**.

Examples

```
sysuse rdrobust_senate, clear
rdrobust vote margin
rdrobustplot
```

With cluster-robust variance and fuzzy RD:

```
rdrobust vote margin, vce(cr3 state)
rdrobustplot, shade
```

Authors

Sebastian Calonico, University of California, Davis. scalonico@ucdavis.edu.
 Matias D. Cattaneo, Princeton University. matias.d.cattaneo@gmail.com.
 Max H. Farrell, University of California, Santa Barbara. mhfarrell@gmail.com.
 Rocio Titiunik, Princeton University. rocio.titiunik@gmail.com.