

Universidad de Oviedo


Trabajo de investigación

Plaza F036-570-DFA0340

Área de Lenguajes y Sistemas Informáticos

Departamento de Informática


Jose Emilio Labra Gayo



Índice general

1	Introducción	5
2	Contexto del trabajo de investigación	7
2.1	Justificación de la temática	7
2.2	Formato del trabajo de investigación	8
3	Resumen trabajo de investigación	9
3.1	Abstract	9
3.2	Introduction	10
3.3	Preliminaries	12
3.4	Knowledge graphs models	13
3.4.1	RDF based knowledge graphs	13
3.4.2	Property graphs	16
3.4.3	Wikibase graphs	18
3.5	Describing Knowledge Graphs	22
3.5.1	Describing and validating RDF	22
3.5.2	Describing and validating Property graphs	25
3.5.3	Describing and validating Wikibase graphs	28
3.6	Knowledge Graphs Subsets	30
3.6.1	Wikibase Subsets: Formal definition	31
3.6.2	Entity-generated subsets	31
3.6.3	Simple Matching-generated subsets	33
3.6.4	ShEx-based Matching generated subsets	34
3.6.5	ShEx + Slurp generated subsets	35
3.6.6	ShEx + Pregel generated subsets	37


3.7	Implementations and preliminary results	45
3.8	Related work	47
3.9	Conclusions	49
3.10	Acknowledgments	49
4	Contribuciones y trabajo futuro	59
4.1	Contribuciones y resultados conseguidos	59
4.2	Líneas futuras de investigación	60
4.3	Conclusiones	61
	Index	63



Universidad de Oviedo

1. Introducción

Este documento contiene el trabajo de investigación realizado por el candidato Jose Emilio Labra Gayo para la plaza de Catedrático de Universidad número 16, convocada por la Universidad de Oviedo en la Resolución de 25 de Junio de 2021, (BOE de 9 de Julio de 2021), con el código F036-570-DFA0340 del Cuerpo de *Catedrático de Universidad*, para el área de conocimiento *Lenguajes y Sistemas Informáticos*.



2. Contexto del trabajo de investigación

El presente trabajo de investigación se enmarca dentro de la línea de investigación llevada a cabo por el candidato en los últimos años dentro del grupo de investigación WESO.

2.1 Justificación de la temática

Se ha escogido como temática para el trabajo de investigación la creación de subconjuntos de grafos de conocimiento mediante Shape Expressions por varios motivos:

- La implicación del candidato en la creación del lenguaje Shape Expressions y sus diferentes aplicaciones. Mediante el presente trabajo se ahonda en una nueva aplicación de Shape Expressions como lenguaje para describir y extraer subconjuntos de Wikidata.
- Puede resolver un problema práctico real que consiste en poder consumir datos de grandes grafos de conocimiento. Actualmente, Wikidata podría decirse que corre el peligro de morir de éxito al aumentar continuamente la cantidad de datos que almacena. Esta gran cantidad de información ofrece una herramienta muy potente, pero tiene el problema de que es difícil para un usuario convencional poder consumir estos datos. La posible existencia de un sistema que permita crear una instantánea de los datos existentes en Wikidata en un determinado dominio y extraerlos de forma fácil para poder integrarlos con otras aplicaciones se ha convertido en una gran demanda por la comunidad de usuarios.
- La participación del candidato como coordinador en varios eventos cuya temática era la creación de subconjuntos de grafos de conocimiento. En concreto:
 - Hackathon virtual asociado al congreso SWAT4(HC)LS 2020 que se celebra en Enero de 2021 y en el que se continúa trabajando en la creación de técnicas de creación y gestión de subconjuntos de Wikidata¹.
 - Biohackathon Europe, 2020. Evento que se celebró de forma virtual y que fue liderado por el candidato. La actividad realizada durante el evento dará lugar a las publicaciones [32, 40]. En dicho evento se identifican varios casos de uso como el proyecto GeneWiki o Scholia, y se consigue generar subconjuntos de Wikidata mediante WDum-

¹https://swat4hcls.wiki.opencura.com/wiki/Main_Page

per y la técnica ShEx+Slurping.

- En el Biohackathon realizado en Fukuoka, Japón, se entra en contacto con Leyla Garcia y Egon Willighagen, entre otros, participando en la presentación de diversas aplicaciones de Shape Expressions. Algunas de las tareas llevadas a cabo en dicho Biohackathon se publicaron en [10]
- En el hackathon SWAT4(HC)LS de 2019 se comienza a plantear la posibilidad de desarrollar herramientas para la creación de subconjuntos de Wikidata.
- El creciente interés en la utilización de grafos de conocimiento, especialmente Wikidata y la involucración del candidato en la comunidad de Wikidata, participando en varios eventos como la Conferencia de Wikidata (WikidataCon) de 2019 y el Wikimedia Hackathon de Praga de 2019. La adopción por parte de Wikidata de esquemas de entidades basados en el lenguaje ShEx suponen la creación de numerosos esquemas para diferentes dominios² que podrán utilizarse para la generación de subconjuntos.
- La subcontratación durante el verano de 2021 del equipo WESO por parte de la Universidad de Virginia para la realización de un prototipo que mejorase el proyecto Scholia, que incluía como tarea la utilización de subconjuntos de Wikidata en el ámbito de Scholia
- Ha sido motivo de interés de Andra Waagmeester y el proyecto GeneWiki [9] la necesidad de creación de subconjuntos relacionados con la información existente en Wikidata sobre enfermedades, tratamientos, medicinas, genes, etc. De hecho, actualmente ya se está colaborando con los miembros de dicho equipo en el análisis y gestión de los primeros subconjuntos de datos generados.
- La concesión del proyecto ANGLIRU en la convocatoria Retos del Plan Nacional de Investigación, que incluye precisamente, como uno de los entregables, la creación de herramientas para la generación de subconjuntos de grafos de conocimiento.
- Puede suponer un avance en la disciplina, dado que se intenta resolver uno de los problemas existentes hoy en día en la Web Semántica, que es mejorar el consumo de datos semánticos, que se espera que redunde en un mayor uso de estas técnicas y a la postre, permita mejorar el acceso al conocimiento.

Los motivos anteriores han servido de aliciente al candidato para involucrarse en los últimos meses en la temática del trabajo de investigación, lo cual ha consistido en realizar el trabajo teórico plasmado en el artículo que se presenta e implementar prototipos de los algoritmos en las librerías WDSUB y SparkWDSUB usando el lenguaje Scala.

2.2 Formato del trabajo de investigación

En el Reglamento para los concursos de acceso a los cuerpos de funcionarios docentes universitarios de la Universidad de Oviedo, aprobado por el Consejo de Gobierno de 18 de diciembre de 2008 (Boletín Oficial del Principado de Asturias de 14 de enero de 2009) se indica que para la segunda prueba del concurso, el candidato debe presentar un resumen de su trabajo de investigación, sin especificar el formato ni el idioma del mismo.


Se ha considerado conveniente presentar el trabajo de investigación con la estructura de un artículo científico extendido y se ha publicado como un *preprint* en el repositorio Arxiv³.

Una vez finalizado el concurso, será enviado para su posible publicación a un congreso o revista de investigación que todavía no ha sido seleccionado.

Por ese motivo, el artículo se presenta en idioma inglés dado que en la convocatoria no se hace mención explícita a requisitos de idioma.

²https://www.wikidata.org/wiki/Wikidata:Database_reports/EntitySchema_directory

³<https://arxiv.org/>



Universidad de Oviedo

3. Resumen trabajo de investigación

Creating Knowledge Graph Subsets using Shape Expressions

Jose Emilio Labra Gayo

3.1 Abstract

The initial adoption of knowledge graphs by Google and later by big companies has increased their adoption and popularity. In this paper we present a formal model for three different types of knowledge graphs which we call RDF-based graphs, property graphs and wikibase graphs.

In order to increase the quality of Knowledge Graphs, several approaches have appeared to describe and validate their contents. Shape Expressions (ShEx) has been proposed as concise language for RDF validation. We give a brief introduction to ShEx and present two extensions that can also be used to describe and validate property graphs (PShEx) and wikibase graphs (WShEx).

One problem of knowledge graphs is the large amount of data they contain, which jeopardizes their practical application. In order to palliate this problem, one approach is to create subsets of those knowledge graphs for some domains. We propose the following approaches to generate those subsets: Entity-matching, simple matching, ShEx matching, ShEx plus Slurp and ShEx plus Pregel which are based on declaratively defining the subsets by either matching some content or by Shape Expressions. The last approach is based on a novel validation algorithm for ShEx based on the Pregel algorithm that can handle big data graphs and has been implemented on Apache Spark GraphX.

3.2 Introduction

The concept of Knowledge Graphs was popularized by Google in 2012 [72] as a tool that collects information about real world entities and makes relationships between them with the goal of improving search results, understand relationships better and make unexpected discoveries. Since then, there has been a tremendous interest and adoption about Knowledge Graphs, with open, general purpose ones as well as closed, proprietary ones like those employed by some big companies. In the former case we can mention DBpedia [4], YAGO [74] or Wikidata [78]. In the latter, some example companies that have announced their use are Airbnb [12], Amazon [36], eBay [62], Facebook [57], IBM [17], LinkedIn [28], Microsoft [71], etc.

There are different models associated with Knowledge Graphs like RDF-based graphs, property graphs and wikibase graphs:

- RDF-based graphs is one of the most well-known data models given that RDF was proposed as a W3C recommendation already in 1999 [58] and a large ecosystem of tools have been created around it. An important aspect of RDF is the use of URIs, which facilitates interoperability and was the basis semantic web and linked data. Around RDF, a whole ecosystem of technologies have appeared, like the SPARQL query language and protocol [27], which enables the creation of public endpoints.
- Graph databases like Neo4j [54] have also been employed to represent knowledge graphs. They have a data model which allows to annotate both nodes and edges with pairs of property-values which has become to be known as property graphs [66].
- Wikidata started in 2012 as a support project for Wikipedia but has been evolving and acquiring more and more importance as a hub of public knowledge. The data model employed by Wikidata combined several aspects from RDF following linked data principles and from property graphs, allowing the annotation of statements by property-values using qualifiers and references. The software suite that implements Wikidata is known as Wikibase and can be used to represent other knowledge graphs with the same data model, we will refer to these kind of knowledge graphs as wikibase graphs. Wikidata also offers an RDF serialization format which can be accessed through a public SPARQL endpoint.

One of the key factors of knowledge graph models is their flexibility which enables easy addition of content. This flexibility also comes with a price for the applications and users that want to consume the data, which are required to use defensive programming techniques to handle lack of some mandatory properties, errors in values, duplicates, etc. It is also difficult for the producers who want to add data. Although they usually have some schema (explicit or implicit) about that represents the structure of the data, it is also difficult to document that the added data conforms to that schema.

In the case of RDF graphs, Shape Expressions (ShEx) were developed in 2014 to describe and validate the topology of RDF graphs [63]. Afterwards, ShEx was adopted in 2019 by Wikidata to describe the RDF serialization of Wikidata content in a new namespace called entity schemas¹.

The success of Knowledge Graphs has implied that the size of their contents also increases dramatically. As an example, the size of compressed Wikidata dumps has been almost doubling every year, from 3.3Gb (31,3Gb uncompressed) in 2014 to 70.5Gb (1.256Gb uncompressed) in 2021 (see figure 3.1). A consequence of these huge sizes is that it is not possible to easily process all the amount of available data by conventional tools, preventing the consumers to analyze and process the content and threatens these technologies to be victims of their own success.

An example of this situation happens in Scholia [56] a web application that leverages on Wikidata to represent information about scholars and their works. The application also contains nice visualizations and comparisons which are based on queries over Wikidata endpoint. Although

¹<https://www.wikidata.org/wiki/Wikidata:Schemas>




Figure 3.1: Size compressed wikidata Json Dumps between 2014-2021. Source: <http://archive.org>

the project provides a lot of interesting information, the more complex visualizations are not possible to obtain because the huge amounts of data generate timeouts.

In order to address these issues, a possible approach is to create subsets of the Knowledge Graphs for some domains. These subsets can capture snapshots of the content at some specific moment and be used to improve the performance of the applications that consume that data, facilitating research work over Knowledge Graphs contents.

In this paper we review different approaches to generate knowledge graphs subsets. Given that the first step to create a subset is to describe the intended content, ShEx seems a natural choice to be used for those descriptions. In this way, some approaches are based on ShEx schemas which describe the intended content of the subsets. To that end, we define two extensions of ShEx: PShEx to describe property graphs and WShEx to describe wikibase graphs.

We define the following approaches to generate subsets for Wikibase graphs which could also be applied to RDF graphs and property graphs:

- *Entity-matching* defines a subset by identifying some target entities. The subset contains information related with those entities and their neighborhood.
- *Simple-matching* defines a subset by a set of matching patterns, for example, the triples that have a given property, that satisfy some condition, etc.
- *ShEx-based matching* uses ShEx shapes without taking into account shape references to check which nodes conform to them. This approach only requires to take into account the neighborhood of a node and can be used to sequentially process the dumps without requiring graph traversal.
- *ShEx+Slurp* consists on validating the graph contents using ShEx and collect the nodes and triples that are being visited during the validation. This approach can refine the obtained subsets but requires graph traversal, which can be difficult when sequentially processing the dumps. If it is used against an endpoint, it can exceed the limit of allowed requests by client.
- *ShEx+Pregel* proposes to validate the graph using an adaptation of the Pregel algorithm [43] for ShEx validation. This approach can process and validate big knowledge graphs. It has the advantage of scalability and in principle, it can handle graph traversal, but it also consumes a large amount of resources.

The main contributions of this paper are:

- We created a formal model for Wikibase graphs which can be compared with the formal model of RDF-graphs and property graphs.
- We created two extensions of ShEx: PShEx for property graphs and WShEx for wikibase

graphs.

- We identify and formally describe five approaches to generate knowledge graphs subsets. Some of them, like *Simple matching* and *ShEx+Slurp* had already been implemented but were not formally described.
- We describe and implement an algorithm for large scale validation of knowledge graphs based on Pregel.

The structure of the paper is as follows: Section 3.3 presents some preliminary definitions about sets and graphs. Section 3.4 introduces knowledge graphs and presents 3 main types of knowledge graphs: RDF-based, Property graphs and Wikibase graphs. Section 3.5 presents techniques to describe knowledge graphs: ShEx for RDF graphs, PShEx for property graphs and WShEx for wikibase graphs. For each of them, we define the abstract syntax and the semantics using inference rules. Section 3.6 presents the problem of creating subsets of knowledge graphs and describes several approaches to create subsets of wikibase graphs. Finally, section 3.8 reviews the related work and section 3.9 presents some conclusions. Along the paper we use a running example based on information about Tim Berners-Lee whose information was obtained from Wikidata (entity Q80).

3.3 Preliminaries

In this section, we provide some basic definitions that we will use in the rest of the paper.

Sets

. The finite set with elements a_1, \dots, a_n is written $\{a_1, \dots, a_n\}$, \emptyset represents the empty set, $S_1 \cup S_2$ is the union of sets S_1 and S_2 , $S_1 \cap S_2$ the intersection and $S_1 \times S_2$ the Cartesian product. $\text{FinSet}(S)$ represents the set of all finite subsets of S . A tuple $\langle A_1, \dots, A_n \rangle$ is the cartesian product $A_1 \times \dots \times A_n$.

Given a set S , its set of partitions is defined as $\text{part}(s) = \{(s_1, s_2) \mid s_1 \cup s_2 = s \wedge s_1 \cap s_2 = \emptyset\}$.

Definition 3.3.1 — Graph. A *graph* is a tuple $G = \langle \mathcal{V}, \mathcal{E} \rangle$, where \mathcal{V} is a set of nodes, and $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{E} \times \mathcal{V}$ is a set of edges.

A multigraph is a graph where it is possible to have more than one edge between the same two nodes.

Definition 3.3.2 — Directed edge-labelled graph. A *directed edge-labelled graph* is a tuple $\mathcal{G} = \langle \mathcal{V}, \mathcal{E}, \mathcal{P} \rangle$, where \mathcal{V} is a set of nodes, \mathcal{P} is a set of labels also called predicates or properties, and $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{L} \times \mathcal{V}$ is a set of edges. Each element $(x, p, y) \in \mathcal{E}$ is called a triple, where x is the subject, p is the predicate or property and y is the object.

Definition 3.3.3 — Triple-based graphs. A *triple-based graphs* is a directed edge-labelled graph $\mathcal{G} = \langle \mathcal{S}, \mathcal{P}, \mathcal{O}, \rho \rangle$ where \mathcal{S} is a set of subjects, \mathcal{P} is a set of predicates or properties and \mathcal{O} is a set of objects or values, and $\rho \subseteq \mathcal{S} \times \mathcal{P} \times \mathcal{O}$. Those sets don't need to be disjoint, and usually $\mathcal{P} \subseteq \mathcal{S} \subseteq \mathcal{O}$.

Definition 3.3.4 — Hypergraph. A *hypergraph* is a tuple $G = \langle \mathcal{V}, \mathcal{E} \rangle$ where \mathcal{V} is a set of nodes and $\mathcal{E} \subseteq \text{FinSet}(\mathcal{V})$ is a set of edges. Notice that \mathcal{E} is a family of subsets of vertices.

Definition 3.3.5 — Bag (73). Given a set of symbols Δ , a *bag* w (also called *multiset*) can be seen as a set whose elements can be repeated and it is defined as a function $w : \Delta \mapsto \mathbb{N}$ that maps a symbol to the number of its occurrences. The set of all bags over Δ is denoted as $\text{Bag}[\Delta]$. The empty bag ϵ has 0 occurrences for every symbol $a \in \Delta$. A bag is usually represented as $\{[0]a \dots$ with elements that can be repeated. The union of two bags w_1 and w_2 is defined as

$w_1 \uplus w_2(a) = w_1(a) + w_2(a)$. A set of bags is a *bag language*. The bag union of two languages L_1 and L_2 is defined as $L_1 \uplus L_2 = \{w_1 \uplus w_2 \mid w_1 \in L_1, w_2 \in L_2\}$.

Definition 3.3.6 — Regular bag expression (73). A *regular bag expression* over a set of symbols Δ is defined by the following grammar: $E ::= \varepsilon \mid a \mid E \mid E; E \mid E^*$, where $a \in \Delta$.

A regular bag expression e defines a bag language $\llbracket e \rrbracket$ whose semantics is: $\llbracket \varepsilon \rrbracket = \{\epsilon\}$, $\llbracket a \rrbracket = \{\{0\}a\}$, $\llbracket e_1 \mid e_2 \rrbracket = \llbracket e_1 \rrbracket \cup \llbracket e_2 \rrbracket$, $\llbracket e_1; e_2 \rrbracket = \llbracket e_1 \rrbracket \uplus \llbracket e_2 \rrbracket$, $\llbracket e^* \rrbracket = \bigcup_{i \geq 0} \llbracket e \rrbracket^i$. A bag b matches a regular bag expression e , denoted as $b \cong e$ if $b \in \llbracket e \rrbracket$.

Definition 3.3.7 — Shape assignment. Given a graph \mathcal{G} with vertex set \mathcal{V} and a finite set of labels \mathcal{L} , a *shape assignment* over \mathcal{G} and \mathcal{L} is a subset of $\mathcal{V} \times \mathcal{L}$. We use τ to denote shape assignments, and we write $n@l$ instead of (n, l) for elements of shape assignments. Note that shape assignments correspond to shape maps in [64] and typings in [6, 73].

3.4 Knowledge graphs models

Although the term *knowledge graphs* was already in use in the 1970s [67], the current notion of knowledge graphs was popularized by Google in 2012 [72]. We adopt an informal definition of knowledge graphs which has been inspired by Hogan et al [31]:

Definition 3.4.1 — Knowledge graph. A *Knowledge graph* is graph of data intended to represent knowledge of some real world domain, whose nodes represent entities of interest and whose edges represent relations between these entities.

The previous definition is deliberately open. The main feature of a knowledge graph is that it is intended to represent information about entities of some real world domain using a graph-based data structure.

Knowledge graphs are usually classified by:

- **Licence/proprietor:** There are public and open knowledge graphs like Yago [74], DBpedia [41] or Wikidata [78] as well as enterprise-based and proprietary knowledge graphs [57] like Google, Amazon, etc.
- **Scope:** there are general-purpose knowledge graphs which contain information about almost all domains like Wikidata as well as domain specific knowledge graphs which contain information from some specific domains like healthcare, education, chemistry, biology, cybersecurity, etc. [1]

Knowledge graphs can be represented using multiple technologies and in fact, the information about how Google's knowledge graph is implemented is not public. Nevertheless, in this paper, we will focus on three main technologies:

- **RDF based knowledge graphs** represent information using directed graphs whose edges are labels.
- **Property graphs** allow property–value pairs and a label to be associated with nodes and edges. Property graphs have been implemented by several popular graph databases like Neo4j [3].
- **Attributed graphs** allow property-value pairs associated with edges to add meta-data about the relationship represented by the edge and the values of those properties can themselves be nodes in the graph. The main example in this category is Wikidata where property-value pairs encode qualifiers and references.

3.4.1 RDF based knowledge graphs

Resource Description Framework (RDF) [15], is a W3C recommendation which is based on directed edge-labelled graphs.




Figure 3.2: Example graph representation of RDF data

The RDF data model defines different types of nodes, including *Internationalized Resource Identifiers (IRIs)* [18] which can be used to globally identify entities on the Web; literals, which allow for representing strings (with or without language tags) and values from other datatypes (integers, decimals, dates, etc.); and *blank nodes*. Blank nodes can be considered as existential variables that denote the existence of some resource for which an IRI or literal is not known or provided. They are locally scoped to the file or RDF store, and are not persistent or have portable identifiers [30].

Definition 3.4.2 — RDF Graph. Given a set of IRIs \mathcal{I} , a set of blank nodes \mathcal{B} and a set of literals \mathcal{Lit} , an *RDF graph* is a triple based graph $\mathcal{G} = \langle \mathcal{S}, \mathcal{P}, \mathcal{O}, \rho \rangle$ where $\mathcal{S} = \mathcal{I} \cup \mathcal{B}$, $\mathcal{P} = \mathcal{I}$, $\mathcal{O} = \mathcal{I} \cup \mathcal{B} \cup \mathcal{Lit}$ and $\rho \subseteq \mathcal{S} \times \mathcal{P} \times \mathcal{O}$

There are several syntaxes for RDF graphs like Turtle, N3, RDF/XML, etc. In this document, we will use Turtle.

■ **Example 3.1** As a running example, we will represent information about Tim Berners-Lee declaring that he was born in London, on 1955, and was employed by CERN and London's country is UK. That information can be encoded in Turtle as:

```

prefix :      <http://example.org/>
prefix xsd:   <http://www.w3.org/2001/XMLSchema#>

:timbl      :birthPlace      :London ;
            :birthDate       "1955-08-06"^^xsd:date ;
            :employer        :CERN .
:London     :country         :UK .
  
```

Figure 3.2 shows a possible visualization of that RDF graph using RDFShape, a tool developed by the authors of this paper which allows to play with RDF graphs² [37]:

■

The neighbors of a node $n \in \mathcal{V}$ in an RDF graph \mathcal{G} are defined as $\text{neighs}(n, \mathcal{G}) = \{(n, p, y) \mid (n, p, y) \in \mathcal{G}\}$.

RDF can be considered the basic element of the semantic web technology stack, forming a simple knowledge representation language on top of which several technologies have been developed like SPARQL for querying RDF data as well as RDFS and OWL to describe vocabularies and ontologies.

²It is possible to interactively play with the example following this permalink: <https://rdfshape.weso.es/link/16344135752>

RDF reification and RDF-*

An important aspect of RDF as a knowledge representation formalism is to be able to represent information about RDF triples themselves, which is called reification. In this section we will present some of the possible approaches for reification using a simple example to help understand the approach used by Wikibase to serialize its data model to RDF [29]. We also present the RDF-* approach which has become popular in the RDF-ecosystem with its support by several RDF stores like GraphDB ³.

■ **Example 3.2** As an example, we may want to qualify the statement that Tim Berners-Lee was employed by CERN, declaring that he was employed at two different points in time: in 1980 and between 1984 and 1994.

The following approaches have been proposed for RDF reification:

- Standard RDF reification was introduced in RDF 1.0 [46]. It consists of using the predicates `rdf:subject`, `rdf:predicate` and `rdf:object` as well as the class `rdf:Statement` to explicitly declare statements.

```
_:s1 rdf:type      rdf:Statement ;
    rdf:subject    :timbl ;
    rdf:predicate   :employer ;
    rdf:object      :CERN ;
    :start          "1980"^^xsd:gYear ;
    :end            "1980"^^xsd:gYear .

_:s2 rdf:type      rdf:Statement ;
    rdf:subject    :timbl ;
    rdf:predicate   :employer ;
    rdf:object      :CERN ;
    :start          "1984"^^xsd:gYear ;
    :end            "1994"^^xsd:gYear .
```

- Create a statement that models the n-ary relation [20]. For example, we can create two nodes `:s1` and `:s2` to represent the the 2 employments of Tim-Berners-Lee at CERN.

```
:timbl :employer :s1, :s2.
:s1 :employerV :CERN;
   :start      "1980"^^xsd:gYear ;
   :end        "1980"^^xsd:gYear .
:s2 :employerV :CERN;
   :start      "1984"^^xsd:gYear ;
   :end        "1994"^^xsd:gYear .
```

- Create *singleton properties* for each statement and link those properties with a specific predicate to the real property [55].

```
:timbl :employer1 :CERN ;
       :employer2 :CERN .

:employer1 :singletonPropertyOf :employer ;
  :start   "1980"^^xsd:date ;
  :end     "1980"^^xsd:date .

:employer2 :singletonPropertyOf :employer ;
  :start   "1984"^^xsd:date ;
  :end     "1994"^^xsd:date .
```

³<https://www.ontotext.com/knowledgehub/fundamentals/what-is-rdf-star/>

- RDF1.1 [15] included the concept of named graphs, which can be used to associate each triple with a different graph.

```
:g1 :timbl      :employer :CERN .
:g1 :employed :start    "1980"^^xsd:date .
:g1 :employed :end      "1980"^^xsd:date .
:g2 :timbl      :employer :CERN .
:g2 :employed :start    "1984"^^xsd:date .
:g2 :employed :end      "1994"^^xsd:date .
```

- RDF-* [16] has been recently introduced as an extension of RDF that includes RDF graphs as either the subjects or objects of a statement.

```
<<:timbl :employer :CERN>> :start "1980"^^xsd:gYear ;
                             :end   "1980"^^xsd:gYear .
<<:timbl :employer :CERN>> :start "1984"^^xsd:gYear ;
                             :end   "1994"^^xsd:gYear .
```

- Wikidata's RDF serialization follows a hybrid approach using a direct link to capture the preferred value and singleton nodes that represent the statements capturing the n-ary relationship [20]. It also follows a convention that employs the same local name of the property preceded by different namespaces: wdt: for the direct link, p for the link between the node and the singleton statements, ps: for the link between the singleton statements and the values, and pq: for the link between the singleton statements and the qualified values. The previous example using Wikidata RDF serialization could be ⁴:

```
:timbl wdt:employer :CERN .
:timbl p:employer :s1 .
:timbl p:employer :s2 .
:s1    ps:employer :CERN ;
      pq:start "1980"^^xsd:gYear ;
      pq:end   "1980"^^xsd:gYear .
:s2    ps:employer :CERN ;
      pq:start "1984"^^xsd:gYear ;
      pq:end   "1994"^^xsd:gYear .
```

■

3.4.2 Property graphs

Property graphs have become popular thanks to several commercial graph databases like Neo4j⁵, JanusGraph⁶ or Sparksee⁷. A property graph has unique identifiers for each node/edge and allows to add property-value annotations to each node/edge in the arc as well as type annotations.

The following definition of a property graph follows [69].

Definition 3.4.3 — Property graph. Given a set of types \mathcal{T} , a set of properties \mathcal{P} , and a set of values \mathcal{V} , a *property graph* \mathcal{G} is a tuple $\langle \mathcal{N}, \mathcal{E}, \rho, \lambda_n, \lambda_e, \sigma \rangle$ where $\mathcal{N} \cap \mathcal{E} = \emptyset$, $\rho: \mathcal{E} \mapsto \mathcal{N} \times \mathcal{N}$ is a total function, $\lambda_n: \mathcal{N} \mapsto \text{FinSet}(\mathcal{T})$, $\lambda_e: \mathcal{E} \mapsto \mathcal{T}$, and $\sigma: \mathcal{N} \cup \mathcal{E} \times \mathcal{P} \mapsto \text{FinSet}(\mathcal{V})$.

A property graph is formed by a set of node identifiers \mathcal{N} and a set of edges \mathcal{E} where ρ associates a pair of nodes (n_1, n_2) to every $e \in \mathcal{E}$ where n_1 is the subject and n_2 is the object, λ_n associates a set of types for node identifiers (notice that property graphs allow nodes to have more than one

⁴We omit the representation of values and use English names instead of numbers for clarity

⁵<https://neo4j.com/>

⁶<https://janusgraph.org/>

⁷<https://www.sparsity-technologies.com/#sparksee>

type), λ_e associates a types for each edge identifier, and σ associates a set of values to pairs (i, p) such that $i \in \mathcal{N} \cup \mathcal{E}$ is a node or edge and $p \in \mathcal{P}$ is a property.

■ **Example 3.3** As an example, we will represent information about Tim Berners-Lee in a property graph encoding his birth place with a relation to a node that represents London, and his birth date with a value for that property in the same node. We can also represent that its employer has been CERN in two times, one in 1980, and another between 1984 and 1994.

$\mathcal{T} = \{\text{Human, City, Metropolis, Country, Organization, birthPlace, country, employer}\}$
 $\mathcal{P} = \{\text{label, birthDate, start, end}\}$
 $\mathcal{V} = \{\text{Tim Berners-Lee, 1955, 1980, 1984, 1994, London, UK}\}$
 $\mathcal{N} = \{n_1, n_2, n_3, n_4\} \quad \mathcal{E} = \{r_1, r_2, r_3, r_4\}$
 $\rho = r_1 \mapsto (n_1, n_2), r_2 \mapsto (n_2, n_3), r_3 \mapsto (n_1, n_4), r_4 \mapsto (n_1, n_4)$
 $\lambda_n = n_1 \mapsto \{\text{Human}\}, n_2 \mapsto \{\text{City, Metropolis}\}, n_3 \mapsto \{\text{Country}\}, n_4 \mapsto \{\text{Organization}\}$
 $\lambda_e = r_1 \mapsto \text{birthPlace}, r_2 \mapsto \text{country}, r_3 \mapsto \text{employer}, r_4 \mapsto \text{employer}$
 $\sigma = (n_1, \text{label}) \mapsto \text{Tim Berners-Lee}, (n_1, \text{birthDate}) \mapsto 1955$
 $(n_2, \text{label}) \mapsto \text{London}, (n_3, \text{label}) \mapsto \text{UK}, (n_4, \text{label}) \mapsto \text{CERN}$
 $(r_3, \text{start}) \mapsto 1980, (r_3, \text{end}) \mapsto 1980, (r_4, \text{start}) \mapsto 1984, (r_4, \text{end}) \mapsto 1994$

■

Figure 3.3 presents a possible visualization of a property graph.




Figure 3.3: Example graph visualization of a property graph

Cypher is a property graph query language that was initially developed for Neo4j [22]. Figure 3.4 presents an example Cypher script that can generate the property graph represented in figure 3.3.

```

CREATE (n1:Human {label:'Tim Berners-Lee', birthDate:1955})
CREATE (n2:City:Metropolis {label:'London'})
CREATE (n3:Country {label:'UK'})
CREATE (n4:Organization {label:'CERN'})
CREATE
  (n1)-[:birthPlace]->(n2),
  (n2)-[:country]->(n3),
  (n1)-[:employer {start:[1980], end:[1980]}]->(n4),
  (n1)-[:employer {start:[1984], end:[1994]}]->(n4),

```

Figure 3.4: Cypher code to generate a sample property graph

Notice that it is possible to have more than one edge between nodes in property graphs, so they can be considered multigraphs.

3.4.3 Wikibase graphs

Wikidata⁸ started in 2012 to support Wikipedia [78]. It has become one of the biggest human knowledge bases, maintained both by humans collaboratively as by bots, which update the contents from external services or databases. Several organizations are donating their data to Wikidata and collaborate in its maintenance providing resources. A remarkable case is Google, which migrated its previous knowledge graph Freebase to Wikidata in 2017 [75].

Apart of Wikipedia, Wikidata has been reported to be used by external applications like Apple's Siri⁹ and it has been adopted as the central hub for knowledge in several domains like life sciences [9], libraries [68] or social science [14]. As of August, 2021, it contains information about more than 94 millions of entities¹⁰ and since its launch there have been more than 1,400 millions of edits.

Wikibase¹¹ is a set of open source tools which run Wikidata. With Wikibase it is possible to create Knowledge graphs that follow the same data model as Wikidata but that represent information from other domains. The projects that are using Wikibase are called Wikibase instances, some examples of wikibase instances are Rhizome¹² or Enslaved¹³. Given that Wikidata was the first and most common Wikibase instance the terms are sometimes used indistinctly.

Wikibase was initially created from MediaWiki software which ensured adoption by the Wikimedia community. Internally, Wikidata content is managed by a relational database (MariaDB) which consists of strings stored and versioned as character blobs [45]. but was not suitable for advanced data analysis and querying. With the goal of facilitating those tasks and integrate Wikibase within the semantic web ecosystem, the Wikimedia Foundation adopted BlazeGraph¹⁴ as a complementary triplestore and graph database. In this way, there are 2 main data models that coexist in Wikibase: a document-centric model based on MediaWiki and an RDF-based model based on RDF which can be used to do SPARQL queries through the Query Service.

A simplified view of Wikibase architecture is depicted in figure 3.5¹⁵.

⁸<http://wikidata.org/>

⁹<https://lists.wikimedia.org/pipermail/wikidata/2017-July/010919.html>

¹⁰<https://www.wikidata.org/wiki/Wikidata:Statistics>

¹¹<https://wikiba.se/>

¹²<https://rhizome.org/about/>

¹³<https://enslaved.org/>

¹⁴<https://blazegraph.com/>

¹⁵A more in-depth view of Wikibase architecture can be found at <https://addshore.com/2018/12/wikidata-architecture-overview-diagrams/>




Figure 3.5: Simplified architecture of Wikibase

Wikibase data model: informal introduction

The Wikibase data model¹⁶ is defined as an abstract data model that can have different serializations like JSON and RDF. It is defined using UML data structures and a notation called Wikidata Object Notation.

Informally, the Wikibase data model is formed from entities and statements about those entities. An entity can either be an item or a property. An item is usually represented using a Q followed by a number and can represent any thing like an abstract or concrete concept. For example, Q80 represents Tim Berners-Lee in Wikidata.

A property is usually represented by a P followed by a number and represents a relationship between an item and a value. For example, P19 represents the property *place of birth* in Wikidata.

The values that can be associated to a property are constrained to belong to some specific datatype. There can be compound datatypes like geographical coordinates.

Some of Wikibase datatypes are: quantities, dates and times, geographic locations and shapes, monolingual and multilingual texts, etc.

A statement consists of:

- A property which is usually denoted using a P followed by a number.
- A declaration about the possible value (in wikibase terms, it is called a *snak*) which can be a specific value, no value declaration or a some value declaration.
- A rank declaration which can be either preferred, normal or deprecated.
- Zero or more qualifiers which consist of a list of property-value pairs
- Zero or more references which consist of a list of property-value pairs.

Wikibase data model: formal definition

We define a formal model for Wikibase which is inspired from Multi-Attributed Relational Structures (MARS) [52]. For brevity, we model both qualifiers and references as attributes and don't handle the no-value and some-value snaks.

Definition 3.4.4 — Wikibase graphs. Given a mutually disjoint set of items \mathcal{Q} , a set of properties \mathcal{P} and a set of data values \mathcal{D} , a *Wikibase graph* is a tuple $\langle \mathcal{Q}, \mathcal{P}, \mathcal{D}, \rho \rangle$ such that

¹⁶<https://www.mediawiki.org/wiki/Wikibase/DataModel>

$\rho \subseteq \mathcal{E} \times \mathcal{P} \times \mathcal{V} \times \text{FinSet}(\mathcal{P} \times \mathcal{V})$ where $\mathcal{E} = \mathcal{Q} \cup \mathcal{P}$ is the set of entities which can be subjects of a statement and $\mathcal{V} = \mathcal{E} \cup \mathcal{D}$ is the set of possible values of a property.

In practice, Wikibase graphs also add the constraint that every item $q \in \mathcal{Q}$ (or property $p \in \mathcal{P}$) has a unique integer identifier $q^i \in \mathbb{N}$ ($p^i \in \mathbb{N}$).

In the Wikibase data model, statements contain a list of property-values and the values can themselves be nodes from the graph. This is different from property graphs, where the set of vertices and the set of values are disjoint.

■ **Example 3.4 — Running example as a Wikibase graph.** We continue with the running example about Tim Berners-lee, but extend it with more information about awards. More concretely, we add the information that Tim Berners-Lee was awarded with the *Princess of Asturias* (PA) award together with Vinton Cerf (vintCerf)¹⁷, and that the country of that award is Spain:

```

 $\mathcal{Q}$  = { timBl, vintCerf, London, CERN, UK, Spain, PA, Human }
 $\mathcal{P}$  = { birthDate, birthPlace, country, employer, awarded,
        start, end, pointTime, togetherWith, instanceOf }
 $\mathcal{D}$  = { 1984, 1994, 1980, 1955 }
 $\rho$  = { (timBl, instanceOf, Human, {}),
        (timBl, birthDate, 1955, {}),
        (timBl, birthPlace, London, {}),
        (timBl, employer, CERN, { start:1980, end:1980 }),
        (timBl, employer, CERN, { start:1984, end:1994 }),
        (timBl, awarded, PA, { pointTime: 2002, togetherWith:vintCerf }),
        (London, country, UK, {}),
        (vintCerf, instanceOf, Human, {}),
        (vintCerf, birthPlace, NewHaven, {}),
        (CERN, awarded, PA, { pointTime: 2013 }),
        (PA, country, Spain, {} ) }

```

Figure 3.6 presents a possible visualization of a wikibase graph.

■

The Wikibase data model supports 2 main export formats: JSON and RDF. The JSON one directly follows the structure of the Wikibase data model and is employed by the JSON Dumps while the RDF serialization follows semantic web and linked data principles.

Wikibase JSON serialization

The JSON serialization follows the Wikibase data model. It basically consists of an array of entities where each entity is a JSON object that captures all the local information about the entity: the labels, descriptions, aliases, sitelinks and statements that have the entity as subject. Each JSON object is represented in a single line. A remarkable feature of this encoding is that it captures the output neighborhood of every entity in a single line making it amenable to processing models that focus on local neighborhoods because the whole graph can be processed in a single pass.

```

[
  { "type": "item", "id": "Q42", "claims": { "P31": [...
  { "type": "item", "id": "Q80", "claims": { "P108": [...
  { "type": "property", "id": "P108", "claims": { ...
  ...
]

```

¹⁷The award was really obtained by Tim Berners-Lee, Vinton Cerf, Robert Kahn and Lawrence Roberts, we included here only the first two for simplicity




Figure 3.6: Visualization of example wikibase graph

Wikibase RDF serialization

The RDF serialization¹⁸ of Wikidata was designed with the goal of being able to represent all the structures of the Wikibase data model in RDF, maintaining compatibility with semantic web vocabularies like RDFS and OWL and avoiding the use of blank nodes [20].

■ **Example 3.5 — RDF serialization of a node.** As an example, the information about Tim Berners-Lee (Q80) declaring that he was as employer (P108) of CERN (Q42944) between 1984 and 1994 is represented as¹⁹:

```
wd:Q80 rdf:type wikibase:Item ;
  wdt:P108 wd:Q42944 ;
  p:P108 :Q80-4fe7940f .

:Q80-4fe7940f rdf:type wikibase:Statement ;
  wikibase:rank wikibase:NormalRank ;
  ps:P108 wd:Q42944 ;
  pq:P580 "1984-01-01T00:00:00Z"^^xsd:dateTime ;
  pq:P582 "1994-01-01T00:00:00Z"^^xsd:dateTime .
```

The RDF serialization uses a direct arc to represent the preferred statement represented by prefix alias wdt: leaving the rest of the values of a property accessible through the namespaces p:, ps: and pq:.

The reification model employed by Wikidata creates auxiliary nodes that represent each statement. In the previous example, the node :Q80-4fe7940f represents the statement which can be qualified with the start and end time.

¹⁸https://www.mediawiki.org/wiki/Wikibase/Indexing/RDF_Dump_Format

¹⁹The full Turtle serialization can be obtained at: <https://www.wikidata.org/wiki/Special:EntityData/Q80.ttl>

Apart of the the dumps, RDF serialization is also employed by the Wikidata Query Service [5, 44] and users of Wikidata are required to use and understand the singleton statement approach and namespace conventions employed.

3.5 Describing Knowledge Graphs

3.5.1 Describing and validating RDF

At the end of 2013, an *RDF Validation Workshop*²⁰ was organized by W3C/MIT to discuss use cases and requirements related with the quality of RDF data. One of the conclusions of the workshop was that there was a need for a high-level language that could describe and validate RDF data.

Shape Expressions (ShEx) were proposed as such a language in 2014 [63]. It was designed as a high-level and concise domain-specific language to describe RDF. The syntax of ShEx is inspired by Turtle and SPARQL, while the semantics is inspired by RelaxNG and XML Schema.

In this section we describe a simplified abstract syntax of ShEx following [7]²¹.

Definition 3.5.1 — ShEx schema. A *ShEx Schema* is defined as a tuple $\langle \mathcal{L}, \delta \rangle$ where \mathcal{L} set of shape labels, and $\delta : \mathcal{L} \rightarrow \mathcal{S}$ is a total function from labels to shape expressions.

The set of shape expressions $se \in \mathcal{S}$ is defined using the following abstract syntax:

se	::=	cond	Basic boolean condition on nodes (node constraint)
		s	Shape
		se ₁ AND se ₂	Conjunction
		@l	Shape label reference for $l \in \mathcal{L}$
s	::=	CLOSED {te}	Closed shape
		{te}	Open shape
te	::=	te ₁ ;te ₂	Each of te ₁ and te ₂
		te ₁ te ₂	Some of te ₁ or te ₂
		te*	Zero or more te
		ε	Empty triple expression
		$_ \xrightarrow{p} @l$	Triple constraint with predicate p

Intuitively, shape expressions define conditions about nodes while triple expressions define conditions about the neighborhood of nodes, and shapes qualify those neighborhoods by disallowing triples with other predicates in the case of closed shapes or allowing them in the case of open shapes.

In this paper we omit the negation and disjunction operator to facilitate the presentation of the subsetting semantics. Adding those operators increases the expressiveness of ShEx to validate RDF graphs but we consider that their use to create subsets is not yet clear so we decided to leave them for further research.

The restrictions imposed on shape expressions schemas in [64] also apply here. Namely, in a schema $(\mathcal{L}, \delta, \mathcal{S})$

- The shape label references used by the definition function δ are themselves defined, i.e. if $@l$ appears in some shape definition, then l belongs to \mathcal{L} ;
- No definition $\delta(l)$ uses a reference $@l$ to itself, neither directly nor transitively, except while traversing a shape. For instance, $\delta(l) = @l \text{ AND } se$ is forbidden, but $\delta(l) = \{ \neg \xrightarrow{p} @l \}$ is allowed.

²⁰<https://www.w3.org/2012/12/rdf-val/>

²¹The full specification of ShEx is available at <https://shex.io/shex-semantics/>

■ **Example 3.6 — Example of ShEx schema.** A ShEx schema that describes the RDF graph presented in example 3.1 can be defined as:

$$\begin{aligned}
 \mathcal{L} &= \{ \text{Person, Place, Country, Organization, Date} \} \\
 \delta(\text{Person}) &= \{ _ \xrightarrow{\text{birthDate}} @\text{Date}; _ \xrightarrow{\text{birthPlace}} @\text{Place}; \\
 &\quad _ \xrightarrow{\text{employer}} @\text{Organization}^* \} \\
 \delta(\text{Place}) &= \{ _ \xrightarrow{\text{country}} @\text{Country} \} \\
 \delta(\text{Country}) &= \{ \} \\
 \delta(\text{Organization}) &= \{ \} \\
 \delta(\text{Date}) &= \text{xsd:Date}
 \end{aligned}$$

ShEx has several concrete syntaxes like a compact syntax (ShExC) and an RDF syntax defined based on JSON-LD (ShExJ) ²².

■ **Example 3.7 — Example of ShEx in ShExC compact syntax.** The previous ShEx schema can be defined using the compact syntax as:

```

:Person {
  :birthPlace @:Place ;
  :birthDate @:Date ;
  :employer @:Organization ;
}
:Place {
  :country @:Country
}
:Country {}
:Organization {}
:Date {}

```

In general, it is possible to visualize ShEx schemas using UML-like class diagrams. Figure 3.7 presents a visualization of the previous schema using RDFShape ²³

Apart of describing RDF data, Shape Expressions have been designed to enable validation and checking if an RDF node conforms to some shape.

The semantics of Shape Expression validation can be defined with a relation between an RDF node, an RDF graph, a ShEx schema and a shape assignment.

As an example of validation, we have implemented the ShEx-s library which is used by RDFShape ²⁴.

The semantics of ShEx schemas is based on a conformance relation parameterized by a shape assignment: we say that node n in graph \mathcal{G} conforms to shape expression se with shape assignment τ , and we write $\mathcal{G}, n, \tau \models se$.

The following rules are defined similar to [6], where it is shown that there exists a unique maximal shape assignment τ_{\max} that allows to define conformance independently on the shape assignment.

The conformance relation is defined recursively on the structure of se by the set of inference rules presented in table 3.1 where $\text{preds}(te)$ is the set of predicates that appear in a triple expression te and can be defined as:

²²See [64] for details.

²³This visualization can be interactively generated following: <https://rdfshape.weso.es/link/16344153229>

²⁴It is possible to see the results of validating the previous example in RDFShape following this link: <https://rdfshape.weso.es/link/16275436158>




Figure 3.7: ShEx schema visualization as UML-like diagrams

$$\begin{array}{l}
 \text{Cond} \frac{\text{cond}(n) = \text{true}}{\mathcal{G}, n, \tau \models \text{cond}} \quad \text{AND} \frac{\mathcal{G}, n, \tau \models se_1 \quad \mathcal{G}, n, \tau \models se_2}{\mathcal{G}, n, \tau \models se_1 \text{ AND } se_2} \\
 \text{ClosedShape} \frac{\text{neighs}(n, \mathcal{G}) = ts \quad \mathcal{G}, ts, \tau \models te}{\mathcal{G}, n, \tau \models \text{CLOSED } \{te\}} \\
 \text{OpenShape} \frac{ts = \{\langle x, p, y \rangle \in \text{neighs}(n, \mathcal{G}) \mid p \in \text{preds}(te)\} \quad \mathcal{G}, ts, \tau \models te}{\mathcal{G}, n, \tau \models \{te\}}
 \end{array}$$

Table 3.1: Inference rules for ShEx shape expressions

$$\begin{array}{ll}
 \text{preds}(te_1; te_2) &= \text{preds}(te_1) \cup \text{preds}(te_2) \\
 \text{preds}(te_1 \mid te_2) &= \text{preds}(te_1) \cup \text{preds}(te_2) \\
 \text{preds}(_ \xrightarrow{p} te) &= \{p\} \\
 \text{preds}(te^*) &= \text{preds}(te) \\
 \text{preds}(\epsilon) &= \emptyset
 \end{array}$$

The rules for node constraint (Cond) and conjunction are as expected. A node n conforms to an open shape with triple expression te if its neighborhood restricted to the triples with predicates from te conform, meaning that triples whose predicates are not mentioned in te are not constrained by the shape (rule OpenShape). Conformance to a closed shape requires to consider the whole neighborhood of the node (rule ClosedShape).

Conformance to a triple expression uses a second conformance relation defined on sets on neighborhood triples ts instead of nodes n . The set of neighborhood nodes ts of a graph \mathcal{G} conforms to a triple expression te with shape assignment τ , written as $\mathcal{G}, ts, \tau \models te$, as defined by the inference rules in table 3.2.

The semantics of ShEx schema can be defined independently of shape assignments. A shape assignment τ for graph \mathcal{G} and \mathcal{S} is called *valid* if for every node n in \mathcal{G} and every shape expression label l defined in \mathcal{S} , if $n@l \in \tau$, then $\mathcal{G}, n, \tau \models @l$.

$$\begin{array}{c}
\text{EachOf} \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \Vdash te_1 \quad \mathcal{G}, ts_2, \tau \Vdash te_2}{\mathcal{G}, ts, \tau \Vdash te_1; te_2} \\
\\
\text{OneOf}_1 \frac{\mathcal{G}, ts, \tau \Vdash te_1}{\mathcal{G}, ts, \tau \Vdash te_1 \mid te_2} \quad \text{OneOf}_2 \frac{\mathcal{G}, ts, \tau \Vdash te_2}{\mathcal{G}, ts, \tau \Vdash te_1 \mid te_2} \\
\\
\text{TripleConstraint} \frac{ts = \{\langle x, p, y \rangle\} \quad \mathcal{G}, y, \tau \models @l}{\mathcal{G}, ts, \tau \Vdash \text{ } \xrightarrow{p} @l} \quad \text{Star}_1 \frac{}{\mathcal{G}, \emptyset, \tau \Vdash te^*} \\
\\
\text{Star}_2 \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \Vdash te \quad \mathcal{G}, ts_2, \tau \Vdash te^*}{\mathcal{G}, ts, \tau \Vdash te^*}
\end{array}$$

Table 3.2: Inference rules for ShEx triple expressions

Lemma 3.5.1 — Boneva et al (7). For every graph \mathcal{G} , there exists a unique maximal valid shape shape assignment τ_{\max} such that if τ is a valid shape assignment for \mathcal{G} and \mathcal{S} , then $\tau \subseteq \tau_{\max}$.

3.5.2 Describing and validating Property graphs

In this section we define a ShEx extension called PShEx that can be used to describe and validate Property graphs. According to the definition of property graphs given in section 3.4.2, nodes and edges can have associated labels as well as a set of property/values. In this way, it is necessary to adapt the definition of ShEx to describe pairs or property/values that we will call qualifiers.

The language PShEx is composed of three main categories: shape expressions (se) that describe the shape of nodes, triple expressions (te) that describe the shape of edge relationships and qualifier expressions (qs) that describe qualifiers sets of property/values associated with node/edge identifiers.

Definition 3.5.2 — PShEx schema. A *PShEx Schema* is a tuple $\langle \mathcal{L}, \delta \rangle$ where \mathcal{L} set of shape labels, and $\delta : \mathcal{L} \rightarrow \mathcal{S}$ is a total function from labels to shape expressions $se \in \mathcal{S}$ defined using the abstract syntax:

se	$::=$	$cond_{t_s}$	Basic boolean condition on set of types $t_s \subseteq \mathcal{T}$
		s	Shape
		$se_1 \text{ AND } se_2$	Conjunction
		$@l$	Shape label reference for $l \in \mathcal{L}$
		qs	Qualifiers of that node
s	$::=$	$CLOSED \{te\}$	Closed shape
		$\{te\}$	Open shape
te	$::=$	$te_1; te_2$	Each of te_1 and te_2
		$te_1 \mid te_2$	Some of te_1 or te_2
		te^*	Zero or more te
		$\sqsubset \xrightarrow{p} @l qs$	Triple constraint with property type p whose nodes satisfy the shape l and qualifiers qs
qs	$::=$	$[ps]$	Open qualifier specifiers ps
		$\lceil ps \rceil$	Closed qualifier specifiers ps
ps	$::=$	ps_1, ps_2	Each of ps_1 and ps_2
		$ps_1 \mid ps_2$	OneOf of ps_1 or ps_2
		ps^*	zero of more ps
		$p : cond_v$	Property p with value conforming to $cond_v$ $cond_v$ is a boolean condition on sets of values $v_s \subseteq \mathcal{V}$

We will omit the list of qualifiers when it is empty.

■ **Example 3.8** As an example, we can define a PShEx schema that describes the property graph from example 3.3 where $hasType_t$ is a condition that is satisfied when the set of types of a node contains the type t , i.e. $hasType_t(vs) = \text{true}$ if $t \in vs$ and $String, Date$ are conditions on the values that are satisfied when the values have the corresponding type.

\mathcal{L}	$=$	$\{ \text{Person, Place, Country, Org} \}$
$\delta(\text{Person})$	$=$	$hasType_{Human} \text{ AND } [label : String, birthDate : Date] \text{ AND } \{$ $\sqsubset \xrightarrow{birthPlace} @Place;$ $\sqsubset \xrightarrow{employer} @Org [start : Date, end : Date]^*$ $\}$
$\delta(\text{Place})$	$=$	$[label : String] \text{ AND } \{$ $\sqsubset \xrightarrow{country} @Country$ $\}$
$\delta(\text{Country})$	$=$	$hasType_{Country} \text{ AND } [label : String] \{ \}$
$\delta(\text{Org})$	$=$	$hasType_{Organization} \text{ AND } [label : String] \{ \}$

■

In order to define the semantic specification of PShEx we will need to define the neighborhood of a node in a property graph.

■ **Definition 3.5.3 — Neighborhood of node in property graph.** The neighbors of a node $n \in \mathcal{N}$ in a property graph $\mathcal{G} = \langle \mathcal{N}, \mathcal{E}, \rho, \lambda_n, \lambda_e, \sigma \rangle$ are defined as $neighs(n) = \{(n, p, y, vs) \mid \exists v \in \mathcal{E} \text{ such that } \rho(v) = (n, y) \wedge \lambda_e(v) = p \wedge vs = \{(k, v) \mid \sigma(k, v) = ws \wedge v \in ws\}\}$

■ **Example 3.9** The neighbors of node n_1 in property graph 3.3 are:

$$neighs(n_1) = \{ (n_1, birthPlace, n_2, \{\}), (n_1, employer, n_4, \{(start, 1980), (end, 1980)\}), (n_1, employer, n_4, \{(start, 1984), (end, 1994)\}) \}$$

■

The semantic specification of PShEx can be defined in a similar way to the ShEx one. Given a property graph \mathcal{G} , and a shape assignment τ , a node identifier $n \in \mathcal{N}$ conforms with a shape expression se , which is represented as $\mathcal{G}, n, \tau \models se$ and follows the rules presented in 3.3 where

$\text{preds}(te)$ is the set of edge labels (or predicates) that appear in a triple expression te and can be defined as:

$$\begin{array}{c}
\text{Cond}_{ts} \frac{\lambda_n(n) = vs \quad \text{cond}_{ts}(vs) = \text{true}}{\mathcal{G}, n, \tau \models \text{cond}_{ts}} \quad \text{AND} \frac{\mathcal{G}, n, \tau \models se_1 \quad \mathcal{G}, n, \tau \models se_2}{\mathcal{G}, n, \tau \models se_1 \text{ AND } se_2} \\
\\
\text{ClosedShape} \frac{\text{neighs}(n, \mathcal{G}) = ts \quad \mathcal{G}, ts, \tau \models s'}{\mathcal{G}, n, \tau \models \text{CLOSED } \{te\}} \\
\\
\text{OpenShape} \frac{ts = \{\langle x, p, y \rangle \in \text{neighs}(n, \mathcal{G}) \mid p \in \text{preds}(te)\} \quad \mathcal{G}, ts, \tau \models te}{\mathcal{G}, n, \tau \models \{te\}}
\end{array}$$

Table 3.3: Rules for PShEx shape expressions

$$\begin{array}{ll}
\text{preds}(te_1; te_2) &= \text{preds}(te_1) \cup \text{preds}(te_2) \\
\text{preds}(te_1 \mid te_2) &= \text{preds}(te_1) \cup \text{preds}(te_2) \\
\text{preds}(_ \xrightarrow{p} te) &= \{p\} \\
\text{preds}(te^*) &= \text{preds}(te) \\
\text{preds}(\epsilon) &= \emptyset
\end{array}$$

As in the case of ShEx, the previous definition uses a second conformance relation defined on sets of triples ts instead of nodes n . The set of neighborhood nodes ts from a property graph \mathcal{G} conforms to a triple expression te with shape assignment τ , written $\mathcal{G}, ts, \tau \models s$, as defined by the inference rules represented in table 3.4.

$$\begin{array}{c}
\text{EachOf} \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \models te_1 \quad \mathcal{G}, ts_2, \tau \models te_2}{\mathcal{G}, ts, \tau \models te_1; te_2} \\
\\
\text{OneOf}_1 \frac{\mathcal{G}, ts, \tau \models te_1}{\mathcal{G}, ts, \tau \models te_1 \mid te_2} \quad \text{OneOf}_2 \frac{\mathcal{G}, ts, \tau \models te_2}{\mathcal{G}, ts, \tau \models te_1 \mid te_2} \\
\\
\text{TripleConstraint} \frac{ts = \{\langle x, p, y, s \rangle\} \quad \mathcal{G}, y, \tau \models @l \quad \mathcal{G}, s, \tau \vdash qs}{\mathcal{G}, ts, \tau \models _ \xrightarrow{p} @l qs} \\
\\
\text{Star}_1 \frac{}{\mathcal{G}, \emptyset, \tau \models te^*} \\
\\
\text{Star}_2 \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \models te \quad \mathcal{G}, ts_2, \tau \models te^*}{\mathcal{G}, ts, \tau \models te^*}
\end{array}$$

Table 3.4: Rules for PShEx triple expressions

In the case of PShEx we declare a new conformance relationship $\mathcal{G}, s, \tau \vdash qs$ between a graph \mathcal{G} a set $s \in P \times V$ of property-value elements, a shape assignment τ and a qualifier specifier qs whose rules are defined in table 3.5 where $\text{props}(ps)$ is the set of properties that appear in a property specifier ps and can be defined as:

$$\begin{array}{ll}
\text{props}(ps_1, ps_2) &= \text{props}(ps_1) \cup \text{props}(ps_2) \\
\text{props}(ps_1 \mid ps_2) &= \text{props}(ps_1) \cup \text{props}(ps_2) \\
\text{props}(ps^*) &= \text{preds}(ps) \\
\text{props}(p : \text{cond}_v) &= \{p\}
\end{array}$$

As in the case of ShEx, the semantics of ShEx schemas can be defined independently on shape

$$\begin{array}{c}
\text{OpenQs} \frac{s' = \{(p, v) \in s \mid p \in \text{props}(ps)\} \quad \mathcal{G}, s', \tau \vdash ps}{\mathcal{G}, s, \tau \vdash [ps]} \quad \text{CloseQs} \frac{\mathcal{G}, s, \tau \vdash ps}{\mathcal{G}, s, \tau \vdash [ps]} \\
\\
\text{EachOfQs} \frac{\mathcal{G}, s, \tau \vdash ps_1 \quad \mathcal{G}, s, \tau \vdash ps_2}{\mathcal{G}, s, \tau \vdash ps_1, ps_2} \\
\\
\text{OneOfQs}_1 \frac{\mathcal{G}, s, \tau \vdash ps_1}{\mathcal{G}, s, \tau \vdash ps_1 \mid ps_2} \quad \text{OneOfQs}_2 \frac{\mathcal{G}, s, \tau \vdash ps_2}{\mathcal{G}, s, \tau \vdash ps_1 \mid ps_2} \\
\\
\text{StarQs}_1 \frac{}{\mathcal{G}, \emptyset, \tau \vdash ps^*} \quad \text{StarQs}_2 \frac{(s_1, s_2) \in \text{part}(s) \quad \mathcal{G}, s_1, \tau \vdash ps \quad \mathcal{G}, s_2, \tau \vdash ps^*}{\mathcal{G}, s, \tau \vdash ps^*} \\
\\
\text{PropertyQs} \frac{s = \{(p, w)\} \quad \text{conv}_v(w) = \text{true}}{\mathcal{G}, s, \tau \vdash p : \text{cond}_v}
\end{array}$$

Table 3.5: Rules for PShEx qualifiers




Figure 3.8: Relationship between ShEx, WShEx and Wikibase data model

assignments. A shape assignment τ for graph \mathcal{G} and \mathcal{S} is called *valid* if for every node n in \mathcal{G} and every shape expression label l defined in \mathcal{S} , if $n @ l \in \tau$, then $\mathcal{G}, n, \tau \models @l$.

3.5.3 Describing and validating Wikibase graphs

Wikidata adopted ShEx in 2019 as the language to define entity schemas which can be used to validate entities. Nevertheless, they describe the RDF serialization of Wikibase entities instead of the Wikibase datamodel. This requires users to be aware of how qualifiers and references are serialized in Wikibase which can lead to duplicated properties. Another problem of ShEx schemas is that they cannot be used to directly describe the contents of Wikidata dumps in JSON which are closer to the Wikibase data model.

To that end, we designed an extension of ShEx called WShEx that can describe the Wikibase data model and so, be used to validate Wikibase dumps in JSON without requiring them to be serialized in RDF. Figure 3.8 represents the relationship between ShEx and WShEx.

WShEx is presented as an extension of the ShEx language defined in section 3.5.1 adapted to the wikibase graphs definitions 3.4.4.

Definition 3.5.4 — WShEx schema. A *WShEx Schema* is defined as a tuple $\langle \mathcal{L}, \delta \rangle$ where \mathcal{L} set of shape labels, and $\delta : \mathcal{L} \rightarrow \mathcal{S}$ is a total function from labels to w-shape expressions.

The set of shape expressions $se \in \mathcal{S}$ is defined using the abstract syntax presented in table 3.6. Notice that it is an extension of the abstract syntax for ShEx modifying the rule for triple constraint adding a new element for qualifier specifiers and adding the corresponding rules for qualifier specifiers.

■ **Example 3.10 — Example of WShEx schema.** A ShEx schema that describes the Wikibase graph presented in example 3.4 can be defined as:

se	$::=$	$cond$	Basic boolean condition on nodes (node constraint)
		$ $ s	Shape
		$ $ $se_1 \text{ AND } se_2$	Conjunction
		$ $ $@l$	Shape label reference for $l \in \mathcal{L}$
s	$::=$	$CLOSED \ s'$	Closed shape
		$ $ s'	Open shape
s'	$::=$	$\{ te \}$	Shape definition
te	$::=$	$te_1; te_2$	Each of te_1 and te_2
		$ $ $te_1 \mid te_2$	Some of te_1 or te_2
		$ $ te^*	Zero or more te
		$ $ $\sqsubseteq \xrightarrow{p} @l \ qs$	Triple constraint with predicate p value conforming to l and qualifier specifier qs
		$ $ ϵ	Empty triple expression
qs	$::=$	$[ps]$	Open property specifier
		$\lceil ps \rceil$	Closed property specifier
ps	$::=$	ps, ps	<i>EachOf</i> property specifiers
		$ $ $ps \mid ps$	<i>OneOf</i> property specifiers
		$ $ ps^*	zero of more property specifiers
		$ $ ϵ	Empty property specifier
		$ $ $p:@l$	Property p with value conforming to shape l

Table 3.6: Abstract syntax of WShEx

\mathcal{L}	$=$	$\{ \text{Person, Place, Country, Organization, Date, Award} \}$
$\delta(\text{Person})$	$=$	$\{ \sqsubseteq \xrightarrow{\text{birthDate}} @\text{Date}; \sqsubseteq \xrightarrow{\text{birthPlace}} @\text{Place};$ $\sqsubseteq \xrightarrow{\text{employer}} @\text{Organization} [\text{start} : @\text{Date}, \text{end} : @\text{Date}]^*$ $\sqsubseteq \xrightarrow{\text{awarded}} @\text{Award} [\text{pointTime} : @\text{Date}, \text{togetherWith} : @\text{Person}]^*$ $\}$
$\delta(\text{Place})$	$=$	$\{ \sqsubseteq \xrightarrow{\text{country}} @\text{Country} \}$
$\delta(\text{Country})$	$=$	$\{ \}$
$\delta(\text{Award})$	$=$	$\{ \sqsubseteq \xrightarrow{\text{country}} @\text{Country} \}$
$\delta(\text{Organization})$	$=$	$\{ \}$
$\delta(\text{Date})$	$=$	$\in \text{xsd:date}$

■

It is possible to define a compact syntax for WShEx in a similar way to ShExC adding the symbols $\{\{ \dots \}\}$ to declare open qualifier specifiers and $\lceil [\dots] \rceil$ for closed ones.

■ **Example 3.11 — Example of WShEx schema using the compact Syntax.**

```

:Researcher {
  birthPlace    @<Place>          ;
  birthDate     @<Time>           ;
  employer      @<Organization> *
    [{ :start    @:Date,
       :end      @:Date
    }] ;
  awarded       @<Award> *
    [{ :pointTime @:Date,
       :togetherWith @:Person
    }]
}
:Place          { country @<Country> }
:Organization    {}

```

:Award	{ country @<Country> }
:Country	{}
:Date	xsd:date

■

The semantics of WShEx is similar to the semantics defined for ShEx and PShEx. We define a conformance relation parameterized by a shape assignment $\mathcal{G}, n, \tau \models se$ with the meaning that node n in graph \mathcal{G} conforms to shape expression se with shape assignment τ according to the rules 3.7.

$$\begin{array}{c}
\text{Cond} \frac{\text{cond}(n) = \text{true}}{\mathcal{G}, n, \tau \models \text{cond}} \quad \text{AND} \frac{\mathcal{G}, n, \tau \models se_1 \quad \mathcal{G}, n, \tau \models se_2}{\mathcal{G}, n, \tau \models se_1 \text{ AND } se_2} \\
\\
\text{ClosedShape} \frac{\text{neighs}(n, \mathcal{G}) = ts \quad \mathcal{G}, ts, \tau \models s'}{\mathcal{G}, n, \tau \models \text{CLOSED } s'} \\
\\
\text{OpenShape} \frac{ts = \{\langle x, p, y \rangle \in \text{neighs}(n, \mathcal{G}) \mid p \in \text{preds}(te)\} \quad \mathcal{G}, ts, \tau \models s'}{\mathcal{G}, n, \tau \models s'}
\end{array}$$

Table 3.7: Inference rules for WShEx shape expressions

We also define a conformance relation $\mathcal{G}, ts, \tau \models te$ which declares that the triples ts in graph \mathcal{G} conform to the triple expression te with the shape assignment τ using the rules 3.8 which takes into account qualifier specifiers.

$$\begin{array}{c}
\text{EachOf} \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \models te_1 \quad \mathcal{G}, ts_2, \tau \models te_2}{\mathcal{G}, ts, \tau \models te_1; te_2} \\
\\
\text{OneOf}_1 \frac{\mathcal{G}, ts, \tau \models te_1}{\mathcal{G}, ts, \tau \models te_1 \mid te_2} \quad \text{OneOf}_2 \frac{\mathcal{G}, ts, \tau \models te_2}{\mathcal{G}, ts, \tau \models te_1 \mid te_2} \\
\\
\text{Star}_1 \frac{}{\mathcal{G}, \emptyset, \tau \models te^*} \\
\\
\text{Star}_2 \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \models te \quad \mathcal{G}, ts_2, \tau \models te^*}{\mathcal{G}, ts, \tau \models te^*} \\
\\
\text{TripleConstraint} \frac{ts = \{\langle x, p, y, s \rangle\} \quad \mathcal{G}, y, \tau \models @l \quad \mathcal{G}, s, \tau \models qs}{\mathcal{G}, ts, \tau \models \perp \xrightarrow{p} @l qs}
\end{array}$$

Table 3.8: Inference rules for WShEx triple expressions

Finally, the conformance relationship $\mathcal{G}, s, \tau \models qs$ between a graph \mathcal{G} a set $s \in P \times V$ of property-value elements, a shape assignment τ and a qualifier specifier qs is defined with the rules 3.9.

3.6 Knowledge Graphs Subsets

In this section we review several approaches to create knowledge graphs subsets. Although we will focus on Wikibase graphs subsets, the approaches described can also be applied to RDF-based graphs and property graphs.

$$\begin{array}{c}
\text{OpenQs} \frac{s' = \{(p, v) \in s \mid p \in \text{preds}(ps)\} \quad \mathcal{G}, s', \tau \vdash ps}{\mathcal{G}, s, \tau \vdash \lfloor ps \rfloor} \quad \text{CloseQs} \frac{\mathcal{G}, s, \tau \vdash ps}{\mathcal{G}, s, \tau \vdash \lceil ps \rceil} \\
\\
\text{EachOfQs} \frac{\mathcal{G}, s, \tau \vdash ps_1 \quad \mathcal{G}, s, \tau \vdash ps_2}{\mathcal{G}, s, \tau \vdash ps_1, ps_2} \\
\\
\text{OneOfQs}_1 \frac{\mathcal{G}, s, \tau \vdash ps_1}{\mathcal{G}, s, \tau \vdash ps_1 \mid ps_2} \quad \text{OneOfQs}_2 \frac{\mathcal{G}, s, \tau \vdash ps_2}{\mathcal{G}, s, \tau \vdash ps_1 \mid ps_2} \\
\\
\text{StarQs}_1 \frac{}{\mathcal{G}, \emptyset, \tau \vdash ps^*} \quad \text{StarQs}_2 \frac{(s_1, s_2) \in \text{part}(s) \quad \mathcal{G}, s_1, \tau \vdash ps \quad \mathcal{G}, s_2, \tau \vdash ps^*}{\mathcal{G}, s, \tau \vdash ps^*} \\
\\
\text{EmptyQs} \frac{}{\mathcal{G}, \emptyset, \tau \vdash \epsilon} \quad \text{PropertyQs} \frac{s = \{(p, v)\} \quad \mathcal{G}, v, \tau \models @l}{\mathcal{G}, s, \tau \vdash p : @l}
\end{array}$$

Table 3.9: Inference rules for WShEx qualifier expressions

3.6.1 Wikibase Subsets: Formal definition

The following definition of Wikibase subset is based on the wikibase graphs definition given at section 3.4.3.

Definition 3.6.1 — Wikibase subset. Given a wikibase graph $\mathcal{G} = \langle \mathcal{Q}, \mathcal{P}, \mathcal{D}, \rho \rangle$, a wikibase subgraph is defined as $\mathcal{G}' = \langle \mathcal{Q}', \mathcal{P}', \mathcal{D}', \rho' \rangle$ such that: $\mathcal{Q}' \subseteq \mathcal{Q}$, $\mathcal{P}' \subseteq \mathcal{P}$, $\mathcal{D}' \subseteq \mathcal{D}$ and $\rho' \subseteq \rho$

■ **Example 3.12 — Example of wikibase subgraph.** Given the wikibase graph from example 3.4 $\mathcal{G}' = \langle \mathcal{Q}', \mathcal{P}', \mathcal{D}', \rho' \rangle$ where

$\mathcal{Q}' = \{\text{timBl}, \text{London}, \text{CERN}\}$
 $\mathcal{P}' = \{\text{birthPlace}, \text{employer}, \text{start}\}$
 $\mathcal{D}' = \{1980, 1984\}$
 $\rho' = \{(\text{timBl}, \text{birthPlace}, \text{London}, \{\}),$
 $(\text{timBl}, \text{employer}, \text{CERN}, \{\text{start} : 1980\}),$
 $(\text{timBl}, \text{employer}, \text{CERN}, \{\text{start} : 1984\})\}$

is a wikibase subgraph of \mathcal{G} . ■

3.6.2 Entity-generated subsets

Wikibase subgraphs can be generated from a set of entities (items or properties), where we collect the subgraph associated with those entities.

■ **Definition 3.6.2 — Item-generated subgraph.** Given a wikibase graph $\mathcal{G} = \langle \mathcal{Q}, \mathcal{P}, \mathcal{D}, \rho \rangle$ and

a subset of items $\mathcal{Q}_s \subset \mathcal{Q}$ generates an *item-generated subgraph* $\langle \mathcal{Q}', \mathcal{P}', \mathcal{D}', \rho' \rangle$ such that:

$$\begin{aligned}\mathcal{Q}' &= \{q \in \mathcal{Q} \mid (q, _, _, _) \vee (_, _, q, _) \in \rho'\} \\ &\quad \cup \{q \in \mathcal{Q} \mid (_, _, _, q_s) \in \rho' \wedge (_, q) \in q_s\} \\ \mathcal{P}' &= \{p \in \mathcal{P} \mid (_, p, _, _) \in \rho'\} \\ &\quad \cup \{p \in \mathcal{P} \mid (_, _, _, q_s) \in \rho' \wedge (p, _) \in q_s\} \\ \mathcal{D}' &= \{d \in \mathcal{D} \mid (_, _, d, _) \in \rho'\} \\ &\quad \cup \{d \in \mathcal{D} \mid (_, _, _, q_s) \in \rho' \wedge (_, d) \in q_s\} \\ \rho' &= \{(q, _, _, _) \in \rho \mid q \in \mathcal{Q}_s\} \\ &\quad \cup \{(_, _, q, _) \in \rho \mid q \in \mathcal{Q}_s\} \\ &\quad \cup \{(_, _, _, q_s) \in \rho \wedge \exists q \in \mathcal{Q}_s \mid (_, q) \in q_s\}\end{aligned}$$

Notice that the item-generated subgraph usually contains more items than the items provided by \mathcal{Q}_s .

■ **Example 3.13 — Example of item-generated subgraph.** Given the wikibase graph from example 3.4 and $\mathcal{Q}_s = \{\text{timBl}\}$ the item generated subgraph is:

$$\begin{aligned}\mathcal{Q}' &= \{\text{timBl}, \text{CERN}, \text{vintCerf}, \text{PA}\} \\ \mathcal{P}' &= \{\text{birthDate}, \text{birthPlace}, \text{employer}, \text{awarded}, \\ &\quad \text{start}, \text{end}, \text{togetherWith}\} \\ \mathcal{D}' &= \{1984, 1994, 1980, 1955\} \\ \rho' &= \{(\text{timBl}, \text{birthDate}, 1955, \{\}), \\ &\quad (\text{timBl}, \text{birthPlace}, \text{London}, \{\}), \\ &\quad (\text{timBl}, \text{employer}, \text{CERN}, \{\text{start} : 1980, \text{end} : 1980\}), \\ &\quad (\text{timBl}, \text{employer}, \text{CERN}, \{\text{start} : 1984, \text{end} : 1994\}), \\ &\quad (\text{timBl}, \text{awarded}, \text{PA}, \{\text{togetherWith} : \text{vintCerf}\})\}\end{aligned}$$

■

Definition 3.6.3 — Property-generated subgraph. Given a wikibase graph $\mathcal{G} = \langle \mathcal{Q}, \mathcal{P}, \mathcal{D}, \rho \rangle$, with the set of entities $\mathcal{E} = \mathcal{Q} \cup \mathcal{P}$ a subset of properties $\mathcal{P}_s \subset \mathcal{P}$ generates a *property generated subgraph* $\langle \mathcal{Q}', \mathcal{P}', \mathcal{D}', \rho' \rangle$ such that:

$$\begin{aligned}\mathcal{Q}' &= \{q \in \mathcal{Q} \mid \exists p \in \mathcal{P}_s \mid (q, p, _, _) \in \rho\} \\ &\quad \cup \{q \in \mathcal{Q} \mid \exists p \in \mathcal{P}_s \mid (_, p, q, _) \in \rho\} \\ &\quad \cup \{q \in \mathcal{Q} \mid (_, _, _, q_s) \in \rho \wedge \exists p \in \mathcal{P}_s \mid (p, _) \in q_s\} \\ \mathcal{P}' &= \{p \in \mathcal{P}_s \mid (_, p, _, _) \in \rho\} \\ &\quad \cup \{p \in \mathcal{P}_s \mid \exists q_s \mid (_, _, _, q_s) \in \rho \wedge (p, _) \in q_s\} \\ \mathcal{D}' &= \{d \in \mathcal{D} \mid \exists p \in \mathcal{P}_s \mid (_, p, d, _) \in \rho\} \\ &\quad \cup \{d \in \mathcal{D} \mid (_, _, _, q_s) \in \rho \wedge \exists p \in \mathcal{P}_s \mid (p, d) \in q_s\} \\ \rho' &= \{(_, p, _, _) \in \rho \mid p \in \mathcal{P}_s\} \\ &\quad \cup \{(_, _, _, q_s) \in \rho \mid \exists p \in \mathcal{P}_s \mid (p, _) \in q_s\}\end{aligned}$$

The property generated subgraph usually contains more properties than the properties provided by \mathcal{P}_s .

■ **Example 3.14 — Example of property-generated subgraph.** Given the wikibase graph from example 3.4 and $\mathcal{P}_s = \{\text{birthDate}, \text{togetherWith}\}$ the property generated subgraph is:

$$\begin{aligned} \mathcal{Q}' &= \{\text{timBl}, \text{vintCerf}, \text{PA}\} \\ \mathcal{P}' &= \{\text{birthDate}, \text{awarded}, \text{togetherWith}\} \\ \mathcal{D}' &= \{1955\} \\ \rho' &= \{(\text{timBl}, \text{birthDate}, 1955, \{\}), \\ &\quad (\text{timBl}, \text{awarded}, \text{PA}, \{\text{togetherWith} : \text{vintCerf}\})\} \end{aligned}$$

■

Notice that it is possible to define a *Datatype-generated subgraph* in a similar way than the previous definitions.

■ **Definition 3.6.4 — Entity-generated subgraph.** Given a subset of entities $\mathcal{E}_s \subset \mathcal{Q} \cup \mathcal{P}$, the entity-generated subgraph is defined as the union of the item-generated subgraph with all the items in \mathcal{E}_s and the property-generated subgraph with all the properties in \mathcal{E}_s .

3.6.3 Simple Matching-generated subsets

■ **Definition 3.6.5 — Matching expression.** Given a wikibase graph $\mathcal{G} = \langle \mathcal{Q}, \mathcal{P}, \mathcal{D}, \rho \rangle$ where $\mathcal{E} = \mathcal{Q} \cup \mathcal{P}$ and $\mathcal{V} = \mathcal{E} \cup \mathcal{D}$, a matching expression M_s is a set of matchers where each matcher m follows the grammar:

m	$::=$	<code>subject(e)</code>	Subject $e \in \mathcal{E}$
		<code>property(p)</code>	Property $p \in \mathcal{P}$
		<code>value(v)</code>	Value $v \in \mathcal{V}$
		<code>qualifier(p,v)</code>	Qualifier with property $p \in \mathcal{P}$ and value $v \in \mathcal{V}$
		<code>qualifiedProp(p)</code>	Qualifier with property $p \in \mathcal{P}$
		<code>qualifiedValue(v)</code>	Qualifier with value $v \in \mathcal{V}$

■ **Example 3.15 — Example of a matching expression.** An example of a matching expression is $M_s = \{\text{property(country)}, \text{qualifiedProp(togetherWith)}\}$ ■

■ **Definition 3.6.6 — Matching-generated subgraph.** Given a matching expression M_s over a wikibase graph $\mathcal{G} = \langle \mathcal{Q}, \mathcal{P}, \mathcal{D}, \rho \rangle$ we can define the matching-generated subgraph as a wikibase graph $\mathcal{G}' = \langle \mathcal{Q}', \mathcal{P}', \mathcal{D}', \rho' \rangle$ such that:

$$\begin{aligned}
\mathcal{Q}' &= \{q \in \mathcal{Q} \mid (q, _, _, _) \in \rho' \cup \{q \in \mathcal{Q} \mid (_, _, q, _) \in \rho'\} \\
&\quad \cup \{q \in \mathcal{Q} \mid (_, _, _, q_s) \in \rho' \wedge (_, q) \in q_s\} \\
\mathcal{P}' &= \{p \in \mathcal{P} \mid (_, p, _, _) \in \rho' \cup \{p \in \mathcal{P} \mid (_, _, _, q_s) \in \rho' \wedge (p, _) \in q_s\} \\
\mathcal{D}' &= \{d \in \mathcal{D} \mid (_, _, d, _) \in \rho'\} \cup \{d \in \mathcal{D} \mid (_, _, _, q_s) \in \rho' \wedge (_, d) \in q_s\} \\
\rho' &= \{(q, _, _, _) \in \rho \mid \text{subject}(q) \in M_s\} \\
&\quad \cup \{(_, p, _, _) \in \rho \mid \text{property}(p) \in M_s\} \\
&\quad \cup \{(_, _, v, _) \in \rho \mid \text{value}(v) \in M_s\} \\
&\quad \cup \{(_, _, _, q_s) \in \rho \mid \text{qualifier}(p, v) \in M_s \wedge \exists (p, v) \in q_s\} \quad \cup \{(_, _, _, q_s) \in \rho \mid \text{qualifiedProp}(p) \in M_s\}
\end{aligned}$$

■ **Example 3.16 — Example of matching-generated subgraph.** Given the wikibase graph \mathcal{G} of example 3.4 and the matching-expression M_s in example ??, the matching-generated subgraph of \mathcal{G} from M_s is the wikibase graph $\mathcal{G}' = \langle \mathcal{Q}', \mathcal{P}', \mathcal{D}', \rho' \rangle$ such that:

$$\begin{aligned}
\mathcal{Q}' &= \{\text{PA, Spain, London, UK, timBl, vintCerf}\} \\
\mathcal{P}' &= \{\text{country, awarded, togetherWith}\} \\
\mathcal{D}' &= \{\} \\
\rho' &= \{(\text{timBl, awarded, PA, \{togetherWith: vintCerf\}}, \\
&\quad (\text{vintCerf, awarded, PA, \{togetherWith: timBl\}}) \\
&\quad (\text{PA, country, Spain, \{\}}) \\
&\quad (\text{London, country, UK, \{\}})\}
\end{aligned}$$

■

The matching approach is followed by WDump²⁵ and WDSUB²⁶.

WDumper defines the expected patterns using a JSON configuration file that describes them or filling a web form which internally generates the JSON file.

In the case of WDSUB, the input format is a WShEx file with a set of shapes and the system processes a Wikidata dump trying to match each entity with any of the Shapes defined in the WShEx file. The algorithm employed in WDSUB to generate a matching expression from a Shape Expression is the following:

3.6.4 ShEx-based Matching generated subsets

ShEx-based matching consists on taking as input a WShEx schema \mathcal{S} and include in the generated subset the nodes whose neighborhood matches any of the shapes from \mathcal{S} after replacing any shape references by a condition that always returns true. The goal of this approach is to use ShEx as a basic description language of the topology of nodes ignoring shape references so the algorithm can be used to check dumps that contain include the information about a node and its neighborhood in a single line. In this way, the subset generator only needs to traverse the dump sequentially one time.

■ **Example 3.17 — ShEx-based matching.** Giveb the following WShEx Schema:

²⁵<https://github.com/bennofs/wdumper>

²⁶<https://github.com/weso/wdsub>

$$\begin{aligned}
\mathcal{L} &= \{ \text{Researcher, Place, Country, Date, Human} \} \\
\delta(\text{Researcher}) &= \{ \begin{array}{l} \text{--} \xrightarrow{\text{instanceOf}} \text{@Human;} \\ \text{--} \xrightarrow{\text{birthDate}} \text{@Date?;} \\ \text{--} \xrightarrow{\text{birthPlace}} \text{@Place} \end{array} \} \\
\delta(\text{Place}) &= \{ \text{--} \xrightarrow{\text{country}} \text{@Country} \} \\
\delta(\text{Date}) &= \in \text{xsd:date} \\
\delta(\text{Human}) &= \in \{\text{Human}\}
\end{aligned}$$

The result of ShEx-based matching on example 3.4 is:

$$\rho = \{ \begin{array}{l} (\text{timBl}, \text{instanceOf}, \text{Human}, \{\}), \\ (\text{timBl}, \text{birthDate}, 1955, \{\}), \\ (\text{timBl}, \text{birthPlace}, \text{London}, \{\}), \\ (\text{London}, \text{country}, \text{UK}, \{\}), \\ (\text{vintCerf}, \text{instanceOf}, \text{Human}, \{\}), \\ (\text{vintCerf}, \text{birthPlace}, \text{NewHaven}, \{\}) \end{array} \}$$

Notice that **vintCerf** is included although the node doesn't conform to the shape person because it has a **birthPlace** declaration whose value is **NewHaven** but there is no **country** property for **NewHaven**.

In the previous example, the ShEx-based matching consisted on validating each node with any of the following shapes:

$$\begin{aligned}
\delta(\text{Researcher}) &= \{ \begin{array}{l} \text{--} \xrightarrow{\text{instanceOf}} \text{true;} \\ \text{--} \xrightarrow{\text{birthDate}} \text{true?;} \\ \text{--} \xrightarrow{\text{birthPlace}} \text{true} \end{array} \} \\
\delta(\text{Place}) &= \{ \text{--} \xrightarrow{\text{country}} \text{true} \}
\end{aligned}$$

Notice that if the original ShEx schema had included the following shape:

$$\delta(\text{Country}) = \{ \}$$

Then, every node would be included in the generated subset because every node would match the Country shape.

■

ShEx-based matching generation has been implemented in WDSUB²⁷.

3.6.5 ShEx + Slurp generated subsets

The concept of *slurp* was introduced in the shex.js²⁸ implementation as a mechanism to collect the nodes and triples visited during validation.

In this way, if we collect that data, the result will be a subset of the graph which contains the portion of the graph that relates to a given ShEx schema. Although the slurp option was not formally defined, we can define it modifying the semantics of ShEx adding a new parameter to the conformance relationship.

We define a conformance relation parameterized by a shape assignment $\mathcal{G}, n, \tau \models se \rightsquigarrow \mathcal{G}'$ with the meaning that node n in graph \mathcal{G} conforms to shape expression se with shape assignment τ and generates a slurp graph \mathcal{G}' . The conformance relation follows the rules 3.10.

We also define a conformance relation $\mathcal{G}, ts, \tau \models te \rightsquigarrow \mathcal{G}'$ which declares that the triples ts in graph \mathcal{G} conform to the triple expression te with the shape assignment τ generating a slurp \mathcal{G}' . The

²⁷<https://github.com/weso/wdsub>

²⁸<https://github.com/shexjs/shex.js>

$$\begin{array}{c}
\text{Cond} \frac{\text{cond}(n) = \text{true}}{\mathcal{G}, n, \tau \models \text{cond} \rightsquigarrow \langle \{n\}, \{\} \rangle} \quad \text{AND} \frac{\mathcal{G}, n, \tau \models se_1 \rightsquigarrow \mathcal{G}_1 \quad \mathcal{G}, n, \tau \models se_2 \rightsquigarrow \mathcal{G}_2}{\mathcal{G}, n, \tau \models se_1 \text{ AND } se_2 \rightsquigarrow \mathcal{G}_1 \cup \mathcal{G}_2} \\
\\
\text{ClosedShape} \frac{\text{neighs}(n, \mathcal{G}) = ts \quad \mathcal{G}, ts, \tau \Vdash s' \rightsquigarrow \mathcal{G}'}{\mathcal{G}, n, \tau \models \text{CLOSED } s' \rightsquigarrow \mathcal{G}'} \\
\\
\text{OpenShape} \frac{ts = \{ \langle x, p, y \rangle \in \text{neighs}(n, \mathcal{G}) \mid p \in \text{preds}(te) \} \quad \mathcal{G}, ts, \tau \Vdash s' \rightsquigarrow \mathcal{G}'}{\mathcal{G}, n, \tau \models s' \rightsquigarrow \mathcal{G}'}
\end{array}$$

Table 3.10: Inference rules for WShEx+slurp shape expressions

relation is defined using the rules 3.11.

$$\begin{array}{c}
\text{EachOf} \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \Vdash te_1 \rightsquigarrow \mathcal{G}_1 \quad \mathcal{G}, ts_2, \tau \Vdash te_2 \rightsquigarrow \mathcal{G}_2}{\mathcal{G}, ts, \tau \Vdash te_1; te_2 \rightsquigarrow \mathcal{G}_1 \cup \mathcal{G}_2} \\
\\
\text{OneOf}_1 \frac{\mathcal{G}, ts, \tau \Vdash te_1 \rightsquigarrow \mathcal{G}_1}{\mathcal{G}, ts, \tau \Vdash te_1 \mid te_2 \rightsquigarrow \mathcal{G}_1} \quad \text{OneOf}_2 \frac{\mathcal{G}, ts, \tau \Vdash te_2 \rightsquigarrow \mathcal{G}_2}{\mathcal{G}, ts, \tau \Vdash te_1 \mid te_2 \rightsquigarrow \mathcal{G}_2} \\
\\
\text{Star}_1 \frac{}{\mathcal{G}, \emptyset, \tau \Vdash te^* \rightsquigarrow \emptyset} \\
\\
\text{Star}_2 \frac{(ts_1, ts_2) \in \text{part}(ts) \quad \mathcal{G}, ts_1, \tau \Vdash te \rightsquigarrow \mathcal{G}_1 \quad \mathcal{G}, ts_2, \tau \Vdash te^* \rightsquigarrow \mathcal{G}_2}{\mathcal{G}, ts, \tau \Vdash te^* \rightsquigarrow \mathcal{G}_1 \cup \mathcal{G}_2} \\
\\
\text{TripleConstraint} \frac{ts = \{ \langle x, p, y, s \rangle \} \quad \mathcal{G}, y, \tau \models @l \rightsquigarrow \langle \mathcal{V}, \mathcal{E} \rangle \quad \mathcal{G}, s, \tau \Vdash qs \rightsquigarrow (qs', \mathcal{G}_{qs})}{\mathcal{G}, ts, \tau \Vdash \text{ } \xrightarrow{p} @l qs \rightsquigarrow \langle \mathcal{V} \cup \{x\} \cup \{y\}, \mathcal{E} \cup (x, p, y, qs') \rangle \cup \mathcal{G}_{qs}}
\end{array}$$

Table 3.11: Inference rules for WShEx+slurp triple expressions

The conformance relationship $\mathcal{G}, s, \tau \vdash qs \rightsquigarrow (qs', \mathcal{G}')$ between a graph \mathcal{G} a set $s \in P \times V$ of property-value elements, a shape assignment τ and a qualifier specifier qs generates a slurp that consists of a pair (qs', \mathcal{G}') where qs' is a set of qualifiers slurped and \mathcal{G}' is the graph slurped. It is defined according to the rules 3.12.

■ **Example 3.18 — ShEx+Slurp example.** Given the following WShEx Schema:

$$\begin{array}{ll}
\mathcal{L} &= \{ \text{Researcher, Place, Country, Date, Human} \} \\
\delta(\text{Researcher}) &= \{ \text{ } \xrightarrow{\text{instanceOf}} @\text{Human}; \\
&\quad \text{ } \xrightarrow{\text{birthDate}} @\text{Date}; \\
&\quad \text{ } \xrightarrow{\text{birthPlace}} @\text{Place} \\
&\quad \} \\
\delta(\text{Place}) &= \{ \text{ } \xrightarrow{\text{country}} @\text{Country} \} \\
\delta(\text{Country}) &= \{ \text{ } \} \\
\delta(\text{Date}) &= \in \text{xsd:date} \\
\delta(\text{Human}) &= \in \{\text{Human}\}
\end{array}$$

The result of running the ShEx+Slurp on example 3.4 is:

$$\begin{array}{l}
\rho = \{ (\text{timBl}, \text{instanceOf}, \text{Human}, \{\}), \\
(\text{timBl}, \text{birthDate}, 1955, \{\}), \\
(\text{timBl}, \text{birthPlace}, \text{London}, \{\}), \\
(\text{London}, \text{country}, \text{UK}, \{\}) \}
\end{array}$$

The main difference between this approach and the previous one is that it retrieves the valid

$$\begin{array}{c}
\text{OpenQs} \frac{s' = \{(p, v) \in s \mid p \in \text{preds}(ps)\} \quad \mathcal{G}, s', \tau \vdash ps \rightsquigarrow (qs, \mathcal{G}')}{\mathcal{G}, s, \tau \vdash [ps] \rightsquigarrow (qs, \mathcal{G}')} \\
\\
\text{CloseQs} \frac{\mathcal{G}, s, \tau \vdash ps \rightsquigarrow (qs, \mathcal{G}')}{\mathcal{G}, s, \tau \vdash [ps] \rightsquigarrow (qs, \mathcal{G}')} \\
\\
\text{EachOfQs} \frac{\mathcal{G}, s, \tau \vdash ps_1 \rightsquigarrow (qs_1, \mathcal{G}_1) \quad \mathcal{G}, s, \tau \vdash ps_2 \rightsquigarrow (qs_2, \mathcal{G}_2)}{\mathcal{G}, s, \tau \vdash ps_1, ps_2 \rightsquigarrow (qs_1 \cup_2, \mathcal{G}_1 \cup \mathcal{G}_2)} \\
\\
\text{OneOfQs}_1 \frac{\mathcal{G}, s, \tau \vdash ps_1 \rightsquigarrow (qs_1, \mathcal{G}_1)}{\mathcal{G}, s, \tau \vdash ps_1 \mid ps_2 \rightsquigarrow (qs_1, \mathcal{G}_1)} \quad \text{OneOfQs}_2 \frac{\mathcal{G}, s, \tau \vdash ps_2 \rightsquigarrow (qs_2, \mathcal{G}_2)}{\mathcal{G}, s, \tau \vdash ps_1 \mid ps_2 \rightsquigarrow (qs_2, \mathcal{G}_2)} \\
\\
\text{StarQs}_1 \frac{}{\mathcal{G}, \emptyset, \tau \vdash ps^* \rightsquigarrow (\{\}, \emptyset)} \\
\\
\text{StarQs}_2 \frac{(s_1, s_2) \in \text{part}(s) \quad \mathcal{G}, s_1, \tau \vdash ps \rightsquigarrow (qs_1, \mathcal{G}_1) \quad \mathcal{G}, s_2, \tau \vdash ps^* \rightsquigarrow qs_2, \mathcal{G}_2}{\mathcal{G}, s, \tau \vdash ps^* \rightsquigarrow (qs_1 \cup qs_2, \mathcal{G}_1 \cup \mathcal{G}_2)} \\
\\
\text{EmptyQs} \frac{}{\mathcal{G}, \emptyset, \tau \vdash \epsilon \rightsquigarrow (\{\}, \emptyset)} \quad \text{PropertyQs} \frac{s = \{(p, v)\} \quad \mathcal{G}, v, \tau \models @l \rightsquigarrow \mathcal{G}'}{\mathcal{G}, s, \tau \vdash p : @l \rightsquigarrow (\{p : v\}, \mathcal{G}')}
\end{array}$$

Table 3.12: Inference rules for WShEx+slurp qualifiers

subset according to the ShEx schema. In this case, the node **vintCerf** is not generated because the value of the property **birthPlace** is **NewHaven** and it has no **country** declaration, so **NewHaven** doesn't conform to the **Place** shape and subsequently, **vintCerf** doesn't conform to the **Person** shape as they are declared in that Schema. ■

Although the ShEx+Slurp approach has not yet been implemented for WShEx, it has already been implemented for ShEx in `shex.js` and in `PyShEx` ²⁹.

One problem of this approach is that it is difficult to scale as it needs to traverse the graph while validating and collecting the slurped graph. The complexity also increases if the implementation wants to adjust the collected triples when checking the different partitions of a node neighborhood. If one of the partitions fails, following the definition it would need to discard the corresponding portion of the graph, which would make the whole process more complex. In practice, implementations just collect the visited nodes and triples without discarding the ones that shouldn't be part of the result.

3.6.6 ShEx + Pregel generated subsets

Pregel [43] has been proposed as a scalable computational model created by Google to handle large graphs. It is based on Bulk Synchronous Parallel (BSP) model which simplifies parallel programming having different computation and communication phases. Pregel is an iterative algorithm where each phase is called a superstep. Following the lemma *think like a vertex*, it is a vertex-centric abstraction where at each superstep, a vertex executes a user defined function (called vertex program) which can update its status and later sends messages to neighbors along graph edges. Supersteps end with a synchronization barrier that guarantees that messages sent at one superstep are received at the beginning of the next superstep. Vertices may change status between active and inactive and the algorithm terminates when all vertices are inactive and no more messages are sent.

²⁹<https://github.com/hsolbrig/PyShEx>

GraphX was proposed in 2014 as a graph processing framework embedded in Apache Spark. Its API includes a variant of Pregel which is used to implement several graph algorithms like PageRank, connected components, triangle counting, etc.

GraphX defines an API for graphs based on RDDs (resilient distributed datasets). An $\text{RDD}[\mathcal{V}]$ is an abstraction of a collection of values of type \mathcal{V} which are immutable and can be partitioned to run data-parallel operations like *map* and *reduce*.

A graph $\text{Graph}[\mathcal{V}, \mathcal{E}]$ represents an abstraction of vertices with values of type \mathcal{V} and edges of type \mathcal{E} where internally the vertices are represented as $\text{RDD}[(\text{Id}, \mathcal{V})]$, i.e. a collection of a tuple with an *Id* (a Long value) and a \mathcal{V} , and edges are represented as $\text{RDD}[(\text{Id}, \text{Id}, \mathcal{E})]$, i.e. a triple where the first and second components are the *Id* of the source and destiny respectively, and the third component is the edge property $p \in \mathcal{E}$. A graph $\text{Graph}[\mathcal{V}, \mathcal{E}]$ also provides what is called a *triplets* view which represents edges as collections of triplets of the form $\text{RDD}[(\mathcal{V}, \mathcal{E}, \mathcal{V})]$. A triplet t will be denoted by the type *Triplet* and provides access to the source vertex (using $t.\text{srcAttr}$), the destiny ($t.\text{dstAttr}$) and the edge property ($t.\text{attr}$).

GraphX provides several built-in operators for graphs³⁰. We will use the following in the rest of the paper:

- `mapVertices(g: Graph[\mathcal{V}, \mathcal{E}], f: (Id, \mathcal{V}) \rightarrow \mathcal{V}): Graph[\mathcal{V}, \mathcal{E}]` maps every pair (id, v) in the vertices of g to ($\text{id}, f(v)$).
- `mapReduceTriples(g: Graph[\mathcal{V}, \mathcal{E}], m: ($\mathcal{V}, \mathcal{E}, \mathcal{V}$) \rightarrow [(Id, \mathcal{M})], r: (\mathcal{M}, \mathcal{M}) \rightarrow \mathcal{M}): RDD[(Id, \mathcal{M})]`, encodes the two-stage parallel computation process commonly known as mapReduce using the triplets view. It takes as parameters, a graph g , a map function m and a reduce function r .
In the first stage it applies the m to each triplet in the graph to generate a list of messages that will be sent to the vertices identified a given id .
In the second stage, it groups all the messages sent to a given vertex applying the reduce function r to each pair of messages.
- `joinVertices(g: Graph[\mathcal{V}, \mathcal{E}], msgs: RDD[(Id, \mathcal{M})], f: ($\text{Id}, \mathcal{V}, \mathcal{M}$) \rightarrow \mathcal{V}): Graph[\mathcal{V}, \mathcal{E}]`, joins the collection of messages sent to a the vertices which have a value (id, m) with the vertex v identified by id and replaces that vertex by $f(\text{id}, v, m)$.

The GraphX Pregel algorithm is defined iteratively where each iteration is usually called a superstep as follows:

Algorithm 1: Pregel algorithm pseudocode as implemented in GraphX

Input parameters:

```

g: Graph[ $\mathcal{V}, \mathcal{E}$ ]
initialMsg:  $\mathcal{M}$ 
vProg: ( $\text{Id}, \mathcal{V}, \mathcal{M}$ )  $\rightarrow$   $\mathcal{V}$ 
sendMsg: Triplet  $\rightarrow$  [( $\text{Id}, \mathcal{M}$ )]
mergeMsg: ( $\mathcal{M}, \mathcal{M}$ )  $\rightarrow$   $\mathcal{M}$ 

```

Output: $g: \text{Graph}[\mathcal{V}, \mathcal{E}]$

```

1 g = mapVertices(g,  $\lambda(\text{id}, v) \rightarrow v\text{Prog}(\text{id}, v, \text{initialMsg})$ )
2 msgs = mapReduceTriples(g, sendMsg, mergeMsg)
3 while size(msgs) > 0 do
4   g = joinVertices(g, msgs, vProg)
5   msgs = mapReduceTriples(g, sendMsg, mergeMsg)
6 return g

```

It takes as input a $\text{Graph}[\mathcal{V}, \mathcal{E}]$ and the following parameters:

³⁰<https://spark.apache.org/docs/latest/graphx-programming-guide.html>

- `initialMsg`: initial message sent to all the vertices
- `vprog` is the vertex program. It is run by each vertex at the beginning of the algorithm using the `initialMsg` and in each superstep using the collected messages sent by the neighbors in the previous superstep.
- `sendMsg` takes as parameter an triplet and returns an iterator with a pair (`id`, `msg`) where `id` represents the id of the vertex which will receive the message and `msg` represents the message that will be sent.
- `mergeMsg` is a function that defines how to merge 2 messages into one. This function must be associative and commutative, and will be invoked to collect all the messages that are sent to a vertex in each superstep.

We have implemented a ShEx validation algorithm based on the Pregel algorithm. The algorithm assumes that there is a ShEx schema $\langle \mathcal{L}, \delta \rangle$ where each label $l \in \mathcal{L}$ identifies a shape expression.

The algorithm annotates each node $n \in \mathcal{V}$ with a status map that represents the validation status with regards to some labels. The new nodes in the graph will be tuples (n, m) where $n \in \mathcal{V}$, and $m : \mathcal{L} \mapsto \text{Status}$ associates a status for each shape label.

A Status is defined as:

Status	::=	Undefined	Default status
		Ok	Node conforms
		Failed	Node doesn't conform
		Pending	Requested to conform
		WaitingFor(ds, oks, fs)	Waiting for some neighbours
			ds = list dependants neighbours
			oks = list of conformant neighbours
			fs = list of non conformant neighbours
			where ds, oks, failed $\in \mathcal{V} \times \mathcal{P} \times \mathcal{L}$

The status can be `Undefined` if there is no information yet (this is the default value) `Ok` if the node conforms to the shape identified by l , `Failed` if it doesn't conform to the shape, `Pending` if the node has been requested to be validated with that label or `WaitingFor(ds, oks, failed)` if the validation of node n depends on the validation of a set of neighbour nodes ds . Each neighbour node is represented by a triple (v, p, l) where v is the neighbour node, p is the property which links n with v , and l is the shape label that the node must conform. During the validation, we may receive information that some of those neighbour nodes have been validated or failed. That information is collected in the set `oks` which is the set of conforming neighbour nodes and `failed` is the set of failed neighbour nodes.

A message can be represented as a map which assigns to each label the following requests:

Msg	::=	Validate	Request to validate
		Checked(oks, fs)	Some neighbours have been checked
			oks = neighbours that have been checked as conformant
			fs = neighbours that have been checked as non-conformant
			where oks, fs $\in \mathcal{V} \times \mathcal{P} \times \mathcal{L}$
		WaitFor(ds)	Request to wait for some neighbours
			where ds $\in \mathcal{V} \times \mathcal{P} \times \mathcal{L}$

The ShEx+Pregel validation traversal is defined with the following pseudo-code.

The algorithm takes as input the parameters:

- `initialLabel` is the initial shape label that is requested to validate every node in the graph. In Shape Expressions, this label is usually annotated with the `start` keyword.
- `checkLocal` checks if the shape expression associated with a label can validate a node locally. It returns `Ok` if the node validates without further dependencies, `Failed`, if it doesn't validate, and `Pending(ls)` if the validation of the node depends on a list of shape labels ls .
- `checkNeighs` checks if the bag of neighbors of a node matches the regular bag expression

Algorithm 2: Pregel-based ShEx validation pseudocode**Input parameters:**

```

g: Graph[V, E]
initialLabel: L
checkLocal: (L, V) → Ok|Failed|Pending(Set[L])
checkNeighs: (L, Bag[(E, L)], Set[(E, L)]) → Ok|Failed
tripleConstraints: L → Set[(E, L)]

```

Output: $g: \text{Graph}[(V, L \mapsto \text{Status}), E]$

```
gs = mapVertices(g, λ(id, v)→(id, (v, λv→Undefined)))
```

```
gs = pregel(Validate, gs, vProg, sendMsg, mergeMsg)
```

```
gs = mapVertices(gs, checkUnsolved)
```

```
return gs
```

```
def checkUnsolved(v,m) = (v,m') where
```

$$m'(l) = \begin{cases} \text{checkNeighs}(l, \emptyset, \emptyset) & \text{if } m(l) = \text{Pending} \\ \text{checkNeighs}(l, \text{oks}, \text{fs} \cup \text{ds}) & \text{if } m(l) = \text{WaitingFor}(\text{ds}, \text{oks}, \text{fs}) \\ m(l) & \text{otherwise} \end{cases}$$

```
def vProg:(Id,V,M)→V = ...see ??
```

associated with the label in the schema.

- `tripleConstraints` returns the list of triple constraints associated with the shape expression indicated by the label.

The algorithm starts by mapping every node to the status which associates any label $l \in \mathcal{L}$ to undefined (`Undefined`). After that, it runs the iterative Pregel algorithm using the `vProg`, `sendMsg` and `mergeMsg` functions defined as above. Once the Pregel algorithm finishes, it replaces the status of any node that is pending or waiting for some neighbours by a last check based on the current information of the neighbours, assuming that if the node didn't receive information that a pending neighbour has validated, it means that there was no evidence of it's validation, and it failed.

`vProg` changes the status map of a node with regards to a label when it receives a message for that label. It can be defined as:

$vProg(id, (n, m), msg) = (n, m')$ where $m'(l) = m(l)$ except for the cases indicated by the following rules:

Figure 3.9 represents a state diagram which shows the different status that a node can have with regards to a shape label. Initially, all nodes have status `Undefined` until they get a message request to validate against some label. If it is possible to validate locally those nodes, then they will go directly to the end state which can be `Ok` or `Failed`. Otherwise, if their validation depends on the neighbours, they will enter the status `Pending` whose nodes are active in the Pregel algorithm and will be activated in the messages generation phase. If they receive a request to wait for some other nodes to be validated, they will go to the state `WaitingFor(ds, oks, fs)` which means that they are waiting for the status of the neighbour nodes `ds`.

In subsequent phases, they can receive notifications that some of those neighbour nodes have either been validated or not updating the corresponding values of `oks` and `fs`. Once all the pending neighbours have either been validated or failed, it will invoke `checkNeighs(l, oks, fs)` to check if the regular expression matches taking into account which neighbours conform or don't conform and passing to the state `Ok` or `Failed` which is inactive.

Once executed the Pregel algorithm, it is possible that some nodes are in state `Pending` and don't receive any message, which means that their validation depends on the existence of some arcs pointing to some neighbours and they didn't receive messages from those arcs, i.e. there are no arcs in the graph. In that case, a last step in the algorithm checks if those nodes can validate with an

$\frac{(\mathbf{n}, \mathbf{m}), l \rightsquigarrow \text{Validate} \quad \text{checkLocal}(l, \mathbf{n}) = r \in \{\text{Ok}, \text{Failed}\}}{\mathbf{m}(l) = s \in \{\text{Undefined}, \text{Pending}\}} \quad \mathbf{m}'(l) = r$
$\frac{(\mathbf{n}, \mathbf{m}), l \rightsquigarrow \text{Validate} \quad \text{checkLocal}(l, \mathbf{n}) = \text{Pending}(\text{ls})}{\mathbf{m}(l) = r \in \{\text{Undefined}, \text{Pending}\}} \quad \begin{array}{l} \mathbf{m}'(l) = \text{Undefined} \\ \mathbf{m}'(l') = \text{Pending} \forall l' \in \text{ls} \end{array}$
$\frac{(\mathbf{n}, \mathbf{m}), l \rightsquigarrow \text{Validate} \quad \mathbf{m}(l) = r \in \{\text{Ok}, \text{Failed}\}}{\mathbf{m}'(l) = r}$
$\frac{(\mathbf{n}, \mathbf{m}), l \rightsquigarrow \text{Validate} \quad \mathbf{m}(l) = \text{WaitingFor}(\text{ds}, \text{oks}, \text{fs})}{\mathbf{m}'(l) = \text{Ok}}$
$\frac{(\mathbf{n}, \mathbf{m}), l \rightsquigarrow \text{Checked}(\text{oks}, \text{fs}) \quad \text{ds} \setminus (\text{oks} \cup \text{fs}) \neq \emptyset \quad \mathbf{m}(l) = \text{WaitingFor}(\text{ds}, \text{oks}', \text{fs}')}{\mathbf{m}'(l) = \text{WaitingFor}(\text{ds}, \text{oks} \cup \text{oks}', \text{fs} \cup \text{fs}'')}$
$\frac{(\mathbf{n}, \mathbf{m}), l \rightsquigarrow \text{Checked}(\text{oks}, \text{fs}) \quad \text{ds} \setminus (\text{oks} \cup \text{fs}) = \emptyset \quad \mathbf{m}(l) = \text{WaitingFor}(\text{ds}, \text{oks}', \text{fs}')}{\mathbf{m}'(l) = \text{checkNeighs}(l, \text{oks} \cup \text{oks}', \text{fs} \cup \text{fs}'')}$

Table 3.13: Definition of \mathbf{v}_{Prog} for Pregel-based ShEx validation




Figure 3.9: State diagram representing the different states in vProg

$\frac{\langle (s, m_s), p, (o, m_o) \rangle \in \mathcal{G} \quad m_s(l) = \text{Pending} \quad \text{tcs}(l, \mathcal{S}) = \perp \xrightarrow{p} @l'}{(s, m_s), l \rightsquigarrow \text{WaitFor}((o, p, l'))}$			
$(o, m_o), l \rightsquigarrow \text{Validate}$			
$\frac{\langle (s, m_s), p, (o, m_o) \rangle \in \mathcal{G} \quad m_s(l) = \text{WaitingFor}(ds, oks, fs) \quad (o, p, l') \in ds \quad m_o(l') = \text{Ok}}{(s, m_s), l \rightsquigarrow \text{Checked}((o, p, l'), \emptyset)}$			
$\frac{\langle (s, m_s), p, (o, m_o) \rangle \in \mathcal{G} \quad m_s(l) = \text{WaitingFor}(ds, oks, fs) \quad (o, p, l') \in ds \quad m_o(l') = \text{Failed}}{(s, m_s), l \rightsquigarrow \text{Checked}(\emptyset, (o, p, l'))}$			

Table 3.14: Definition of sendMsg for Pregel-based ShEx validation

empty neighbourhood.

In order to define $\text{sendMsg}(\text{Triplet}):[(\text{Id}, \text{Msg})]$ we will use the notation $(x, m_x), l \rightsquigarrow \text{Msg}$ to represent that message Msg is sent to the node x with status map m_x for label l .

Table ?? represents the rules that declare which messages are sent for each triplet view which is represented as $\langle (s, m_s), p, (o, m_o) \rangle$ where (s, m_s) is the subject, p the predicate and (o, m_o) the object:

Finally mergeMsg merges the messages that arrive to the same node and can be defined as:

$$\text{mergeMsg}((n, m), l \rightsquigarrow \text{msg}_1, (n, m), l \rightsquigarrow \text{msg}_2) = (n, m), l \rightsquigarrow \text{msg}_1 \oplus \text{msg}_2$$

where

$$\begin{aligned}
 \text{Validate} \oplus y &= y \\
 \text{Validate} \oplus \text{Checked}(oks, fs) &= \text{Checked}(oks, fs) \\
 \text{Validate} \oplus \text{WaitFor}(ds) &= \text{WaitFor}(ds) \\
 \text{Checked}(oks, fs) \oplus \text{Validate} &= \text{Checked}(oks, fs) \\
 \text{Checked}(oks, fs) \oplus \text{Checked}(oks', fs') &= \text{Checked}(oks \cup oks', fs \cup fs') \\
 \text{Checked}(oks, fs) \oplus \text{WaitFor}(ds) &= \text{Checked}(oks \cup ds, fs \cup fs) \\
 \text{WaitFor}(ds) \oplus \text{Validate} &= \text{WaitFor}(ds) \\
 \text{WaitFor}(ds) \oplus \text{Checked}(oks, fs) &= \text{Checked}(oks \cup ds, fs) \\
 \text{WaitFor}(ds) \oplus \text{WaitFor}(ds') &= \text{WaitFor}(ds \cup ds')
 \end{aligned}$$

The algorithm presented in figure 2 required as parameters a function $\text{checkLocal}: (\mathcal{L}, \mathcal{V}) \rightarrow \text{Ok} | \text{Failed} | \text{Pending}(\text{Set}[\mathcal{L}])$ that returns Ok if it is possible to check that the node conforms to a shape label locally, Failed if it is possible to check that a node doesn't conform to a shape label locally,

and $\text{Pending}(ls)$ if the conformance of a node depends on the arcs in ls .

Figure 3 presents a possible implementation of checkLocal for WShEx.

Algorithm 3: Definition of $\text{checkLocal}:(\mathcal{L}, \mathcal{V}) \rightarrow \text{Ok} \mid \text{Failed} \mid \text{Pending}(\text{Set}[\mathcal{L}])$

```

def checkLocal( $l, n$ ) = checkLocal( $\delta(l), n$ )
def checkLocal( $se, n$ ) = match  $se$ 
  case  $se_1 \text{ AND } se_2 \Rightarrow \text{combine}(\text{checkLocal}(se_1, n), \text{checkLocal}(se_2, n))$ 
  case  $@l \Rightarrow \text{checkLocal}(\delta(l), n)$ 
  case  $\{ te \} \Rightarrow \text{checkLocal}(te, n)$ 
  case CLOSED  $\{ te \} \Rightarrow \text{checkLocal}(te, n)$ 
def checkLocal( $te, n$ ) = match  $te$ 
  case  $te_1; te_2 \Rightarrow \text{combine}(\text{checkLocal}(te_1, n), \text{checkLocal}(te_2, n))$ 
  case  $te_1 \mid te_2 \Rightarrow \text{combine}(\text{checkLocal}(te_1, n), \text{checkLocal}(te_2, n))$ 
  case  $te^* \Rightarrow \text{checkLocal}(te, n)$ 
  case  $\_ \xrightarrow{p} @l qs \Rightarrow \text{Pending}\{l\}$ 
def combine( $r_1, r_2$ ) = match ( $r_1, r_2$ )
  case ( $\text{Ok}, \text{Ok}$ )  $\Rightarrow \text{Ok}$ 
  case ( $\text{Ok}, \text{Pending}(ls)$ )  $\Rightarrow \text{Pending}(ls)$ 
  case ( $\text{Ok}, \text{Failed}$ )  $\Rightarrow \text{Failed}$ 
  case ( $\text{Pending}(ls), \text{Ok}$ )  $\Rightarrow \text{Pending}(ls)$ 
  case ( $\text{Pending}(ls_1), \text{Pending}(ls_2)$ )  $\Rightarrow \text{Pending}(ls_1 \cup ls_2)$ 
  case ( $\text{Pending}(ls), \text{Failed}$ )  $\Rightarrow \text{Failed}$ 
  case ( $\text{Failed}, \_$ )  $\Rightarrow \text{Failed}$ 

```

The definition of $\text{checkNeighs}:(\mathcal{L}, \text{Bag}[(\mathcal{E}, \mathcal{L})], \text{Set}[(\mathcal{E}, \mathcal{L})]) \rightarrow \text{Ok} \mid \text{Failed}$ is shown in figure 4.

Algorithm 4: Definition of $\text{checkNeighs}:(\mathcal{L}, \text{Bag}[(\mathcal{E}, \mathcal{L})], \text{Set}[(\mathcal{E}, \mathcal{L})]) \rightarrow \text{Ok} \mid \text{Failed}$

```

def checkNeighs( $l, w, fs$ ) = checkNeighs( $\delta(l), w, fs$ )
def checkNeighs( $se, w, fs$ ) = match  $se$ 
  case  $\text{cond} \Rightarrow \text{Ok}$ 
  case  $se_1 \text{ AND } se_2 \Rightarrow \text{checkNeighs}(se_1, w, fs) \wedge \text{checkNeighs}(se_2, w, fs)$ 
  case  $@l \Rightarrow \text{checkNeighs}(\delta(l), w, fs)$ 
  case  $\{ te \} \Rightarrow w \cong \text{rbe}(te)$ 
  case CLOSED  $\{ te \} \Rightarrow w \cong \text{rbe}(te) \wedge fs = \emptyset$ 
def rbe( $te$ ) = match  $te$ 
  case  $te_1; te_2 \Rightarrow \text{rbe}(te_1); \text{rbe}(te_2)$ 
  case  $te_1 \mid te_2 \Rightarrow \text{rbe}(te_1) \mid \text{rbe}(te_2)$ 
  case  $te^* \Rightarrow \text{rbe}(te)^*$ 
  case  $\_ \xrightarrow{p} @l qs \Rightarrow (p, l)$ 

```

Finally, $\text{tripleConstraints}:\mathcal{L} \rightarrow \text{Set}[(\mathcal{E}, \mathcal{L})]$ returns the triple constraints associated with a shape label. It is defined in figure 5

■ **Example 3.19 — Pregel+ShEx example.** As an example, we will use the Wikibase graph from example 3.4 to validate the ShEx schema from example 3.18. We replace the shape labels by their initial so we will use:

Algorithm 5: Definition of `tripleConstraints`: $\mathcal{L} \rightarrow \text{Set}[(\mathcal{E}, \mathcal{L})]$

```

def tripleConstraints(se)=match se
  case cond  $\Rightarrow \{\}$ 
  case  $se_1 \text{ AND } se_2 \Rightarrow \text{tripleConstraints}(se_1) \cup \text{tripleConstraints}(se_2)$ 
  case  $@l \Rightarrow \text{tripleConstraints}(\delta(l))$ 
  case  $\{te\} \Rightarrow \text{tripleConstraints}(te)$ 
  case CLOSED  $\{te\} \Rightarrow \text{tripleConstraints}(te)$ 

def tripleConstraints(te)=match te
  case  $te_1; te_2 \Rightarrow \text{tripleConstraints}(te_1) \cup \text{tripleConstraints}(te_2)$ 
  case  $te_1 | te_2 \Rightarrow \text{tripleConstraints}(te_1) \cup \text{tripleConstraints}(te_2)$ 
  case  $te^* \Rightarrow \text{tripleConstraints}(te)$ 
  case  $\_ \xrightarrow{p} @l \text{ qs} \Rightarrow \{(p, l)\}$ 

```

$\mathcal{L} = \{ \text{Researcher, Place, Country, Date, Human} \}$
 $\delta(R) = \{ _ \xrightarrow{\text{instanceOf}} @H; _ \xrightarrow{\text{birthDate}} @D; _ \xrightarrow{\text{birthPlace}} @P \}$
 $\delta(P) = \{ _ \xrightarrow{\text{country}} @C \}$
 $\delta(C) = \{ \}$
 $\delta(D) = \in \text{xsd:date}$
 $\delta(H) = \in \{\text{Human}\}$

The first step of the algorithm will send a message to every node requesting it to validate with the shape `Researcher`, and after running `vProg` the status of every node will be `Pending` on shape `Researcher`. In the first superstep, the messages that will be generated by each triple are³¹:

Triple	Messages
$(\text{timBl}, \text{birthPlace}, \text{London})$	$\text{timBl}, R \rightsquigarrow \text{WaitFor}((\text{London}, \text{birthPlace}, P))$ $\text{London}, P \rightsquigarrow \text{Validate}$
$(\text{timBl}, \text{instanceOf}, \text{Human})$	$\text{timBl}, H \rightsquigarrow \text{WaitFor}((\text{Human}, \text{instanceOf}, H))$ $\text{Human}, H \rightsquigarrow \text{Validate}$
$(\text{vintCerf}, \text{birthPlace}, \text{NewHaven})$	$\text{vintCerf}, P \rightsquigarrow \text{WaitFor}((\text{NewHaven}, \text{birthPlace}, P))$ $\text{Human}, H \rightsquigarrow \text{Validate}$
$(\text{vintCerf}, \text{instanceOf}, \text{Human})$	$\text{vintCerf}, H \rightsquigarrow \text{WaitFor}((\text{Human}, \text{instanceOf}, H))$ $\text{Human}, H \rightsquigarrow \text{Validate}$

After running `vProg` the status of all nodes except `timBl` and `vintCerf` with regards to the label `R` will be `Failed` because they will fail to check `Local`. The status of both `timBl` and `vintCerf` will be waiting for the validation of their neighborhood nodes.

After superstep 2, the messages generated will be:

Triple	Messages
$(\text{London}, \text{country}, \text{UK})$	$\text{London}, P \rightsquigarrow \text{WaitFor}((\text{UK}, \text{country}, C))$ $\text{UK}, C \rightsquigarrow \text{Validate}$
$(\text{timBl}, \text{instanceOf}, \text{Human})$	$\text{timBl}, R \rightsquigarrow \text{Checked}((\text{Human}, \text{instanceOf}, H), \{\})$
$(\text{vintCerf}, \text{instanceOf}, \text{Human})$	$\text{vintCerf}, P \rightsquigarrow \text{Checked}((\text{Human}, \text{instanceOf}, H), \{\})$
$(\text{vintCerf}, \text{birthPlace}, \text{NewHaven})$	$\text{vintCerf}, P \rightsquigarrow \text{Checked}((\{\}), (\text{NewHaven}, \text{birthPlace}, P))$

After running `vProg`, the status of `UK` will be `Ok` for shape label `C`, the status of `London` will be waiting for `UK` to validate as `C`, the status of `vintCerf` will be `Failed` for shape label `R` (it fails because the value `birthPlace` failed). In the third superstep, the messages generated will be:

Triple	Messages
$(\text{London}, \text{country}, \text{UK})$	$\text{London}, P \rightsquigarrow \text{Checked}((\text{UK}, \text{country}, C), \{\})$

Which will change the status of `London` to `Ok` for shape label `P`. In the fourth superstep, the

³¹For simplicity, for each node (x, m_x) we show only x and we omit qualifiers in the triples as they are always empty

messages that will be sent are:

Triple	Messages
(timBl , birthPlace , London)	timBl , $R \rightsquigarrow \text{Checked}((\text{London}, \text{birthPlace}, P), \{\})$

And after running `vProg` the status of **timBl** for shape label `R` will be `ok`. In the next superstep, no more messages will be sent and all the nodes will be inactive, finalizing the Pregel algorithm.

The nodes that have a `ok` status for some shape are:

Node	Shape Label
timBl	<code>R</code>
London	<code>P</code>
UK	<code>C</code>

And the generated subset will consist of collecting information about those nodes:

$\rho = \{$ (**timBl**, **instanceOf**, **Human**, $\{\}$),
 (**timBl**, **birthDate**, 1955, $\{\}$),
 (**timBl**, **birthPlace**, **London**, $\{\}$),
 (**London**, **country**, **UK**, $\{\}$),
 $\}$

Representing Wikidata in Spark GraphX

Spark GraphX supports a kind of property graphs where vertices and edges can have an associated value. The type `Graph[VD,ED]` is used to represent a graph whose vertices are pairs of values of type `(VertexId,VD)` where `VertexId=Long` represents a unique vertex identifier and `VD` represents the value associated with the vertex.

When representing Wikidata graphs in Spark GraphX it is necessary to take into account which entities will be represented as vertices. We opted to include as nodes in the graph only those nodes that can be subjects of statements, i.e. wikidata entities (items and properties), leaving out primitive values like literals, dates, etc. We separated the statements associated with an entity in two kind of statements: local statements, which are embedded inside the value of a node and whose values can be accessed without traversing the graph, and entity statements, whose values are other entities which have their corresponding vertex in the graph.

In this way, the `WShEx` also needs to distinguish triple expressions between local ones and entity ones.

3.7 Implementations and preliminary results

Although we have implemented some of the approaches presented in the paper, further work needs to be done in order to have all the possible implementations. In table 3.15, we present an overview of the approaches presented in the paper and their implementation.

	RDF graphs	Property graphs	Wikibase graphs
Formal definition	Done, ex.[26]	Done, [39, 63]	[This paper]
Description with Shape Expressions	ShEx [6, 63, 73]	PShEx [This paper]	WShEx [This paper]
Entity-generated subsets	–	–	WDumper
Matching generated subsets	–	–	WDumper
ShEx-based matching	–	–	WDSUB
ShEx+Slurping	shex.js PyShEx	–	–
ShEx + Pregel	–	–	SparkWDSUB

Table 3.15: Overview of implementation/formal definition status

The two implementations created by the authors of this paper are WDSUB and SparkWDSUB. They have been implemented in Scala and are mainly proof-of-concepts which have not yet been thoroughly tested and optimized so the results presented here are preliminary.

WDSUB takes as input a simple ShEx file containing the schema and another file with a Wikibase dump. It extracts the subset that matches the ShEx without taking into account shape references. It uses two approaches, one based on Wikidata toolkit³², and another one based on the fs2 library³³. We tested it using a virtual server running on XCP-ng 8.2 (CentOS 8 stream) with 32 cores and 64Gb of RAM and it was able to process the JSON Wikidata dump from 2021, which has 1.256,55Gb uncompressed, in 5h 15min.

SparkWDSUB implements the Pregel+ShEx approach. It has been built on top of the Spark GraphX library³⁴. In order to obtain greater flexibility, it defines a generic PSchema class³⁵ which defines a generic graph validation algorithm.

Given a target graph `Graph[VD,ED]` of vertex `VD` and edges `ED`, after running Pregel, it will return `ShapedGraph[VD,L,E,P]` which will contain information about the shapes labels `L` associated with a vertex `VD` in a graph with properties `P` and possible errors `E` and the `MsgMap[L,E,P]` class that represents the messages sent to a vertex.

The PSchema class is defined as follows:

```
class PSchema[VD, ED, L, E, P]
  (checkLocal: (L, VD) => Either[E, Set[L]],
   checkNeighs: (L, Bag[(P,L)], Set[(P,L)]) => Either[E, Unit],
   getTripleConstraints: L => List[(P,L)],
   cnvEdge: ED => P,
  ) {
  def vprog(id: VertexId,
            g: Shaped[VD, L, E, P],
            msg: MsgMap[L, E, P]): Shaped[VD, L, E, P] = {
    . . . }

  def sendMsg(t: EdgeTriplet[Shaped[VD, L, E, P], ED]
             ): Iterator[(VertexId, MsgMap[L, E, P])] = {
    . . . }

  def mergeMsg(p1: MsgMap[L,E,P],
               p2: MsgMap[L,E,P]): MsgMap[L,E,P] = {
    . . . }

  def runPregel(graph: Graph[VD,ED],
                initialLabel: L,
                maxIterations: Int = Int.MaxValue,
                ): Graph[Shaped[VD,L,E,P], ED] = {
    Pregel(shapedGraph(graph),
            initialMsg(initialLabel),
            maxIterations)(vprog, sendMsg, mergeMsg)
    .mapVertices(checkRemaining)
  }
}
```

where `checkRemaining` checks which of the nodes with Pending status are valid or not.

³²https://www.mediawiki.org/wiki/Wikidata_Toolkit

³³<https://fs2.io/>

³⁴<http://spark.apache.org/graphx/>

³⁵<https://github.com/weso/sparkwdsb/blob/master/src/main/scala/es/weso/pschema/PSchema.scala>

The previous interface enables the possible implementation with different validation languages like ShEx, PShEx or WShEx.

SparkWDSUB currently offers an implementation for a simplified version of WShEx which implements the `checkLocal`, `checkNeighs`, `getTripleConstraints` and `cnvEdge` to convert an edge `ED` into a property `P`.

We have run an experiment on AWS using 512 cores, 3.904Gb RAM and 121.600Gb hard disk, and it was possible to generate subsets for the 2014 Wikidata dump (31.3 GB) in 3 minutes, while with the 2021 Wikidata dump (1.256,55 Gb uncompressed) it took 36 minutes.

In the experiments we used the following ShEx schema to obtain cities:

```
prefix wde: <http://www.wikidata.org/entity/>

Start = @<City>

<City> {
  wde:P31 @<CityCode>
}
<CityCode> [ wde:Q515 ]
```

3.8 Related work

Knowledge graphs

An introduction to Knowledge graphs is provided by [31], which cites other books [21, 34, 59] and surveys like [2, 23, 60, 79, 80, 81]. In this paper, we follow two of the graph models provided in that survey: directed labeled graphs, which we call RDF-graphs, and property graphs; and add a new one: wikibase graphs. Our definition of wikibase graphs has been inspired by MARS (Multi-Attributed Relational Structures) [52], which are a generalized notion of property graphs. In that paper, they also define MAPL (Multi-Attributed Predicate Logic) as a logical formalism that can be used for ontological reasoning.

Knowledge graph descriptions

Since the appearance of ShEx in 2014, there has been a lot of interest about RDF validation and description. In 2017, the data shapes working group proposed SHACL (Shapes Constraint Language) as a W3C recommendation [35]. Although SHACL can be used to describe RDF, its main purpose is to validate and check constraints about RDF data makes it less usable to describe RDF subsets.

ShEx was adopted by Wikidata in 2019 to define entity schemas [76]. We consider that ShEx adapts better to describe data models than SHACL, which is more focused on constraint violations. A comparison between both is provided in [38] while in [39], a simple language is defined that can be used as a common subset of both.

Improving quality of Knowledge graphs in general, and Wikidata in particular, has been the focus of some recent research like [61, 70, 77].

Following the work on MARS, there has been some recent work about adding an inference layer on top of Wikidata. The project SQID [51] combines inference and visualization to create a Wikidata browser. Another possibility that has been explored is to use MARS reasoning to define constraints [47].

Big data processing and graphs

There has been a lot of interest in the last decade to develop scalable algorithms that can process big data graphs. In 2010, Pregel was proposed by Google [43] as a suitable model for large-scale graph computing. Following that publication, several systems were developed like GraphLab [42], PowerGraph [24] and GraphX [25] which followed the lemma *thinking like a vertex*[53] where scalable graph are based on local iterations over the nodes of a graph and their neighbors.

GraphX was a framework that internally represented graphs using Apache Spark's Resilient Distributed Datasets (RDDs) [82] enabling to implement graph-parallel abstractions and algorithms like Pregel. A functional definition of Spark using Haskell has been proposed in [13]. It would be interesting to use that functional specification to prove the correctness of the algorithm proposed in this paper. Another related line of work is the creation of domain specific languages to facilitate encoding of Pregel-based algorithms like Palgol [83] or Fregel [19].

Knowledge graphs subsets

Although it is possible to create subsets of RDF graphs using SPARQL construct queries, the approach usually requires some scripts to launch the queries as SPARQL doesn't support recursion so it is not possible to represent cyclic data models. There has been a proposal to extend SPARQL with recursion [65], but it is not part of most existing SPARQL processors.

RDFSlice [48, 49] was proposed as a system that generated RDF data fragments from large endpoints like DBpedia. It defines a subset of SPARQL called sliceSPARQL. A new version, called Torpedo, was proposed in [50], which improves the performance and adds further expressivity. The use of SPARQL to generate subsets is one important difference with the work presented in this paper. We consider that ShEx improves the expressiveness and usability of SPARQL to describe data models and subsets as it allows cyclic or recursive data models and has a declarative syntax that is specifically defined for such endeavor.

The creation of Wikidata subsets has been a topic of interest since the 12th International SWAT4HCLS Conference³⁶. It was later selected as a topic in the Elixir Europe Biohackathon 2020³⁷ and the SWAT4HCLS 2021 hackathon from which a preprint was generated that collects the different approaches proposed [40].

One of the approaches was WDumper³⁸, which was created as a tool that processed Wikidata dumps and generates subsets from those dumps. It takes two inputs: a JSON compressed dump and a JSON configuration file that describes the different filters, and generates as output an RDF compressed dump. The tool can be run as a web service locally and is also deployed at <https://tools.wmflabs.org/wdumps>. It also contains a web service that allows the user to introduce the different filters filling a form which generates a dump generation request that is added to a queue. It is possible to see the list of previously requested dumps. Once the dump has been generated, it can be uploaded to Zenodo. WDumper is divided in two main modules, the backend, which has been implemented in Java using the Wikidata Toolkit library³⁹ and the frontend that has been implemented in Typescript. The use of WDumper to generate Wikidata subsets is described in [32] where 4 subsets are created about the topics: politicians, military politicians, UK universities and GeneWiki data. That paper also presents several use case scenarios and discusses some strengths and weaknesses. In this paper, we present a formal definition of WDumper in the context of other subset generation approaches like the ShEx-based ones.

³⁶This page was created to collect information: https://www.wikidata.org/wiki/Wikidata:WikiProject_Schemas/Subsetting

³⁷<https://github.com/elixir-europe/BioHackathon-projects-2020/tree/master/projects/35>

³⁸<https://github.com/bennofs/wdumper>

³⁹<https://github.com/Wikidata/Wikidata-Toolkit>

The Python library WikidataSets [8] generates Wikidata subsets from specific topics. In the paper the authors generated subsets for the following topics: humans, countries, companies, animal species and films. The tool obtains items following the instances of a topic or subclasses of the topic.

KGTK (Knowledge graph toolkit) [33] is a tool that works with knowledge graphs by defining a common format called KGTK format based on hypergraphs. It is possible to import and export data from different formats like Wikidata or ConceptNet, do several operations over those graphs like: validation, cleaning, graph manipulation (sort, column removal, edge filtering) and graph merging (join, cat) operations. The tool also supports graph querying and analytics operations. Given that KGTK can take as input Wikidata dumps and generate Wikidata dumps as output, it is possible to use KGTK to generate subsets of Wikidata. More recently, the authors have published a paper where they apply KGTK to create personalized versions of wikidata using a query language that they call Kypher[11], which is an adapted version of Cypher for KGTK. Internally, it uses a tabular data model which allows to translate Kypher queries to SQLite⁴⁰. According to the paper, it can create very efficient queries processing the whole Wikidata in a laptop system. The main difference with our approach is that we use Shape Expressions to describe the data model of the subset. Further work could be done to see if it was possible to translate Shape Expression definitions to Kypher.

3.9 Conclusions

In this paper, we have presented three formal models for knowledge graphs: RDF-based graphs, property graphs and wikibase graphs. We also defined a shape expressions language that can be used to describe and validate data in those models: ShEx for RDF-based graphs, PShEx for property graphs and WShEx for wikibase graphs.

Given the success of knowledge graphs, their size has been increasing in a way that it is not possible to process their contents using conventional tools making it necessary to have some mechanism to extract subsets from them. Finally, we review some approaches to generate subsets from Wikibase graphs. The first two approaches, entity-matching and simple matching can be implemented by processing Wikibase dumps sequentially. The third approach takes as input a WShEx schema, and matches the different entities and their local neighbors with the shapes ignoring shape references. This approach can be used to efficiently process dumps sequentially but doesn't take into account the relations in the graph. The fourth approach, ShEx+Slurp, adds an option to the ShEx processor to collect the visited triples while it is validating the data. This approach can do graph traversal but also require a large number of requests for nodes neighbors which may not be possible to apply it behind endpoints that limit the number of requests. The final approach that we proposed applies the Pregel algorithm to validate all nodes. This approach does graph traversal and can also handle large graphs.

All the approaches have been implemented, although not all of them within the same system, so a proper comparison is not yet possible. Further work needs to be done on improving the implementations, applying them to some use cases and assessing their advantages and challenges.


3.10 Acknowledgments

We want to thank Eric Prud'hommeaux, Andra Waagmeester, Tom Baker, Kat Thornton and Iovka Boneva as well as all the members of the Shape Expressions Community Group. The Wikidata and Wikibase community provided a great environment and software whose potential we are still discovering, special thanks to Lydia Pintscher, Adam Shorland, Daniel Mietchen, Egon Willighagen, Finn Årup Nielsen, etc. Some parts of this research took inspiration from several

⁴⁰<https://www.sqlite.org/>

events like 2019 and 2020 biohackathons and SWAT4HCLS. Special thanks to Dan Brickley for helping with the coordination and insights on the Wikidata subsetting project. Markus Krötzsch's lectures and papers have also been a source of inspiration for the Wikibase formal model and Tim Berners-lee's running example.

Guillermo Facundo Colunga, Pablo Menéndez Suárez, Jorge Álvarez Fidalgo and Daniel Fernández Álvarez from the WESO research group have also helped with the experiments on Wikidata Subsetting and Scholia.



Bibliography

- [1] Bilal Abu-Salih. “Domain-specific knowledge graphs: A survey”. In: *Journal of Network and Computer Applications* 185 (July 2021), page 103076. DOI: 10.1016/j.jnca.2021.103076 (cited on page 13).
- [2] Tareq Al-Moslmi et al. “Named Entity Extraction for Knowledge Graphs: A Literature Overview”. In: *IEEE Access* 8 (2020), pages 32862–32881. DOI: 10.1109/ACCESS.2020.2973928. URL: <https://doi.org/10.1109/ACCESS.2020.2973928> (cited on page 47).
- [3] Renzo Angles et al. “Foundations of Modern Query Languages for Graph Databases”. In: *ACM Computing Surveys* 50.5 (2017), 68:1–68:40. DOI: 10.1145/3104031 (cited on page 13).
- [4] Sören Auer et al. “DBpedia: A Nucleus for a Web of Open Data”. In: *The Semantic Web, 6th International Semantic Web Conference, 2nd Asian Semantic Web Conference, ISWC 2007 + ASWC 2007, Busan, Korea, November 11-15, 2007*. Edited by Karl Aberer et al. Volume 4825. Lecture Notes in Computer Science. Springer, 2007, pages 722–735. ISBN: 978-3-540-76297-3 (cited on page 10).
- [5] Adrian Bielefeldt, Julius Gonsior, and Markus Krötzsch. “Practical Linked Data Access via SPARQL: The Case of Wikidata”. In: *Proceedings of the WWW2018 Workshop on Linked Data on the Web (LDOW-18)*. Edited by Tim Berners-Lee et al. Volume 2073. CEUR Workshop Proceedings. CEUR-WS.org, 2018 (cited on page 22).
- [6] Iovka Boneva, Jose Emilio Labra Gayo, and Eric Prud’hommeaux. “Semantics and Validation of Shapes Schemas for RDF”. In: *International Semantic Web Conference*. 2017 (cited on pages 13, 23, 45, 60, 62).
- [7] Iovka Boneva, Jose Emilio Labra Gayo, and Eric G. Prud’hommeaux. “Semantics and Validation of Shapes Schemas for RDF”. In: *The Semantic Web - ISWC 2017 - 16th International Semantic Web Conference, Vienna, Austria, October 21-25, 2017, Proceedings, Part I*. Edited by Claudia d’Amato et al. Volume 10587. Lecture Notes in Computer Science. Springer, Oct. 2017, pages 104–120. ISBN: 978-3-319-68287-7 (cited on pages 22, 25).

- [8] Armand Boschini and Thomas Bonald. “WikiDataSets: Standardized sub-graphs from Wikidata”. In: *arXiv:1906.04536 [cs, stat]* (Oct. 2019). arXiv: 1906.04536. URL: <http://arxiv.org/abs/1906.04536> (cited on page 49).
- [9] Sebastian Burgstaller-Muehlbacher et al. “Wikidata as a semantic framework for the Gene Wiki initiative”. In: *Database 2016* (2016), baw015. DOI: 10.1093/database/baw015 (cited on pages 8, 18).
- [10] Leyla Jael Garcia Castro et al. “Data validation and schema interoperability”. In: (Apr. 2020). DOI: 10.37044/osf.io/8qdse (cited on page 8).
- [11] H. Chalupsky et al. “Creating and Querying Personalized Versions of Wikidata on a Laptop”. In: *The 2nd Wikidata Workshop* (2021). URL: <https://arxiv.org/abs/2108.07119> (cited on page 49).
- [12] Spencer Chang. *Scaling Knowledge Access and Retrieval at Airbnb*. AirBnB Medium Blog. <https://medium.com/airbnb-engineering/scaling-knowledge-access-and-retrieval-at-airbnb-665b6ba21e95>. Sept. 2018 (cited on page 10).
- [13] Yu-Fang Chen et al. “An Executable Sequential Specification for Spark Aggregation”. In: *Networked Systems*. Springer International Publishing, 2017, pages 421–438. DOI: 10.1007/978-3-319-59647-1_31 (cited on page 48).
- [14] Constance Crompton et al. “Familiar Wikidata: The Case for Building a Data Source We Can Trust”. en. In: (2020). DOI: 10.48404/POP.2020.02 (cited on page 18).
- [15] Richard Cyganiak, David Wood, and Markus Lanthaler. *RDF 1.1 Concepts and Abstract Syntax, W3C Recommendation 25 February 2014*. W3C Recommendation. World Wide Web Consortium, Feb. 2014. URL: <https://www.w3.org/TR/2014/REC-rdf11-concepts-20140225/> (cited on pages 13, 16).
- [16] Richard Cyganiak, David Wood, and Markus Lanthaler. *RDF-star and SPARQL-star*. Draft Community Group Report. World Wide Web Consortium, July 2021. URL: <https://w3c.github.io/rdf-star/cg-spec> (cited on page 16).
- [17] Deepika Devarajan. *Happy Birthday Watson Discovery*. IBM Cloud Blog. <https://www.ibm.com/blogs/bluemix/2017/12/happy-birthday-watson-discovery/>. Dec. 2017 (cited on page 10).
- [18] Martin Dürst and Michel Suignard. *Internationalized Resource Identifiers (IRIs)*. RFC 3987. Internet Engineering Task Force, Jan. 2005. URL: <http://www.ietf.org/rfc/rfc3987.txt> (cited on page 14).
- [19] Kento Emoto et al. “Think like a vertex, behave like a function! a functional DSL for vertex-centric big graph processing”. In: 51.9 (Dec. 2016), pages 200–213. DOI: 10.1145/3022670.2951938 (cited on page 48).
- [20] Fredo Erxleben et al. “Introducing Wikidata to the Linked Data Web”. In: *Proceedings of the 13th International Semantic Web Conference (ISWC 2014)*. Edited by Peter Mika et al. Volume 8796. LNCS. Springer, Oct. 2014, pages 50–65. DOI: 10.1007/978-3-319-11964-9_4 (cited on pages 15, 16, 21).
- [21] Dieter Fensel et al. *Knowledge Graphs - Methodology, Tools and Selected Use Cases*. Springer, 2020. ISBN: 978-3-030-37438-9. DOI: 10.1007/978-3-030-37439-6 (cited on page 47).
- [22] Nadime Francis et al. “Cypher”. In: *Proceedings of the 2018 International Conference on Management of Data*. ACM, May 2018. DOI: 10.1145/3183713.3190657 (cited on page 17).


- [23] Genet Asefa Gesese, Russa Biswas, and Harald Sack. “A Comprehensive Survey of Knowledge Graph Embeddings with Literals: Techniques and Applications”. In: *Proceedings of the Workshop on Deep Learning for Knowledge Graphs (DL4KG2019)*. 2019, pages 31–40 (cited on page 47).
- [24] Joseph E. Gonzalez et al. “PowerGraph: Distributed Graph-Parallel Computation on Natural Graphs”. In: *10th USENIX Symposium on Operating Systems Design and Implementation (OSDI 12)*. Hollywood, CA: USENIX Association, Oct. 2012, pages 17–30. ISBN: 978-1-931971-96-6. URL: <https://www.usenix.org/conference/osdi12/technical-sessions/presentation/gonzalez> (cited on page 48).
- [25] Joseph E. Gonzalez et al. “GraphX: Graph Processing in a Distributed Dataflow Framework”. In: *11th USENIX Symposium on Operating Systems Design and Implementation (OSDI 14)*. Broomfield, CO: USENIX Association, Oct. 2014, pages 599–613. ISBN: 978-1-931971-16-4. URL: <https://www.usenix.org/conference/osdi14/technical-sessions/presentation/gonzalez> (cited on page 48).
- [26] Claudio Gutierrez, Carlos Hurtado, and Alberto Mendelzon. “Formal aspects of querying RDF databases”. In: *SWDB’03: Proceedings of the First International Conference on Semantic Web and Databases*. Berlin, Germany: CEUR-WS.org, 2003 (cited on pages 45, 59, 62).
- [27] Steve Harris, Andy Seaborne, and Eric Prud’hommeaux. *SPARQL 1.1 Query Language, W3C Recommendation 21 March 2013*. W3C Recommendation. World Wide Web Consortium, Mar. 2013. URL: <https://www.w3.org/TR/2013/REC-sparql11-query-20130321/> (cited on page 10).
- [28] Qi He, Bee-Chung Chen, and Deepak Agarwal. *Building The LinkedIn Knowledge Graph*. LinkedIn Blog. <https://engineering.linkedin.com/blog/2016/10/building-the-linkedin-knowledge-graph>. Oct. 2016 (cited on page 10).
- [29] Daniel Hernández, Aidan Hogan, and Markus Krötzsch. “Reifying RDF: What Works Well With Wikidata?” In: *Proceedings of the 11th International Workshop on Scalable Semantic Web Knowledge Base Systems*. Edited by Thorsten Liebig and Achille Fokoue. Volume 1457. CEUR Workshop Proceedings. CEUR-WS.org, 2015, pages 32–47 (cited on page 15).
- [30] Aidan Hogan et al. “Everything you always wanted to know about blank nodes”. In: *Journal of Web Semantics* 27–28 (2014), pages 42–69. DOI: 10.1016/j.websem.2014.06.004 (cited on page 14).
- [31] Aidan Hogan et al. “Knowledge Graphs”. In: *ACM Computing Surveys* 54.4 (July 2021), pages 1–37. DOI: 10.1145/3447772 (cited on pages 13, 47, 61).
- [32] Seyed Amir Hosseini Beghaeiraveri, Alasdair J. G. Gray, and Fiona J. McNeill. “Experiences of Using WDumper to Create Topical Subsets from Wikidata”. English. In: *CEUR Workshop Proceedings* 2873 (June 2021). ISSN: 1613-0073 (cited on pages 7, 48).
- [33] Filip Ilievski et al. “KGTK: A Toolkit for Large Knowledge Graph Manipulation and Analysis”. In: *Lecture Notes in Computer Science*. Springer International Publishing, 2020, pages 278–293. DOI: 10.1007/978-3-030-62466-8_18 (cited on page 49).
- [34] Mayank Kejriwal. *Domain-Specific Knowledge Graph Construction*. Springer Briefs in Computer Science. Springer, 2019. ISBN: 978-3-030-12374-1. DOI: 10.1007/978-3-030-12375-8 (cited on page 47).
- [35] Holger Knublauch and Dimitris Kontokostas. *Shapes Constraint Language (SHACL), W3C Recommendation 20 July 2017*. W3C Recommendation. World Wide Web Consortium, June 2017. URL: <https://www.w3.org/TR/2017/REC-shacl-20170720/> (cited on page 47).

- [36] Arun Krishnan. *Making search easier: How Amazon's Product Graph is helping customers find products more easily*. Amazon Blog. <https://blog.aboutamazon.com/innovation/making-search-easier>. Aug. 2018 (cited on page 10).
- [37] Jose Emilio Labra Gayo, Daniel Fernández Álvarez, and Herminio García-González. "RDF-Shape: An RDF Playground Based on Shapes". In: *Proceedings of the ISWC 2018 Posters and Demonstrations, Industry and Blue Sky Ideas Tracksco-located with 17th International Semantic Web Conference*. Volume 2180. CEUR Workshop Proceedings. 2018 (cited on page 14).
- [38] Jose Emilio Labra Gayo et al. *Validating RDF Data*. Volume 7. Synthesis Lectures on the Semantic Web: Theory and Technology. Morgan & Claypool, Sept. 2017, pages 1–328. DOI: 10.2200/s00786ed1v01y201707wbe016. URL: <https://doi.org/10.2200/s00786ed1v01y201707wbe016> (cited on page 47).
- [39] Jose Emilio Labra Gayo et al. "Challenges in RDF Validation". In: *Current Trends in Semantic Web Technologies: Theory and Practice*. Edited by Giner Alor-Hernández et al. Studies in Computational Intelligence. Springer, 2019, pages 121–151. DOI: 10.1007/978-3-030-06149-4_6 (cited on pages 45, 47, 59, 62).
- [40] Jose Emilio Labra Gayo et al. "Knowledge graphs and wikidata subsetting". In: *BioHackrXiv Preprints* (2021). DOI: <https://doi.org/10.37044/osf.io/wu9et> (cited on pages 7, 48).
- [41] Jens Lehmann et al. "DBpedia - A large-scale, multilingual knowledge base extracted from Wikipedia". In: *Semantic Web Journal* 6.2 (2015), pages 167–195 (cited on page 13).
- [42] Yucheng Low et al. "Distributed GraphLab". In: *Proceedings of the VLDB Endowment* 5.8 (Apr. 2012), pages 716–727. DOI: 10.14778/2212351.2212354 (cited on page 48).
- [43] Grzegorz Malewicz et al. "Pregel: a system for large-scale graph processing". In: *Proceedings of the 2010 ACM SIGMOD International Conference on Management of data*. ACM, June 2010. DOI: 10.1145/1807167.1807184 (cited on pages 11, 37, 48, 60).
- [44] Stanislav Malyshev et al. "Getting the Most out of Wikidata: Semantic Technology Usage in Wikipedia's Knowledge Graph". In: *Proceedings of the 17th International Semantic Web Conference (ISWC'18)*. Edited by Denny Vrandečić et al. Volume 11137. LNCS. Springer, 2018, pages 376–394 (cited on page 22).
- [45] Stanislav Malyshev et al. "Getting the most out of Wikidata: Semantic technology usage in Wikipedia's knowledge graph". In: *The Semantic Web - ISWC 2018 - 17th International Semantic Web Conference, Monterey, CA, USA, October 8-12*. Springer, 2018, pages 376–394 (cited on page 18).
- [46] Frank Manola and Eric Miller. *Resource Description Framework: RDF Primer*. W3C Recommendation. World Wide Web Consortium, Feb. 2004. URL: <https://www.w3.org/TR/2004/REC-rdf-primer-20040210> (cited on page 15).
- [47] David Martin and Peter P. Schneider. "Wikidata Constraints on MARS". In: *Proceedings of the 1st Wikidata Workshop (Wikidata 2020)*. Volume 2773. 2020. URL: <http://ceur-ws.org/Vol-2773/paper-12.pdf> (cited on page 47).
- [48] Edgard Marx et al. "Large-scale RDF Dataset Slicing". In: *7th IEEE International Conference on Semantic Computing, September 16-18, 2013, Irvine, California, USA*. 2013. URL: http://svn.aksw.org/papers/2013/ICSC_SLICE/public.pdf (cited on page 48).
- [49] Edgard Marx et al. "Towards an Efficient RDF Dataset Slicing". In: *International Journal of Semantic Computing* 07.04 (2013), pages 455–477. DOI: 10.1142/S1793351X13400151 (cited on page 48).

- [50] Edgard Marx et al. “Torpedo: Improving the State-of-the-Art RDF Dataset Slicing”. In: *11th IEEE International Conference on Semantic Computing, Jan 30-Feb 1, 2017, San Diego, California, USA*. 2017. URL: https://svn.aksw.org/papers/2017/Torpedo_ICSC/public.pdf (cited on page 48).
- [51] Maximilian Marx and Markus Krötzsch. “SQID: Towards Ontological Reasoning for Wikidata”. In: *Proceedings of the ISWC 2017 Posters & Demonstrations Track*. Edited by Nadeschda Nikitina and Dezhao Song. CEUR Workshop Proceedings. CEUR-WS.org, Oct. 2017 (cited on page 47).
- [52] Maximilian Marx, Markus Krötzsch, and Veronika Thost. “Logic on MARS: Ontologies for generalised property graphs”. In: *Proceedings of the 26th International Joint Conference on Artificial Intelligence (IJCAI’17)*. Edited by Carles Sierra. International Joint Conferences on Artificial Intelligence, Aug. 2017, pages 1188–1194. DOI: 10.24963/ijcai.2017/165 (cited on pages 19, 47, 59).
- [53] Robert Ryan McCune, Tim Weninger, and Greg Madey. “Thinking Like a Vertex”. In: *ACM Computing Surveys* 48.2 (Nov. 2015), pages 1–39. DOI: 10.1145/2818185 (cited on page 48).
- [54] Justin J. Miller. “Graph Database Applications and Concepts with Neo4j”. In: *Proceedings of the Southern Association for Information Systems Conference, Atlanta, GA, USA March 23rd-24th, 2013*. AIS eLibrary, 2013, pages 141–147. URL: <https://aisel.aisnet.org/sais2013/24> (cited on page 10).
- [55] Vinh Nguyen, Olivier Bodenreider, and Amit Sheth. “Don’t like RDF reification?” In: *Proceedings of the 23rd international conference on World wide web - WWW ’14*. ACM Press, 2014. DOI: 10.1145/2566486.2567973 (cited on page 15).
- [56] Finn Årup Nielsen, Daniel Mietchen, and Egon Willighagen. “Scholia, Scientometrics and Wikidata”. In: *Lecture Notes in Computer Science*. Springer International Publishing, 2017, pages 237–259. DOI: 10.1007/978-3-319-70407-4_36 (cited on page 10).
- [57] Natasha F. Noy et al. “Industry-scale Knowledge Graphs: Lessons and Challenges”. In: *ACM Queue* 17.2 (2019), page 20 (cited on pages 10, 13).
- [58] Ora Lassila and Ralph R. Swick. *Resource Description Framework (RDF) Model and Syntax Specification*. <https://www.w3.org/TR/1999/REC-rdf-syntax-19990222/>. 1999. URL: <https://www.w3.org/TR/1999/REC-rdf-syntax-19990222/> (cited on page 10).
- [59] Jeff Z. Pan et al., editors. *Exploiting Linked Data and Knowledge Graphs in Large Organizations*. Springer, 2017. ISBN: 978-3-319-45652-2. DOI: 10.1007/978-3-319-45654-6 (cited on page 47).
- [60] Heiko Paulheim. “Knowledge graph refinement: A survey of approaches and evaluation methods”. In: *Semantic Web Journal* 8.3 (2017), pages 489–508. DOI: 10.3233/SW-160218 (cited on page 47).
- [61] Alessandro Piscopo and Elena Simperl. “What we talk about when we talk about wikidata quality”. In: *ACM*, Aug. 2019. DOI: 10.1145/3306446.3340822 (cited on page 47).
- [62] R. J. Pittman et al. *Cracking the Code on Conversational Commerce*. eBay Blog. <https://www.ebayinc.com/stories/news/cracking-the-code-on-conversational-commerce/>. Apr. 2017 (cited on page 10).

- [63] Eric Prud'hommeaux, Jose Emilio Labra Gayo, and Harold Solbrig. "Shape Expressions: An RDF Validation and Transformation Language". In: *Proceedings of the 10th International Conference on Semantic Systems, SEMANTICS 2014, Leipzig, Germany, September 4-5, 2014*. Edited by Harald Sack et al. ACM Press, Sept. 2014, pages 32–40. ISBN: 978-1-4503-2927-9. DOI: 10.1145/2660517.2660523 (cited on pages 10, 22, 45, 59, 62).
- [64] Eric Prud'hommeaux et al. *Shape Expressions Language 2.0*. Apr. 2017. URL: <https://shexspec.github.io/spec/> (cited on pages 13, 22, 23).
- [65] Juan L. Reutter, Adrián Soto, and Domagoj Vrgoč. "Recursion in SPARQL". In: *International Semantic Web Conference (ISWC)*. Springer International Publishing, 2015, pages 19–35. DOI: 10.1007/978-3-319-25007-6_2 (cited on page 48).
- [66] Marko A. Rodriguez and Peter Neubauer. "Constructions from dots and lines". In: *Bulletin of the American Society for Information Science and Technology* 36.6 (Aug. 2010), pages 35–41. DOI: 10.1002/bult.2010.1720360610 (cited on page 10).
- [67] Edward W. Schneider. "Course Modularization Applied: The Interface System and Its Implications For Sequence Control and Data Analysis". In: *Association for the Development of Instructional Systems (ADIS), Chicago, Illinois, April 1972*. 1973 (cited on page 13).
- [68] Dan Scott and Stacy Allison-Cassin. "Wikidata: a platform for your library's linked open data". In: *Code4Lib Journal* 40 (May 2018). URL: <https://journal.code4lib.org/articles/13424> (cited on page 18).
- [69] Philipp Seifer, Ralf Lämmel, and Steffen Staab. "ProGS: Property Graph Shapes Language (Extended Version)". In: *International Semantic Web Conference*. Volume 12922. Springer, Oct. 2021, pages 392–401. DOI: https://doi.org/10.1007/978-3-030-88361-4_23. arXiv: 2107.05566 [cs.DB] (cited on pages 16, 59).
- [70] Kartik Shenoy et al. "A Study of the Quality of Wikidata". URL: <https://arxiv.org/pdf/2107.00156.pdf> (cited on page 47).
- [71] Saurabh Shrivastava. *Bring rich knowledge of people, places, things and local businesses to your apps*. Bing Blogs. <https://blogs.bing.com/search-quality-insights/2017-07/bring-rich-knowledge-of-people-places-things-and-local-businesses-to-your-apps>. July 2017 (cited on page 10).
- [72] Amit Singhal. *Introducing the Knowledge Graph: things, not strings*. Google Blog. <https://www.blog.google/products/search/introducing-knowledge-graph-things-not/>. May 2012 (cited on pages 10, 13).
- [73] Slawek Staworko et al. "Complexity and Expressiveness of ShEx for RDF". In: *18th International Conference on Database Theory, ICDT 2015*. Volume 31. LIPIcs. Schloss Dagstuhl - Leibniz-Zentrum fuer Informatik, 2015, pages 195–211 (cited on pages 12, 13, 45, 62).
- [74] Fabian M. Suchanek, Gjergji Kasneci, and Gerhard Weikum. "YAGO: A core of semantic knowledge unifying WordNet and Wikipedia". In: *Proceedings of the 16th International Conference on World Wide Web, WWW 2007, Banff, Alberta, Canada, May 8-12, 2007*. Edited by Carey L. Williamson et al. ACM Press, May 2007, pages 697–706. ISBN: 978-1-59593-654-7 (cited on pages 10, 13).
- [75] Thomas Pellissier Tanon et al. "From Freebase to Wikidata". In: *Proceedings of the 25th International Conference on World Wide Web*. International World Wide Web Conferences Steering Committee, Apr. 2016. DOI: 10.1145/2872427.2874809 (cited on page 18).

- [76] Katherine Thornton et al. “Using Shape Expressions (ShEx) to Share RDF Data Models and to Guide Curation with Rigorous Validation”. In: *The Semantic Web - 16th International Conference, ESWC 2019, Portorož, Slovenia, June 2-6, 2019, Proceedings*. Edited by Pascal Hitzler et al. Volume 11503. Lecture Notes in Computer Science. Springer, June 2019, pages 606–620. ISBN: 978-3-030-21347-3. DOI: 10.1007/978-3-030-21348-0_39 (cited on page 47).
- [77] Houcemeddine Turki et al. “Using logical constraints to validate information in collaborative knowledge graphs: a study of COVID-19 on Wikidata”. en. In: (2020). DOI: 10.5281/ZENODO.4445363 (cited on page 47).
- [78] Denny Vrandečić and Markus Krötzsch. “Wikidata: A Free Collaborative Knowledge base”. In: *Communications of the ACM* 57.10 (2014), pages 78–85 (cited on pages 10, 13, 18).
- [79] Xiu-Qing Wang and Shun-Kun Yang. “A Tutorial and Survey on Fault Knowledge Graph”. In: *International 2019 Cyberspace Congress, CyberDI and CyberLife, Beijing, China, December 16–18, 2019, Proceedings, Part II*. Edited by Huansheng Ning. Springer, Dec. 2019, pages 256–271 (cited on page 47).
- [80] Guohui Xiao et al. “Virtual Knowledge Graphs: An Overview of Systems and Use Cases”. In: *Data Intelligence* 1.3 (2019), pages 201–223. DOI: 10.1162/dint_a_00011. URL: https://doi.org/10.1162/dint%5C_a%5C_00011 (cited on page 47).
- [81] Jihong Yan et al. “A retrospective of knowledge graphs”. In: *Frontiers of Computer Science* 12.1 (2018), pages 55–74. DOI: 10.1007/s11704-016-5228-9. URL: <https://doi.org/10.1007/s11704-016-5228-9> (cited on page 47).
- [82] Matei Zaharia et al. “Resilient Distributed Datasets: A Fault-Tolerant Abstraction for In-Memory Cluster Computing”. In: *9th USENIX Symposium on Networked Systems Design and Implementation (NSDI 12)*. San Jose, CA: USENIX Association, Apr. 2012, pages 15–28. ISBN: 978-931971-92-8. URL: <https://www.usenix.org/conference/nsdi12/technical-sessions/presentation/zaharia> (cited on page 48).
- [83] Yongzhe Zhang, Hsiang-Shang Ko, and Zhenjiang Hu. “Palgol: A High-Level DSL for Vertex-Centric Graph Processing with Remote Data Access”. In: Springer International Publishing, 2017, pages 301–320. DOI: 10.1007/978-3-319-71237-6_15 (cited on page 48).



4. Contribuciones y trabajo futuro

4.1 Contribuciones y resultados conseguidos

Aunque en el artículo se relacionan las principales contribuciones y resultados conseguidos, se describen a continuación con un poco más de detalle y alguna valoración personal relativa al contexto en el que se han producido:

- Se realiza una presentación unificada en la que se definen los grafos RDF, los *property graphs* y los grafos de Wikibase. Las dos primeras definiciones no son nuevas: la definición de grafos RDF es bastante convencional y aparece en numerosos artículos sobre RDF como [26], la definición de *property-graphs* es una adaptación de la definición planteada en [69].
- La definición de Wikibase graphs se considera una aportación de este artículo. En el artículo se presenta una definición formal de lo que se denomina como grafos basados en Wikibase, que son los que se utilizan en Wikidata y otros proyectos basados en la tecnología de Wikibase. La definición está inspirada por el trabajo del artículo [69] en el que se realiza una definición formal de *Property graphs* y el artículo [52] en el que se realiza una definición del formalismo lógico subyacente a los grafos de Wikibase, que denominan MARS *multi-attributed relational structures*.
- Se define un lenguaje para la descripción de *property graphs* denominado PShEx, que es una extensión de ShEx añadiendo restricciones sobre cualificadores para nodos y para relaciones. Esta definición se inspira por un lado en la propia definición de ShEx, definida en [39, 63] y en la propuesta de [69] que añade restricciones inspiradas en SHACL a *property graphs*.
- Se define un lenguaje para la descripción de *Wikibase graphs* denominado WShEx, que es una extensión de ShEx añadiendo restricciones sobre cualificadores sobre relaciones. Esta definición se realiza a partir de la definición de PShEx y permite realizar descripciones del modelo de datos de Wikibase que pueden utilizarse para extraer subconjuntos de Wikidata mediante definiciones en WShEx. Es importante indicar que aunque ShEx puede utilizarse para validar datos en grafos Wikibase mediante esquemas de entidades, en realidad, lo que se valida es la serialización a RDF del modelo de datos de Wikibase. Mediante WShEx se puede describir directamente el modelo de datos de Wikibase tratando los cualificadores como entidades de primer orden.

- Se caracterizan técnicas para extraer subconjuntos de grafos de Wikibase, que permiten comparar las ventajas e inconvenientes de cada una. En concreto, se caracterizan las siguientes técnicas:
 - Subconjuntos generados por entidades (items o propiedades)
 - Subconjuntos generados mediante encaje
 - Subconjuntos generados mediante encaje basado en ShEx
 - Subconjuntos generados mediante *slurping*
 - Subconjuntos generados mediante validación a gran escala
- Se define formalmente la técnica de validación en ShEx con *slurping* para WShEx. Esta técnica consiste en recolectar los nodos y tripletas que se encuentran durante el proceso de validación. Aunque los validadores *shex.js*¹ y *PyShEx*² ofrecen una implementación de esta técnica, no existía una definición formal de la misma.
- Se define un algoritmo de validación a gran escala inspirado en el algoritmo Pregel [43]. En el artículo se presenta una descripción formal del algoritmo para el lenguaje WShEx.
- Se lleva a cabo una implementación del algoritmo anterior utilizando la librería Spark GraphX, obteniendo los primeros resultados de validaciones a gran escala que permiten extraer subconjuntos a partir de los nodos validados.

4.2 Líneas futuras de investigación

El trabajo de investigación aquí presentado ha permitido al candidato abrir nuevas líneas de investigación en las cuales todavía no se había trabajado y que se considera que pueden ser prometedoras:

- Finalizar la validación de la implementación en Spark GraphX de los algoritmos aquí presentados. Actualmente, se ha creado un prototipo experimental³ que funciona y ofrece resultados prometedores. Sin embargo, el prototipo trabaja todavía con un subconjunto de ShEx y hay aspectos que todavía están parcialmente implementados.
- Implementar el algoritmo Pregel+ShEx con otras librerías basadas en Prefel como Apache Giraph⁴ que permitan comparar tiempos de respuesta y consumo de recursos.
- Implementar variantes del algoritmo como *ShEx+Slurping* en una misma librería con el fin poder comparar las diferentes técnicas. Actualmente, la generación mediante encaje de grafos está implementada en *WDumper* (Java) y *WDSUB* (Scala), la técnica *ShEx+Slurping* está implementada en *ShEx.js* (Javascript) y *PyShEx* (Python) y el algoritmo *ShEx + Pregel* está implementado en Scala, con lo que realizar una comparación entre ambos no sería justa al involucrar aspectos asociados a los respectivos lenguajes y entornos.
- Demostrar la corrección de los algoritmos presentados. Actualmente se ha llevado a cabo una implementación que devuelve los resultados esperados pero sería interesante llevar a cabo una demostración más formal de que los resultados generados mediante *ShEx+ Slurping* son equivalentes a los generados mediante *ShEx+Pregel*, por ejemplo.
- Ampliar la expresividad del lenguaje ShEx utilizado en el presente trabajo para incluir negaciones y disyunciones. En la presentación aquí realizada se decidió prescindir de dichos operadores porque su uso no parece necesario para la descripción de subconjuntos y su inclusión complicaba algunas de las deficiones al interaccionar con la recursividad. No obstante, una línea de trabajo futuro será analizar en más detalle si pueden incluirse en el lenguaje con una semántica basada en estratificación como se hizo en ShEx [6].

¹<https://github.com/shexjs/shex.js>

²<https://github.com/hsolbrig/PyShEx>

³<https://github.com/weso/sparkwdsb>

⁴<https://giraph.apache.org/>

- Dado que los esquemas de entidades existentes utilizan ShEx, sería importante crear una herramienta que permita convertir esquemas ShEx en esquemas WShEx. En principio no parece un trabajo complicado desde un punto de vista teórico, dado que sería cuestión de identificar los patrones utilizados en la serialización a RDF de referencias y cualificadores.
- Completar la definición práctica del lenguaje WShEx. Tal y como se ha presentado en el artículo, el lenguaje WShEx tiene una definición simplemente formal, con una implementación que internamente utiliza el analizador sintáctico de ShEx y transforma los esquemas a WShEx. Es necesario desarrollar una gramática para WShEx, decidiendo, por ejemplo cómo distinguir entre referencias y cualificadores. Además, será necesario contemplar cómo representar los tipos de datos complejos utilizados en Wikibase como cantidades, coordenadas geográficas, formas geométricas, tiempos, etc.⁵, así como los rangos⁶.
- La validación mediante Shape Expressions de grandes grafos de conocimiento como Wikidata mediante tecnologías de procesamiento escalables como Apache Spark y Pregel. Esta línea se considera muy prometedora y con grandes aplicaciones, puesto que se desconoce la existencia de validadores que permitan afrontar grafos de conocimiento del tamaño de Wikidata y el algoritmo presentado en el presente trabajo sí lo permite.
- Adaptar y crear herramientas basadas en WShEx para que puedan ser utilizadas por los usuarios de la comunidad Wikibase. A modo de ejemplo, la herramienta Wikishape⁷ podría incluir un editor basado en WShEx que podría por un lado utilizarse para validar entidades, y por otro para crear subconjuntos.
- La definición formal de grafos Wikidata, en un mismo ámbito que los *property graphs* y los grafos RDF, permite la comparación en un mismo marco de dichas tecnologías, facilitando la identificación de las características comunes y diferenciadoras de las mismas. La difusión de este tipo de trabajo sigue la línea de [31] añadiendo un nuevo tipo de grafos de conocimiento que aquí se ha denominado *Wikibase graphs* cuyo modelo de datos es por un lado, una simplificación de los *property graphs* al no admitir cualificadores sobre nodos, pero por otro lado, una generalización de los mismos, al admitir nodos como valores en los cualificadores.

La tabla 4.1 presenta un resumen de las características que se han implementado y las que faltarían por implementarse o que se dejan como trabajo futuro. Se incluye una referencia a los artículos o implementaciones que siguen una determinada técnica. En el caso de que no se haya llevado a cabo la implementación correspondiente se indica mediante el símbolo: Pendiente

4.3 Conclusiones

El trabajo de investigación aquí presentado permite abrir varias líneas de investigación que se desarrollarán en el grupo de investigación.

A corto plazo, el candidato ha sido invitado a liderar el proyecto *21 – Handling Knowledge Graph Subsets*⁸ en el Biohackathon Europe que se celebrará en Barcelona del 8 al 12 de Noviembre de 2021 y en el que se presentarán los primeros resultados de los algoritmos aquí descritos.

Posteriormente, la idea es completar el artículo desarrollado para enviarlo a un congreso o revista especializado. Es posible que incluso se divida el trabajo en 2 o más partes, presentando por un lado las extensiones del lenguaje ShEx para *property graphs* y por otro lado, el trabajo para la creación de subconjuntos de grandes grafos de conocimiento mediante el algoritmo adaptado de Pregel.

Como se puede ver en la tabla 4.1, existen varias celdas que están todavía pendientes de rellenar y que podrían suponer nuevas líneas de trabajo.

⁵https://www.mediawiki.org/wiki/Wikibase/DataModel#Datatypes_and_their_Values

⁶https://www.mediawiki.org/wiki/Wikibase/DataModel#Ranks_of_Statements

⁷<https://wikishape.weso.es/>


⁸<https://github.com/elixir-europe/biohackathon-projects-2021/tree/main/projects/21>

	Grafos RDF	<i>Property graphs</i>	<i>Wikibase graphs</i>
Definición formal	Realizado Ej.[26]	Realizado [39, 63]	Presente trabajo
Descripción y validación con Shape Expressions	ShEx [6, 63, 73]	PShEx Presente trabajo	WShEx Presente trabajo
Definición formal Entity generated subsets	Pendiente	Pendiente	Presente trabajo
Implementación basada en Entity generated subsets	Pendiente	Pendiente	WDumper
Definición formal Matching generated sub- sets	Pendiente	Pendiente	Presente trabajo
Implementación Matching generated sub- sets	Pendiente	Pendiente	WDumper
Definición formal ShEx-based matching	Pendiente	Pendiente	Presente trabajo
Implementación ShEx-based matching	Pendiente	Pendiente	WDSUB
Definición formal ShEx + Slurping	Pendiente	Pendiente	Presente trabajo
Implementación ShEx+Slurping	shex.js PyShEx	Pendiente	Pendiente
Definición formal ShEx + Pregel	Pendiente	Pendiente	Presente trabajo
Implementación ShEx + Pregel	Pendiente	Pendiente	SparkWDSUB

Cuadro 4.1: Resumen de aspectos realizados anteriormente, desarrollados en el presente trabajo de investigación o pendientes de realizar

El trabajo aquí presentado forma parte de uno de los entregables del proyecto de investigación ANGLIRU descrito en el otro ejercicio, lo cual ha permitido arrancar a trabajar en dicho proyecto, ofreciendo unos primeros resultados para el mismo.

El candidato tiene intención de seguir trabajando en las líneas descritas anteriormente, integrando el trabajo desarrollado con el proyecto de investigación ANGLIRU y tratando de contribuir a mejorar la gestión de grafos de conocimiento que, desde una perspectiva más ambiciosa, ayudan a mejorar el conocimiento de la humanidad en general.



Universidad de Oviedo

Índice alfabético

A

Airbnb 10
Amazon 10, 13
ANGLIRU 8
Apple 18
Attributed graphs 13

B

bag 12
bag language 12
Biohackathon 7, 48
biology 13
blank nodes 14
BlazeGraph 18

C

Cartesian product 12
CERN 14
chemistry 13
ConceptNet 49
cybersecurity 13
Cypher 17

D

Datatype-generated subgraph 33
Datatypes 19

datatypes 14
dates 14
DBpedia 10, 13, 48
decimals 14
Directed edge-labelled graph 12

E

eBay 10
education 13
Enslaved 18
Entity 19
Entity schemas 10, 47

F

Facebook 10
Freebase 18

G

Google 10, 13, 18
Graph 12
graph databases 13
GraphDB 15
GraphLab 48
GraphX 48

H

healthcare 13

hypergraph 12

I

IBM 10

integers 14

Internationalized Resource Identifiers 14

IRIs 14

Item 19

item generated subgraph 32

J

JanusGraph 16

JSON 19, 20

K

KGTK 49

Knowledge Graph 13

Knowledge graphs 47

Kypher 49

L

language tags 14

LinkedIn 10

literals 14

London 14

M

MAPL 47

MariaDB 18

MARS 47

Mediawiki 18

mergeMsg 42

Microsoft 10

Multi-Attributed Predicate Logic 47

Multi-Attributed Relational Structures 47

multigraph 12

multiset 12

N

N3 14

named graphs 16

Neighbourhood of node in property graph .. 26

Neo4j 13, 16

New4j 10

O

object 12

OWL 14

P

PowerGraph 48

predicate 12

Pregel 38, 40, 48

Property 19

property generated subgraph 32

Property graphs 10, 13, 16, 49

property-value annotations 16

PShEx 11, 49

PShEx Schema 25

PyShEx 45

Q

Query service 18

R

RDD 48

RDF 13, 15, 18, 19, 48

RDF 1.0 15

RDF data model 14

RDF graph 14

RDF serialization 10, 20

RDF store 14

RDF-* 15, 16

RDF-based graphs 10, 49

RDF/XML 14

RDFS 14

RDFSShape 14

RDFSlice 48

Regular bag expression 13

reification 15

Resilient Distributed Datasets 48

Rhizome 18

S

Scala 8

Scholia 8, 10

sendMsg 42

Set 12

SHACL 47

Shape assignment 13

Shape Expressions 10

shape maps 13
 ShEx 10, 47, 49
 ShEx Schema 22
 ShEx+Pregel 11, 49
 ShEx+Slurp 11, 49
 shex.js 45
 singleton properties 15
 Siri 18
 sliceSPARQL 48
 Sparksee 16
 SparkWDSUB 8, 47
 SPARQL 14, 18, 48
 SQID 48
 SQLite 49
 Standard RDF reification 15
 Statement 19
 subject 12
 superstep 38
 SWAT4HCLS 7, 48

T

Tim Berners-Lee 12, 14
 Torpedo 48
 triple 12
 triple based graph 14
 triple-based graphs 12
 Turtle 14
 type annotations 16
 typings 13

U

UML 19
 unique identifiers 16

V

vProg 40

W

W3C recommendation 13, 47
 WDSUB 8, 46
 WDumper 45, 48
 Wikibase 15, 18
 Wikibase graphs 49
 Wikibase instance 18
 Wikidata 10, 13, 18, 48, 49
 Wikidata Object Notation 19
 Wikipedia 10, 18

WShEx 11, 49

Y

YAGO 10
 Yago 13

Z

Zenodo 48