C1195 (BK)

14290

Vapor management valve



F02103

Pin	Circuit	Circuit function
1	34 (LB/OG)	PCM power relay, output
2	191 (LG/BK)	Vapor management valve, control

C1197

14290

Medium speed fan control relay



F05129

Pin	Circuit	Circuit function
30	60 (BK/LG)	Voltage supplied at all times (overload protected)
85	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
86	3886 (BK)	Medium speed fan control relay, control
87	3829 (LB/BK)	Medium speed fan control relay, output
87A	–	not used

C2007 (GN)

14401

Passive anti–theft transceiver



F04245

Pin	Circuit	Circuit function
1	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
2	57 (BK)	Ground
3	167 (BN/OG)	TX, signal
4	168 (RD/BK)	RX, signal

C2008 (NA/GV)

14401

Brake shift interlock



F08179

Pin	Circuit	Circuit function
1	665 (OG/YE)	Overdrive cancel switch (7G550), signal
2	570 (BK/WH)	Ground
3	57 (BK)	Ground
4	640 (RD/YE)	Voltage supplied in Start and Run (overload protected)
5	605 (RD)	Brake shift interlock relay, output
6	–	not used
7	1415 (LB/YE)	Instrument cluster Park/Neutral Position (PNP) switch input
8	1420 (YE/LB)	Key removal inhibit solenoid, Switched, Ground