C228b

14401

A205
Electronic Automatic Temperature Control (EATC) module (19980)



F13013

Pin	Circuit	Circuit function
1	915 (PK/LB)	SCP Bus –
2	729 (RD/WH)	Voltage supplied at all times (overload protected)
3	57 (BK)	Ground
4	470 (PK/BK)	Sensor signal return (reference/ground)
5	435 (YE/LB)	signal, return
6	436 (RD/LG)	Air temperature door variable resistor +
7	767 (LB/OG)	Ambient air temperature sensor (19E702), feed
15	914 (TN/OG)	SCP Bus +
16	1040 (RD/BK)	Voltage in Run (overload protected)
17	–	not used
18	437 (YE/LG)	Air temperature door variable resistor, wiper
19	–	not used
20	468 (BN)	Sunload sensor (19E663), input

C237

14A005



F16034

(1) 832 (LB/PK)
(2) 720 (RD/YE)
1070 (BN/LB)
(3) 1040 (RD/BK)
(4) 1521 (LG)
(5) 1445 (RD/LG)
595 (LB/RD)
(6) 1523 (DG)
(7) 799 (OG/BK)
(8) 1068 (LG/BK)

14401



F16087

(9) 856 (VT)
(10) 833 (TN)
(11) 798 (LG/RD)
(12) 1507 (WH/RD)
(13) 828 (VT/LB)
(14) 1048 (LB/WH)
(15) 690 (GY)
(16) 48

C233

14401

B206
In–vehicle temperature sensor (19C734)



F02291

Pin	Circuit	Circuit function
1	470 (PK/BK)	Sensor signal return (reference/ground)
2	790 (WH/OG)	In–vehicle temperature sensor (19C734), input