C199 (NA)

12A581

A274
AX4S/AX4N Transmission



F10076

Pin	Circuit	Circuit Function
1	237 (OG/YE)	Shift solenoid A
2	276 (BN)	Voltage supplied in Start and Run (overload protected)
3	125 (DB/WH)	Torque Converter Clutch (TCC) solenoid
4	–	not used
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
6	315 (VT/OG)	Shift solenoid B
7	276 (BN)	Voltage supplied in Start and Run (overload protected)
8	971 (PK/BK)	Shift solenoid C
9	359 (GY/RD)	signal, return
10	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid

C202a

14401

N442
Multifunction switch
(13K359)



F07051

Pin	Circuit	Circuit Function
1	589 (OG)	wiper, (front wiper), Intermittent wiper circuit
2	1041 (BN/OG)	Voltage in Run (overload protected)
3	164 (VT/LB)	High beam lamp, feed
4	993 (BN/WH)	Wiper switch circuit, (front wiper), Intermittent wiper circuit
5	196 (DB/OG)	Flash–to–pass, feed
6	590 (DB/WH)	Multifunction switch (13K359), to, Wiper Control Module (WCM)
7	383 (RD/WH)	Voltage supplied at all times (overload protected)