C197b

14B060

Starter motor
(11002)



F01115

Pin	Circuit	Circuit function
1	2037 (RD)	Battery cable +

C199 (WH)

7C078

Transmission hard-
ware unit



F10093

Pin	Circuit	Circuit function
1	–	not used
2	359 (GY/RD)	signal, return
3	924 (BN/OG)	Torque Converter Clutch (TCC) solenoid
4	361 (RD)	Voltage supplied in Start and Run (overload protected)
5	923 (OG/BK)	Transmission Fluid Temperature (TFT) sensor, input
6	925 (WH/YE)	Electronic Pressure Control (EPC) solenoid, control
7	237 (OG/YE)	Shift solenoid A
8	315 (VT/OG)	Shift solenoid B
9	–	not used
10	–	not used

C201a (TN)

14401

Generic Electronic
Module (GEM)
(14B205)



F04417

Pin	Circuit	Circuit function
1	1006 (DG/WH)	Voltage supplied at all times (overload protected)
2	226 (WH/BK)	Power window motor, left front +/–
3	991 (TN/LB)	Master window adjust switch (14529) +/–
4	400 (LB/BK)	Voltage in Run or Accessory (overload protected)

C201b (BK)

14401

Generic Electronic
Module (GEM)
(14B205)



F04417

Pin	Circuit	Circuit function
1	1205 (BK)	Ground
2	1001 (WH/YE)	Voltage supplied at all times (overload protected)
3	193 (YE/LG)	Voltage supplied at all times (overload protected)
4	397 (BK/WH)	Ground