Component Testing – Power seat switch, left – without memory

COMPONENT TESTING PROCEDURE

TO TEST	Connect Self-Powered Test Light or Ohmmeter to Terminals	Move Switch to These Positions	A Good Switch Will Indicate
Backrest Circuit	3 and 7	Rest	Open Circuit
		Backrest forward	Open Circuit
		Backrest rearward	Closed Circuit
	3 and 8	Rest	Open Circuit
		Backrest forward	Closed Circuit
		Backrest rearward	Open Circuit
	6 and 7	Rest	Open Circuit
		Backrest forward	Closed Circuit
		Backrest rearward	Open Circuit
	6 and 8	Rest	Open Circuit
		Backrest forward	Open Circuit
		Backrest rearward	Closed Circuit
Forward Rearward Circuit	3 and 1	Rest	Open Circuit
		Seat forward	Open Circuit
		Seat rearward	Closed Circuit
	3 and 2	Rest	Open Circuit
		Seat forward	Closed Circuit
		Seat rearward	Open Circuit
	6 and 1	Rest	Open Circuit
		Seat forward	Closed Circuit
		Seat rearward	Open Circuit
	6 and 2	Rest	Open Circuit
		Seat forward	Open Circuit
		Seat rearward	Closed Circuit
Height Circuit	3 and 5	Rest	Open Circuit
		Front height up	Open Circuit
		Front height down	Closed Circuit
	3 and 4	Rest	Open Circuit
		Front height up	Closed Circuit
		Front height down	Open Circuit
	6 and 5	Rest	Open Circuit
		Front height up	Closed Circuit
		Front height down	Open Circuit
	6 and 4	Rest	Open Circuit
		Front height up	Open Circuit
		Front height down	Closed Circuit