C1030

14290

Daytime Running Lamps (DRL) module



F06110

Pin	Circuit	Circuit function
1	13 (RD/BK)	Low beam, Lamp, Power, feed
2	196 (DB/OG)	Voltage supplied at all times (overload protected)
3	298 (VT/OG)	Voltage in Run (overload protected)
4	57 (BK)	Ground
5	12 (LG/BK)	High beam lamp, Power, feed
6	–	not used

C1033 (BK)

* Natural Gas Vehicle (NGV)
** Marauder

12B637



F16020

(1) 1025 (OG/YE)
(2) 1021 (LG/YE)
(3) 1030 (DG/VT)
(4) 1029 (WH/RD)
(5) 328 (YE/LG)
*295 (LB/PK)
(6) 676 (PK/OG)
**295 (LB/PK)
(7) 321 (GY/WH)
*39 (RD/WH)
(8) 191 (LG/BK)
*321 (GY/WH)
(9) 654 (YE/LG)
*388 (YE/LB)
(10) 57 (BK)
(11) 388 (YE/LB)
*654 (YE/LG)
(12) 36 (YE/WH)
**1040 (RD/BK)
(13) 74 (GY/LB)
(14) 94 (RD/BK)
(15) 387 (RD/WH)
(16) 33 (WH/PK)

14290



F16145

(1) 1025 (OG/YE)
(2) 1021 (LG/YE)
(3) 1030 (DG/VT)
(4) 1029 (WH/RD)
(5) 328 (YE/LG)
*298 (VT/OG)
(6) 298 (VT/OG)
*676 (PK/OG)
(7) 321 (GY/WH)
*39 (RD/WH)
(8) 191 (LG/BK)
*321 (GY/WH)
(9) 654 (YE/LG)
*388 (YE/LB)
(10) 57 (BK)
(11) *654 (YE/LG)
388 (YE/LB)
(12) 1040 (RD/BK)
(13) 74 (GY/LB)
(14) 94 (RD/BK)
(15) 387 (RD/WH)
(16) 33 (WH/PK)